

Constrained BRSKI (cBRSKI)

draft-ietf-anima-constrained-voucher-27



Image: various brands of constrained brewski

IETF 122, Bangkok, March 2025

Esko Dijk – [IoTconsultancy.nl](https://www.ioTconsultancy.nl)
(presenting)

Co-authors:

M. Richardson

P. van der Stok

P. Kampanakis


[GitHub](https://github.com)

Recap & Goal – Constrained BRSKI

- › **BRSKI onboarding, for constrained (IoT) devices & networks**
- › Suitable for 6LoWPAN networks and other constrained IP networks.
Minimize **onboarding time** & **code overhead**:
 - minimize data size
 - minimize round-trips
 - minimize different-formats parsing
 - minimize optional functions
- › Modifications
 - CoAP + DTLS ⇨ instead of HTTP + TLS
 - COSE-signed CBOR ⇨ instead of CMS-signed JSON
 - EST-coaps (RFC 9148) ⇨ instead of 'classic' EST (RFC 7030)

Recap & Goal – Constrained BRSKI

- › BRSKI onboarding, for constrained (IoT) devices & networks



Updates Since -25 (@IETF-121)

- › Many editorial updates!
- › Clarify use of COSE “x5bag” to store the signer’s X509 certificates
 - Allows Registrar to fully check Voucher signature
 - No overhead of these certificates on the constrained network segment
- › Require CBOR format for BRSKI telemetry messages
 - avoid needless variation
- › Added base Resource Type for “ace.est”
 - simplify & minimize EST-coaps discovery operation

Nearing completion – what's missing?

- › Describe how a voucher can have “signing timestamp” [#310](#)
 - Re-use COSE method for this: *include CWT claim “iat” parameter* ([RFC 8392](#))
- › Update the BRSKI Parameters Registry [PR #328](#)
 - Changes field “URI” to more correct “Path Segment”
- › Progress the dependencies
 - draft-ietf-anima-constrained-join-proxy *see 2 slides from now*
 - draft-ietf-anima-rfc8366bis

Implementations

- › Appendix A.1 lists open source projects
 - Client & simulation code work was at IETF 121 Hackathon!
- › cBRSKI features are partly implemented
 - providing confidence that it works
- › Currently, no plans for a full implementation

Join Proxy for Bootstrapping of Constrained Network Elements

draft-ietf-anima-constrained-join-proxy-16

IETF 122, Bangkok, March 2025

Esko Dijk – [IoTconsultancy.nl](https://www.ioconsultancy.nl)
(presenting)

Co-authors:

M. Richardson
P. van der Stok
P. Kampanakis




Image: various brands of constrained brewski

[GitHub](https://github.com)

Recap & Goal – Join Proxy for cBRSKI

- › Join Proxy (**JP**) residing on constrained nodes for cBRSKI



Updates Since -15 (since Nov 2023)

- › Simplify stateless / stateful Join Proxy mode selection [#69](#)
 - Mode is either defined by a “profile” (single choice) or configured in network
 - Avoiding “autodetect” of mode reduces errors / testing-efforts / dead code
- › Editorial overhaul & corrections
 - Applied all known pending reviews (TSVART, IOTDIR, WGLC, WG, ...)
 - Security Considerations expanded
- › Focus on default CoAP discovery of Registrars / Join Proxies, remove GRASP/6TiSCH/... discovery
 - Other discovery methods delegated to [draft-ietf-anima-brski-discovery](#)


Next Steps

› Registrar Selection Problem

- Join Proxy may discover “malicious Registrar” [#33](#)
- Registrar may be unresponsive – try another? [#65](#)
- The problem is that the Pledge **knows if it's making progress**, but the Join Proxy **determines** the Registrar destination.
- In some cBRSKI implementations, no discovery but **configuration** of 1 Registrar.

› After above is solved:

With so many text changes, have a 2nd WGLC?



Thank You!

Comments or Questions?

[GitHub cBRSKI](#)
[GitHub Join Proxy](#)



Image: various brands of constrained brewski