



香港科技大學
THE HONG KONG
UNIVERSITY OF SCIENCE
AND TECHNOLOGY

Confucius Queue Management

Adapting Home Routers to Congestion Control's
Reactions for Consistent Low Latency

[draft-zhang-iccr-g-confucius](#)

Bochun Zhang and Zili Meng

March 17, 2025



Background

- Flows have different objectives and behaviors.




Page Loading Time (PLT)



Throughput




Delay Jitters





Competing with Bursty Traffic


- Some flows (e.g., Web flows) can be extremely bursty.
- 8 active flows in the median in the Alexa Top 1000 websites.



Script (>100 KB):
edge.permutive.app, imasdk.googleapis.com, z.moatads.com,
securepubads.g.doubleclick.net, assets.bounceexchange.com,
cdn.doubleverify.com, www.googletagmanager.com






Motivating Example



Interactive streaming flows,
such as videoconferencing, are
both heavy and real-time (HRT).




Motivating Example

Volatile: Web flows will degrade video flows.



Motivating Example

Volatile: Web flows will degrade video flows.
Unfair: Web or HRT flows far from fair share.





Motivating Example

Volatile: Web flows will degrade video flows.

Unfair: Web or HRT flows far from fair share.

Impractical: Routers cannot know which is which.



But the page loading time is
113% more than FQ!



Tame Volatility & Achieve Fairness


- Two root causes of delay degradation:

1. The sender needs some time to react.

- Feedback loop (RTT)
- **Responsiveness (CCA)**

2. The excessively sent packets need to be drained.

- Scheduling policy






Tame Volatility & Achieve Fairness

- Reducing the available bandwidth gently will help.

Intuitively, drain more packets at the beginning and give CCAs some time to react!





Confucius Algorithm

- Deficit Weighted Round Robin (DWRR)
- When the new flows join the competition, instead of **directly setting its weight to 1**, we **gradually increase its weight from $\frac{1}{F_{new}}$ to 1**




Algorithm 1: Reweight: run every $1/\lambda$ ms.

```
1 Reweight ()
2   foreach  $f \in \mathcal{F}_{new}$  do
3      $w_f \leftarrow 2w_f$  // The weight doubles every  $1/\lambda$  ms
4    $ratio = \frac{\sum_{i \in \mathcal{F}_{new}} w_i}{\sum_{i \in (\mathcal{F}_{all} - \mathcal{F}_{new})} w_i}$ 
5   if  $ratio < 1$  then // New flows are the minority
6     foreach  $f \in \mathcal{F}_{new}$  do
7        $w_f \leftarrow w_f / ratio$ 
8   foreach  $f \in \mathcal{F}_{new}$  do
9     if  $w_f \geq 1$  then // The new flow is old enough
10       $\mathcal{F}_{new} \leftarrow \mathcal{F}_{new} - \{f\}$ 
11       $w_f \leftarrow 1$ 
```

Smooth Queue Management


Reducing the bandwidth *gently* will help.

Intuitively, drain more packets at the beginning and give CCAs some time to react!







Examples of Confucius




(a) New flows impact the RT flow.



(b) New flows arrive one by one.




(c) New flows arrive and complete.




(d) New flows are RT flows.

Evaluation

- ns-3 simulation (over 2000 websites and 5 bandwidth datasets)



(a) When the RT flow uses Copa.




(b) When the RT flow uses GCC.



Evaluation

- Linux kernel implementation over OpenWrt






Theoretical features

- The amount of jammed traffic is theoretically bounded.
 - No matter how many and how long the competing flows are.

The exponential decrease follows how CCAs reduce their rates. This bounds the delay degradation.



The area (integral) under an exponential curve is bounded for any time. This bounds the FCT degradation.

Thank you!

Questions? Comments?

More information at: [draft-zhang-iccr-g-confucius](#)