

Signaling Optimization Objective and Bounded Metrics for MPLS Fast Reroute Backup LSP Tunnels

draft-deshmukh-mpls-frr-ext-01



Abhishek Deshmukh, HPE

Vishnu Pavan Beeram, HPE

Introduction

- [RFC4090] defines RSVP-TE signaling procedures to establish backup label-switched path (LSP) tunnels for local repair of LSP tunnels.
 - It introduces the FAST_REROUTE object, which allows the head-end Label Switched Router (LSR) of a local-protection-desiring LSP to signal the constraints used for the path computation of a backup LSP tunnel at each point of local repair (PLR).
 - The constraints carried in the FAST_REROUTE object are limited to priorities, affinities, hop limit, and bandwidth.
 - Implementations rely on the local policy at the PLR to determine the optimization objective and other relevant constraints for computing the backup path.

Class-Num = 205 [FAST_REROUTE]
C-Type = 1

0	1	2	3
Length (bytes)		Class-Num	C-Type
Setup Prio	Hold Prio	Hop-limit	Flags
Bandwidth			
Include-any			
Exclude-any			
Include-all			

- This document enhances the options available at the head-end LSR of a local-protection-desiring LSP to influence the path computation of the backup LSP tunnel at the PLR.
 - It introduces an extensible TLV- based RSVP object, FAST_REROUTE_EXT, for signaling the optimization objective and bounded metric constraints to be imposed on the backup LSP tunnel path computation.
 - The signaling procedures defined in the document are backward-compatible with implementations that only understand the FAST_REROUTE object.

Optimization Objective

- An optimization objective is typically represented as a quantifiable metric that an algorithm aims to optimize (minimize or maximize, depending on the metric type) when selecting a TE path.
 - For example, the optimization objective used in the backup path computation could be (but not limited to) any of the following:
 - Minimize the cumulative "IGP Metric" along the traversed path.
 - Minimize the cumulative "TE Metric" along the traversed path.
 - Minimize the cumulative "Delay-Average" along the traversed path.
 - Minimize the cumulative "Unreserved Bandwidth" along the traversed path.
 - In certain scenarios where the path computation is deemed a multi-parameter optimization problem and multiple optimization objectives are considered, a normalization weight may be required for each objective.

Bounded Metrics

- A bounded metric is a constraint parameter that is used to define a bound that a computed TE path must satisfy.
 - The bounded metric can be of path-scope or link-scope.
- A path-scoped bounded metric is used when the bound is to be imposed on the cumulative metric associated with a path.
 - Example: Ensure that the cumulative "TE Metric" along the traversed path does not exceed 1000.
- A link-scoped bounded metric is used when the bound is to be imposed on the metric associated with a link.
 - Example: Ensure that the "Delay Variation Threshold" on a traversed link does not exceed 15ms.

Procedure at the Ingress

- The optimization objective and/or the bounded metrics for the backup LSP MAY be specified at the ingress of the primary LSP via explicit configuration.
- The user may explicitly specify whether the optimization objective and/or bounded metrics of the local-protection-desiring LSP are to be inherited by the backup LSP at the PLR, or whether different values are to be used.
- If there is no such explicit configuration, the local PLR policy will dictate the optimization objective and the bounded metrics used for the backup LSP.
- If such explicit configuration is present, then the ingress of the primary LSP MUST signal an RSVP PATH message with the FAST_REROUTE_EXT object.
 - The presence of the FAST_REROUTE_EXT object in the PATH message is to be deemed as a companion object to the FAST_REROUTE object.
 - It is deemed a request to the PLR to establish the backup path using the optimization objective and/or the specified bounded metrics.
 - The ingress MUST NOT include the FAST_REROUTE_EXT object in the PATH message unless it also includes the FAST_REROUTE object.
 - When the ingress receives the corresponding RESV message, it can determine whether each PLR was able to cater to the signaled request by checking whether the "FRR_EXT protection" flag in the RESV RRO sub-object for that PLR is set.

Procedure at the PLR

- A PLR that does not understand the FAST_REROUTE_EXT object MUST ignore the object in the PATH message but forward it unexamined and unmodified.
 - The class number used for the object will ensure this behavior.
 - In such a scenario, the local policy on PLR will dictate the optimization objective and bounded metrics for the backup path computation.
- A PLR that understands the FAST_REROUTE_EXT object but does not find the companion FAST_REROUTE object in the PATH message MUST reject the PATH with the following error - {Policy Control Failure (2), Missing FAST_REROUTE object (TBA3)}.
- A PLR that understands the FAST_REROUTE_EXT object but cannot cater to the requested optimization objective and bounded metrics MAY fall back onto the optimization objective and bounded metrics dictated by local policy.
 - In such a scenario, the PLR MUST NOT set the "FRR_EXT protection" flag in the corresponding RESV RRO sub-object.
- A PLR that understands the FAST_REROUTE_EXT object and caters to the requested optimization objective and bounded metrics successfully MUST set the "FRR_EXT protection" flag in the corresponding RESV RRO sub-object.

Protocol Extensions:

FAST_REROUTE_EXT Object

- The FAST_REROUTE_EXT Object carries a set of TLVs.
- It MAY be carried in an RSVP PATH message.
- It MUST carry at least one TLV when present.
- It MUST always be accompanied with a FAST_REROUTE object in the RSVP PATH message.

Class-Num = TBA1 (Format - 11bbbbbb) C-Type = 1

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                                                    |
//                                                                    //
|                                                                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

* TLVs
- Series of TLVs.

Each TLV has the form:

```

0                               1
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      |      (TLV contents)      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

* The Length field in the TLV contains the total length of the TLV in bytes, including the Type and Length fields. The Length MUST be at least 4 and MUST be a multiple of 4.

Protocol Extensions:

FAST_REROUTE_EXT Object – Optimization Metric TLV

- Optimization Metric TLV carries the Metric-Type to be used in the optimization objective.
- In scenarios where multiple optimization objectives are desired, multiple Optimization Metric TLVs (each with a unique "Metric Type") MAY be packed into the FAST_REROUTE_EXT object.
 - In such scenarios, the weight field is used for normalizing different metrics.
 - When only one optimization objective is specified, the weight field is set to zero and is ignored.

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      | Metric Type |      Weight      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

* Type = 1 - Optimization Metric TLV
* Length = 4
* Metric Type:
  - 1 IGP
  - 2 TE
  - 3 Unreserved-Bandwidth
  - 4 Delay-Minimum
  - 5 Delay-Average
  - 6 Delay-Maximum
* Weight: Metric Normalization Weight

```

Protocol Extensions:

FAST_REROUTE_EXT Object – Bounded Metric TLV

- Bounded Metric TLV is used to carry the bound value for the specified Metric-Type.
- There can be more than one Bounded Metric TLV (each with a unique "Metric Type") packed into the FAST_REROUTE_EXT object.
- The Bounded Metric TLV, if present, MUST include a non-zero "Metric Bound" value.
- If there is a desire to specify a metric-bound for the same metric that is being optimized for, then the expectation is that both Optimization Metric TLV and Bounded Metric TLV for the same metric type are included in the FAST_REROUTE_EXT object.
- There MUST be at most one instance of the Bounded Metric TLV for each metric type with the same L flag (Link Scope) value.
- If two or more instances of a Bounded Metric TLV with the same L flag value are present for a metric type, only the first instance MUST be considered, and other instances MUST be ignored.

```

0                               1                               2
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-----+-----+-----+-----+-----+-----+-----+-----+
|      Type      |      Length      | Metric Type |      |L|
+-----+-----+-----+-----+-----+-----+-----+-----+
|                                     Metric Bound                                     |
+-----+-----+-----+-----+-----+-----+-----+-----+

* Type = 2 Bounded Metric TLV
* Length = 8
* Metric Type:
  - 1 IGP
  - 2 TE
  - 3 Unreserved-Bandwidth
  - 4 Delay-Minimum
  - 5 Delay-Average
  - 6 Delay-Maximum
  - 7 Delay-Variation-Threshold
* L Flag: Link-Scope
* Metric Bound: Bounded metric value. The units used and whether
  the bound is upper or lower depends on the metric-type.

```

- The presence of two Bounded Metric TLVs of the same type with a different value of the L flag is allowed.

Protocol Extensions: RRO IPv4/IPv6 Sub-Object Flag

FRR_EXT protection: TBA2

- The PLR MUST set this bit in the RESV RRO IPv4/IPv6 sub-object when it has successfully catered to the optimization objective and/or bounded metrics specified in the FAST_REROUTE_EXT object received in the corresponding PATH message.
- The PLR MUST NOT set this bit if the request was not catered to.

Next Steps

- Request feedback.
- Request early code-point allocation.