

What can we do with near-term Quantum Networks?


Garazi Muguruza Lasa

21st July, 2026

SURF



| What is a quantum network: node capabilities




Funded by
the European Union




Quantum internet: A vision for the road ahead
S. Wehner, D. Elkouss, R. Hanson *Science* 362.6412 (2018):
eaam9288. See **RFC 9583**.

| Near-term: what happens inside QKD boxes?





| Near-term: what happens inside QKD boxes?



Classical post-processing:
share partial information about



What other applications
are there by changing the
classical post-processing?



check website

Quantum communication knowledge bank

Beyond QKD

I. Introduction

II. Applications and primitives

III. Summary

IV. Diagram

V. Challenges

2.10 Multi-party computing

Distrusting parties can compute a function jointly on their private inputs, without having to reveal anything other than the outcome, that is, without having to share their data. In principle such protocol would be possible if we encrypted all our data in a way that we could compute homomorphically on it (the computations *commute* with the encryption), and in fact *Homomorphic Encryption* is a subset of Multi-Party Computing. However, the idea is that by relaxing the requirement of no communication between the parties we could obtain more efficient protocols. In practice, known quantum-enhanced constructions of MPC rely of quantum Oblivious Transfer, such that on a first stage oblivious keys are pre-processed using quantum communication, and can be later used when the function to compute is chosen, such that the second stage can consist only of classical communication.

Reference: The typical construction of MPC from OT consists of first obtaining 2-party computing as shown by <https://dl.acm.org/doi/pdf/10.1145/62212.62215> (OT → 2PC) and <https://mmp.cs.illinois.edu/pub/mpc-ot.pdf> (2PC → MPC), these constructions where proven to be quantum-secure by Unruh <https://arxiv.org/abs/0910.2912>. If we instead assume the QROM, we can construct MPC from OT directly <https://arxiv.org/abs/2304.10480>.

Classical state of the art: Classically there are multiple constructions based on: secret sharing, FHE, OT... but they all rely on classical authenticated channels (thus trapdoor-OWF or public-key cryptography).


Quantum advantage: Since quantumly OT can be constructed just from extractable and equivocal commitments, quantum-enhanced MPC only requires the existence of OWF (as opposed to trapdoor-OWF classically). In practice, this means that it can be built from symmetric cryptography's tools, whose security hasn't been challenges by quantum computers.

Hardware requirements: The construction on top of OT is information-theoretically secure with an addition of constant rounds of classical communication, thus the same hardware requirements apply. That is, the ability to generate BB84 states suffices (although there are no complete security proofs for weak coherent pulses).




check website

SURF



Multi-Party Computing

Joint operations on datasets of mutually distrusting parties.




Classically:
~~PKI~~ → Oblivious Transfer (OT) → MPC

can we replace PKI by quantum communication?

(similar constraints as QKD)


Quantum Multi-Party Computing




Assumptions: quantum links between every 2 parties

Steps:

1. quantum comm between every 2 parties



2. classical post-processing of OT keys:




3. chose a function to jointly compute
4. classical post-processing of MPC

Bonus: if parties have access to **quantum computers** they can jointly compute **quantum operations**.

Position Verification

Verify that a message comes from a specific location.

verifiers trust each other




Classically:
~~GNSS positioning, radio-wave signals~~

Insecure against
jamming, spoofing,
collusions... (classical
attacks)

Quantum Position Verification

Verify that a message comes from a specific location.

verifiers trust each other




the sender cannot lie

Assumptions: quantum links to the prover

Steps:

1. quantum comm from the prover to the verifiers



2. classical post-processing



- Position-based authentication.
- Its security is much less understood than QKD.

Conclusions

- We need more access to the QKD devices.
- We need to understand what is the quantum advantage (if any) of the primitives.
- We need more noise and performance analysis of cryptographic primitives.
- We need to know which trade-offs between security and performance we deem acceptable.

does any of these applications ring a bell?

what network architectures would they need?





**Thank you for
your
attention!**
✉ garazi.muguruzalasa@surf.nl