

72nd IETF Kerberos Working Group

draft-ietf-krb-wg-anon-05.txt
Last Call Issues

Last Call - draft-ietf-krb-wg-anon-05.txt

A018 - Anonymous AS Realm

Sam Hartman <hartmans-ietf@mit.edu>

- With anonymous PKINIT, what should the client realm be?

PROPOSAL

- When anonymous PKINIT is used, the returned realm name **MUST** be the anonymous realm

Last Call - draft-ietf-krb-wg-anon-05.txt

A028 - AD-INITIAL-VERIFIED-CAS
Jeffrey Hutzelman <jhutz@cmu.edu>

- Draft -05 said the KDC MAY remove AD-INITIAL-VERIFIED-CAS subject to policy.
- Draft -07 says is SHOULD do so.
- Is this change OK?

Last Call - draft-ietf-krb-wg-anon-05.txt

A019 - Anonymous vs cross-realm policy
Sam Hartman <hartmans-ietf@mit.edu>

- How should anonymous realms interact with cross-realm policy?

Last Call - draft-ietf-krb-wg-anon-05.txt

A020 - Which KDC?

Sam Hartman <hartmans-ietf@mit.edu>

- In the anonymous AS request, which KDC do you contact for the anonymous ticket?

Last Call - draft-ietf-krb-wg-anon-05.txt

A022 - Is anonymous@REALM anonymous?

Ken Raeburn <raeburn@mit.edu>:

- WELLKNOWN/ANONYMOUS@REALM gives the server some information about the identity of the client.

- Should this be treated as anonymous at the GSS-API layer?

Last Call - draft-ietf-krb-wg-anon-05.txt

A023 - GSS Import anonymous
Ken Raeburn <raeburn@mit.edu>:

- Should importing an anonymous Kerberos principal name and calling `display_name` get `NT-ANONYMOUS` back as the type?
- or
- Should `NT-ANONYMOUS` names only be generated by `accept_sec_context`?

Last Call - draft-ietf-krb-wg-anon-05.txt

A016 - display_name

Sam Hartman <hartmans-ietf@mit.edu>

- If I call `gss_display_name` on an anonymous principal in an acceptor, what do I expect to get back?