

MANET Autoconfiguration (Autoconf)
Internet-Draft
Intended status: Informational
Expires: April 21, 2011

C. Perkins
Tellabs
T. Clausen
Ecole Polytechnique
October 18, 2010

MANET address autoconfiguration for legacy hosts
draft-perkins-autoconf-leghost-00

Abstract

This document describes methods by which a host running only DHCPv6 or Neighbor Discovery can obtain an address suitable for use in an ad hoc network.

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 21, 2011.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- 1. Introduction 3
- 2. Details about DHCPv6 operation 4
- 3. Details about operation using Router Advertisement 4
- 4. Pictorial representation of address assignment 4
- 5. Security Considerations 4
- 6. IANA Considerations 5
- 7. References 5
 - 7.1. Normative References 5
 - 7.2. Informative References 5
- Appendix A. Acknowledgements 5

1. Introduction

This document describes methods by which a host running only DHCPv6 [RFC3315] or Neighbor Discovery [RFC4862] can obtain an address suitable for use in an ad hoc network. Let us call such a host to be a "legacy host". It is agreed that legacy hosts are not routers and do not forward packets.

The basic mechanism in our proposal is very simple. DHCP Request packets and certain Router Solicitations are treated as requests to obtain an address. Any router receiving such an address allocation request initiates an Address Allocation protocol procedure appropriate for the MANET (Mobile Ad Hoc Network) in which the router resides. There are numerous examples of such address allocation protocols [bernardos-survey]. In the case of routers running proactive MANET protocols, simple inspection of the routing table may suffice for the router to determine a unique address for the requesting host. In the case of routers running only reactive protocols, additional steps may be necessary.

Once the router has determined a unique address appropriate for the requesting host, the router returns either DHCP Request or Router Advertisement to the requesting host. In the case of the Router Advertisement, the router presumes that the host will follow standard practice. Namely, the host is presumed to make use of the prefix provided by the router along with the host ID of the requesting host. In many cases, the prefix supplied by the router will be such that no link-local addresses are supported within the range of addresses defined by the prefix, because the prefix will be /128. Such allocations do not require additional steps by the host, and the /128 prefix supplied by the router will typically already contain the host ID of the requesting host.

The cases of interest may be classified into two general categories, depending upon whether or not the ad hoc network (i.e., the MANET) is attached to the Internet. If the MANET is attached to the Internet, then the MANET as a whole is addressable from the Internet according to a routing prefix appropriate for the point of attachment of the MANET. In this case, addresses assigned to the requesting host by the allocating router will be selected from the routing prefix for the MANET.

Otherwise, the address will be selected from a generalized MANET prefix (MANET_LOCAL_PREFIX) which is not reachable from the Internet. Any address assignments from the MANET_LOCAL_PREFIX are only valid within the connected domain defined by the routers in the MANET containing the legacy host and its neighboring router(s). The operation of legacy hosts using such addresses allocated from the

6. IANA Considerations

This document does not have any IANA actions.

7. References

7.1. Normative References

- [RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", RFC 3315, July 2003.
- [RFC4193] Hinden, R. and B. Haberman, "Unique Local IPv6 Unicast Addresses", RFC 4193, October 2005.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", RFC 4862, September 2007.

7.2. Informative References

- [bernardos-survey] Bernardos, CJ., Calderon, M., and H. Moustafa, "Survey of IP address autoconfiguration mechanisms for MANETs", draft-bernardos-manet-autoconf-survey-05.txt (work in progress), 2010.

Appendix A. Acknowledgements

This document has benefitted from discussions with the following people, in no particular order: Buu-Minh Ta.

Authors' Addresses

Charles E. Perkins
Tellabs

Phone: +1-408-435-0777 x337
EMail: charliep@wichorus.com

Thomas Clausen
Ecole Polytechnique

Phone: +33-671-116-128
EMail: thomas@thomasclausen.org

