

# A Mechanism for Transporting User to User Call Control Information in SIP

draft-johnston-cuss-sip-uui-00

Alan Johnston <alan.b.johnston@gmail.com>  
Joanne McMillen <c.joanne.mcmillen@gmail.com>  
James Rafferty <james.rafferty@dialogic.com>

# History

- Initial version draft-johnston-sipping-cc-uui-00 was submitted in 2006.
- Most of the text adopted from draft-johnston-sipping-cc-uui-09.
- Revised as draft-johnston-cuss-sip-cc-uui-00 after formation of CUSS WG
  - Added James Rafferty as co-author
- No revision since September interim

# Mechanism Background

- Based on the requirements and use cases in draft-ietf-cuss-cc-uui-reqs-00
- Why INFO is not used
  - INFO can only be sent in a dialog
  - Call control UUI needs to be transported at time of dialog establishment
- Why Other Protocol Encapsulation Not Used
  - Some protocols (ISDN, NSS, etc.) have UUI transport
  - If these protocols are being encapsulated, there is no need for a native SIP UUI mechanism
  - However, it is unreasonable to implement one of these protocols just to get UUI transport

# Discovery Mechanism

- To meet REQ-8, a SIP option tag is proposed
  - Allows for routing to a SIP/ISDN gateway that supports the UUI mechanism
  - E.g. Supported: uui
- To meet REQ-10, SIP feature tags are proposed
  - Feature tags defined for each application that uses UUI (e.g. each purpose value)
  - Allows for discovery and preferential routing to UAs that understand the UUI application
  - E.g. Contact: <gw@isp.example.com>;sip.uui-isdn

# Transport Mechanism Options

- MIME body
- Header field

# MIME Body

- SIP can carry any body without any extensions
- Bodies are difficult to work with in redirection and REFER scenarios (REQ-3)
- Bodies can not be removed by proxies (REQ-9)
- Bodies for UUI will require Multipart MIME when SDP is present
- Escaping MIME body into SDP has similar problems (REQ-3 difficult, REQ-9 not met), but does not require Multipart MIME

# Header Field

- Similar to Call-Info header field, but without URL to dereference
- Meets all requirements
- Multiple instances of deployed running code today

# Security Comparison

- Security Requirements draft-ietf-cuss-sip-uuu are TBD
- Body security
  - S/MIME RFC 3261 Section 23.3 Securing MIME bodies
  - RFC 4474 integrity protection
- Header
  - S/MIME RFC 3261 Section 23.4 SIP Header Privacy and Integrity using S/MIME: Tunneling SIP
    - Header is effectively carried as a body
  - No RFC 4474 integrity protection
    - Could possibly be added



# Proposed Mechanism

- A header field “User-to-User” to transport UUI
- Define parameters for
  - Encoding - encoding method (hex, IA5, etc)
  - Content - actual contents of UUI if known
  - Purpose - application generating and consuming UUI
- Create IANA registry for these parameters
- Each new purpose would require a standards track RFC

# Next Steps

- Come to consensus on header vs. body
- WG adoption of a mechanism draft to meet the requirements