

Internet Engineering Task Force  
Internet-Draft  
Updates: 6733 (if approved)  
Intended status: Standards Track  
Expires: April 04, 2014

T. Tsou  
Huawei Technologies (USA)  
R. Hao  
Comcast Cable  
T. Taylor, Ed.  
Huawei Technologies  
October 01, 2013

Realm-Based Redirection In Diameter  
draft-ietf-dime-realm-based-redirect-13

Abstract

The Diameter protocol includes a capability for message redirection, controlled by an application-independent "redirect agent". In some circumstances, an operator may wish to redirect messages to an alternate domain without specifying individual hosts. This document specifies an application-specific mechanism by which a Diameter server or proxy (node) can perform such a redirection when S-NAPTR is not used for dynamic peer discovery. A node performing this new function is referred to as a "Realm-based Redirect Server".

This memo updates Sections 6.13 and 6.14 of RFC6733 with respect to the usage of the Redirect-Host-Usage and Redirect-Max-Cache-Time AVPs.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 04, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1.	Introduction . . . . .	2
1.1.	Terminology . . . . .	3
2.	Support of Realm-Based Redirection Within Applications . . . . .	3
3.	Realm-Based Redirection . . . . .	4
3.1.	Configuration of the Realm-based Redirect Server . . . . .	5
3.2.	Behaviour of Diameter Nodes . . . . .	5
3.2.1.	Behaviour at the Realm-based Redirect Server . . . . .	5
3.2.2.	Proxy Behaviour . . . . .	6
3.2.3.	Client Behaviour . . . . .	6
3.3.	The Redirect-Realm AVP . . . . .	7
3.4.	DIAMETER_REALM_REDIRECT_INDICATION Protocol Error Code . . . . .	7
4.	Security Considerations . . . . .	7
5.	IANA Considerations . . . . .	8
6.	Acknowledgements . . . . .	8
7.	References . . . . .	9
7.1.	Normative References . . . . .	9
7.2.	Informative References . . . . .	9
	Authors' Addresses . . . . .	9

## 1. Introduction

The Diameter base protocol [RFC6733] specifies a basic redirection service provided by redirect agent. The redirect indication returned by the redirect agent is described in Section 6.1.8 and Sections 6.12-6.14 of [RFC6733], and provides to the message sender one or more individual hosts as destination of the redirected message.

However, consider the case where an operator has offered a specific service but no longer wishes to do so. The operator has arranged for an alternative domain to provide the service. To aid in the transition to the new arrangement, the original operator maintains a redirect server to indicate to the message sender the alternative domain to which redirect the request. However, the original operator should be relieved from configuring in the redirect server a list of hosts to contact in the alternative operator's domain, and should

simply be able to provide redirect indications to the domain as a whole.

### 1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Within this specification, the term "realm-based redirection" is used to refer to a mode of operation where a realm rather than an individual host is returned as redirect indication.

The term "Realm-based Redirect Server" denotes the Diameter node (Diameter server or proxy) that returns the realm-based redirection. The behaviour of the Realm-based Redirect Server itself is a slight modification of the behaviour of a basic redirect agent as described in Section 6.1.8 of [RFC6733].

This document uses a number of terms consistently with their usage in [RFC6733]: "Diameter client", "Diameter node", "Diameter peer", "Diameter server", "proxy", "realm" or "domain", "redirect agent", and "session" as defined in Section 1.2, and "application" as defined implicitly by Sections 1.3.4, 2.3, and 2.4.

## 2. Support of Realm-Based Redirection Within Applications

The DNS-based dynamic peer discovery mechanism defined in the Diameter base protocol [RFC6733] provides a simple mechanism for realm-based redirection, using the S-NAPTR DDDS application [RFC3958]. When S-NAPTR is used for peer discovery, redirection of Diameter requests from the original realm to a new realm may be performed by updating the existing NAPTR resource records for the original realm as follows: the NAPTR RR for the desired application(s) and supported application protocol(s) provided by the new realm will have an empty FLAG field and the REPLACEMENT field will contain the new realm to use for the next DNS lookup. The new realm can be arbitrary; the restriction in [RFC6733] that the NAPTR replacement field match the domain of the original query does not apply for realm-based redirect purposes.

However, the use of DNS-based dynamic peer discovery is optional for Diameter implementations. For deployments which do not make use of S-NAPTR peer discovery, support of realm-based redirection needs to be specified as part of functionality supported by a Diameter application. In this way, support of the considered Diameter application (discovered during capabilities exchange procedures as defined in Diameter base protocol [RFC6733]) indicates implicit

support of the realm-based redirection mechanism. A new application specification can incorporate the mechanism specified here by making it mandatory to implement for the application, and referencing this specification normatively.

The result of making realm-based redirection an application-specific behaviour is that it cannot be performed by a redirect agent as defined in [RFC6733], but **MUST** be performed instead by an application-aware Diameter node (Diameter server or proxy) (hereafter called a "Realm-based Redirect Server").

An application can specify that realm-based redirection operates only on complete sessions beginning with the initial message, or on every message within the application, even if earlier messages of the same session were not redirected. This distinction matters only when realm-based redirection is first initiated. In the former case, existing sessions will not be disrupted by the deployment of realm-based redirection. In the latter case, existing sessions will be disrupted if they are stateful.

### 3. Realm-Based Redirection

This section specifies an extension of the Diameter base protocol [RFC6733] to achieve realm-based redirection. The elements of this solution are:

- o a new result code, `DIAMETER_REALM_REDIRECT_INDICATION` (3xxx TBD1);
- o a new attribute-value pair (AVP), `Redirect-Realm` (code TBD2); and
- o associated behaviour at Diameter nodes implementing this specification.

This behaviour includes the optional use of the `Redirect-Host-Usage` and `Redirect-Max-Cache-Time` AVPs. In this document, these AVPs apply to the peer discovered by a node acting on the redirect server's response, an extension to their normal usage as described in Sections 6.13 and 6.14 of [RFC6733].

Section 3.2.2 and Section 3.2.3 describe how a proxy or client may update its routing table for the application and initial realm, as a result of selecting a peer in the new realm after realm-based redirection. Note that as a result, the proxy or client will automatically route subsequent requests for that application to the new realm (with the possible exception of requests within sessions already established with the initial realm) until the cached routing entry expires. This should be borne in mind if the rerouting is intended to be temporary.

### 3.1. Configuration of the Realm-based Redirect Server

A Diameter node (Diameter server or proxy) acting as Realm-based Redirect Server MUST be configured as follows to execute realm-based redirection:

- o configured with an application that incorporates realm-based redirection;
- o the Local Action field of the routing table described in Section 2.7 of [RFC6733] is set to LOCAL;
- o an application-specific field is set to indicate that the required local action is to perform realm-based redirection;
- o an associated application-specific field is configured with the identities of one or more realms to which the request should be redirected.

### 3.2. Behaviour of Diameter Nodes

#### 3.2.1. Behaviour at the Realm-based Redirect Server

As mentioned in Section 2, an application can specify that realm-based redirection operates only on complete sessions beginning with the initial message (i.e., to prevent disruption of established sessions), or on every message within the application, even if earlier messages of the same session were not redirected.

If a Realm-based Redirect Server configured as described in Section 3.1 receives a request to which realm-based redirection applies, the Realm-based Redirect Server MUST reply with an answer message with the 'E' bit set, while maintaining the Hop-by-Hop Identifier in the header. The Realm-based Redirect Server MUST include the Result-Code AVP set to DIAMETER\_REALM\_REDIRECT\_INDICATION. The Realm-based Redirect Server MUST also include the alternate realm identifier(s) with which it has been configured, each in a separate Redirect-Realm AVP instance.

The Realm-based Redirect Server MAY include a copy of the Redirect-Host-Usage AVP, which SHOULD be set to REALM\_AND\_APPLICATION. If this AVP is added, the Redirect-Max-Cache-Time AVP MUST also be included. Note that these AVPs apply to the peer discovered by a node acting on the Realm-based Redirect Server's response, as described in the next section. This is an extension of their normal usage as described by Sections 6.13 and 6.14 of [RFC6733].

Realm-based redirection MAY be applied even if a Destination-Host AVP is present in the request, depending on the operator-based policy.

### 3.2.2. Proxy Behaviour

A proxy conforming to this specification that receives an answer message with the Result-Code AVP set to `DIAMETER_REALM_REDIRECT_INDICATION` MUST attempt to reroute the original request to a server in a realm identified by a Redirect-Realm AVP instance in the answer message, and if it fails MUST forward the indication toward the client. To reroute the request, it MUST take the following actions:

1. Select a specific realm from amongst those identified in instances of the Redirect-Realm AVP in the answer message.
2. If successful, locate and establish a route to a peer in the realm given by the Redirect-Realm AVP, using normal discovery procedures as described in Section 5.2 of [RFC6733].
3. If again successful:
  - a. update its cache of routing entries for the realm and application to which the original request was directed, taking into account the Redirect-Host-Usage and Redirect-Max-Cache-Time AVPs, if present in the answer.
  - b. Remove the Destination-Host (if present) and Destination-Realm AVPs from the original request and add a new Destination-Realm AVP containing the realm selected in the initial step.
  - c. Forward the modified request.
4. If either of the preceding steps 2-3 fail and additional realms have been identified in the original answer, select another instance of the Redirect-Realm AVP in that answer and repeat steps 2-3 for the realm that it identifies.

### 3.2.3. Client Behaviour

A client conforming to this specification MUST be prepared to receive either an answer message containing a Result-Code AVP set to `DIAMETER_REALM_REDIRECT_INDICATION`, or, as the result of proxy action, some other result from a realm differing from the one to which it sent the original request. In the case where it receives `DIAMETER_REALM_REDIRECT_INDICATION`, the client SHOULD follow the same

steps prescribed in the previous section for a proxy, in order both to update its routing table and to obtain service for the original request.

### 3.3. The Redirect-Realm AVP

The Redirect-Realm AVP (code TBD2) is of type DiameterIdentity. It specifies a realm to which a node receiving a redirect indication containing the result code value `DIAMETER_REALM_REDIRECT_INDICATION` and the Redirect-Realm AVP SHOULD route the original request.

### 3.4. `DIAMETER_REALM_REDIRECT_INDICATION` Protocol Error Code

The `DIAMETER_REALM_REDIRECT_INDICATION` (3xxx TBD1) Protocol error code indicates that a server has determined that the request within an application supporting realm-based redirection could not be satisfied locally and the initiator of the request SHOULD direct the request directly to a peer within a realm that has been identified in the response. When set, the Redirect-Realm AVP MUST be present.

## 4. Security Considerations

The general recommendations given in the section 13 of the Diameter base protocol [RFC6733] apply. Specific security recommendations related to the realm-based redirection defined in this document are described below.

Realm-based redirection implies a change of the business relationships between organizations. Before redirecting a request towards a realm different from the initial realm, the client or proxy MUST ensure that the authorization checks have been performed at each connection along the path toward the realm identified in the realm-based redirect indication. Details on Diameter authorization path set-up are given in section 2.9 of [RFC6733]. Section 13 of [RFC6733] provides recommendations on how to authenticate and secure each peer-to-peer connection (using on TLS, DTLS or IPsec) along the way, thus permitting the necessary hop-by-hop authorization checks.

Although it is assumed that the administrative domains are secure, a compromised Diameter node acting as Realm-Based Redirect Server would be able to redirect a large number of Diameter requests towards a victim domain which would then be flooded with undesired Diameter requests. Such an attack is nevertheless discouraged by the use of secure Diameter peer-to-peer connections and authorization checks, since these would enable a potential victim domain to discover from where an attack is coming. That in itself, however, does not prevent such a DoS attack.

Because realm-based redirection defined in this document implies that the Destination-Realm AVP in a client-initiated request can be changed by a Diameter proxy in the path between the client and the server, any cryptographic algorithm that would use the Destination-Realm AVP as input to the calculation performed by the client and the server would be broken by this form of redirection. Application specifications that would rely on such cryptographic algorithm SHOULD NOT incorporate this realm-based redirection.

## 5. IANA Considerations

This specification adds a new AVP code [TBD2] Redirect-Realm in the AVP Code registry under Authentication, Authorization, and Accounting (AAA) Parameters.

This specification allocates a new Result-Code value `DIAMETER_REALM_REDIRECT_INDICATION` (3xxx TBD1) in the Result-Code AVP Values (code 268) - Protocol Errors registry under Authentication, Authorization, and Accounting (AAA) Parameters.

## 6. Acknowledgements

Glen Zorn, Sebastien Decugis, Wolfgang Steigerwald, Mark Jones, Victor Fajardo, Jouni Korhonen, Avi Lior, and Lionel Morand contributed comments that helped to shape this document. As shepherd, Lionel contributed a second set of comments that added polish to the document before it was submitted to the IESG. Benoit Claise picked up additional points which were quickly resolved with Lionel's help. During IETF Last Call Review, Enrico Marocco picked up some important editorial corrections. Stefan Winter contributed text on the use of S-NAPTR as an alternative method of realm-based redirection already specified in [RFC6733]. Derek Atkins performed a review on behalf of the Security Directorate. Lionel noted one more correction.

Finally, this document benefited from comments and discussion raised by IESG members Stewart Bryant, Stephen Farrell, Barry Leiba, Pete Resnick, Jaari Arkko, and Sean Turner during IESG review.

The authors are very grateful to Lionel Morand for his active role as document shepherd. At each stage, he worked to summarize and resolve comments, making the editor's role easy. Thank you.

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC6733] Fajardo, V., Arkko, J., Loughney, J., and G. Zorn, "Diameter Base Protocol", RFC 6733, October 2012.

### 7.2. Informative References

- [RFC3958] Daigle, L. and A. Newton, "Domain-Based Application Service Location Using SRV RRs and the Dynamic Delegation Discovery Service (DDDS)", RFC 3958, January 2005.

## Authors' Addresses

Tina Tsou  
Huawei Technologies (USA)  
2330 Central Expressway  
Santa Clara, CA 95050  
USA

Phone: +1 408 330 4424  
Email: Tina.Tsou.Zouting@huawei.com  
URI: <http://tinatsou.weebly.com/contact.html>

Ruibing Hao  
Comcast Cable  
One Comcast Center  
Philadelphia, PA 19103  
USA

Phone: +1 215 286 3991(O)  
Email: Ruibing\_Hao@cable.comcast.com

Tom Taylor (editor)  
Huawei Technologies  
Ottawa  
Canada

Email: tom.taylor.stds@gmail.com