

PCP Working Group
Internet-Draft
Intended status: Informational
Expires: September 7, 2011

Z. Cao
G. Chen
H. Deng
T. Sun
China Mobile
March 6, 2011

Requirements for Always Online Applications
draft-cao-pcp-mobapp-online-00

Abstract

This document discusses several requirements for always online mobile applications which reveals that PCP only solution does not fill the gap.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 7, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
1.1. Conventions used in this document	3
2. Scenario and Problems	3
3. Requirements for Always-online Mobile Applications	4
3.1. R1: Support for NAT and Firewall State Keep-alive	4
3.2. R2: Keep the State on Mobile App Server	4
3.3. R3: Keep the State on Mobile Network Gateway	4
3.4. R4: Relieve Burden on Air Interface	5
4. Security Considerations	5
5. IANA Considerations	5
6. Normative References	5
Authors' Addresses	5

1. Introduction

This document discusses several requirements for always online mobile applications which reveals that PCP only solution does not fill the gap.

1.1. Conventions used in this document


The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

2. Scenario and Problems

Figure 1 depicts the scenario of the mobile network environment. BS is the radio Base Station which provides wireless connectivity to the MN. The MNG/FW is the MN's default router which provides IP address management and NAT/Firewall functionality. The Border Router (BR) as the name implies, borders the Internet for the mobile network. The BR does not perform subscriber management for the mobile network. The mobile application server is server on the Internet that provides application layer service to the MN.

To make the mobile application behave like always online, there are several states that need to be kept. Below, we take Instant Message applications as an example,

1. Mobile App Server: the server needs to know if the mobile client is still active and if the mobile node is still on-line. Mobile application developers always make the mobile client send keep alive messages at an interval.
2. NAT state: The GW/FW needs to keep the NAT binding state for the TCP/UDP mappings. Once the NAT states staled, the mobile application server is not able to push messages to the mobile client.
3. IP address state: the mobile network normally uses the so called "packet data protocol (PDP)" to manage the IP connection with the MN.
4. Wireless Channel State: when packets are ready, the mobile node needs to acquire the wireless channel in order to receive or transmit those packet.



MNG: Mobile Network Gateway

FW: Firewall

BR: Border Router

Figure 1: Mobile Client/Server Applications

3. Requirements for Always-online Mobile Applications

The requirements that need to be addressed by an always-online mobile applications.

3.1. R1: Support for NAT and Firewall State Keep-alive

Mapping states on the NAT box or Firewall should be retained in order to make the MN visible and reachable from outside. PCP [I-D.ietf-pcp-base] is an instant solution this problem, however it does not take into account the other problems as list below.

3.2. R2: Keep the State on Mobile App Server

The mobile application server needs to keep track of the mobile node in order to know the status of the mobile application. For example, mobile Instant Message servers need to know the MN's presence status and notify their friends accordingly.

Note: most mobile applications send keep alive messages between the MN and the server in order to keep the state on both the App Server and the NAT/FW.

3.3. R3: Keep the State on Mobile Network Gateway

The IP connection between the MN and Mobile Network Gateway (MNG) is managed by a certain Packet Data Protocol (PDP) in the mobile network. The MNG frequently releases the resources and state of IP connection after a setup timeout. In order to make the mobile applications always online, the state on the MNG should be

maintained.

3.4. R4: Relieve Burden on Air Interface

In order to maintain any states mentioned above, it necessarily send many small packets between the MN and MNG or MN and the APP Server which incurs a huge burden on the air interface. Whenever transmitting packets, one dedicated channel is required. When the channel is released, the paging procedure is triggered. Both of these incur a lot of signalling on the air interface. It is highly indispensable to relieve the burden on air interface.

4. Security Considerations

TBD.

5. IANA Considerations

This document does not require any IANA actions.

6. Normative References

[I-D.ietf-pcp-base]

Wing, D., Cheshire, S., Boucadair, M., Penno, R., and F. Dupont, "Port Control Protocol (PCP)", draft-ietf-pcp-base-06 (work in progress), February 2011.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

Authors' Addresses

Zhen Cao
China Mobile
Unit2, 28 Xuanwumenxi Ave,Xuanwu District
Beijing 100053
China

Email: zehn.cao@gmail.com

Gang Chen
China Mobile
Unit2, 28 Xuanwumenxi Ave,Xuanwu District
Beijing 100053
China

Email: chengang@chinamobile.com

Hui Deng
China Mobile
Unit2, 28 Xuanwumenxi Ave,Xuanwu District
Beijing 100053
China

Email: denghui@chinamobile.com

Tao Sun
China Mobile
Unit2, 28 Xuanwumenxi Ave,Xuanwu District
Beijing 100053
China

Email: suntao@chinamobile.com

