

Networking Working Group  
Internet-Draft  
Intended status: BCP  
Expires: September 14, 2011

O. Gnawali  
P. Levis  
Stanford University  
March 13, 2011

Recommendations for Efficient Implementation of RPL  
draft-gnawali-roll-rpl-recommendations-01

Abstract

RPL is a flexible routing protocol applicable to a wide range of Low Power and Lossy Networks. To enable this wide applicability, RPL provides many configuration options and gives implementers choices on how to implement various components of RPL. Drawing on our experiences, we distill the design choices and configuration parameters that lead to efficient RPL implementations and operations.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at  
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on September 14, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the BSD License.

## Table of Contents

1. Introduction . . . . .	3
2. Terminology . . . . .	3
3. Set the Minimum Trickle Interval with Care . . . . .	3
4. Use Large Maximum Trickle Interval . . . . .	4
5. Use Small Trickle Redundancy Constant . . . . .	4
6. Poison Route Sparingly . . . . .	4
7. Preserve Neighbor Information . . . . .	4
8. Slow-Down Datapath Traffic During Path Inconsistency . . . . .	4
9. Choose Better Path Cost Over Route Stability . . . . .	5
10. Acknowledgements . . . . .	5
11. IANA Considerations . . . . .	5
12. Security Considerations . . . . .	5
13. References . . . . .	5
13.1. Normative References . . . . .	5
13.2. Informative References . . . . .	5
Authors' Addresses . . . . .	6

## 1. Introduction

RPL [I-D.ietf-roll-rpl] is a routing protocol that is applicable in a wide range of settings in networks characterized by low power and lossy links (LLN). Because RPL is designed to work in a wide range of settings, it offers many configuration parameters and choices in how different mechanisms are implemented. This flexibility is essential to ensure the wide applicability of this protocol.

One can take advantage of this flexibility to implement and configure RPL in the most efficient way for a given network. However, it is easy to inadvertently configure RPL to work inefficiently in the network. These design choices must be made carefully drawing on implementation and operational experiences.

In this document, we describe aspects of configuration and mechanisms that impact the performance of RPL. We hope these descriptions serve as guidelines and best practices for RPL implementers and enables them to understand why certain design and configuration choices are favored over others.

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

This terminology used in this document is consistent with the terminologies described in [I-D.ietf-roll-terminology], [I-D.ietf-roll-rpl], and [I-D.ietf-roll-routing-metrics].

This document does not introduce new terms.

## 3. Set the Minimum Trickle Interval with Care

The minimum Trickle interval determines the fastest rate at which RPL will send DIOs. It is not useful to have multiple DIOs in the transmit queue at a given node. The information in the older DIOs is likely already stale when the new DIO is generated. In systems that cannot cancel the packets that are already in the queue, it is advisable to set the minimum interval to be much larger than the minimum link layer packet time.

#### 4. Use Large Maximum Trickle Interval

The maximum Trickle interval determines the slowest rate at which RPL will send DIOs. It is recommended that the maximum interval is set to several hours. A large interval does not necessarily make RPL less agile or the routing information stale. Trickle will operate at a rate between the minimum and maximum interval depending on the dynamics in the network.

#### 5. Use Small Trickle Redundancy Constant

If a node receives more DIOs than the redundancy constant, it does not transmit, i.e., suppresses, its DIO. The rationale for this suppression is that the additional DIOs do not help discover new or better paths if certain number of DIOs have already been transmitted in the neighborhood of a node. In general, the smaller this number the more efficient the route discovery. Setting this value too small can lead to network partitioning as many nodes will suppress their DIOs and will not be discovered. A constant of 3-5 has been found adequate in deployments.

#### 6. Poison Route Sparingly

It is often not necessary for a node to poison a route explicitly by advertising a rank of INFINITY. With datapath validation, it is easy to detect a loop and coupled with adaptive beaconing, the routes can be repaired quickly without additional explicit mechanism for route poisoning. Poisoning the route does not prevent loops because the control packet can get dropped on the lossy link.

#### 7. Preserve Neighbor Information

The neighborhood information is useful even when a node detects that it has lost a route. It is recommended that the nodes not flush the entire or subset of the neighbor table even when a node loses its route or detects a loop. It is sufficient to mark the nodes in the table with the updated information that resulted in route loss or loops, e.g., marking the particular parent with a rank of INFINITY.

#### 8. Slow-Down Datapath Traffic During Path Inconsistency

When a node detects that a path is inconsistent through datapath validation, it tasks the control plane to repair the topology and make it consistent. During this time, although the route is

available, it is advisable that the data packets are sent at lower rates to reduce contention with the control packets. This slow-down can increase data packet latency or lead to queue overflow.

#### 9. Choose Better Path Cost Over Route Stability

With bursty links, a link metric designed to reflect link quality accurately can change rapidly. Other link metrics may also change rapidly. As a result, the path cost computed using these agile metrics can change rapidly. Selecting the best path then implies frequent parent changes. Route flapping is not detrimental to the performance of many network protocols such as sensor data collection over UDP. Hence, oftentimes, it is better to optimize for path cost than for path stability.

#### 10. Acknowledgements

Thanks to Ulrich Herberg and Mukul Goyal for valuable comments.

#### 11. IANA Considerations

None.

#### 12. Security Considerations

Security considerations to be developed in accordance to the output of the WG.

#### 13. References

##### 13.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

##### 13.2. Informative References

[I-D.ietf-roll-routing-metrics]  
Vasseur, J. and D. Networks, "Routing Metrics used for Path Calculation in Low Power and Lossy Networks", draft-ietf-roll-routing-metrics-01 (work in progress), October 2009.

[I-D.ietf-roll-rpl]

Winter, T., Thubert, P., Brandt, A., Clausen, T., Hui, J.,  
Kelsey, R., Levis, P., Pister, K., Struik, R., and J.  
Vasseur, "RPL: IPv6 Routing Protocol for Low power and  
Lossy Networks", draft-ietf-roll-rpl-18 (work in  
progress), February 2011.

[I-D.ietf-roll-terminology]

Vasseur, J., "Terminology in Low power And Lossy  
Networks", draft-ietf-roll-terminology-01 (work in  
progress), May 2009.

Authors' Addresses

Omprakash Gnawali  
Stanford University  
S255 Clark Center, 318 Campus Drive  
Stanford, CA 94305  
USA

Phone: +1 650 725 6086  
Email: [gnawali@cs.stanford.edu](mailto:gnawali@cs.stanford.edu)

Philip Levis  
Stanford University  
358 Gates Hall, Stanford University  
Stanford, CA 94305  
USA

Email: [pal@cs.stanford.edu](mailto:pal@cs.stanford.edu)

