

Internet Engineering Task Force  
Internet-Draft  
Intended status: Standards Track  
Expires: July 23, 2011

S. Harnedy  
Booz Allen Hamilton  
R. Cole  
US Army CERDEC  
I. Chakeres  
CenGen  
January 19, 2011

Definition of Managed Objects for the DYMO Manet Routing Protocol  
draft-ietf-manet-dymo-mib-04

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring aspects of the DYMO routing process. The DYMO-MIB also reports state information, performance information, and notifications. In addition to configuration, this additional state, performance and notification information is useful to management operators troubleshooting DYMO routing problems.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 23, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	3
2. The Internet-Standard Management Framework . . . . .	3
3. Conventions . . . . .	3
4. Overview . . . . .	3
4.1. DYMO Management Model . . . . .	4
4.2. Terms . . . . .	5
5. Structure of the MIB Module . . . . .	5
5.1. Textual Conventions . . . . .	6
5.2. The Configuration Group . . . . .	6
5.3. The State Group . . . . .	7
5.3.1. Routing Table . . . . .	7
5.4. The Performance Group . . . . .	7
5.5. The Notifications Group . . . . .	8
6. Relationship to Other MIB Modules . . . . .	8
6.1. Relationship to the SNMPv2-MIB . . . . .	9
6.2. MIB modules required for IMPORTS . . . . .	9
7. Definitions . . . . .	9
8. Security Considerations . . . . .	35
9. IANA Considerations . . . . .	37
10. Contributors . . . . .	37
11. Acknowledgements . . . . .	38
12. References . . . . .	38
12.1. Normative References . . . . .	38
12.2. Informative References . . . . .	38
Appendix A. Change Log . . . . .	39
Appendix B. Open Issues . . . . .	40
Appendix C. . . . .	40

## 1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring aspects of a Dynamic MANET On-demand (DYMO) routing [I-D.ietf-manet-dymo] process. The DYMO-MIB also reports state information, performance metrics, and notifications. In addition to configuration, this additional state, performance and notification information is useful to management stations troubleshooting routing problems.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

## 3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

## 4. Overview

The Dynamic MANET On-demand (DYMO) routing protocol [I-D.ietf-manet-dymo] is intended for use by mobile nodes in wireless, multihop networks. DYMO determines unicast routes among DYMO routers within the network in an on-demand fashion, offering improved convergence in dynamic topologies.

A DYMO router's MIB contains DYMO process configuration parameters (e.g. interfaces), state information (e.g. sequence number), performance counters (e.g. number of control messages), and notifications.


#### 4.1. DYMO Management Model

This section describes the management model for the DYMO routing protocol.

The MIB is comprised of four groups, i.e., Notifications, Configuration, State and Performance. The configuration of the managed devices is controlled by the objects in the Configuration Group. These are divided into Nodal and Interface objects. The bulk of the DYMO configuration is in the Nodal objects which control protocol behavior. The Interface objects merely identify/configure interfaces to enable DYMO routing over their interface. The Nodal objects are further divided into routing (or protocol) objects and Gateway objects. Gateway objects define other routing prefixes for which the node acts as a routing proxy on behalf of these non-local prefixes.

The Configuration Objects drive the behavior of the managed DYMO device and hence determines the information in the remaining groups, i.e., State, Performance and Notifications. The State objects primarily present the resulting forwarding table objects. The Performance group primarily is comprised of counters for monitoring the number of DYMO routing messages received locally, per node and per interface. The Notifications group contains objects which monitor changes to the interface configuration and the gateway prefixes configuration.

See the below diagram outlining the DYMO-MIB device management model.



#### 4.2. Terms

The following definitions apply throughout this document:

- o Configuration Objects - switches, tables, objects which are initialized to default settings or set through the management interface defined by this MIB.
- o Tunable Configuration Objects - objects whose values affect timing or attempt bounds on the DYMO protocol.
- o State Objects - automatically generated values which define the current operating state of the DYMO protocol process in the router.
- o Performance Objects - automatically generated values which help an operator or automated tool to assess the performance of the DYMO protocol process on the router and the overall routing performance within the DYMO routing domain.

#### 5. Structure of the MIB Module

This section presents the structure of the DYMO MIB module. The objects are arranged into the following groups:

- o dymoMIBNotifications - defines the notifications associated with the DYMO-MIB. These are currently limited to notifications of interface state changes and gateway prefix changes.

- o dymoMIBObjects - defines the objects forming the basis for the DYMO-MIB. These objects are divided up by function into the following groups:
  - o
    - \* Configuration Group - This group contains the DYMO objects that configure specific options that determine the overall performance and operation of the routing protocol for the router device and its interfaces.
    - \* State Group - Contains information describing the current state of the DYMO process such as the DYMO routing table.
    - \* Performance Group - Contains objects which help to characterize the performance of the DYMO process, typically statistics counters. There are two types of DYMO statistics: global counters and per interface counters.
- o dymoMIBConformance - defines minimal and full conformance of implementations to this DYMO-MIB.

#### 5.1. Textual Conventions

The textual conventions used in the DYMO-MIB are as follows. The RowStatus and TruthValue textual conventions are imported from RFC 2579 [RFC2579]. The DymoInterfaceOperStatus is defined within the DYMO-MIB. This contains the current operational status of the DYMO interface.

#### 5.2. The Configuration Group

The DYMO device is configured with a set of controls. The list of configuration controls for the DYMO device follow.

Protocol Configuration Parameters:

- o DID
- o MSG\_HOPLIMIT
- o ROUTE\_TIMEOUT
- o ROUTE\_AGE\_MIN\_TIMEOUT
- o ROUTE\_SEQNUM\_AGE\_MAX\_TIMEOUT

- o ROUTE\_USED\_TIMEOUT
- o ROUTE\_DELETE\_TIMEOUT
- o ROUTE\_RREQ\_WAIT\_TIME
- o UNICAST\_MESSAGE\_SENT\_TIMEOUT
- o MSG\_HOPLIMIT
- o DISCOVERY\_ATTEMPTS\_MAX

Protocol Configuration Tables:

- o Responsible Hosts - If RESPONSIBLE\_ADDRESSES is set to other than self address, then the DYMO router must be configured with the set of host addresses for which it is to generate RREP messages.
- o Interfaces - If DYMO\_INTERFACES is set to other than all, then the DYMO router must be told which interfaces to run the DYMO protocol over. This is a table containing the interfaces and associated information.

### 5.3. The State Group

The State Subtree reports current state information. State information from the DYMO-MIB is primarily contained in the 'Routing' Table.

#### 5.3.1. Routing Table

The DYMO routing table contains information related to IP forwarding entries found by the node's DYMO processes.

### 5.4. The Performance Group

The Performance subtree reports primarily counters that relate to DYMO protocol activity. The DYMO performance objects consists of per node and per interface objects:

- o OwnSequenceNumber
- o RREQ initiated
- o RREQ sent
- o RREQ received

- o RREP initiated
- o RREP sent
- o RREP received
- o RRER initiated
- o RRER sent
- o RRER received
- o Per interface statistics table with the following entries:
  - o
    - \* RREQ initiated
    - \* RREQ sent
    - \* RREQ received
    - \* RREP initiated
    - \* RREP sent
    - \* RREP received
    - \* RRER initiated
    - \* RRER sent
    - \* RRER received

#### 5.5. The Notifications Group

The Notifications Subtree contains the list of notifications supported within the DYMO-MIB and their intended purpose or utility. This group is currently contains two notification objects, one related to status changes in DYMO interfaces and one related to changes in the gateway prefixes table.

#### 6. Relationship to Other MIB Modules

The text of this section specifies the relationship of the MIB modules contained in this document to other standards, particularly to standards containing other MIB modules. Definitions imported from other MIB modules and other MIB modules that SHOULD be implemented in



conjunction with the MIB module contained within this document are identified in this section.

#### 6.1. Relationship to the SNMPv2-MIB

The 'system' group in the SNMPv2-MIB [RFC3418] is defined as being mandatory for all systems, and the objects apply to the entity as a whole. The 'system' group provides identification of the management entity and certain other system-wide data. The DYMO-MIB does not duplicate those objects.

#### 6.2. MIB modules required for IMPORTS

The DYMO-MIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], INET-ADDRESS-MIB [RFC4001] and IF-MIB [RFC2863].

### 7. Definitions

```
MANET-DYMO-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Counter32, Integer32, Unsigned32, mib-2
        FROM SNMPv2-SMI                                -- [RFC2578]

    TEXTUAL-CONVENTION, RowStatus, TruthValue
        FROM SNMPv2-TC                                -- [RFC2579]

    MODULE-COMPLIANCE, OBJECT-GROUP,
    NOTIFICATION-GROUP
        FROM SNMPv2-CONF                                -- [RFC2580]

    InetAddress, InetAddressType,
    InetAddressPrefixLength
        FROM INET-ADDRESS-MIB                          -- [RFC4001]

    InterfaceIndexOrZero
        FROM IF-MIB                                    -- [RFC2863]
;

```

```
manetDymoMIB MODULE-IDENTITY
    LAST-UPDATED "201101191200Z" -- January 19, 2011
    ORGANIZATION "IETF MANET Working Group"
    CONTACT-INFO
        "WG E-Mail: manet@ietf.org

```

WG Chairs: ian.chakeres@gmail.com  
jmacker@nrl.navy.mil

Editors: Sean Harnedy  
Booz Allen Hamilton  
333 City Boulevard West  
Orange, CA 92868  
USA  
+1 714 938-3898  
harnedy\_sean@bah.com

Robert G. Cole  
US Army CERDEC  
Space and Terrestrial Communications  
328 Hopkins Road  
Aberdeen Proving Ground, MD 21005  
USA  
+1 410 278-6779  
robert.g.cole@us.army.mil

Ian D Chakeres  
CenGen  
9250 Bendix Road North  
Columbia, Maryland 21045  
USA  
ian.chakeres@gmail.com"

#### DESCRIPTION

"This MIB module contains managed object definitions for the Dynamic MANET On-demand (DYMO) routing protocol as defined in: Chakeres, I., and C. Perkins, Dynamic MANET On-demand (DYMO) Routing, draft-ietf-manet-dymo-21, July 26, 2010.

Copyright (C) The IETF Trust (2008). This version of this MIB module is part of RFC xxxx; see the RFC itself for full legal notices."

#### -- Revision History

REVISION "201101191200Z" -- January 19, 2011

#### DESCRIPTION

"Fifth draft of this MIB module published as draft-ietf-manet-dymo-mib-04.txt.

Changes include:

- Incorporated the DYMO ID by adding Instance Table.
- Added dymoSetNotification for improved control of DYMO Notifications.

```
- Updated various object names to be consistent
  with current draft-ietf-manet-dymo-21.
"
REVISION      "200910251200Z"    -- October 25, 2009
DESCRIPTION
  "Fourth draft of this MIB module published as
  draft-ietf-manet-dymo-mib-03.txt.
  - Minor changes to textual material, including
    additions to the IMPORTS text.
  - Added DEFVAL clauses to all read-write
    configuration objects with defaults identified
    in the DYMO draft."
REVISION      "200902241200Z"    -- February 24, 2009
DESCRIPTION
  "Third draft of this MIB module published as
  draft-ietf-manet-dymo-mib-02.txt.
  - Minor changes to dymoInterfacesTable and
    dymoResponsibleAddrTable.
  - Added global dymoAdminStatus and interface
    specific dymoIfAdminStatus.
  - Imported InterfaceIndexOrZero type from
    IF-MIB."
REVISION      "200811031200Z"    -- November 03, 2008
DESCRIPTION
  "Second draft of this MIB module published as
  draft-ietf-manet-dymo-mib-01.txt. Minor changes to
  dymoInterfacesTable and dymoResponsibleAddrTable."
REVISION      "200805141200Z"    -- May 14, 2008
DESCRIPTION
  "Initial draft of this MIB module published as
  draft-ietf-manet-dymo-mib-00.txt."
-- RFC-Editor assigns XXXX
::= { mib-2 999 }    -- to be assigned by IANA

--
-- TEXTUAL CONVENTIONS
--

Status ::= TEXTUAL-CONVENTION
  STATUS      current
  DESCRIPTION
    "An indication of the operability of a DYMO
    function or feature.  For example, the status
    of an interface: 'enabled' indicates that
    it is willing to communicate with other DYMO routers,
    and 'disabled' indicates that it is not."
  SYNTAX      INTEGER { enabled (1), disabled (2) }
```

```
--
-- Top-Level Object Identifier Assignments
--

dymoMIBNotifications OBJECT IDENTIFIER ::= { manetDymoMIB 0 }
dymoMIBObjects        OBJECT IDENTIFIER ::= { manetDymoMIB 1 }
dymoMIBConformance    OBJECT IDENTIFIER ::= { manetDymoMIB 2 }

--
-- dymoConfigurationGroup
--
-- This group contains the DYMO objects that configure specific
-- options that determine the overall performance and operation
-- of the routing protocol for the router device and its
-- interfaces.
--

dymoConfigurationGroup OBJECT IDENTIFIER ::= { dymoMIBObjects 1 }

--
-- DYMO Global Router Configuration Group
--

dymoRouterConfigGroup OBJECT IDENTIFIER ::= {dymoConfigurationGroup 1}

dymoInstanceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DymoInstanceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The DYMO Instance Table describes the DYMO
         ...."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
         I., and C. Perkins, July 2010. The DID."
    ::= { dymoRouterConfigGroup 1 }

dymoInstanceEntry OBJECT-TYPE
    SYNTAX      DymoInstanceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The DYMO instance entry describes one DYMO
         process as indexed by its DID."
    INDEX { dymoInstanceIndex }
    ::= { dymoInstanceTable 1 }

DymoInstanceEntry ::=
```

```
SEQUENCE {
    dymoInstanceIndex
        Integer32,
    dymoInstanceId
        Integer32,
    dymoInstanceAdminStatus
        Status,
    dymoInstanceRowStatus
        RowStatus
}

dymoInstanceIndex OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The instance index for this DYMO process."
    ::= { dymoInstanceEntry 1 }

dymoInstanceId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The DYMO ID of this instance of the
         DYMO process."
    ::= { dymoInstanceEntry 2 }

dymoInstanceAdminStatus OBJECT-TYPE
    SYNTAX      Status
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The administrative status of this DYMO
         process in the router. Multiple processes are
         allowed. The value 'enabled' denotes that the
         DYMO Process is active on at least one interface;
         'disabled' disables it on all interfaces.

         This object is persistent and when written
         the entity SHOULD save the change to non-volatile storage."
    ::= { dymoInstanceEntry 3 }

dymoInstanceRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
```

DESCRIPTION  
"This object permits management of the table  
by facilitating actions such as row creation,  
construction, and destruction. The value of  
this object has no effect on whether other  
objects in this conceptual row can be  
modified."  
::= { dymoInstanceEntry 4 }

dymoMaxHopLimit OBJECT-TYPE  
SYNTAX Unsigned32 (0..255)  
UNITS "hops"  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
"The maximum number of hops. The suggested value  
default is 10 hops. This is the DYMO MSG\_HOPLIMIT  
parameter value."  
REFERENCE  
"Dynamic MANET On-demand (DYMO) Routing, Chakeres,  
I., and C. Perkins, July 2010. Table 2 Suggested  
Parameter Values."  
DEFVAL { 10 }  
::= { dymoRouterConfigGroup 2 }

dymoRouteTimeout OBJECT-TYPE  
SYNTAX Unsigned32 (1..65535)  
UNITS "milliseconds"  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
"The route timeout value. The suggested default  
value is 5000 milliseconds. This is the  
DYMO ROUTE\_TIMEOUT parameter value."  
REFERENCE  
"Dynamic MANET On-demand (DYMO) Routing, Chakeres,  
I., and C. Perkins, July 2010. Table 2 Suggested  
Parameter Values."  
DEFVAL { 5000 }  
::= { dymoRouterConfigGroup 3 }

dymoRouteAgeMinTimeout OBJECT-TYPE  
SYNTAX Unsigned32 (1..65535)  
UNITS "milliseconds"  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
"The minimum route age timeout value. The

suggested default value is 1000 milliseconds.  
This is the DYMO ROUTE\_AGE\_MIN\_TIMEOUT parameter value."

REFERENCE  
"Dynamic MANET On-demand (DYMO) Routing, Chakeres, I., and C. Perkins, July 2010. Table 2 Suggested Parameter Values."

DEFVAL { 1000 }

::= { dymoRouterConfigGroup 4 }

dymoRouteSeqnumAgeMaxTimeout OBJECT-TYPE  
SYNTAX Unsigned32 (1..65535)  
UNITS "milliseconds"  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
"The maximum route age timeout value. The suggested default value is 60,000 milliseconds. This is the DYMO ROUTE\_SEQNUM\_AGE\_MAX\_TIMEOUT parameter value."  
REFERENCE  
"Dynamic MANET On-demand (DYMO) Routing, Chakeres, I., and C. Perkins, July 2010. Table 2 Suggested Parameter Values."  
DEFVAL { 60000 }

::= { dymoRouterConfigGroup 5 }

dymoRouteUsedTimeout OBJECT-TYPE  
SYNTAX Unsigned32 (1..65535)  
UNITS "milliseconds"  
MAX-ACCESS read-write  
STATUS current  
DESCRIPTION  
"The route used timeout value. The suggested default value is to set this to the dymoRouteTimeout object value (whose default is 5000 milliseconds). This is the DYMO ROUTE\_USED\_TIMEOUT parameter value."  
REFERENCE  
"Dynamic MANET On-demand (DYMO) Routing, Chakeres, I., and C. Perkins, July 2010. Table 2 Suggested Parameter Values."  
DEFVAL { 5000 }

::= { dymoRouterConfigGroup 6 }

dymoRouteDeleteTimeout OBJECT-TYPE  
SYNTAX Unsigned32 (1..65535)

```

UNITS          "milliseconds"
MAX-ACCESS     read-write
STATUS         current
DESCRIPTION
    "The route delete timeout value. The
    suggested default value is 2 * dymoRouteTimeout
    value (which is equal to 10000 milliseconds
    if using the default value for the
    dymoRouteTimeout value). This is the
    DYMO ROUTE_DELETE_TIMEOUT parameter value."
REFERENCE
    "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
    I., and C. Perkins, July 2010. Table 2 Suggested
    Parameter Values."
DEFVAL { 10000 }
::= { dymoRouterConfigGroup 7 }

dymoRouteRreqWaitTime OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS        "milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The Route Request wait time. The suggested default
        value is 2000 milliseconds. This is the DYMO
        ROUTE_RREQ_WAIT_TIME parameter value."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
        I., and C. Perkins, July 2010. Table 2 Suggested
        Parameter Values."
    DEFVAL { 2000 }
    ::= { dymoRouterConfigGroup 8 }

dymoDiscoveryAttemptsMax OBJECT-TYPE
    SYNTAX      Unsigned32 (1..16)
    UNITS        "attempts"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "The number of Route Request retry attempts. The
        suggested default value is 3. This is the
        DYMO DISCOVERY_ATTEMPTS_MAX parameter value."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
        I., and C. Perkins, July 2010. Table 2 Suggested
        Parameter Values."
    DEFVAL { 3 }
    ::= { dymoRouterConfigGroup 9 }
```



```
dymoUnicastMsgSentTimeout OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS       "milliseconds"
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
        "The message sent timeout value for unicast packets.
        The suggested default value is 1000 milliseconds.
        This is the DYMO UNICAST_MESSAGE_SENT_TIMEOUT
        parameter value."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
        I., and C. Perkins, July 2010. Table 2 Suggested
        Parameter Values."
    DEFVAL { 1000 }
 ::= { dymoRouterConfigGroup 10 }
```

```
--
-- DYMO Interfaces Configuration Table
--
```

```
dymoInterfaceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DymoInterfaceEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The DYMO Interface Table describes the DYMO
        interfaces that are participating in the
        DYMO routing protocol. The ifIndex is from
        the interfaces group defined in the Interfaces
        Group MIB."
    REFERENCE
        "RFC 2863 - The Interfaces Group MIB, McCloghrie,
        K., and F. Kastenholtz, June 2000."
 ::= { dymoConfigurationGroup 2 }
```

```
dymoInterfaceEntry OBJECT-TYPE
    SYNTAX      DymoInterfaceEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "The DYMO interface entry describes one DYMO
        interface as indexed by its ifIndex."
    INDEX { dymoIfIndex }
 ::= { dymoInterfaceTable 1 }
```

```
DymoInterfaceEntry ::=
    SEQUENCE {
        dymoIfIndex
            InterfaceIndexOrZero,
        dymoIfAdminStatus
            Status,
        dymoIfRowStatus
            RowStatus
    }

dymoIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The ifIndex for this DYMO interface."
    ::= { dymoInterfaceEntry 1 }

dymoIfAdminStatus OBJECT-TYPE
    SYNTAX      Status
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The DYMO interface's administrative status.
        The value 'enabled' denotes that the interface
        is running the DYMO routing protocol.
        The value 'disabled' denotes that the interface is
        external to DYMO."
    ::= { dymoInterfaceEntry 2 }

dymoIfRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object permits management of the table
        by facilitating actions such as row creation,
        construction, and destruction. The value of
        this object has no effect on whether other
        objects in this conceptual row can be
        modified."
    ::= { dymoInterfaceEntry 3 }

--
-- DYMO Responsible Address Table
--
```

```
dymoResponsibleAddrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DymoResponsibleAddrEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The DYMO Responsible Address Table is a
         list of IP address prefixes, and their
         associated prefix length for which the
         DYMO router is responsible."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
         I., and C. Perkins, July 2010. Table 3 Important
         Settings."
    ::= { dymoConfigurationGroup 3 }

dymoResponsibleAddrEntry OBJECT-TYPE
    SYNTAX      DymoResponsibleAddrEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A single host address range. Information
         in this table is persistent and when this object
         is written, the entity SHOULD save the change to
         non-volatile storage."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
         I., and C. Perkins, July 2010. Table 3 Important
         Settings."
    INDEX { dymoResponsibleAddrIndex }
    ::= { dymoResponsibleAddrTable 1 }

DymoResponsibleAddrEntry ::=
    SEQUENCE {
        dymoResponsibleAddrIndex
            Unsigned32,
        dymoResponsibleAddrType
            InetAddressType,
        dymoResponsibleAddr
            InetAddress,
        dymoResponsibleAddrPrefixLen
            InetAddressPrefixLength,
        dymoResponsibleAddrRowStatus
            RowStatus
    }

dymoResponsibleAddrIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
```

```
STATUS      current
DESCRIPTION
    "This object is the index into this table."
 ::= { dymoResponsibleAddrEntry 1 }

dymoResponsibleAddrType OBJECT-TYPE
SYNTAX      InetAddressType
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The type of the dymoResponsibleAddr, as defined
     in the InetAddress MIB [RFC 4001]."
```

```
REFERENCE
    "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
     I., and C. Perkins, July 2010. Table 3 Important
     Settings."
 ::= { dymoResponsibleAddrEntry 2 }

dymoResponsibleAddr OBJECT-TYPE
SYNTAX      InetAddress
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The destination IP address of this route. The type
     of this address is determined by the value of the
     dymoResponsibleAddrType object."
```

```
REFERENCE
    "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
     I., and C. Perkins, July 2010. Table 3 Important
     Settings."
 ::= { dymoResponsibleAddrEntry 3 }

dymoResponsibleAddrPrefixLen OBJECT-TYPE
SYNTAX      InetAddressPrefixLength
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Indicates the number of leading one bits that form the
     mask to be logical-AND'd with the destination address
     before being compared to the value in the dymoResponsibleAddr
     field."
```

```
REFERENCE
    "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
     I., and C. Perkins, July 2010. Table 3 Important
     Settings."
 ::= { dymoResponsibleAddrEntry 4 }

dymoResponsibleAddrRowStatus OBJECT-TYPE
```

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This object permits management of the table
    by facilitating actions such as row creation,
    construction, and destruction. The value of
    this object has no effect on whether other
    objects in this conceptual row can be
    modified."
::= { dymoResponsibleAddrEntry 5 }

--
-- dymoStateGroup
--
--     Contains information describing the current state of the DYMO
--     process such as the DYMO routing table.
--

dymoStateGroup  OBJECT IDENTIFIER ::= { dymoMIBObjects 2 }

dymoCurrentSeqNum  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current DYMO sequence number. The DYMO sequence
        numbers allow nodes to judge the freshness of routing
        information and ensures loop freedom. If the sequence
        number has been assigned to be the largest possible
        number representable as a 16-bit unsigned integer
        (i.e., 65,535), then the sequence number is set to
        256 when incremented. Setting the sequence number
        to 256 allows other nodes to detect that the number
        has rolled over and the node has not lost its sequence
        number (e.g., via reboot)."
    ::= { dymoStateGroup 1 }

--
-- DYMO Routing Table
--

dymoRoutingTable  OBJECT-TYPE
    SYNTAX      SEQUENCE OF DymoRoutingEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

"The DYMO Routing Table describes the current routing information learned via DYMO control messages."

## REFERENCE

"Dynamic MANET On-demand (DYMO) Routing, Chakeres, I., and C. Perkins, July 2010. Table 2 Suggested Parameter Values."

::= { dymoStateGroup 2 }

dymoRoutingEntry OBJECT-TYPE

SYNTAX DymoRoutingEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The DYMO routing entry contains a piece of routing information for a particular set of addresses."

INDEX { dymoRoutingIpAddressType,  
          dymoRoutingIpAddress,  
          dymoRoutingPrefixLen }

::= { dymoRoutingTable 1 }

DymoRoutingEntry ::=

SEQUENCE {  
    dymoRoutingIpAddressType  
        InetAddressType,  
    dymoRoutingIpAddress  
        InetAddress,  
    dymoRoutingPrefixLen  
        InetAddressPrefixLength,  
    dymoRoutingSeqNum  
        Unsigned32,  
    dymoRoutingNextHopIpAddressType  
        InetAddressType,  
    dymoRoutingNextHopIpAddress  
        InetAddress,  
    dymoRoutingNextHopInterface  
        InterfaceIndexOrZero,  
    dymoRoutingForwardingFlag  
        TruthValue,  
    dymoRoutingBrokenFlag  
        TruthValue,  
    dymoRoutingDist  
        Unsigned32  
}

dymoRoutingIpAddressType OBJECT-TYPE

SYNTAX InetAddressType

```
MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "The routing table address IP address type."
REFERENCE
    "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
    I., and C. Perkins, July 2010. Table 3 Important
    Settings."
::= { dymoRoutingEntry 1 }

dymoRoutingIpAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The routing table Inet IPv4 or IPv6 address."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
        I., and C. Perkins, July 2010. Table 3 Important
        Settings."
    ::= { dymoRoutingEntry 2 }

dymoRoutingPrefixLen OBJECT-TYPE
    SYNTAX      InetAddressPrefixLength
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The prefix length. This is a decimal value that
        indicates the number of contiguous, higher-order
        bits of the address that make up the network
        portion of the address."
    REFERENCE
        "Dynamic MANET On-demand (DYMO) Routing, Chakeres,
        I., and C. Perkins, July 2010. Table 3 Important
        Settings."
    ::= { dymoRoutingEntry 3 }

dymoRoutingSeqNum OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The interface sequence number. This
        is the DYMO SeqNum associated with this
        routing information."
    ::= { dymoRoutingEntry 4 }

dymoRoutingNextHopIpAddrType OBJECT-TYPE
```

SYNTAX            InetAddressType  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION  
    "The IP address type of the next hop."  
::= { dymoRoutingEntry 5 }

dymoRoutingNextHopIpAddress OBJECT-TYPE

SYNTAX            InetAddress  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION  
    "The IP address of the next hop."  
::= { dymoRoutingEntry 6 }

dymoRoutingNextHopInterface OBJECT-TYPE

SYNTAX            InterfaceIndexOrZero  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION  
    "The interface ifIndex for sending  
    packets toward the destination route  
    address."  
::= { dymoRoutingEntry 7 }

dymoRoutingForwardingFlag OBJECT-TYPE

SYNTAX            TruthValue  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION  
    "The Forwarding Flag indicates whether  
    this route can be used for forwarding  
    data packets. A value 'true(1)'  
    indicates that this route is being used  
    for forwarding of data packets, while  
    a value 'false(2)' indicates that it is  
    not being used for forwarding."  
::= { dymoRoutingEntry 8 }

dymoRoutingBrokenFlag OBJECT-TYPE

SYNTAX            TruthValue  
MAX-ACCESS       read-only  
STATUS            current  
DESCRIPTION  
    "The Broken Flag indicates whether  
    this Route is broken. This flag is set  
    if the next-hop becomes unreachable or  
    in response to processing a RERR. A value



'true(1)' indicates that this route is broken, while a value 'false(2)' indicates that it is not broken."  
 ::= { dymoRoutingEntry 9 }

dymoRoutingDist OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

UNITS "hops"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The distance to the destination address's DYMO router. This is a metric of the distance a message or piece of information has traversed. The minimum value of distance is the number of IP hops traversed. The maximum value is 65,535.

This parameter is an optional field in the DYMO routing table. If the DYMO Route.Dist is not supported by this device, then this object should be set to '0'."

REFERENCE

"Dynamic MANET On-demand (DYMO) Routing, Chakeres, I., and C. Perkins, April 2008. Section 3 Terminology."

::= { dymoRoutingEntry 10 }

--

-- DYMO Performance Group (Performance Management)

--

-- Contains objects which help to characterize the  
 -- performance of the DYMO process, typically statistics  
 -- counters. There are two types of DYMO statistics:  
 -- global counters and per interface counters.  
 --

dymoPerformanceGroup OBJECT IDENTIFIER ::= { dymoMIBObjects 3 }

dymoGlobalPerfGroup OBJECT IDENTIFIER ::= { dymoPerformanceGroup 1 }

dymoRreqOriginated OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

```
STATUS          current
DESCRIPTION
    "A counter of the number of
    RREQ messages that this DYMO
    device has initiated."
 ::= { dymoGlobalPerfGroup 1 }

dymoRreqForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREQ messages that this DYMO
        device has forwarded, i.e., this
        device neither originated or
        terminated the RREQ message."
 ::= { dymoGlobalPerfGroup 2 }

dymoRreqReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREQ messages that this DYMO
        device has received as the
        target of the message."
 ::= { dymoGlobalPerfGroup 3 }

dymoRrepOriginated OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREP messages that this DYMO
        device has initiated."
 ::= { dymoGlobalPerfGroup 4 }

dymoRrepForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREP messages that this DYMO
        device has forwarded, i.e, this
```

```
        device neither originated or
        terminated the RREP message."
 ::= { dymoGlobalPerfGroup 5 }
```

```
dymoRrepReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A counter of the number of
        RREP messages that this DYMO
        device has received as the
        target of the message."
 ::= { dymoGlobalPerfGroup 6 }
```

```
dymoRrerOriginated OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A counter of the number of
        RRER messages that this DYMO
        device has initiated."
 ::= { dymoGlobalPerfGroup 7 }
```

```
dymoRrerForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A counter of the number of
        RRER messages that this DYMO
        device has forwarded, i.e., this
        device neither originated or
        terminated the RRER message."
 ::= { dymoGlobalPerfGroup 8 }
```

```
dymoRrerReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A counter of the number of
        RRER messages that this DYMO
        device has received as the
        target of the message."
 ::= { dymoGlobalPerfGroup 9 }
```

```
--
-- Per DYMO Interface Performance Table
--

dymoInterfacePerfGroup OBJECT IDENTIFIER ::= {dymoPerformanceGroup 2}

dymoInterfacePerfTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DymoInterfacePerfEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The DYMO Interface Performance Table
        describes the DYMO statistics per
        interface."
    ::= { dymoInterfacePerfGroup 1 }

dymoInterfacePerfEntry OBJECT-TYPE
    SYNTAX      DymoInterfacePerfEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The DYMO Interface Performance entry
        describes the statistics for a particular
        DYMO interface."
    INDEX { dymoIfPerfIfIndex }
    ::= { dymoInterfacePerfTable 1 }

DymoInterfacePerfEntry ::=
    SEQUENCE {
        dymoIfPerfIfIndex
            InterfaceIndexOrZero,
        dymoIfRreqOriginated
            Counter32,
        dymoIfRreqForwarded
            Counter32,
        dymoIfRreqReceived
            Counter32,
        dymoIfRrepOriginated
            Counter32,
        dymoIfRrepForwarded
            Counter32,
        dymoIfRrepReceived
            Counter32,
        dymoIfRrerOriginated
            Counter32,
        dymoIfRrerForwarded
            Counter32,
        dymoIfRrerReceived
```

```
        Counter32
    }

dymoIfPerfIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The ifIndex for this DYMO interface
        that is collecting this set of
        performance management statistics."
    ::= { dymoInterfacePerfEntry 1 }

dymoIfRreqOriginated OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREQ messages that this DYMO
        interface has initiated."
    ::= { dymoInterfacePerfEntry 2 }

dymoIfRreqForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREQ messages that this DYMO
        interface has forwarded, i.e., this
        interface neither originated nor
        terminated the RREQ message."
    ::= { dymoInterfacePerfEntry 3 }

dymoIfRreqReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
        RREQ messages that this DYMO
        interface has received as the
        target of the message."
    ::= { dymoInterfacePerfEntry 4 }

dymoIfRrepOriginated OBJECT-TYPE
    SYNTAX      Counter32
```

```
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "A counter of the number of
     RREP messages that this DYMO
     interface has initiated."
 ::= { dymoInterfacePerfEntry 5 }

dymoIfRrepForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
         RREP messages that this DYMO
         interface has forwarded, i.e., this
         interface neither originated nor
         terminated the RREP message."
 ::= { dymoInterfacePerfEntry 6 }

dymoIfRrepReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
         RREP messages that this DYMO
         interface has received as the
         target of the message."
 ::= { dymoInterfacePerfEntry 7 }

dymoIfRrerOriginated OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
         RRER messages that this DYMO
         interface has initiated."
 ::= { dymoInterfacePerfEntry 8 }

dymoIfRrerForwarded OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of
         RRER messages that this DYMO
```

```
        interface has forwarded, i.e., this
        interface neither originated nor
        terminated the RRER message."
 ::= { dymoInterfacePerfEntry 9 }

dymoIfRrerReceived OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A counter of the number of
        RRER messages that this DYMO
        interface has received as the
        target of the message."
 ::= { dymoInterfacePerfEntry 10 }

--
-- Notifications
--

dymoMIBNotifControl OBJECT IDENTIFIER ::= { dymoMIBNotifications 1 }
dymoMIBNotifObjects OBJECT IDENTIFIER ::= { dymoMIBNotifications 2 }

-- dymoMIBNotifControl

dymoSetNotification OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4))
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "A 4-octet string serving as a bit map for
        the notification events defined by the DYMO
        notifications. This object is used to enable
        and disable specific DYMO notifications where
        a 1 in the bit field represents enabled. The
        right-most bit (least significant) represents
        notification 0.

        This object is persistent and when written
        the entity SHOULD save the change to
        non-volatile storage.
        "
 ::= { dymoMIBNotifControl 1 }
```

```
-- dymoMIBNotifObjects

dymoInstanceAdminStatusChange NOTIFICATION-TYPE
    OBJECTS      { dymoInstanceAdminStatus,
                   dymoInstanceDid
                   }
    STATUS       current
    DESCRIPTION   "This notification is generated when the
                   administrative status of a DYMO process changes."
 ::= { dymoMIBNotifObjects 1 }

dymoInterfaceAdminStatusChange NOTIFICATION-TYPE
    OBJECTS      { dymoIfAdminStatus }
    STATUS       current
    DESCRIPTION   "This notification is generated when the
                   administrative status of a DYMO interface changes."
 ::= { dymoMIBNotifObjects 2 }

dymoResponsibleAddrEntryChange NOTIFICATION-TYPE
    OBJECTS      { dymoResponsibleAddrRowStatus }
    STATUS       current
    DESCRIPTION   "This notification is generated when the status
                   of an entry in the DYMO Responsible Address
                   Table changes. This includes the creation or
                   deletion of a row."
 ::= { dymoMIBNotifObjects 3 }

--
-- Compliance Statements
--

dymoCompliances OBJECT IDENTIFIER ::= { dymoMIBConformance 1 }
dymoMIBGroups   OBJECT IDENTIFIER ::= { dymoMIBConformance 2 }

dymoBasicCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION "The basic implementation requirements for
                 managed network entities that implement
                 the DYMO routing protocol."
    MODULE -- this module
    MANDATORY-GROUPS { dymoConfigObjectsGroup }
 ::= { dymoCompliances 1 }

dymoFullCompliance MODULE-COMPLIANCE
    STATUS current
```



```
DESCRIPTION "The full implementation requirements for managed
             network entities that implement the DYMO routing
             protocol."
MODULE -- this module
MANDATORY-GROUPS { dymoConfigObjectsGroup,
                   dymoStateObjectsGroup,
                   dymoPerfObjectsGroup,
                   dymoNotifObjectsGroup,
                   dymoNotificationGroup }
 ::= { dymoCompliances 2 }

--
-- Units of Conformance
--

dymoConfigObjectsGroup OBJECT-GROUP
  OBJECTS {
    dymoInstanceAdminStatus,
    dymoInstanceDid,
    dymoInstanceRowStatus,
    dymoMaxHopLimit,
    dymoRouteTimeout,
    dymoRouteAgeMinTimeout,
    dymoRouteSeqnumAgeMaxTimeout,
    dymoRouteUsedTimeout,
    dymoRouteDeleteTimeout,
    dymoRouteRreqWaitTime,
    dymoDiscoveryAttemptsMax,
    dymoUnicastMsgSentTimeout,
    dymoIfAdminStatus,
    dymoIfRowStatus,
    dymoResponsibleAddrType,
    dymoResponsibleAddr,
    dymoResponsibleAddrPrefixLen,
    dymoResponsibleAddrRowStatus
  }
  STATUS current
  DESCRIPTION
    "Set of DYMO configuration objects implemented
     in this module."
 ::= { dymoMIBGroups 1 }

dymoStateObjectsGroup OBJECT-GROUP
  OBJECTS {
    dymoCurrentSeqNum,
    dymoRoutingSeqNum,
    dymoRoutingNextHopIpAddrType,
    dymoRoutingNextHopIpAddress,
```

```
        dymoRoutingNextHopInterface,
        dymoRoutingForwardingFlag,
        dymoRoutingBrokenFlag,
        dymoRoutingDist
    }
    STATUS current
    DESCRIPTION
        "Set of DYMO state objects implemented
        in this module."
    ::= { dymoMIBGroups 2 }

dymoPerfObjectsGroup OBJECT-GROUP
    OBJECTS {
        dymoRreqOriginated,
        dymoRreqForwarded,
        dymoRreqReceived,
        dymoRrepOriginated,
        dymoRrepForwarded,
        dymoRrepReceived,
        dymoRrerOriginated,
        dymoRrerForwarded,
        dymoRrerReceived,
        dymoIfRreqOriginated,
        dymoIfRreqForwarded,
        dymoIfRreqReceived,
        dymoIfRrepOriginated,
        dymoIfRrepForwarded,
        dymoIfRrepReceived,
        dymoIfRrerOriginated,
        dymoIfRrerForwarded,
        dymoIfRrerReceived
    }
    STATUS current
    DESCRIPTION
        "Set of DYMO statistic objects implemented
        in this module for performance management."
    ::= { dymoMIBGroups 3 }

dymoNotifObjectsGroup OBJECT-GROUP
    OBJECTS {
        dymoSetNotification
    }
    STATUS current
    DESCRIPTION
        "Set of DYMO notifications objects implemented
        in this module."
    ::= { dymoMIBGroups 4 }
```

```
dymoNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
    dymoInstanceAdminStatusChange,
    dymoInterfaceAdminStatusChange,
    dymoResponsibleAddrEntryChange
  }
  STATUS current
  DESCRIPTION
    "Set of DYMO notifications implemented in this
    module."
 ::= { dymoMIBGroups 5 }

END
```

## 8. Security Considerations

[TODO] Each specification that defines one or more MIB modules MUST contain a section that discusses security considerations relevant to those modules. This section MUST be patterned after the latest approved template (available at <http://www.ops.ietf.org/mib-security.html>). Remember that the objective is not to blindly copy text from the template, but rather to think and evaluate the risks/vulnerabilities and then state/document the result of this evaluation.

[TODO] if you have any read-write and/or read-create objects, please include the following boilerplate paragraph.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o [TODO] writable MIB objects that could be especially disruptive if abused MUST be explicitly listed by name and the associated security risks MUST be spelled out; RFC 2669 has a very good example.
- o [TODO] list the writable tables and objects and state why they are sensitive.

[TODO] else if there are no read-write objects in your MIB module, use the following boilerplate paragraph.

There are no management objects defined in this MIB module that have

a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

[TODO] if you have any sensitive readable objects, please include the following boilerplate paragraph.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o [TODO] you must explicitly list by name any readable objects that are sensitive or vulnerable and the associated security risks MUST be spelled out (for instance, if they might reveal customer information or violate personal privacy laws such as those of the European Union if exposed to unauthorized parties)
- o [TODO] list the tables and objects and state why they are sensitive.

[TODO] discuss what security the protocol used to carry the information should have. The following three boilerplate paragraphs should not be changed without very good reason. Changes will almost certainly require justification during IESG review.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 9. IANA Considerations

[TODO] In order to comply with IESG policy as set forth in <http://www.ietf.org/ID-Checklist.html>, every Internet-Draft that is submitted to the IESG for publication MUST contain an IANA Considerations section. The requirements for this section vary depending what actions are required of the IANA. see RFC4181 section 3.5 for more information on writing an IANA clause for a MIB module document.

[TODO] select an option and provide the necessary details.

Option #1:

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
sampleMIB	{ mib-2 XXX }

Option #2:

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "XXX" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.

Note well: prior to official assignment by the IANA, a draft document MUST use place-holders (such as "XXX" above) rather than actual numbers. See RFC4181 Section 4.5 for an example of how this is done in a draft MIB module.

Option #3:

This memo includes no request to IANA.

## 10. Contributors

This MIB document uses the template authored by D. Harrington which is based on contributions from the MIB Doctors, especially Juergen Schoenwaelder, Dave Perkins, C.M.Heard and Randy Presuhn.

## 11. Acknowledgements

## 12. References

## 12.1. Normative References

- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3418, December 2002.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [I-D.ietf-manet-dymo] Chakeres, I. and C. Perkins, "Dynamic MANET On-demand (DYMO) Routing", draft-ietf-manet-dymo-21 (work in progress), July 2010.

## 12.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

## Appendix A. Change Log

This section identifies the changes that have been made from draft-ietf-manet-dymo-mib-00 .

These changes were made from draft-ietf-manet-dymo-mib-00 to draft-ietf-manet-dymo-mib-01.

1. Only minor changes of a typographic nature, e.g., read-only to read-write on MAX\_ACCESS clauses of a few configuration objects.

These changes were made from draft-ietf-manet-dymo-mib-01 to draft-ietf-manet-dymo-mib-02.

1. Added the ForwardingFlag and BrokenFlag objects to the DYMO Routing Table.
2. Added the TruthValue Textual Convention to handle the new Routing Table objects.
3. Added the DYMO device management model to the introductory sections of this draft.
4. General clean up of the introductory sections of this draft.

These changes were made from draft-ietf-manet-dymo-mib-02 to draft-ietf-manet-dymo-mib-03.

1. Minor changes to the textual material and added to the IMPORTS text in the introductory material.
2. Added DEFVAL clauses to all read-write configuration objects having default values identified in the DYMO specification.

These changes were made from draft-ietf-manet-dymo-mib-03 to draft-ietf-manet-dymo-mib-04.

1. Incorporated the DID into the Configuration Group by changing the dymoAdminStatus object to an Instance Table. This allows for the presence of multiple DYMO processes concurrent on the same router.
2. Added the dymoNotifObjectsGroup and its dymoSetNotifications object to allow for individual control of the DYMO Notifications. Updated the Conformance sections accordingly.
3. Renamed several of the Configuration Objects to be consistent with the naming within the current draft-ietf-manet-dymo-21.

## Appendix B. Open Issues

This section contains the set of open issues related to the development and design of the DYMO-MIB. This section will not be present in the final version of the MIB and will be removed once all the open issues have been resolved.

1. Work on the Security Section. This MIB does have settable objects, but not sensitive objects (true?).
2. Work on the relationship to other MIBs, IF-MIB, NHDP-MIB.
3. Cleanup all the [TODOs] from the MIB template.

## Appendix C.

```
*****
* Note to the RFC Editor (to be removed prior to publication) *
*                                                                 *
* 1) The reference to RFCXXXX within the DESCRIPTION clauses *
* of the MIB module point to this draft and are to be         *
* assigned by the RFC Editor.                                   *
*                                                                 *
* 2) The reference to RFCXXX2 throughout this document point *
* to the current draft-ietf-manet-dymo-xx.txt. This           *
* need to be replaced with the XXX RFC number.                *
*                                                                 *
*****
```

## Authors' Addresses

Sean Harnedy  
Booz Allen Hamilton  
333 City Boulevard West  
Orange, California 92868  
USA

Phone: +1 714 938-3898  
EMail: harnedy\_sean@bah.com



Robert G. Cole  
US Army CERDEC  
328 Hopkins Road, Bldg 245  
Aberdeen Proving Ground, Maryland 21005  
USA

Phone: +1 410 278 6779  
EMail: robert.g.cole@us.army.mil  
URI: <http://www.cs.jhu.edu/~rgcole/>

Ian D Chakeres  
CenGen  
9250 Bendix Road North  
Columbia, Maryland 21045  
USA

EMail: [ian.chakeres@gmail.com](mailto:ian.chakeres@gmail.com)  
URI: <http://www.ianchak.com/>

