

Internet Engineering Task Force
Internet-Draft
Intended status: Standards Track
Expires: November 29, 2011

M. Goyal, Ed.
University of Wisconsin
Milwaukee
E. Baccelli
M. Philipp
INRIA
A. Brandt
Sigma Designs
J. Martocci
Johnson Controls
May 28, 2011

A Compression Format for RPL Control Messages
draft-goyal-roll-rpl-compression-00

Abstract

This document specifies a compression format for RPL ICMPv6 RPL control messages.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 29, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
1.1. Terminology	3
2. RPL ICMPv6 Message Compression	3
3. RPL Base Object Compression	4
3.1. Compressing the DODAG Information Object	4
4. Compressing the RPL Options	6
4.1. DODAG Configuration Option	6
4.2. Metric/Constraint Objects	8
4.2.1. Compressed Node State and Attributes Object	9
4.2.2. Compressed Node Energy Object	9
4.2.3. Compressed Hop Count Object	10
4.2.4. Compressed Throughput Object	10
4.2.5. Compressed Latency Object	10
4.2.6. Compressed ETX Object	10
5. Examples	11
5.1. A DIO With A Configuration Option, A Route Information Option and A Metric Container	11
5.2. A DIO With A Configuration Option, A Route Discovery Option and A Metric Container	12
6. Security Considerations	14
7. IANA Considerations	14
8. References	14
8.1. Normative References	14
8.2. Informative References	14
Authors' Addresses	15

1. Introduction

RPL [I-D.ietf-roll-rpl] is an IPv6 routing protocol for low power and lossy networks. It defines a number of ICMPv6 control messages for its operation. These messages are susceptible to fragmentation when RPL is deployed over a link layer with a small payload (e.g. IEEE 802.15.4, where the MAC payload can be as small as 81 bytes). This document specifies a compression format for ICMPv6 RPL control messages to minimize such fragmentation. This document currently defines the compression format for RPL's DODAG Information Object (DIO) base object, DODAG Configuration Option and some of the Routing Metric/Constraint objects. Later versions of this document may include the compression formats for other RPL messages and options.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Additionally, this document uses terminology from [I-D.ietf-roll-rpl], [I-D.ietf-roll-routing-metrics], [I-D.ietf-roll-p2p-rpl] and [I-D.ietf-6lowpan-hc].

2. RPL ICMPv6 Message Compression

Various fields of a compressed ICMPv6 messages are as follows:

- o Type: 155, as specified in [I-D.ietf-roll-rpl];
- o Code: The Code value of the compressed version of an RPL ICMPv6 message is obtained by setting the 7th bit in the Code value associated with the corresponding uncompressed message. For example, the Code associated with a compressed DODAG Information Object is 0x40.
- o Checksum: The 16-bit Checksum for a compressed RPL message is calculated in the same manner as for the uncompressed message.
- o Base: The Base object carried in the message is compressed in the manner described in Section 3.
- o Option(s): An option carried in a compressed RPL ICMPv6 message MAY be compressed as described in Section 4 or it MAY be carried uncompressed as in an uncompressed message.

3. RPL Base Object Compression

This section defines the compression format for various Base objects associated with RPL ICMPv6 messages.

3.1. Compressing the DODAG Information Object




Figure 1: The Compression Format for DODAG Information Object

The format of a compressed DODAG Information Object (DIO) base object is shown in Figure 1 and consists of the following fields:

- o C: This flag is set to 1 if the 3rd byte of the DIO contains an 8-bit identifier of the "context" that provides values of all elided fields in the DIO base object and the options it contains. Otherwise, this flag is set to 0. The description of the contexts in use in an LLN and how RPL nodes come to know of these contexts is out of scope for this document.
- o I: This flag indicates whether the RPLInstanceID field is elided or not. This flag is set to 1 if the RPLInstanceID field is present inline in the compressed DIO. This flag is set to 0 if the RPLInstanceID field is elided. In this case, the implicit value of the RPLInstanceID depends on the context if present. In the absence of the context, the implicit value of the RPLInstanceID depends on the value of the L flag as discussed next.
- o L: This flag is meaningful only when both C and I flags are 0, i.e. the RPLInstanceID field is elided but no context is identified. In this case, the L flag is set to 1 if the elided RPLInstanceID is local and has implicit value 128. The L flag is set to 0 if the elided RPLInstanceID field is global and has implicit value 0. If either of C and I flag is set to 1, the L flag MUST be set to 0 on transmission and ignored on reception.
- o V: This flag is set to 1 if the Version Number is carried inline in the DIO message. The flag is set to 0 if the Version Number is elided. In this case, the implicit value of the Version Number depends on the context if present. If no context is present, the implicit value of the Version Number is assumed to be zero.

- o R: This flag indicates whether the Rank field in the DIO is shortened or not. This flag is set to 1 if the full 16-bit Rank is present inline in the compressed DIO. The flag is set to 0 if the 4-bit long Ra field contains the rank value.
- o G: This flag indicates whether the byte containing the Grounded, Mode of Operation and DODAG Preference fields is elided or not. This flag is set to 1 if the above-mentioned byte is carried inline. The flag is set to 0, if this byte is elided. In this case, the implicit values of Grounded, Mode of Operation and DODAGPreference fields depend on the context if present. If no context is present, the implicit values of these fields are as follows:
 - * The Grounded flag has implicit value 0, i.e., the DODAG is not grounded.
 - * The Mode of Operation field has implicit value 0, i.e., the DODAG does not maintain any downward routes.
 - * The DODAG Preference field has implicit value 0, i.e., least preferred.
- o T: This flag is set to 1 if the DTSN field is carried inline. The flag is set to 0, if the DTSN field is elided. In this case, the implicit value of the DTSN field depends on the context if present. If no context is present, the implicit value of this field is assumed to be zero.
- o F: This flag indicates whether the Flags and Reserved fields in the DIO are elided or not. This flag is set to 1 if these fields are carried inline. The flag is set to 0, if these fields are elided. In this case, the values of these fields depend on the context if present. If no context is present, both fields are assumed to be zero.
- o Ra: This field contains the 4-bit rank value if the R flag is set to 0.
- o Compr: This field contains the number of prefix octets that are elided from the DODAGID field. For example, the Compr value will be zero if full 16-octet DODAGID field is carried inline in the compressed DIO.
- o Inline Fields: The context identifier, if present, occupies the 3rd byte of the compressed DIO base object. Any inline fields in the compressed DIO appear in the same order as in the uncompressed format defined in [I-D.ietf-roll-rpl].

4. Compressing the RPL Options

This section defines the compression format for some of the RPL options that may be carried inside an RPL control message. These RPL options SHOULD be compressed when carried inside an RPL control message compressed in the manner described in this document. The other RPL options, for which a compression format is not specified in this document, MUST follow the format in which they are defined when carried inside an RPL control message compressed as described in this document.




Figure 2: Format of a Compressed RPL Option

The compression format of an RPL option is shown in Figure 2. It consists of:

- o Option Type: The Option Type value for a compressed RPL option is same as that of the uncompressed option with the most significant bit (MSB) set to 1.
- o Option Length: The Option Length is 8 bits long as in case of an uncompressed RPL option.

4.1. DODAG Configuration Option




Figure 3: Format of a Compressed DODAG Configuration Option

The format of the compressed DODAG Configuration Option is shown in Figure 3. The compressed DODAG Configuration option begins with an octet consisting of flags that specify whether the individual fields in the option are elided or not. The implicit value of an elided field depends on the context identified in the DIO base object. If DIO base object does not identify a context, the implicit value of an elided field is as specified below:

- o F: This flag indicates whether the byte in the uncompressed DODAG Configuration option, consisting of the Flags, A and PCS fields, is elided or not. This flag is set to 1 if this byte is carried inline. The flag is set to 0, if this byte is elided. If the DIO base object does not contain a context, the implicit values of elided A and PCS fields are zero and DEFAULT_PATH_CONTROL_SIZE (as defined in [I-D.ietf-roll-rpl]) respectively.
- o T1: This flag indicates whether the DIOIntervalDoublings and DIOIntervalMin fields are elided or not. This flag is set to 1 if these fields are carried inline. The flag is set to 0, if these fields are elided. If DIO base object does not contain a context identifier, these fields, if elided, assume their default values as defined in [I-D.ietf-roll-rpl].
- o T2: This flag indicates whether the DIORedundancyConstant field is elided or not. This flag is set to 1 if DIORedundancyConstant is carried inline. The flag is set to 0, if this field is elided. In this case, the field assumes its default value as defined in [I-D.ietf-roll-rpl] if the DIO base object does not identify a context.
- o I1: This flag indicates whether the MaxRankIncrease field is elided or not. This flag is set to 1 if this field is carried inline. The flag is set to 0 if this field is elided. In this case, the MaxRankIncrease field assumes its default value (as defined in [I-D.ietf-roll-rpl]) if the DIO base object does not identify a context.
- o I2: This flag indicates whether the MinHopRankInc field is elided or not. This flag is set to 1 if this field is carried inline. The flag is set to 0 if this field is elided. In this case, the MinHopRankInc field assumes its default value (as defined in [I-D.ietf-roll-rpl]) if the DIO base object does not identify a context.
- o O: This flag indicates whether the OCP field is elided or not. This flag is set to 1 if this field is carried inline. The flag is set to 0 if this field is elided. In this case, if the DIO base object does not identify a context, RPL Objective Function 0 [I-D.ietf-roll-of0] is the OCP in effect.
- o R: This flag indicates whether the byte marked as Reserved in the uncompressed format is elided or not. This flag is set to 1 if this byte is carried inline. The flag is set to 0 if this byte is elided. In this case, the Reserved byte is assumed to have value 0.

- o L: This flag indicates whether the Default Lifetime and Lifetime Unit fields are elided or not. This flag is set to 1 if these fields are carried inline. The flag is set to 0 if these fields are elided. In this case, the life time of the routes associates with this DODAG is infinity unless another value is specified in the context identified in the DIO base object.
- o Inline fields: Any inline fields in the compressed DODAG Configuration option appear in the same order as in the uncompressed format.

Note that a compressed DODAG Configuration Option can be as small as 3 bytes, whereas an uncompressed DODAG Configuration Option is 16 bytes long.

4.2. Metric/Constraint Objects




Figure 4: Generic Format of a Compressed Routing Metric/Constraint Object

A compressed Metric Container Option contains compressed Routing Metric/Constraint objects as defined in this document. A compressed Metric Container Option MUST NOT contain uncompressed Routing Metric/Constraint objects defined in [I-D.ietf-roll-routing-metrics]. The generic format of a compressed Routing Metric/Constraint Object is shown in Figure 4. A compressed Routing Metric/Constraint Object always has a fixed size as defined in this document. Thus, "recorded" metrics and sub-objects/TLV options within a metric object are not allowed. Various fields inside a compressed Routing Metric/Container Object header are as follows:

- o Type: The type of the routing metric/constraint object.
- o C: This flag is set to one if the object represents a constraint. This flag is set to zero if the object represents a metric.
- o O/P: If the object represents a constraint, this flag is set to one if the constraint is optional. Otherwise, the flag is set to zero. If the object represents a metric, this bit represents, along with P2 bit, a 2-bit "precedence" field.
- o P2: This bit is relevant only when the object represents a metric. Along with the O/P bit, this bit forms a 2-bit "precedence" field.

to indicate the precedence of this metric relative to other metrics in the container. The precedence values range from 0 to 3, 0 being the highest precedence.

- o A: This field is relevant only for metrics and indicates the manner in which the routing metric must be aggregated:

- * A=0x00: The routing metric is additive
- * A=0x01: The routing metric reports a maximum
- * A=0x02: The routing metric reports a minimum
- * A=0x03: The routing metric is multiplicative

4.2.1. Compressed Node State and Attributes Object




Figure 5: Compressed Node State and Attributes Object

The compressed Node State and Attributes object has Type value 0 and is shown in Figure 5. The A and O flags in the object have same meaning and function as the corresponding flags in the uncompressed object defined in [I-D.ietf-roll-routing-metrics].

4.2.2. Compressed Node Energy Object




Figure 6: Compressed Node Energy Object

The compressed Node Energy object has Type value 1 and is shown in Figure 6. Various fields in the object have same meaning and function as the corresponding fields in Node Energy sub-object defined in [I-D.ietf-roll-routing-metrics]. Note that the E-E field has been reduced from 8 bits to 4 bits.

4.2.3. Compressed Hop Count Object




Figure 7: Compressed Hop Count Object

The compressed Hop Count object has Type value 2 and is shown in Figure 7. It consists of a 8-bit hop count value.

4.2.4. Compressed Throughput Object




Figure 8: Compressed Throughput Object

The compressed Throughput object has Type value 3 and is shown in Figure 8. It consists of a 16-bit value expressed in units of kilo bytes per second.

4.2.5. Compressed Latency Object




Figure 9: Compressed Latency Object

The compressed Latency object has Type value 4 and is shown in Figure 9. It consists of a 16-bit value expressed in units of milliseconds.

4.2.6. Compressed ETX Object




Figure 10: Compressed ETX Object

The compressed ETX object has Type value 5 and is shown in Figure 10. It consists of a 16-bit value, which has the same meaning and function as the ETX field inside ETX sub-object inside ETX object defined in [I-D.ietf-roll-routing-metrics].

5. Examples

In this section, we compare the sizes of RPL control messages with and without the compression mechanism specified in this document.

5.1. A DIO With A Configuration Option, A Route Information Option and A Metric Container

Consider an uncompressed multicast DIO message that has a Configuration Option, a Route Information Option and a Metric Container with one ETX metric object and one ETX constraint object. This message consists of the following components:

- o IPv6 header: A typical IPv6 header, compressed as per [I-D.ietf-6lowpan-hc], for a multicast DIO message consists of 5 bytes as follows:
 - * 2 byte LOWPAN_IPHC Base Encoding
 - * 1 byte Context Identifier Extension
 - * 1 byte Next Header
 - * 1 byte Group ID to identify all-RPL-nodes multicast address.
- o 4 bytes for ICMP Type, Code and Checksum fields;
- o 24 bytes for DIO Base Object;
- o 16 bytes for DODAG Configuration Option;
- o 24 byte Route Information Option;
- o 14 bytes for Metric Container consisting of:
 - * 2 bytes for Type and Option Length fields;
 - * 6 bytes for ETX metric object (4 bytes header + 2 bytes body);

- * 6 bytes for ETX constraint object (4 bytes header + 2 bytes body).

Thus, the total length of such a DIO is 87 bytes.

The same message, when compressed in the manner described in this document, consists of:

- o 5 bytes of IPv6 header compressed as per [I-D.ietf-6lowpan-hc] in the manner described in the previous paragraph;
- o 4 bytes for ICMP Type, Code and Checksum fields;
- o 4 bytes of compressed DIO Base Object consisting of 2 bytes of header and 2 bytes for DODAGID (the best case scenario);
- o 3 bytes of compressed DODAG Configuration Option, including 2 bytes for Type and Option Length fields;
- o 24 bytes of Route Information Option;
- o 8 bytes for Metric Container consisting of:
 - * 2 bytes for Type and Option Length fields;
 - * 3 bytes for ETX metric object (1 byte header + 2 bytes body);
 - * 3 bytes for ETX constraint object (1 byte header + 2 bytes body).

Thus, the total length of the compressed DIO is 48 bytes.

5.2. A DIO With A Configuration Option, A Route Discovery Option and A Metric Container

Consider an uncompressed multicast DIO message that has a Configuration Option, a Route Discovery Option (defined in [I-D.ietf-roll-p2p-rpl]) and a Metric Container with one ETX metric object and one ETX constraint object. This message consists of the following components:

- o 5 bytes of IPv6 header compressed as per [I-D.ietf-6lowpan-hc] in the manner described in the previous section;
- o 4 bytes for ICMP Type, Code and Checksum fields;
- o 24 bytes for DIO Base Object;

- o 16 bytes for DODAG Configuration Option;
- o 26 bytes for Route Discovery Option consisting of:
 - * 4 bytes for Type, Option Length and other fixed length fields;
 - * 2 bytes for the Target address field;
 - * 20 bytes for the Address vector (assuming 10 2-byte long elements).
- o 14 bytes for Metric Container consisting of:
 - * 2 bytes for Type and Option Length fields;
 - * 6 bytes for ETX metric object (4 bytes header + 2 bytes body);
 - * 6 bytes for ETX constraint object (4 bytes header + 2 bytes body).

Thus, the total length of such a DIO is 89 bytes.

The same message, when compressed in the manner described in this document, consists of:

- o 5 bytes of IPv6 header compressed as per [I-D.ietf-6lowpan-hc];
- o 4 bytes for ICMP Type, Code and Checksum fields;
- o 4 bytes of compressed DIO Base Object consisting of 2 bytes of header and 2 bytes for DODAGID (the best case scenario);
- o 3 bytes of compressed DODAG Configuration Option, including 2 bytes for Type and Option Length fields;
- o 26 bytes of Route Information Option;
- o 8 bytes for Metric Container consisting of:
 - * 2 bytes for Type and Option Length fields;
 - * 3 bytes for ETX metric object (1 byte header + 2 bytes body);
 - * 3 bytes for ETX constraint object (1 byte header + 2 bytes body).

Thus, the total length of the compressed DIO is 50 bytes.

6. Security Considerations

TBA

7. IANA Considerations

TBA

8. References

8.1. Normative References

[I-D.ietf-roll-routing-metrics]

Vasseur, J., Kim, M., Pister, K., Dejean, N., and D. Barthel, "Routing Metrics used for Path Calculation in Low Power and Lossy Networks", draft-ietf-roll-routing-metrics-19 (work in progress), March 2011.

[I-D.ietf-roll-rpl]

Winter, T., Thubert, P., Brandt, A., Clausen, T., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., and J. Vasseur, "RPL: IPv6 Routing Protocol for Low power and Lossy Networks", draft-ietf-roll-rpl-19 (work in progress), March 2011.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

8.2. Informative References

[I-D.ietf-6lowpan-hc]

Hui, J. and P. Thubert, "Compression Format for IPv6 Datagrams in Low Power and Lossy Networks (6LoWPAN)", draft-ietf-6lowpan-hc-15 (work in progress), February 2011.

[I-D.ietf-roll-of0]

Thubert, P., "RPL Objective Function 0", draft-ietf-roll-of0-12 (work in progress), May 2011.

[I-D.ietf-roll-p2p-rpl]

Goyal, M., Baccelli, E., Brandt, A., Cragie, R., and J. Martocci, "Reactive Discovery of Point-to-Point Routes in Low Power and Lossy Networks", draft-ietf-roll-p2p-rpl-03 (work in progress), May 2011.

[I-D.ietf-roll-terminology]

Vasseur, J., "Terminology in Low power And Lossy Networks", draft-ietf-roll-terminology-05 (work in progress), March 2011.

Authors' Addresses

Mukul Goyal (editor)
University of Wisconsin Milwaukee
3200 N Cramer St
Milwaukee, WI 53211
USA

Phone: +1 414 2295001
Email: mukul@uwm.edu

Emmanuel Baccelli
INRIA

Phone: +33-169-335-511
Email: Emmanuel.Baccelli@inria.fr
URI: <http://www.emmanuelbaccelli.org/>

Matthias Philipp
INRIA

Email: matthias.philipp@inria.fr

Anders Brandt
Sigma Designs

Phone: +45-29609501
Email: abr@sdesigns.dk

Jerald Martocci
Johnson Controls

Phone: +1-414-524-4010
Email: jerald.p.martocci@jci.com

