

Softwire
Internet-Draft
Intended status: Standards Track
Expires: January 8, 2012

Y. Cui
J. Dong
P. Wu
Tsinghua University
July 7, 2011

Softwire Mesh Management Information Base(MIB)
draft-cui-softwire-mesh-mib-02

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular it defines objects for managing softwire mesh [RFC5565].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 8, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	3
2. The Internet-Standard Management Framework	3
3. Terminology	3
4. Conventions	3
5. Structure of the MIB Module	3
5.1. The swmSupportedTunnelTable Subtree	4
5.2. The swmEncapsTable Subtree	4
5.3. The swmBGPNeighborTable Subtree	4
5.4. The swmMIBConformance Subtree	4
6. Relationship to Other MIB Modules	4
6.1. Relationship to the IF-MIB	4
6.2. Relationship to the IP Tunnel MIB	5
6.3. MIB modules required for IMPORTS	5
7. Definitions	6
8. Security Considerations	11
9. IANA Considerations	12
10. References	12
10.1. Normative References	12
10.2. Informative References	13
10.3. URL References	13

1. Introduction

Software mesh framework RFC 5565 [RFC5565] is a tunneling mechanism which enables connectivity between islands of IPv4, IPv6 or dual-stack networks across single IPv4 or IPv6 backbone networks. In software mesh solution, extended multiprotocol-BGP (MP-BGP) is used to set up tunnels and advertise prefixes among address family border routers (AFBRs).

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular it defines objects for managing software mesh [RFC5565].

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. Terminology

This document uses terminology from software problem statement RFC 4925 [RFC4925] and software mesh framework RFC5565 [RFC5565].

4. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

5. Structure of the MIB Module

The software mesh MIB provides a way to configure and manage the software mesh objects through SNMP.

5.1. The swmSupportedTunnelTable Subtree

Since AFBR need to negotiate with BGP peer what kind of tunnel they use, it should firstly announce what kind tunnels it supports. The swmSupportedTunnelTable subtree provides the information about what kind of tunnels the AFBR supports. According to section 4 of RFC 5512, current software mesh tunnel includes IP-IP, GRE or L2TPv3.

5.2. The swmEncapsTable Subtree

The swmEncapsTable subtree provides software mesh NLRI-NH information about the AFBR. It indicates which E-IP destination address will be encapsulated according to the arriving packet's I-IP destination address.

5.3. The swmBGPNeighborTable Subtree

The subtree provides software mesh BGP neighbor information about the AFBR. It includes the address of software mesh BGP peer. It also includes what kind of tunnel that the AFBR would use to communicate with this BGP peer.

5.4. The swmMIBConformance Subtree

The subtree provides conformance information of MIB objects.

6. Relationship to Other MIB Modules

6.1. Relationship to the IF-MIB

The Interfaces MIB [RFC2863] defines generic managed objects for managing interfaces. Each logical interface (physical or virtual) has an ifEntry in the Interfaces MIB [RFC2863]. Tunnels are handled by creating a logical interface (ifEntry) for each tunnel. Software mesh tunnel also acts as a virtual interface, which has corresponding entries in IP Tunnel MIB and Interface MIB. Those corresponding entries are indexed by ifIndex.

The ifOperStatus in ifTable would be used to represent whether the mesh function of the AFBR has been started. During the BGP OPEN phase, if the software mesh capability is negotiated, the mesh function could be considered to be started, and ifOperStatus is "up", else the ifOperStatus is "down".

If it's IPv4-over-IPv6 software mesh tunnel, the ifInUcastPkts represents the number of IPv6 packets which would be decapsulated to IPv4 in the virtual interface. The ifOutUcastPkts represents the number of IPv6 packets which have been encapsulated from IPv4

packets. Particularly, if these IPv4 packets need to be fragmented, the number counted here is the packets after fragmentation.

If it's IPv6-over-IPv4 software mesh tunnel, the ifInUcastPkts represents the number of IPv4 packets which would be decapsulated to IPv6 in the virtual interface. The ifOutUcastPkts represents the number of IPv4 packets which have been encapsulated from IPv6. Particularly, if these IPv6 packets need to be fragmented, the number counted here is the packets after fragmentation. Similar definition apply to other counting objects in ifTalbe.

6.2. Relationship to the IP Tunnel MIB

The IP Tunnel MIB [RFC4087] contains objects common to all IP tunnels, including software mesh. Additionally, tunnel encapsulation specific MIB (like what is defined in this document) extend the IP tunnel MIB to further describe encapsulation specific information.

In case of software mesh, Since it's a point to multi-point tunnel, we need to specify a ecapsulation talbe to support E-IP routing between AFBRs to achieve correct forwarding in E-IP networks and correct encapsulation on AFBRs. Each AFBR also needs to know information about remote BGP peers (AFBRs).

The implementation of the IP Tunnel MIB is required for software mesh. The tunnelIfEncapsMethod in the tunnelIfEntry should be set to softwareMesh("xx"), and corresponding entry in the software mesh MIB module will exist for every tunnelIfEntry with this tunnelIfEncapsMethod. The tunnelIfRemoteInetAddress must be set to 0.0.0.0 for IPv4 or :: for IPv6 because it's a point to multi-point tunnel.

Since tunnelIfAddressType in tunnelIfTable represents the type of address in the corresponding tunnelIfLocalInetAddress and tunnelIfRemoteInetAddress objects, we also can use the tunnelIfAddressType to specify the software mesh tunnel is IPv4-over-IPv6 or IPv6-over-IPv4 when the tunnelIfEncapsMethod is softwareMesh: When tunnelIfAddressType is IPv4, the encapsulation would be IPv6-over-IPv4; When tunnelIfAddressType is IPv6, the encapsulation would be IPv4-over-IPv6.

6.3. MIB modules required for IMPORTS

The following MIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], IF-MIB [RFC2863] and INET-ADDRESS-MIB [RFC4001].

7. Definitions

```
SOFTWARE-MESH-MIB DEFINITIONS ::= BEGIN

IMPORTS
    TruthValue, TEXTUAL-CONVENTION
    TimeStamp
        FROM SNMPv2-TC

    OBJECT-GROUP, MODULE-COMPLIANCE
        FROM SNMPv2-CONF

    MODULE-IDENTITY, OBJECT-TYPE, mib-2, Unsigned32, Counter32,
    Counter64
        FROM SNMPv2-SMI

    IANAtunnelType          FROM IANAifType-MIB;

    InetAddress, InetAddressPrefixLength
        FROM INET-ADDRESS-MIB

swmMIB MODULE-IDENTITY
    LAST-UPDATED "201107070000Z"          -- July 7, 2011
    ORGANIZATION "Softwire Working Group"
    CONTACT-INFO "

        Yong Cui
        Email: yong@csnet1.cs.tsinghua.edu.cn

        Jiang Dong
        Email: dongjiang@csnet1.cs.tsinghua.edu.cn

        Peng Wu
        Email: weapon@csnet1.cs.tsinghua.edu.cn

        Email comments directly to ther softwire WG Mailing
        List at softwires@ietf.org
    "

    DESCRIPTION
        "This MIB module contains managed object definitions for
        the softwire mesh framework."

    REVISION      "201107070000Z"
    DESCRIPTION
        "draft-02 version"
::= {transmission xxx} --xxx to be replaced with correct value

-- swmSupportedTunnelTable
swmSupportedTunnelTable OBJECT-TYPE
```

```

SYNTAX      SEQUENCE OF swmSupportedTunnelEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table of objects that shows what kind of tunnels
    can be supported in the AFBR."
 ::= { swmMIB 1 }

swmSupportedTunnelEntry OBJECT-TYPE
SYNTAX      swmSupportedTunnelEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A set of objects that shows what kind of tunnels
    can be supported in the AFBR. Ef the AFBR supports
    several kinds of tunnel type, The
    swmSupportedTunnelTalbe would has sveral entries."
INDEX { swmSupportedTunnelType }
 ::= { swmSupportedTunnelTable 1 }

swmSupportedTunnelEntry ::=
    SEQUENCE {
        swmSupportedTunnelType          IANATunnelType
    }

swmSupportedTunnelType OBJECT-TYPE
SYNTAX      IANATunnelType
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "Represents the kind of tunneling type that the AFBR
    support. "
 ::= { swmSupportedTunnelTypeEntry 1 }
-- end of swmSupportedTunnelTable

--swmEncapsTable
swmEncapsTable OBJECT-TYPE
SYNTAX      SEQUENCE OF swmEncapsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table of objects that display and control the
    softwire mesh encapsulation information."
 ::= { swmMIB 2 }

swmEncapsEntry OBJECT-TYPE
SYNTAX      swmEncapsEntry
MAX-ACCESS  not-accessible

```

```

STATUS      current
DESCRIPTION
    "A set of objects that display and control the
    software mesh encapsulation information."
INDEX { ifIndex,
        swmEncapsIIPDst,
        swmEncapsIIPMask
      }
 ::= { swmEncapsTable 1 }

swmEncapsEntry ::=
SEQUENCE {
    swmEncapsIIPDst      InetAddress,
    swmEncapsIIPMask     InetAddressPrefixLength,
    swmEncapsEIPDst      InetAddress
}

swmEncapsIIPDst OBJECT-TYPE
SYNTAX      InetAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The destination I-IP address that decide which
    E-IP address will be encapsulated. The address Type
    is opposite to tunnelIfAddressType in tunnelIfTable."
 ::= { swmEncapsEntry 1 }

swmEncapsIIPMask OBJECT-TYPE
SYNTAX      InetAddressPrefixLength
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The prefix length of I-IP address."
 ::= { swmEncapsEntry 2 }

swmEncapsEIPDst OBJECT-TYPE
SYNTAX      InetAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The E-IP address that will be encapsulated
    according to the I-IP address. The address Type
    is the same as tunnelIfAddressType in tunnelIfTable.
    Since the tunnelIfRemoteInetAddress in tunnelIfTable
    should be 0.0.0.0 or ::, swmEncapsEIPDst is the
    destination address used in the outer IP header."
 ::= { swmEncapsEntry 3 }
-- End of swmEncapsTable

```



```

-- swmBGPNeighborTable
swmBGPNeighborTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF swmBGPNeighborEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table of objects that display the software mesh
        BGP neighbor information."
    ::= { swmMIB 3 }

swmBGPNeighborEntry OBJECT-TYPE
    SYNTAX      swmBGPNeighborEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of objects that display the software mesh
        BGP neighbor information."
    INDEX {
        ifIndex,
        swmBGPNeighborInetAddress
    }
    ::= { swmBGPNeighborTable 1 }

swmBGPNeighborEntry ::=
    SEQUENCE {
        swmBGPNeighborInetAddress      InetAddress,
        swmBGPNeighborTunnelType      IANATunnelType
    }

swmBGPNeighborInetAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The address of the ABFR's BGP neighbor. The
        address type is the same as tunnelIfAddressType
        in tunnelIfTable"
    ::= { swmBGPNeighborEntry 1 }

swmBGPNeighborTunnelType OBJECT-TYPE
    SYNTAX      IANATunnelType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Represents the kind of tunneling type that the
        AFBR used to communication with the BGP neighbor"
    ::= { swmBGPNeighborEntry 2 }
-- End of swmBGPNeighborTable

```

```
-- conformance information
swmMIBConformance
    OBJECT IDENTIFIER ::= { swmMIB 4 }
swmMIBCompliances
    OBJECT IDENTIFIER ::= { swmMIBConformance 1 }
swmMIBGroups
    OBJECT IDENTIFIER ::= { swmMIBConformance 2 }

-- compliance statements
swmMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Describes the requirements for conformance to the software
        mesh MIB."

    MODULE -- this module
    MANDATORY-GROUPS {
        swmSupportedTunnelGroup,
        swmEncapsGroup,
        swmBGPNeighborGroup }
    ::= { swmMIBCompliances 1 }

swmSupportedTunnelGroup    OBJECT-GROUP
    OBJECTS {
        swmSupportedTunnelType
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to show
        what kind of tunnel the AFBR supports."
    ::= { swmMIBGroups 1 }

swmEncapsGroup            OBJECT-GROUP
    OBJECTS {
        swmEncapsIIPDst,
        swmEncapsIIPMask,
        swmEncapsEIPDst
    }
    STATUS current
    DESCRIPTION
        "The collection of objects which are used to display
        software mesh encapsulation information."
    ::= { swmMIBGroups 2 }

swmBGPNeighborGroup       OBJECT-GROUP
    OBJECTS {
        swmBGPNeighborInetAddress,
        swmBGPNeighborTunnelType
```

```
}
STATUS    current
DESCRIPTION
    "The collection of objects which are used to display
    software mesh BGP neighbor information."
 ::= { swmMIBGroups 3 }

END
```

8. Security Considerations

The swmMIB module can be used for configuration of certain objects, and anything that can be configured can be incorrectly configured, with potentially disastrous results.

There are some management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o Unauthorized changes to the swmVif4over6Table and swmVif6over4Table may disrupt the configuration of the 4over6 mtu and 6over4 mtu of the virtual interface.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

9. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry, and the following IANA-assigned tunnelType values recorded in the IANAtunnelType-MIB registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
swmMIB	{ transmission XXX }

```
IANAtunnelType ::= TEXTUAL-CONVENTION
    SYNTAX      INTEGER {
                                softwareMesh ("XX")      -- software Mesh tunnel
    }
```

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [RFC4925] Li, X., Dawkins, S., Ward, D., and A. Durand, "Softwire Problem Statement", RFC 4925, July 2007.
- [RFC5512] Mohapatra, P. and E. Rosen, "The BGP Encapsulation Subsequent Address Family Identifier (SAFI) and the BGP Tunnel Encapsulation Attribute", RFC 5512, April 2009.
- [RFC5565] Wu, J., Cui, Y., Metz, C., and E. Rosen, "Softwire

Mesh Framework", RFC 5565, June 2009.

10.2. Informative References

- [RFC2223] Postel, J. and J. Reynolds, "Instructions to RFC Authors", RFC 2223, October 1997.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", RFC 2629, June 1999.
- [RFC4181] Heard, C., "Guidelines for Authors and Reviewers of MIB Documents", BCP 111, RFC 4181, September 2005.

10.3. URL References

- [idguidelines] IETF Internet Drafts editor,
"http://www.ietf.org/ietf/lid-guidelines.txt".
- [idnits] IETF Internet Drafts editor,
"http://www.ietf.org/ID-Checklist.html".
- [xml2rfc] XML2RFC tools and documentation,
"http://xml.resource.org".
- [ops] the IETF OPS Area, "http://www.ops.ietf.org".
- [ietf] IETF Tools Team, "http://tools.ietf.org".

Authors' Addresses

Yong Cui
Tsinghua University
Department of Computer Science, Tsinghua University
Beijing 100084
P.R.China

Phone: +86-10-6260-3059
EMail: yong@csnet1.cs.tsinghua.edu.cn

Jiang Dong
Tsinghua University
Department of Computer Science, Tsinghua University
Beijing 100084
P.R.China

Phone: +86-10-6278-5822
EMail: dongjiang@csnet1.cs.tsinghua.edu.cn

Peng Wu
Tsinghua University
Department of Computer Science, Tsinghua University
Beijing 100084
P.R.China

Phone: +86-10-6278-5822
EMail: weapon@csnet1.cs.tsinghua.edu.cn

