

Internet Engineering Task Force
Internet-Draft
Intended status: Informational
Expires: December 29, 2011

S. Tsuchiya, Ed.
Cisco Systems
S. Kawamura
NEC BIGLOBE, Ltd.
R. Bush
C. Pelsser
Internet Initiative Japan, Inc.
June 27, 2011

Route Flap Damping Deployment Status Survey
draft-shishio-grow-isp-rfd-implement-survey-02

Abstract

BGP Route Flap Damping [RFC2439] is a mechanism that targets route stability. It penalizes routes that flap with the aim of reducing CPU load on the routers.

But it has side-effects. Thus, in 2006, RIPE recommended not to use Route Flap Damping (see [RIPE-378]).

Now, some researchers propose to turn RFD, with less aggressive parameters, back on [draft-ymbk-rfd-usable].

This document describes results of a survey conducted among service provider on their use of BGP Route Flap Damping.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 29, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the

document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Survey Purpose	3
2. Survey's target and period	3
2.1. For Japan	3
2.2. For Global	3
3. Survey Results	3
3.1. Q1.Which is the best description of your job role?	3
3.1.1. Japan	3
3.1.2. Global	3
3.2. Q2.Do you use Route Flap Damping ?	4
3.3. Q3.If you select No on Q2,why?	4
3.4. Q4.If you select Yes on Q2,what parameter do you use?	4
3.5. Q5.Do you know Randy Bush et. al's report ''Route Flap Damping Considered Usable?''	5
3.6. Q6.IOS's max-penalty is currently limited to 20K. Do you need this limitation to be relaxed to over 50K?	5
3.7. Q7.According to [draft-ymbk-rfd-usable],Suppress Threshold should be set to 6K.Do you think the default value on implementations should be changed to 6K?''	5
3.8. Q8.If you have any comments, please fill this box.	5
3.8.1. Japan	5
3.8.2. Global	6
4. Summary of data	6
5. Acknowledgements	7
6. IANA Considerations	7
7. Security Considerations	7
8. References	7
8.1. Normative References	7
8.2. Informative References	7
Appendix A. Additional Stuff	8
Authors' Addresses	8

1. Survey Purpose

RIPE published some recommendations such as [RIPE-178],[RIPE-210],[RIPE-229] and [RIPE-378].

The purpose of this survey is to understand the current usage and requirements of Route Flap Damping [RFC2439] among service providers.

2. Survey's target and period

2.1. For Japan

Target: Japan Network Operator Group janog@janog.gr.jp

Period: Jan 28,2011 - Feb 12,2011

2.2. For Global

Target: All operators who has answered the survey
<https://www.surveymonkey.com/s/rfd-survey>.

We posted this document to the following mailing list.

North American Network Operators Group nanog@nanog.org
RIPE Routing Working Group routing-wg@ripe.net
Asia Pacific OperatorS Forum apops@apops.net
Africa Network Operators Group afnog@afnog.org
South Asian Network Operators Group sanog@sanog.org
Latin America and Caribbean Region Network Operators Group
lacnog@lacnic.net

Period:Mar 7,2011 - May 25,2011

3. Survey Results

3.1. Q1.Which is the best description of your job role?

3.1.1. Japan

This question did not exist for Japan version.

3.1.2. Global

BGP operator:27
 Researcher:1
 Engineer of vendor:3
 Engineer of Network/System Integrator:13
 Student:0
 Other:0

3.2. Q2.Do you use Route Flap Damping ?

Answer	Japan	Global	Total Number	Percentage[%]
YES	5	8	13	20.6
NO	8	36	49	77.8
Skipped Q2.	1	0	1	1.6

3.3. Q3.If you select No on Q2,why?

Answer	Japan	Global	Total Number	Percentage[%]
Do not have the need	3	7	10	19.6
Did not know about the feature	2	3	5	9.8
No benefits expected	3	7	10	19.6
Customers would complain	1	4	5	9.8
Because I read [RIPE-378]	2	13	15	29.4
Other	3	3	6	11.8

1 person answered Q3,even if he selected "Yes" on Q2.

3.4. Q4.If you select Yes on Q2,what parameter do you use?

Answer	Japan	Global	Total Number	Percentage[%]
Default parameters	3	3	6	40.0
[RIPE-178]	0	1	1	6.7
[RIPE-210]	0	0	0	0.0
[RIPE-229]	0	1	1	6.7
Other	3	4	7	46.7

1 person answered Q4, even if he selected "No" on Q2.

- 3.5. Q5.Do you know Randy Bush et. al's report ''Route Flap Damping Considered Usable?''

Answer	Japan	Global	Total Number	Percentage[%]
YES	12	21	33	52.4
NO	7	22	29	46.0
Skipped Q5.	0	1	1	1.6

One person skipped Q2, but answered Q5.

- 3.6. Q6.IOS's max-penalty is currently limited to 20K. Do you need this limitation to be relaxed to over 50K?

Answer	Japan	Global	Total Number	Percentage[%]
YES	10	14	24	38.1
NO	9	23	32	50.8
Skipped Q6.	0	7	7	11.1

- 3.7. Q7.According to [draft-ymbk-rfd-usable],Suppress Threshold should be set to 6K.Do you think the default value on implementations should be changed to 6K?''

Answer	Japan	Global	Total Number	Percentage[%]
YES	N/A	17	17	38.6
NO	N/A	18	18	40.9
Skipped Q7.	N/A	9	9	20.5

This question did not exist for Japan version.

- 3.8. Q8.If you have any comments, please fill this box.

Free format

- 3.8.1. Japan

-Our peer seems to have damping enabled, and our prefix gets damped sometimes.

-We do not enable damping because we think that customers want a non-damped route.

-From the perspective of a downstream ISP, if our upstream told us that an outage occurred because a route was damped, I may call and ask "is it written in the agreement that you will do this?"

-We use damping pretty heavily

-I had RFD turned on until this morning when I discovered our router has CSCtd26215 issues. I would like to turn on a "useful" RFD.

3.8.2. Global

-Statistical reports from big Service Providers may better visualize the situation.

-best current practices is nice, but always needs to be adjusted to reflect local network settings.

-We used RFD in the past and came to the conclusion that we do not want to use RFD any more. We still have it configured to be able to get Flap statistics out of our Cisco boxes, but no prefixes get dampended

-We recently removed all RFD from the configs due to the information read on the topic among the preso's on the NANOG Archive.

-after seeing this survey, I read the draft; sounds promising; would be nice to see vendors start to implement it.

-Q3, other: Juniper RFD is broken, default values count penalty for both update and withdrawal, and they would not fix that. No clear motivation for us, has caused outage when our customers (with primary and backup connection to us) had a flapping link.

-Strong desire to see the path vector penalized rather than the prefix.

4. Summary of data

From the survey we see that there are many service providers with RFD disabled. The reason varies among providers, but it is clear that there are those who wish that RFD was made useful. [draft-ymbk-rfd-usable] describes how to improve RFD with minor changes to some parameters. From the comments in the survey, the most significant fear of enabling RFD is its impact on customers.

5. Acknowledgements

We thank the 63 respondant to this survey.

6. IANA Considerations

This document has no actions for IANA.

7. Security Considerations

This document has no security considerations.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2439] Villamizar, C., Chandra, R., and R. Govindan, "BGP Route Flap Damping", RFC 2439, November 1998.

8.2. Informative References

- [I-D.ymbk-rfd-usable]
Pelsser, C., Bush, R., Patel, K., Mohapatra, P., and O. Maennel, "Making Route Flap Damping Usable", draft-ymbk-rfd-usable-00 (work in progress), March 2011.
- [RIPE-178]
Barber, T., Doran, S., Panigl, C., and J. Schmitz, "RIPE Routing-WG Recommendation for coor-dinated route-flap damping parameters", Feb 1998, <ftp://ftp.ripe.net/ripe/docs/ripe-178.txt>.
- [RIPE-210]
Barber, T., Doran, S., Karrenberg, D., Panigl, C., and J. Schmitz, "RIPE Routing-WG Recommendation for coordinated route-flap damping parameters", May 2000, <ftp://ftp.ripe.net/ripe/docs/ripe-210.txt>.
- [RIPE-229]
Panigl, C., Schmitz, J., Smith, P., and C. Vistoli, "RIPE Routing-WG Recommendations for Coordinated Route-flap Damping Parameters", Oct 2001,

<<ftp://ftp.ripe.net/ripe/docs/ripe-229.txt>>.

[RIPE-378]

Smith, P. and C. Panigl, "RIPE Routing Working Group
Recommendations On Route-flap Damping", May 2006,
<<http://www.ripe.net/ripe/docs/ripe-378>>.

[Route Flap Damping Considered Usable?]

Pelsser, C., Maennel, O., Patel, K., and R. Bush, "Route
Flap Damping Considered Useable", Nov 2011, <[http://
ripe61.ripe.net/presentations/222-101117.ripe-rfd.pdf](http://ripe61.ripe.net/presentations/222-101117.ripe-rfd.pdf)>.

Appendix A. Additional Stuff

This becomes an Appendix.

Authors' Addresses

Shishio Tsuchiya (editor)
Cisco Systems
Shinjuku Mitsui Building, 2-1-1, Nishi-Shinjuku
Shinjuku-Ku, Tokyo 163-0409
Japan

Phone: +81 3 6434 6543
Email: shtsuchi@cisco.com

Seiichi Kawamura
NEC BIGLOBE, Ltd.
14-22, Shibaura 4-chome
Minatoku, Tokyo 108-8558
JAPAN

Phone: +81 3 3798 6085
Email: kawamucho@mesh.ad.jp

Randy Bush
Internet Initiative Japan, Inc.
5147 Crystal Springs
Bainbridge Island, Washington 98110
US

Phone: +1 206 780 0431 x1
Email: randy@psg.com

Cristel Pelsser
Internet Initiative Japan, Inc.
Jinbocho Mitsui Buiding, 1-105
Kanda-Jinbocho, Chiyoda-kun 101-0051
JP

Phone: +81 3 5205 6464
Email: cristel@iiij.ad.jp

