

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 18, 2012

H. Asaeda
Keio University
R. Huang
Q. Wu
Huawei
September 15, 2011

RTCP XR Blocks for Synchronization Delay and Offset Metrics Reporting
draft-asaeda-xrblock-rtcp-xr-synchronization-02

Abstract

This document defines an RTCP XR Report Block and associated SDP parameters that allow the reporting of synchronization delay and offset metrics for use in a range of RTP applications.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 18, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1.	Introduction	3
2.	Terminology	3
2.1.	Standards Language	3
3.	Applicability	3
4.	RTP Flows Initial Synchronization Delay Report Block	4
4.1.	Metric Block Structure	4
4.2.	Definition of Fields in RTP Flow Initial Synchronization Delay Metrics Block	4
5.	RTP Flows General Synchronization Offset Metrics Block	5
5.1.	Metric Block Structure	5
5.2.	Definition of Fields in RTP Flow General Synchronization Offset Metrics Block	6
6.	SDP Signaling	6
7.	IANA Considerations	7
8.	Security Considerations	8
9.	Acknowledgements	8
10.	References	8
10.1.	Normative References	8
10.2.	Informative References	9
Appendix A.	Change Log	9
A.1.	draft-asaeda-xrblock-rtcp-xr-synchronization-00	9
A.2.	draft-asaeda-xrblock-rtcp-xr-synchronization-01	9
A.3.	draft-asaeda-xrblock-rtcp-xr-synchronization-02	9
	Authors' Addresses	9

1. Introduction

This draft defines a new block type to augment those defined in [RFC3611], for use in a range of RTP applications.

This new block type supports reporting of Initial synchronization delay. Information is recorded about the difference between the start of RTP sessions and the time the RTP receiver acquires all components of RTP sessions [RFC6051]. It also supports reporting of the general Synchronization offset status of an arbitrary number of streams, with the same RTCP CNAME. Information is recorded about the synchronization offset time of each RTP stream relative to the reference RTP stream with the same CNAME and General Synchronization Offset of zero.

The metrics belong to the class of transport level metrics defined in [MONARCH] (work in progress).

2. Terminology

2.1. Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

3. Applicability

The report blocks defined in this document could be used by dedicated network monitoring applications.

When joining each session in layered video sessions [RFC6190] or the multimedia sessions, a receiver may not synchronize playout across the multimedia sessions or layered video sessions until RTCP SR packets have been received on all the components of RTP sessions. The components of RTP sessions are referred to as each RTP stream for each media type in multimedia sessions or each RTP stream at each layer in the layered video sessions. . For unicast session, the delay due to negotiation of NAT pinholes, firewall holes, quality-of-service, and media security keys is contributed to such initial synchronization playout. For multicast session, such initial synchronization delay varies with the session bandwidth and the number of members, the number of senders in the session. The RTP flow Initial synchronization delay block can be used to report the initial synchronization delay of these RTP streams beyond the information carried in the standard RTCP packet format. In the

absence of packet loss, the initial synchronization delay equals to the average time taken to receive the first RTCP packet in the RTP session with the longest RTCP reporting interval. In the presence of packet loss, the media synchronization needs to be based on the in-band mapping of RTP and NTP- format timestamps [RFC6051] or wait until the reporting interval has passed, and the next RTCP SR packet is sent.


In an RTP multimedia session, there can be an arbitrary number of streams, with the same RTCP CNAME. The RTP Flows General Synchronization Offset block can be used to report the general Synchronization offset status of these RTP streams beyond the information carried in the standard RTCP packet format. In the multimedia session, the first RTP packet can be chosen as the basic packet of reference RTP stream.

4. RTP Flows Initial Synchronization Delay Report Block

This block reports Initial synchronization delay beyond the information carried in the standard RTCP packet format. Information is recorded about the the difference between the start of RTP sessions and the time the RTP receiver acquires all components of RTP sessions [RFC6051].

4.1. Metric Block Structure

The RTP Flows Initial Synchronization Delay Report Block has the following format:



4.2. Definition of Fields in RTP Flow Initial Synchronization Delay Metrics Block

Block type (BT): 8 bits

The Statistics Summary Report Block is identified by the constant <RFISD>.

Block length: 16 bits

The constant 2, in accordance with the definition of this field in Section 3 of RFC 3611 [RFC3611].

SSRC of Source: 32 bits

The SSRC of the RTP data packet source being reported upon by this report block. (Section 4.1 of [RFC3611]).

Initial Synchronization Delay: 32 bits


The average delay, expressed in units of 1/65536 seconds, between the RTCP packets received on all of the components RTP sessions and the beginning of session [RFC6051]. The value is calculated based on the information contained in RTCP SR packets or the in-band mapping of RTP and NTP- format timestamps [RFC6051]. If there is no packet loss, the initial synchronisation delay is expected to equal to the average time taken to receive the first RTCP packet in the RTP session with the longest RTCP reporting interval.

5. RTP Flows General Synchronization Offset Metrics Block

In the RTP multimedia sessions, there can be an arbitrary number of Streams and each type of media (e.g., audio or video) is sent in a separate RTP streams. The receiver associates RTP streams to be synchronised by means of RTCP CNAME contained in the RTCP Source Description (SDS) packets [RFC3550]. This block reports the general Synchronization offset status of these RTP streams beyond the information carried in the standard RTCP packet format. Information is recorded about the synchronization offset time of each RTP stream relative to the reference RTP stream with the same CNAME and General Synchronisation Offset of zero.

5.1. Metric Block Structure

The RTP Flow General Synchronization Offset Report Block has the following format:



5.2. Definition of Fields in RTP Flow General Synchronization Offset Metrics Block

Block type (BT): 8 bits

The RTP Flow General Synchronization Offset Report Block is identified by the constant <RFGSO>.

Block length: 16 bits

The constant 3, in accordance with the definition of this field in Section 3 of RFC 3611 [RFC3611].

SSRC of Source: 32 bits

The SSRC of the RTP data packet source being reported upon by this report block. (Section 4.1 of [RFC3611]).

General synchronization offset: 32 bits

This field represents the synchronization offset time of one RTP stream in milliseconds relative to the reference RTP stream with the same CNAME and General Synchronisation Offset of zero [RFC6051] This value is calculated based on the interarrival time between arbitray RTP packet and the reference RTP packet with the same CNAME , and timestamps of this arbitray RTP packet and the reference RTP packet with the same CNAME.

6. SDP Signaling

Two new parameters are defined for the two report blocks defined in this document to be used with Session Description Protocol (SDP) [RFC4566] using the Augmented Backus-Naur Form (ABNF) [RFC5234]. They have the following syntax within the "rtcp-xr" attribute [RFC3611]:

```
rtcp-xr-attrib = "a=rtcp-xr:"
                 [xr-format *(SP xr-format)] CRLF
xr-format = RTP-flows-init-syn
           / RTP-flows-general-syn

RTP-flows-init-syn = "RTP-flows-init-syn"
                   ["=" max-size]
                   max-size = 1*DIGIT ; maximum block size in octets

RTP-flow-general-syn = "RTP-flows-general-syn"
                      ["=" max-size]
                      max-size = 1*DIGIT ; maximum block size in octets
```

Refer to Section 5.1 of RFC 3611 [RFC3611] for a detailed description and the full syntax of the "rtcp-xr" attribute.

7. IANA Considerations

New report block types for RTCP XR are subject to IANA registration. For general guidelines on IANA allocations for RTCP XR, refer to Section 6.2 of [RFC3611].

This document assigns two new block type values in the RTCP XR Block Type Registry:

```
Name:          RFISD
Long Name:     RTP Flows Initial Synchronization Delay
Value         <RFISD>
Reference:    Section 4
```

```
Name:          RFGSO
Long Name:     RTP Flows General Synchronization Offset Metrics Block
Value         <RFGSO>
Reference:    Section 5
```

This document also registers two new SDP [RFC4566] parameters for the "rtcp-xr" attribute in the RTCP XR SDP Parameters Registry:

```
* "RTP-flows-init-syn"
* "RTP-flows-general-syn"
```

The contact information for the registrations is:

Qin Wu
sunseawq@huawei.com
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012, China

8. Security Considerations

The new RTCP XR report blocks proposed in this document introduces no new security considerations beyond those described in [RFC3611].

9. Acknowledgements

The authors would like to thank Bill Ver Steeg, David R Oran, Ali Begen, Colin Perkins, Roni Even, Youqing Yang, Wenxiao Yu and Yinliang Hu for their valuable comments and suggestions on this document.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, RFC 3550, July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", RFC 3611, November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", RFC 4566, July 2006.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008.
- [RFC6051] Perkins, C. and T. Schierl, "Rapid Synchronisation of RTP Flows", RFC 6051, November 2010.
- [RFC6190] Wenger, S., Wang, Y., Schierl, T., and A. Eleftheriadis, "RTP Payload Format for Scalable Video Coding", RFC 6190, May 2011.

10.2. Informative References

[MONARCH] Wu, Q., "Monitoring Architectures for RTP",
ID draft-ietf-avtcore-monarch-00, April 2011.

Appendix A. Change Log

Note to the RFC-Editor: please remove this section prior to publication as an RFC.

A.1. draft-asaeda-xrblock-rtcp-xr-synchronization-00

This document is separated from draft-wu-xrblock-rtcp-xr-quality-monitoring-01 with some editorial changes and focuses on RTP Flow Initial Synchronization Delay and RTP Flows General Synchronization Offset.

A.2. draft-asaeda-xrblock-rtcp-xr-synchronization-01

Separate Synchronization Delay and Offset Metrics Block into two independent block based on comments on the list.

A.3. draft-asaeda-xrblock-rtcp-xr-synchronization-02

The following are the major changes compared to previous version 01:

- o Clarify which synchronization is reported in section 4 and 5.
- o Allow calculating the synchronization delay based on RTP header extension defined in RFC6051
- o Explain what the components of RTP session are in section 3.

Authors' Addresses

Hitoshi Asaeda
Keio University
Graduate School of Media and Governance
5322 Endo
Fujisawa, Kanagawa 252-0882
Japan

Email: asaeda@wide.ad.jp

Rachel Huang
Huawei Technologies Co., Ltd.
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: Rachel@huawei.com

Qin Wu
Huawei Technologies Co., Ltd.
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: sunseawq@huawei.com

