

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: February 17, 2012

R. Huang
Q. Wu
Huawei
H. Asaeda
Keio University
August 16, 2011

RTCP XR Report Block for TS Decodability Statistics Metric reporting
draft-huang-xrblock-rtcp-xr-decodability-01

Abstract

This document defines an RTCP XR Report Block that allows the reporting of decodability Statistics Metric used for Transport Stream.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 17, 2012.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	3
2. Terminology	3
2.1. Standards Language	3
2.2. Acronyms	3
3. TR 101 290 Decodability Statistics Metric Report Block	3
4. SDP Signaling	6
5. IANA Considerations	6
6. Security Considerations	7
7. References	7
7.1. Normative References	7
7.2. Informative References	8
Authors' Addresses	8

1. Introduction

This draft defines a new block type to augment those defined in [RFC3611] for use in Transport Stream. The new block type supports the reporting of consistency of Transport Stream [ETSI] by checking TS header information. This new block type can be useful for identifying the existence, and characterizing the severity, of a packet transport problem which may affect users' perception of a service delivered over RTP, also useful for verifying the continued correct operation of an existing system management and providing accurate measures of Transport Stream quality for operators.

The new report block is in compliance with the monitoring architecture specified in [I-D.ietf-pmol-metrics-framework] (work in progress). The metric is applicable to any other types of RTP application that use TS standard format for transmission and storage of audio, video, and data.

2. Terminology

2.1. Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

In addition, the following terms are defined:

2.2. Acronyms

SSRC

Synchronization Source [RFC3550]

TS

Transport Stream [ISO-IEC.13818-1.2007]

3. TR 101 290 Decodability Statistics Metric Report Block

This block reports decodability statistics metric beyond the information carried in the standard RTCP packet format. Information is recorded about basic monitoring parameters necessary to ensure that the TS can be decoded including the number of Transport Stream Synchronization Losses, Sync byte errors, Continuity count errors, and continuous monitoring parameters including Transport errors, Program Clock Reference (PCR) errors, PCR repetition errors, PCR discontinuity indicator errors, and Presentation Time Stamp (PTS)

errors [ETSI]. Such information can be useful for network management and real time application quality monitoring.

Note that this metric report block is not only applicable to MPEG-2 transport streams[RFC2250],but also applicable to any other Transport Streams that adopt other audio and video codec.

The Decodability Metrics Block has the following format:

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-----+-----+-----+-----+-----+-----+-----+-----+
|      BT=TBD      |      rvd      |      block length      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|                               SSRC of source                               |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      begin_seq      |      end_seq      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|                               Number of TSs                               |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      Transport Stream Synchronization Losses      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|                               Sync byte errors                               |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      Continuity count errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      Transport errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      PCR errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      PCR repetition errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      PCR discontinuity indicator errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+
|      PTS errors      |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

block type (BT): 8 bits

A TR 101 290 decodability metrics report block is identified by the constant <TDM>.

rvd: 8 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

block length: 16 bits

The constant 11, in accordance with the definition of this field in Section 3 of RFC 3611 [RFC3611].

SSRC of source: 32 bits

As defined in Section 4.1 of [RFC3611].

begin_seq: 16 bits

As defined in Section 4.1 of [RFC3611].

end_seq: 16 bits

As defined in Section 4.1 of [RFC3611].

Number of TSs: 32 bits

Number of Transport Streams in the above sequence number interval.

Transport Stream Synchronization Losses: 32 bits

Number of Transport Stream Synchronization Losses in the above sequence number interval.

Sync byte errors: 32 bits

Number of Transport sync byte errors in the above sequence number interval.

Continuity count error: 32 bits

Number of Transport Continuity count errors in the above sequence number interval.

Transport errors: 32 bits

Number of Transport errors in the above sequence number interval.

PCR errors: 32 bits

Number of PCR errors in the above sequence number interval.

PCR repetition errors: 32 bits

Number of Transport PCR repetition errors in the above sequence number interval.

PCR discontinuity indicator errors: 32 bits

Number of PCR discontinuity indicator errors in the above sequence number interval.

PTS errors: 32 bits

Number of PTS errors in the above sequence number interval.

4. SDP Signaling

One new parameter is defined for the one report blocks defined in this document to be used with Session Description Protocol (SDP) [RFC4566] using the Augmented Backus-Naur Form (ABNF) [RFC5234]. They have the following syntax within the "rtcp-xr" attribute [RFC3611]:

```
rtcp-xr-attrb = "a=rtcp-xr:"  
                [xr-format *(SP xr-format)] CRLF
```

```
xr-format = decodability-metrics
```

```
decodability-metrics = "decodability-metrics"
```

Refer to Section 5.1 of RFC 3611 [RFC3611] for a detailed description and the full syntax of the "rtcp-xr" attribute.

5. IANA Considerations

New report block types for RTCP XR are subject to IANA registration. For general guidelines on IANA allocations for RTCP XR, refer to Section 6.2 of [RFC3611].

This document assigns one new block type values in the RTCP XR Block Type Registry:

Name:	TDM
Long Name:	TR 101 290 Decodability Metrics
Value	<TDM>
Reference:	section 3

This document also registers one SDP [RFC4566] parameters for the "rtcp-xr" attribute in the RTCP XR SDP Parameters Registry:

* "decodability-metrics"

The contact information for the registrations is:

Rachel Huang
rachel.huang@huawei.com
101 Software Avenue, Yuhua District
Nanjing, JiangSu 210012 China

6. Security Considerations

This proposed RTCP XR report block introduces no new security considerations beyond those described in [RFC3611].

7. References

7.1. Normative References

- [ETSI] ETSI, "Digital Video Broadcasting (DVB); Measurement guidelines for DVB systems", Technical Report TR 101 290, 2001.
- [ISO-IEC.13818-1.2007]
International Organization for Standardization,
"Information technology - Generic coding of moving
pictures and associated audio information: Systems",
ISO International Standard 13818-1, October 2007.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2250] Hoffman, D., Fernando, G., Goyal, V., and M. Civanlar, "RTP Payload Format for MPEG1/MPEG2 Video", RFC 2250, January 1998.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, RFC 3550, July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", RFC 3611, November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", RFC 4566, July 2006.

- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008.

7.2. Informative References

- [DSLRF] Rahrer, T., Ed., Fiandra, Ed., and Wright, Ed., "Triple-play Services Quality of Experience (QoE) Requirements", DSL Forum Technical Report TR-126, December 2006.
- [G.1082] ITU-T, "Measurement-based methods for improving the robustness of IPTV performance", ITU-T Recommendation G.1082, April 2009.
- [I-D.ietf-avtcore-monarch]
Wu, Q., Ed., Hunt, G., and P. Arden, "Monitoring Architectures for RTP", June 2011.
- [I-D.ietf-pmol-metrics-framework]
Clark, A., "Framework for Performance Metric Development".
- [IEEE] IEEE, "Human Perception of Jitter and Media Synchronization", IEEE Journal on Selected Areas in Communications Vol. 14, No. 1, January 1996.
- [P.NAMS] ITU-T, "Non-intrusive parametric model for the Assessment of performance of Multimedia Streaming", ITU-T Recommendation P.NAMS, November 2009.

Authors' Addresses

Rachel Huang
Huawei
101 Software Avenue, Yuhua District
Nanjing 210012
China

Email: rachel.huang@huawei.com

Qin Wu
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: bill.wu@huawei.com

Hitoshi Asaeda
Keio University
Graduate School of Media and Governance 5322 Endo
Fujisawa, Kanagawa 252-0882
Japan

Email: asaeda@wide.ad.jp

