

# draft-perreault-opsawg-natmib-bis

Presenter: Tina Tsou

IETF 82, Taipei

2011-11-15

# NAT-MIB

- RFC 4008
- Generic NAT MIB
- IPv4 and IPv6 support (NAT[46][46])
- Required by draft-ietf-behave-lsn-requirements
- Missing many features
- Missing features are currently implemented in various proprietary MIBs
  - This suggests a need for standardization

# Missing Features (incomplete)

- DS-Lite
  - Sharing address pools between interfaces
- CGN
  - Per-subscriber state table indexing
  - Per-subscriber statistics
  - Per-pool statistics
  - Notifications for IP/port exhaustion, quota exceeded, etc.
  - Configurable limits and/or throttles for allocations
  - Low and a high thresholds in order to add more IP addresses or reclaim some if they are unused
- NAT64
  - Expose pref64 in MIB
  - Various semantics changes required
- PCP
  - Do we need anything?
- Various
  - Update to RFC 4787 terminology
  - Support protocols other than just TCP and UDP
  - Clarify existing traps
  - Add examples of DS-Lite, CGN, and NAT64 configurations

# Proposals

- Add milestone to this working group's charter:  
“Produce a revision of RFC 4008 taking into account recent developments such as DS-Lite, CGN, and NAT64.”
- Adopt draft-perreault-opsawg-natmib-bis as WG document for fulfilling the above.

# BEHAVE? OPSAWG? V[46]OPS?

- If this WG is not the right place for this work, where should it go instead?