

Internet Engineering Task Force
Internet-Draft
Intended status: Experimental
Expires: June 10, 2015

R. Cole
US Army CERDEC
J. Macker
Naval Research Laboratory
A. Bierman
YumaWorks, Inc.
December 7, 2014

Definition of Managed Objects for Performance Reporting
draft-ietf-manet-report-mib-04

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring autonomous report generation on any device that supports MIBs containing objects that resolve to type Integer32 (i.e., Integer32, Counter, Gauge, or TimeTicks). to be used for performance monitoring. This allows a management station to instruct a device to build off-line reports to be collected either through notifications to the management station or queried asynchronously by the management station. Hence, this capability allows network operators to reduce the SNMP polling traffic burden on Mobile Ad-Hoc and Disruption Tolerant Networks which is problematic of SNMP performance management applications.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 10, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. The Internet-Standard Management Framework	3
3. Conventions	4
4. Overview	4
4.1. reportSampledMIB Module Management Model	4
4.2. Terms	5
5. Structure of the MIB Module	6
5.1. Textual Conventions	7
5.2. Tables and Indexing	7
6. Relationship to Other MIB Modules	8
6.1. Relationship to the SNMPv2-MIB	8
6.2. Relationship to the RMON2-MIB	9
6.3. Relationship to the DISMAN-EVENT-MIB	9
6.4. Relationship to the DISMAN-EXPRESSION-MIB	10
6.5. MIB modules required for IMPORTS	10
7. Definitions	11
8. Security Considerations	26
9. Applicability Statement	29
10. IANA Considerations	30
11. Contributors	30
12. Acknowledgements	30
13. References	30
13.1. Normative References	30
13.2. Informative References	31
Appendix A. Change Log	31
Appendix B. Open Issues	33
Appendix C.	34

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring autonomous, off-line report generation for performance monitoring on any device supporting MIBs containing variables that resolve to type Integer32 (i.e., Integer32, Counter, Gauge, or TimeTicks). This reportSampledMIB module allows for the report generation to occur on the same device as containing the referenced counter object. This should be useful to devices or networks where efficient use of bandwidth is of concern or where intermittent connectivity is common. Hence, the reportSampledMIB module is useful for devices managed over some Mobile Ad-Hoc Networks (MANETs) or Disruption Tolerant Networks (DTNs).

This version of the reportSampledMIB module offers one type of off-line reporting. The MIB offers a means to collect sampled measurements related to defined MIB objects. This type of reporting is contained in the reportSampledMibObjects. Other types of report data are possible, including statistical data. However, it was felt wise to focus on a more limited scope off-line reporting capability and gain experimental use and application prior to expending energy developing a more extensive off line reporting capability.

The reportSampledMIB module relies upon the dismanEventMIB module RFC 2981 [RFC2981] to monitor the progress of reports being developed within the reportSampledMIB module and to trigger an events, i.e., notifications containing reports, at the appropriate times. This is discussed below in more detail in the section entitled 'Relationship to the DISMAN-EVENT-MIB'. Further, more sophisticated performance objects for monitoring from the reportSampledMIB module can be defined through the dismanExpressionMIB module RFC 2982 [RFC2982]

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

4. Overview

The reportSampledMIB module references performance objects in other MIBs and generates off-line performance reports related to those referenced objects. The reportSampledMIB module can be coincident with the other MIB modules on the same device containing the referenced performance related object.

4.1. reportSampledMIB Module Management Model

This section describes the management model for the reportSampledMIB module process.

The reportSampledMIB module objects are primarily contained within four tables. These are:

- o reportSampledControlTable - this is the control table within the reportSampledMIB module. This identifies the OIDs to be monitored which define the core of the Reports. The control table sets the sampling frequency for the Measurements and the number of Measurements that will define each Report.
- o reportSampledCurrentReportsStatusTable - This table tracks the status, i.e., the current number of collected Measurements per each Study. This information can be used by the dismanEventMIB module to determine when to trigger a notification to the Report owner containing the Measurements and associated data comprising the just completed Report.
- o reportSampledCurrentReportsTable - This table holds the Measurements for the Reports which are in current development.
- o reportSampledHistoricalReportsTable - This table holds the completed Reports for each Study for archival purposes, i.e., the Study owners can perform table walks to retrieve archived Reports or Studies.

The below figure illustrates the four main tables within the reportSampledMIB module. Further, if the dismanEventMIB module is so configured to generate triggered notifications, the below figure highlights the 'boolean trigger' and the notification generation. The figure further illustrates the movement of completed Reports from

the reportSampledCurrentReportsTable to the reportSampledHistoricalReportsTable upon Report Completion.



4.2. Terms

The following definitions apply throughout this document:

- o Sampled - periodic measurement of target OIDs.
- o Measurement - a single instance of a sampling event.
- o Report - a collection of consecutive Measurements on the same Sampled target OID.

- o Study - a series of Reports on the same Sampled target OID.
- o Current Report - a Report which is in the process of being developed.
- o A Completed Report - contains a pre-defined number of Sampled Measurements.
- o Historical Report - a Report which has previously Completed, and is being stored locally for archival purposes.

5. Structure of the MIB Module

This section presents the structure of the reportSampledMIB module. The objects are arranged into the following groups:

- o reportSampledMibNotifications - defines the notifications associated with the reportSampledMIB module. These objects define notifications which track the behavior of the reportSampledMib module. A single notification is defined in the reportSampledMIB module which reports a series of failed measurement attempts in the process of building a Report. Associated with this notification is a control object which defines a threshold of failures which would initiate the notification. These notifications do not cover the triggered notifications which carry the performance Reports generated by the reportSampledMib module. These triggered notifications are defined through the use of the dismanEventMIB module.
- o reportSampledMibObjects - defines the objects forming the basis for the reportSampledMIB module. These objects are basically divided up by function into the following four tables:
 - * reportSampledControlTable - This group contains the objects which support the generation (collection) of Studies comprising of Reports exposing sampled Measurement values.
 - * reportSampledCurrentReportsStatusTable - This group contains the objects which track the collection of Measurements for current (in-progress) Reports. This table allows the dismanEventMIB module to set triggers for Completed Reports which it can then send to the report owner through triggered notifications.
 - * reportSampledCurrentReportsTable - This group contains the objects which represent the Measurement data associated with Current (in-progress) Reports. Once the Report completes, it is moved to the reportSampledHistoricalReportsTable for

archival purposes.

- * reportSampledHistoricalReportsTable - This group contains the objects which represent archived Completed Reports. This allows the report owners to asynchronously retrieve Reports via table walks if so desired.
- o reportSampledMibConformance - Defines a single basic conformance of implementations of this reportSampledMIB module.

5.1. Textual Conventions

No textual conventions are defined in the reportSampledMIB module.

5.2. Tables and Indexing

The reportSampledMIB module contains four tables which control and record data related to the creation, notification and storage of Reports. Specifically:

- o the control and generation of remote performance Reports, i.e., reportSampledControlTable
- o the status of the Current Reports' development, i.e., reportSampledCurrentReportsStatusTable,
- o the Current Reports development and interim data, i.e., reportSampledCurrentReportsTable, and
- o the historical storage of remote performance Reports, i.e. reportSampledHistoricalReportsTable.

The reportSampledMIB module's tables are indexed via the following constructs:

- o reportSampledStudyIndex - an index that uniquely identifies a particular Study. The Study is comprised of multiple Reports, the number of Reports being stored is defined by the reportSampledStudyMaximumNumberOfHistoricalReports object.
- o reportSampledCurrentMeasurementIndex - an index that uniquely identifies an atomic Measurement associated with a Report.
- o reportSampledHistoricalReportIndex - an index that uniquely identifies an archived Completed Report resident within the reportSampledHistoricalReportsTable.

- o reportSampledHistoricalMeasurementIndex - an index that uniquely identifies an atomic Measurement comprising an archived Completed Report.

These tables and their indexing are:

- o reportSampledControlTable - this table contains a list of data-collection configuration entries defining aspects of the studies and their reports to be generated. These include, e.g., number of reports per study, the number Reports to be archived, etc. This table has 'INDEX { reportSampledStudyIndex }'.
- o reportSampledCurrentReportsStatusTable - this table contains objects which track the development of current Reports, e.g., the number of current Measurements collected for each Report under development. This table has 'INDEX { reportSampledStudyIndex }'. For each (active) Study, there exists only one Current Report under development.
- o reportSampledCurrentReportsTable - this table contains the Measurements which are developing the Current Reports. This table has 'INDEX { reportSampledStudyIndex, reportSampledCurrentMeasurementIndex }'.
- o reportSampledHistoricalReportsTable - this table contains the Reports which have completed. This table has 'INDEX { reportSampledStudyIndex, reportSampledHistoricalReportIndex, reportSampledHistoricalMeasurementIndex }'.

6. Relationship to Other MIB Modules

The text of this section specifies the relationship of the MIB modules contained in this document to other standards, particularly to standards containing other MIB modules. Definitions imported from other MIB modules and other MIB modules that SHOULD be implemented in conjunction with the MIB module contained within this document are identified in this section.

6.1. Relationship to the SNMPv2-MIB

The 'system' group in the SNMPv2-MIB [RFC3418] is defined as being mandatory for all systems, and the objects apply to the entity as a whole. The 'system' group provides identification of the management entity and certain other system-wide data. The reportSampledMIB module does not duplicate those objects.

6.2. Relationship to the RMON2-MIB

The reportSampledMIB module is closely related to and was inspired by the the RMON2-MIB module [RFC2021] usrHistoryGroup. The use of control tables to establish the periodic collection of measurement data for creation of performance reports was pulled from earlier work on the RMON2-MIB module.

6.3. Relationship to the DISMAN-EVENT-MIB

The reportSampledMIB module was developed to fundamentally work with the dismanEventMIB module RFC 2981 [RFC2981] in order to offer a complete and efficient off-line reporting capability for bandwidth challenged networks such as Mobile Ad-Hoc Networks (MANETs). This is accomplished through defining trigger test and associated notification actions indexed by mteOwner, mteTriggerName, mteObjectsName and mteEventName within the dismanEventMIB module. Specifically (within the dismanEventMIB module):

In the mteTriggerTable and specifically by setting

- o 'mteTriggerTest == boolean(1)',
- o 'mteTriggerSampleType == absoluteValue(1)',
- o 'mteTriggerValueID ==
reportSampledNumberOfMeasurementsForCurrentReport',
- o 'mteTriggerValueIDWildcard == false(1)',
- o 'mteTriggerFrequency == 0.5*reportSampledStudySamplingInterval',
and
- o 'mteTriggerEnabled == true'.

In the mteTriggerBooleanTable and specifically by setting

- o 'mteTriggerBooleanComparison == equal(2)',
- o 'mteTriggerBooleanValue == value of
reportSampledStudyNumberReportMeasurements', and
- o 'mteTriggerBooleanStartup == false'.

In the mteObjectsTable and specifically by setting

- o 'mteObjectsID == reportSampledCurrentMeasurementValue' and reportSampledCurrentMeasurementTime' and reportSampledCurrentMeasurementStatus' with
- o 'mteObjectsIDWildcard == true' // for each.

In the mteEventTable and specifically by setting

- o 'mteEventActions == notification(0)' and
- o 'mteEventEnabled == true' // for each.

In the mteEventNotificationTable and specifically by setting

- o 'mteEventNotification == mteTriggerFired' and the appropriate names for the
- o 'mteEventNotificationObjectOwner == mteOwner' and
- o 'mteEventNotificationObjects == mteObjectsName'.

These settings within the dismanEventMIB module will result in notifications generated by the dismanEventMIB module which will carry the recently completed reportSampledMIB module reports.

Set up properly, the dismanEventMIB module will trigger a notification each time the reportSampledCurrentTable contains a completed Report. This Report will be sent in a notification containing three columns of the reportSampledCurrentTable, i.e., the Value, the Time and the Status, due to the use of wildcarding within the dismanEventMIB module.

Simultaneously, the reportSampledMIB module will move the completed Current Report into the reportSampledHistoricalReportsTable and restart collection for the next Report within the reportSampledCurrentReportsTable.

6.4. Relationship to the DISMAN-EXPRESSION-MIB

In conjunction with the dismanExpressionMIB module RFC 2982 [RFC2982], the reportSampledMIB module can be used to develop reports on relatively sophisticated object expressions.

6.5. MIB modules required for IMPORTS

Citations are not permitted within a MIB module, but any module mentioned in an IMPORTS clause or document mentioned in a REFERENCE clause is a Normative reference, and must be cited someplace within

the narrative sections. Therefore, the imported items in this MIB module, such as Textual Conventions, that are not already cited, are cited in this section. Since relationships to other MIB modules should be described in the narrative text, this section will cite modules from which Textual Conventions are imported.

The reportSampledMIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], SNMP-FRAMEWORK-MIB [RFC3411], and SNMPv2-MIB [RFC3418].

7. Definitions

```
REPORT-SAMPLED-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,  
Gauge32, Integer32, experimental  
FROM SNMPv2-SMI -- [RFC2578]
```

```
TimeStamp  
FROM SNMPv2-TC -- [RFC2579]
```

```
sysUpTime  
FROM SNMPv2-MIB -- [RFC3418]
```

```
SnmpAdminString  
FROM SNMP-FRAMEWORK-MIB -- [RFC3411]
```

```
MODULE-COMPLIANCE, OBJECT-GROUP,  
NOTIFICATION-GROUP  
FROM SNMPv2-CONF -- [RFC2580]  
;
```

```
reportSampledMIB MODULE-IDENTITY  
LAST-UPDATED "201412011300Z" -- December 01, 2014  
ORGANIZATION "IETF MANET Working Group"  
CONTACT-INFO  
"WG E-Mail: manet@ietf.org  
  
WG Chairs: sratliff@cisco.com  
          jmacker@nrl.navy.mil  
  
Editors: Robert G. Cole  
         US Army CERDEC
```

6010 Frankford Road
Aberdeen Proving Ground, MD 21005
USA
+1 443 395-8744
robert.g.cole@us.army.mil

Joseph Macker
Naval Research Laboratory
Washington, D.C. 20375
USA
macker@itd.nrl.navy.mil

Andy Bierman
YumaWorks, Inc.
andy@yumaworks.com"

DESCRIPTION

"This MIB module contains managed object definitions for the autonomous reporting of performance object counters. Copyright (C) The IETF Trust (2009). This version of this MIB module is part of RFC xxxx; see the RFC itself for full legal notices."

-- Revision History

REVISION "201412011300Z" -- December 01, 2014

DESCRIPTION

"The ninth draft of this MIB module published as draft-ietf-manet-report-mib-04.txt.

Revisions to this draft include

- a) A major restructuring of the MIB module in order to leverage the dismanEventMIB module for the automatic notification of Completed Reports.
- b) Efforts to incorporate this MIB module into the DISMAN management architecture.

"

REVISION "201211051300Z" -- November 05, 2012

DESCRIPTION

"The seventh draft of this MIB module published as draft-ietf-manet-report-mib-03.txt.

Revisions to this draft include

- a) Added a 'Tables and Indexing' section to the body of this document.
- b) Added an 'Applicability Statement' section to the body of this document."

REVISION "201201311300Z" -- January 31, 2012

DESCRIPTION

"The sixth draft of this MIB module published as

draft-ietf-manet-report-mib-02.txt.

Revisions to this draft include

- a) Pulled the statistical and historical reporting from the MIB module and left only the sampled reporting, in order to greatly simplify the first instance of this reporting MIB module.
- b) Renamed the module, the reportSampledMIB module.
- c) Leveraged the RMON2-MIB module more effectively through the use of the AUGMENTS clause.
- d) Changed the module to 'experimental'."

REVISION "201102171300Z" -- February 17, 2011
DESCRIPTION

"The fifth draft of this MIB module published as draft-ietf-manet-report-mib-01.txt. This document has been promoted to a MANET Working Group draft.

Revisions to this draft include

- a) Proposed changes to the statsReport table to simplify communications between device and mgmt application,
- b) Added Notifications,
- c) Changed the reporting structure of the Sampled and the History reporting to align with the structure of the Statistics reports for the purpose of allowing for efficient notification and collection of data reports.
- d) Ran through smilint to clean up all errors and most warning. A few still remain."

REVISION "201007051300Z" -- July 05, 2010
DESCRIPTION

"The fourth draft of this MIB module published as draft-ietf-manet-report-mib-00.txt. This document has been promoted to a MANET Working Group draft.

Significant revisions to this draft include

- a) added support for proxy configurations through the addition of address objects associated with the referenced counter objects associated with the performance reports."

REVISION "201003021300Z" -- March 02, 2010
DESCRIPTION

"The third draft of this MIB module published as draft-cole-manet-report-mib-02.txt. Significant revisions to this draft include a) changed naming

```

    of usrHistoryGroup to sampledGroup and b) added
    a historyGroup."
REVISION    "200910251300Z"    -- October 25, 2009
DESCRIPTION
    "The second draft of this MIB module published as
    draft-cole-manet-report-mib-01.txt. Significant
    revisions to this draft include a) the inclusion of
    raw data collection borrow blatantly from the
    usrHistory Group within RMON2, b) the deletion of
    the CurrentHistoryTable from version -00,
    c) modifications to the overall structure of the
    MIB, and d) the definition of various Compliance
    options for implementations related to this MIB."
REVISION    "200904281300Z"    -- April 28, 2009
DESCRIPTION
    "Initial draft of this MIB module published as
    draft-cole-manet-report-mib-00.txt."
-- RFC-Editor assigns XXXX
 ::= { experimental 998 }    -- to be assigned by IANA

-- TEXTUAL CONVENTIONS
-- None

--
-- Top-Level Object Identifier Assignments
--
reportSampledMibNotifications OBJECT IDENTIFIER
                               ::= { reportSampledMIB 0 }
reportSampledMibObjects       OBJECT IDENTIFIER
                               ::= { reportSampledMIB 1 }
reportSampledMibConformance   OBJECT IDENTIFIER
                               ::= { reportSampledMIB 2 }

-- The reportSampledMibObjects assignments are :
--     reportSampledControlTable           - 1
--     reportSampledCurrentReportsStatusTable - 2
--     reportSampledCurrentReportsTable     - 3
--     reportSampledHistoricalReportsTable  - 4

--
-- The Control Table
--
reportSampledControlTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF reportSampledControlEntry
    MAX-ACCESS  not-accessible

```

```

STATUS      current
DESCRIPTION
    "A table to configure measurement Studies which
    are comprised of multiple Reports."
REFERENCE
    "tbd."
 ::= { reportSampledMibObjects 1 }

reportSampledControlEntry OBJECT-TYPE
SYNTAX      ReportSampledControlEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A list of parameters that control the creation of
    off-line performance Studies.

    The objects in this table are persistent and when
    written the device SHOULD save the change to
    non-volatile storage.  For further information
    on the storage behavior for these objects, refer
    to the description for the reportSampledStudyEntryStatus
    object."
INDEX       { reportSampledStudyIndex }
 ::= { reportSampledControlTable 1 }

ReportSampledControlEntry ::= SEQUENCE {
    reportSampledStudyIndex          Integer32,
    reportSampledStudyOwner          SnmpAdminString,
    reportSampledStudyName          SnmpAdminString,
    reportSampledStudyOid           Integer32,
    reportSampledStudySamplingInterval Integer32,
    reportSampledStudyNumberReportMeasurements Integer32,
    reportSampledStudyMaximumNumberOfHistoricalReports Integer32,
    reportSampledStudyEntryStatus    RowStatus
}

reportSampledStudyIndex OBJECT-TYPE
SYNTAX      Integer32 (1..127)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A unique index that identifies a specific performace
    Study.  Each Study is comprised of multiple
    Reports.  Each Report is comprised of multiple
    atomic Measurements on a specified object."
 ::= { reportSampledControlEntry 1 }

reportSampledStudyOwner OBJECT-TYPE

```

```
SYNTAX      SnmpAdminString (SIZE (0..32))
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The owner of the Study."
DEFVAL      { 'H }
 ::= { reportSampledControlEntry 2 }

reportSampledStudyName OBJECT-TYPE
SYNTAX      SnmpAdminString (SIZE (0..32))
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The name of the Study."
DEFVAL      { 'H }
 ::= { reportSampledControlEntry 3 }

reportSampledStudyOid OBJECT-TYPE
SYNTAX      OBJECT IDENTIFIER
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The target OID of the Study.  Each Study makes
    periodic Measurements on a specified object
    which is local to this device.  Currently, the
    objects of study are limited to objects that
    resolve to Integer32 (i.e., Integer32, Counter,
    Gauge, or TimeTicks)."
 ::= { reportSampledControlEntry 4 }

reportSampledStudySamplingInterval OBJECT-TYPE
SYNTAX      Integer32 (1..2147483647)
UNITS       "seconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The time (in seconds) between sampled Measurement
    instances."
DEFVAL      { 10 }
 ::= { reportSampledControlEntry 5 }

reportSampledStudyNumberReportMeasurements OBJECT-TYPE
SYNTAX      Integer32 (1..2147483647)
UNITS       "count"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The number of Measurements per Report for this Study."
```

```
DEFVAL      { 10 }
 ::= { reportSampledControlEntry 6 }
```

```
reportSampledStudyMaximumNumberOfHistoricalReports OBJECT-TYPE
SYNTAX      Integer32 (1..2147483647)
UNITS       "count"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The number of Historical Reports to archive locally
    for this specific Study. The Historical Reports are
    archived locally in the
    reportSampledHistoricalReportsTable (below)."
```

```
DEFVAL      { 10 }
 ::= { reportSampledControlEntry 7 }
```

```
reportSampledStudyEntryStatus OBJECT-TYPE
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This object permits management of this table
    by facilitating actions such as row creation,
    construction, and destruction. The value of
    this object has no effect on whether other
    objects in this conceptual row can be
    modified.
```

An entry may not exist in the 'active' state unless all objects in the entry have a defined appropriate value. For objects with DEFVAL clauses, the management station does not need to specify the value of these objects in order for the row to transit to the 'active' state; the default value for these objects is used. For objects that do not have DEFVAL clauses, then the network manager MUST specify the value of these objects prior to this row transitioning to the 'active' state.

When this object transitions to 'active', all objects in this row SHOULD be written to non-volatile (stable) storage. Read-create objects in this row MAY be modified. When an object in a row with smfCfgIfRowStatus of 'active' is changed, then the updated value MUST be reflected in SMF and this new object value MUST be written to non-volatile storage.

If this object is not equal to 'active', all associated entries in the reportSampledCurrentReportsStatusTable,

```

        the reportSampledCurrentReportsTable, and the
        reportSampledHistoricalReportsTable MUST be deleted."
 ::= { reportSampledControlEntry 8 }

--
-- the Current Reports Status Table
--
reportSampledCurrentReportsStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF reportSampledCurrentReportsStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table to tracking the progress of measurements of current
        reports in development.  Of particular note is the object
        reportSampledNumberOfMeasurementsForCurrentReport which
        can be compared to the value of the object
        reportSampledStudyNumberReportMeasurements by the
        dismanEventMIB module and generate triggered
        notifications to the Study owner containing the
        recently Completed Reports."
    REFERENCE
        "tbd."
 ::= { reportSampledMibObjects 2 }

reportSampledCurrentReportsStatusEntry OBJECT-TYPE
    SYNTAX      ReportSampledCurrentReportsStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of parameters that track the status of
        current Reports in development."
    INDEX       { reportSampledStudyIndex }
 ::= { reportSampledCurrentReportsStatusTable 1 }

ReportSampledCurrentReportsStatusEntry ::= SEQUENCE {
    reportSampledNumberOfCurrentReport      Integer32,
    reportSampledNumberOfMeasurementsForCurrentReport Integer32
}

reportSampledNumberOfCurrentReport OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    UNITS       "count"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number within the Study series of this
        current Report.  For each new Report within

```

```

        the Study, this value MUST increment by
        one. For the first Report in this Study,
        the initial value of this object MUST be
        set to one. The value MUST wrap back to one
        when the value has reached the maximum."
 ::= { reportSampledCurrentReportsStatusEntry 1 }

reportSampledNumberOfMeasurementsForCurrentReport OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    UNITS       "count"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Measurements collected so far for
        for this specific Report. The initial value
        of this object MUST be one. The value MUST
        increment be one for each attempted Measurement.
        The maximum value for this object is
        reportSampledStudyNumberReportMeasurements.
        Once this value is reached and the next
        Measurement is attempted, the Current Report is
        considered Completed, the agent MUST copy
        the Completed Report's data from the
        reportSampledCurrentReportsTable into the
        reportSampledHistoricalReportsTable, and the
        next Measurement (strating the next Report in the
        Study series) MUST be numbered with the value of
        this object as one."
 ::= { reportSampledCurrentReportsStatusEntry 2 }

--
-- the Current Reports Table
--
reportSampledCurrentReportsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF ReportSampledCurrentReportsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of measurements being collected for active
        Reports."
    REFERENCE
        " TBD."
 ::= { reportSampledMibObjects 3 }

reportSampledCurrentReportsEntry OBJECT-TYPE
    SYNTAX      ReportSampledCurrentReportsEntry
    MAX-ACCESS  not-accessible

```

```

STATUS      current
DESCRIPTION
    "A list of entries storing the measurements from
    active Reports.  Once an active, current Report
    completes (when the value of the associated
    reportSampledNumberOfMeasurementsForCurrentReport
    equals the value of the associated
    reportSampledStudyNumberReportMeasurements), the
    agent MUST move the Report's data from the
    reportSampledCurrentReportsTable to the
    reportSampledHistoricalReportTable."
INDEX       { reportSampledStudyIndex,
              reportSampledCurrentMeasurementIndex }
 ::= { reportSampledCurrentReportsTable 1 }

ReportSampledCurrentReportsEntry ::= SEQUENCE {
    reportSampledCurrentMeasurementIndex  Integer32,
    reportSampledCurrentMeasurementValue  Integer32,
    reportSampledCurrentMeasurementTime   sysUpTime,
    reportSampledCurrentMeasurementStatus INTEGER
}

reportSampledCurrentMeasurementIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index for this table which represents
        the number of Measurements collected so far for
        for this current Report.  The initial value
        of this object MUST be one.  The value MUST
        increment be one for each attempted Measurement.
        The maximum value for this object is
        reportSampledStudyNumberReportMeasurements.
        Once this value is reached and the next
        Measurement is attempted, the Current Report is
        considered Completed, the agent MUST copy
        the Completed Report's data from the
        reportSampledCurrentReportsTable into the
        reportSampledHistoricalReportsTable, and the
        next Measurement (strating the next Report in the
        Study series) MUST be numbered with the value of
        this object as one."
    ::= { reportSampledCurrentReportsEntry 1 }

reportSampledCurrentMeasurementValue OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only

```

```
STATUS      current
DESCRIPTION
    "A single measurement for this Study for
    this Current Report.  The objects identifying
    the measurement MUST resolve to type Integer32
    (i.e., Integer32, Counter, Gauge, or TimeTicks).
    to be used for performance monitoring on this device."
 ::= { reportSampledCurrentReportsEntry 2 }

reportSampledCurrentMeasurementTime OBJECT-TYPE
SYNTAX      sysUpTime
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The systemUpTime of the device on which the
    measurement was made for this Measurement."
 ::= { reportSampledCurrentReportsEntry 3 }

reportSampledCurrentMeasurementStatus OBJECT-TYPE
SYNTAX      INTEGER {
    valueNotAvailable(1),
    valuePositive(2),
    valueNegative(3)
}
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object indicates the validity and sign of the
    data in the associated value recorded by the
    reportSampledCurrentMeasurementValue object."
 ::= { reportSampledCurrentReportsEntry 4 }

--
-- Historical Reports Table
--
reportSampledHistoricalReportsTable OBJECT-TYPE
SYNTAX      SEQUENCE OF ReportSampledHistoricalReportsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table archiving non-active Reports for each
    defined Study up to a maximum number of Reports
    per Study."
 ::= { reportSampledMibObjects 4 }

reportSampledHistoricalReportsEntry OBJECT-TYPE
SYNTAX      ReportSampledHistoricalReportsEntry
```

```

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "A list of entries storing the measurements from
    Completed Reports. Once an active, current Report
    completes (when the value of the associated
    reportSampledNumberOfMeasurementsForCurrentReport
    equals the value of the associated
    reportSampledStudyNumberReportMeasurements), the
    agent MUST move the Report's data from the
    reportSampledCurrentReportsTable to this
    reportSampledHistoricalReportTable."
REFERENCE
    " TBD. "
INDEX      { reportSampledStudyIndex,
              reportSampledHistoricalReportIndex,
              reportSampledHistoricalMeasurementIndex }
 ::= { reportSampledHistoricalReportsTable 1 }

ReportSampledHistoricalReportsEntry ::= SEQUENCE {
    reportSampledHistoricalReportIndex      Integer32,
    reportSampledHistoricalMeasurementIndex Integer32,
    reportSampledHistoricalMeasurementValue Integer32,
    reportSampledHistoricalMeasurementTime sysUpTime,
    reportSampledHistoricalMeasurementStatus INTEGER
}

reportSampledHistoricalReportIndex OBJECT-TYPE
SYNTAX      Integer32 (1..2147483647)
MAX-ACCESS not-accessible
STATUS      current
DESCRIPTION
    "An index that uniquely identifies the particular Report
    archived in this table for the specific Study
    (identified by the reportSampledStudyIndex).
 ::= { reportSampledHistoricalReportsEntry 1 }

reportSampledHistoricalMeasurementIndex OBJECT-TYPE
SYNTAX      Integer32 (1..2147483647)
MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "An index that uniquely identifies a Measurement for
    a specific Report archived in this table for a
    Specific Study."
 ::= { reportSampledHistoricalReportsEntry 2 }

reportSampledHistoricalReportsValue OBJECT-TYPE

```

```
SYNTAX      Integer32(1..2147483647)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "A single measurement for this Study for
    this Completed Report.  The objects identifying
    the measurement MUST resolve to type Integer32
    (i.e., Integer32, Counter, Gauge, or TimeTicks).
    to be used for performance monitoring on this device."
 ::= { reportSampledHistoriclReportsEntry 3 }

reportSampledHistoricalMeasurementTime OBJECT-TYPE
SYNTAX      sysUpTime
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The systemUpTime of the device on which the
    measurement was made for this Measurement."
 ::= { reportSampledHistoriclReportsEntry 5 }

reportSampledHistoricalMeasurementStatus OBJECT-TYPE
SYNTAX      INTEGER {
    valueNotAvailable(1),
    valuePositive(2),
    valueNegative(3)
}
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "This object indicates the validity and sign of the
    data in the associated value recorded by the
    reportSampledHistoricalMeasurementValue object."
 ::= { reportSampledHistoriclReportsEntry 5 }

--
-- Notifications
--

-- The following notification objects to define issues with making
-- and storing measurements.

-- Actions which report data, i.e., Reports, are to be handled by
-- the dismanEventMIB module.

reportSampledNotificationObjects OBJECT IDENTIFIER
 ::= {reportSampledMibNotifications 0}
reportSampledNotificationControl OBJECT IDENTIFIER
```

```
 ::= { reportSampledMibNotifications 1 }

--
-- reportSampledNotificationObjects
--
reportSampledDataCollectionFailure NOTIFICATION-TYPE
    OBJECTS      { reportSampledStudyOwner, -- The entity that
                  reportSampledStudyName, -- configured this Study
                  reportSampledStudyOid  -- The name of the Study
                  }                          -- that is failing to
                  -- collect measurement data
                  -- The Object ID being
                  -- monitored in this Study
    STATUS      current
    DESCRIPTION
        "The reportSampledDataCollectionFailure is a notification
        sent when the number of consecutive measurement failures
        within a Current Report, as indicated by consecutive values
        of the reportSampledCurrentMeasurementStatus being set
        to 'valueNotAvailable(1)', exceeds the value of the
        threshold value defined in the
        reportSampledDataCollectionFailureThreshold object."
    ::= { reportSampledNotificationObjects 1 }

--
-- nhdpNotificationsControl
--
reportSampledDataCollectionFailureThreshold OBJECT-TYPE
    SYNTAX      Integer32 (1..255)
    UNITS       "count"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "A threshold value for the number of
        consecutive measurement failures within a
        Current Report as indicated by consecutive values
        of the reportSampledCurrentMeasurementStatus being
        being set to 'valueNotAvailable(1)' which
        exceed the value of this threshold. A value of
        '255' for this threshold indicates that the
        reportSampledDataCollectionFailure notification
        is never to be sent. "
    DEFVAL     { 10 }
    ::= { nhdpNotificationsControl 1 }
```

```
--
-- Compliance Statements
--

-- Mandatory compliance for the reportSampledMIB module will
-- include all objects defined within the module.
reportSampledCompliances OBJECT IDENTIFIER
    ::= { reportSampledMIBConformance 1 }
reportSampledMIBGroups OBJECT IDENTIFIER
    ::= { reportSampledMIBConformance 2 }

reportSampledCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION "The reportSampled basic implementation requirements
                for managed network entities that implement
                the REPORT Sampled process."
    MODULE -- this module
    MANDATORY-GROUPS { reportSampledLocalGroup }
    ::= { reportSampledCompliances 1 }

--
-- Units of Conformance
--
reportSampledLocalGroup OBJECT-GROUP
    OBJECTS {
        reportSampledStudyOwner,
        reportSampledStudyName,
        reportSampledStudyOid,
        reportSampledStudySamplingInterval,
        reportSampledStudyNumberReportMeasurements,
        reportSampledStudyMaximumNumberOfHistoricalReports,
        reportSampledStudyEntryStatus,

        reportSampledNumberOfCurrentReport,
        reportSampledNumberOfMeasurementsForCurrentReport,

        reportSampledCurrentMeasurementValue,
        reportSampledCurrentMeasurementTime,
        reportSampledCurrentMeasurementStatus,

        reportSampledHistoricalMeasurementValue,
        reportSampledHistoricalMeasurementTime,
        reportSampledHistoricalMeasurementStatus,

        reportSampledDataCollectionFailure,
        reportSampledDataCollectionFailureThreshold
    }
}
```

```
STATUS current
DESCRIPTION
  "The basic set of objects in this reportSampledMIB module
  to be implemented in order to meet the minimal compliance
  conditions."
 ::= { reportSampledMIBGroups 1 }

END
```

8. Security Considerations

This reportSampledMIB module defines a capability where the local device may poll other MIB modules on the device to collect performance data. These capabilities defined within the reportSampledMIB module are control-able by a network management application through SNMP. As such, a network management application could potentially use the reportSampledMIB module as a mechanism to implement a limited Distributed Denial-of-Service (DDoS) attack against remote devices by overloading their SNMP processing. Care should be taken to secure access to the reportSampledMIB module agent. Specifically, access control mechanisms and authentication mechanisms (via SNMPv3) should always be used for SNMP SET operations. Further, some objects may contain data deemed sensitive and authentication and encryption mechanisms (via SNMPv3) should be used for SNMP GET operations.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

These are the tables and objects and their sensitivity/vulnerability:

- o The reportSampledControlTable is a writable table whose columnar objects are read-create. The following objects with MAX ACCESS of read-create and their security sensitivities are:
 - o
 - * reportSampledStudyOwner - this object is an administrative string which identifies the the owner of the Study.
 - * reportSampledStudyName - this object is an administrative string which gives a name to the Study defined by the objects in this table.

- * reportSampledStudyOid - this object identifies the the Object ID from another MIB module resident on this local device which forms the measurement basis for the Study. Depending upon the object and the associated process responsible for its maintenance, polling this object too frequently may place an undo burden on the process resulting in diminishing its overall ability to perform its operation.
- * reportSampledStudySamplingInterval - this object identifies the time interval being sampling events. If set too low, the device may not be able to sample the object on remote devices fast enough to satisfy the requested interval. Further, setting this value too low could be used to overwhelm the processing capabilities of the remote agent, resulting in a form of Denial-of-Service (DoS) attack.
- * reportSampledStudyNumberReportsMeasurements - this object identifies the requested number of measurements (and associated storage/memory) for each identified object for each Study instance. As such, this related to the total device memory necessary to hold the collected data for the identified reports. The device must determine whether it has the necessary storage. If not, the device can reject this value when requested by returning the to protect itself against memory overruns.
- * reportSampledStudyMaximumNumberOfHistoricalReports - this object identifies the requested number of Reports for each identified object for each Study instance. As such, this related to the total device memory necessary to hold the collected data for the identified reports. The device must determine whether it has the necessary storage. If not, the device can reject this value when requested by returning the to protect itself against memory overruns.
- * reportSampledStudyEntryStatus - this is the RowStatus object controlling the configuration of this table row.
- o The reportSampledCurrentReportsStatusTable is a read-only table containing state information. The information in this Table relates to performance measurements on the underlying Mobile Ad-Hoc Network (MANET). As such, some of this information may be deemed sensitive to the overall performance of the MANET and to the organization to which the MANET belongs.
- o The reportSampledCurrentReportsTable is a read-only table containing state information. The information in this Table relates to performance measurements on the underlying Mobile Ad-

Hoc Network (MANET). As such, some of this information may be deemed sensitive to the overall performance of the MANET and to the organization to which the MANET belongs.

- o The reportSampledHistoricalReportsStatusTable is a read-only table containing state information. The information in this Table relates to performance measurements on the underlying Mobile Ad-Hoc Network (MANET). As such, some of this information may be deemed sensitive to the overall performance of the MANET and to the organization to which the MANET belongs.
- o The reportSampledDataCollectionFailure notification object reports information regarding the inability of the reportSampledMIB module from completing its configured reporting mission, including the specific information that the module is failing to collect. To some organizations this information may be deemed sensitive to its mission and may want to protect this information through encryption mechanisms.
- o The reportSampledDataCollectionFailureThreshold object controls the ability of the device to report information regarding the inability of the reportSampledMIB module from completing its configured reporting mission. If set to low, notifications may be produced too frequently causing processor burdens to the agent and the collecting manager, and generating too much management traffic for a bandwidth constrained MANET to support. If set too high, notifications may not be produced frequently enough for the collecting manager to properly track the MANET system performance.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

9. Applicability Statement

This document describes objects for configuring parameters of the remote report generation process on a router or other device. This MIB module, denoted reportSampledMIB module, also reports performance information and notifications. The reportSampledMIB module provides for the remote control, collection and notification of performance reports on devices. As such, it eliminates the need for periodic polling for counters from remote management stations as a means for generating performance reports. This is hoped to greatly reduce management overhead on the MANET. This sections provides some examples of how this MIB module can be used in MANET network deployments. A fuller discussion of MANET network management use cases and challenges will be provided elsewhere.

In the following, two scenarios are identified where this MIB module is useful. This list is not complete and other scenarios are possible.

- o For Mobile vehicles with Low Bandwidth Satellite Link to a Fixed Network Operations Center (NOC) - Here the vehicles carrying the MANET routers carry multiple wireless interfaces, one of which is a relatively low-bandwidth on-the-move satellite connection which interconnects a fix NOC to the nodes of the MANET. Standards-based methods for monitoring and fault management from the fixed NOC are necessary for this deployment option. However, to reduce polling overhead over the low bandwidth communications links, the reportSampledMIB module can be deployed the remote MANET nodes for the remote generation of performance reports.
- o For Fixed NOC and Mobile Local Manager in Larger Vehicles - for larger vehicles, a hierarchical network management arrangement is useful. Centralized network management is performed from a fixed NOC while local management, as provided by this reportSampledMIB module is performed locally from within the vehicles. Standards-based methods for configuration, monitoring, fault and performance management are necessary for this deployment option.

10. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
reportSampledMIB	{ experimental XXX }

11. Contributors

This MIB document uses the template authored by D. Harrington which is based on contributions from the MIB Doctors, especially Juergen Schoenwaelder, Dave Perkins, C.M.Heard and Randy Presuhn.

12. Acknowledgements

We would like to thank Bert Wijnen for pointing out the existence of the usrHistory group within RMON2 and in answering our numerous questions on the usrHistory group. Further, we wish to thank U. Herberg for promoting additions to this MIB through his thoughtful consideration of performance monitoring requirements for other MIBs within the MANET WG, e.g., NHDP and OLSR MIBs.

13. References

13.1. Normative References

- [RFC2021] Waldbusser, S., "Remote Network Monitoring Management Information Base Version 2 using SMIV2", RFC 2021, January 1997.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.

- [RFC2981] Kavasseri, R., "Event MIB", RFC 2981, October 2000.
- [RFC2982] Kavasseri, R., "Distributed Management Expression MIB", RFC 2982, October 2000.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, December 2002.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3418, December 2002.

13.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

Appendix A. Change Log

Changes from draft-ietf-manet-report-mib-03 to draft-ietf-manet-report-mib-04 draft.

1. This version 04 of the reportSampledMIB module represents a fairly significant restructuring of the MIB module. This restructuring was necessary in order to align the remote distributed reporting capabilities of this MIB module with the prior DISMAN Working Group (WG) efforts at the IETF.
2. The reportSampledCurrentReportsStatusTable was added to allow a network manager to automate notifications of completed reports from this MIB module using the dismanEventMIB module.
3. The notifications in this reportSampledMIB module were reduced to only notifications related to the operation of the data collections and no longer addressing the reporting of the performance data itself. This later data is now carried in notifications under the control of the dismanEventMIB module.

Changes from draft-ietf-manet-report-mib-01 to draft-ietf-manet-report-mib-02 draft.

1. Stripped the Statistical and the Historical Reports from this draft in order to greatly simplify the initial development and experiments of this MIB module.

2. Changed the RFC category to Experimental.
3. Completed the Security section.
4. Relied upon the AUGMENTS statement to simplify further this MIB definition.

Changes from draft-ietf-manet-report-mib-00 to draft-ietf-manet-report-mib-01 draft.

1. Proposed additions to the statsReports in order to potentially simplify data transmission to management applications.
2. Added some Notification definitions and their relationship to the three reports' structure, i.e., statsReports, sampledReports, and historyReports.
3. In the process of adding notifications for the Sampled and the History reports, decided to restructure the reports from their previously rolling storage model to the fixed interval reporting used all along in the Statistics reporting. This allows the agent to notify the management application that a report has completed and that it is ready to be pulled from the agent storage.
4. Ran MIB through smilint checker and cleaned up all errors and most warnings. A few warnings remain to be addressed.
5. Cleaned up textual material.

Changes from draft-cole-manet-report-mib-02 to draft-ietf-manet-report-mib-00 draft.

1. Major change was the incorporation of the IP address objects associated with all objects of type 'OBJECT IDENTIFIER'. This allows the reportSampledMIB module to exist as a proxy report generation capability on a device separate but in close proximity to the device monitoring the referenced object.
2. Cleaned up the up front text, reducing the repetition with the object descriptions in the MIB.
3. Worked on and added sections discussing the relationship to other MIBs.

Changes from draft-cole-manet-report-mib-01 to draft-cole-manet-report-mib-02 draft.

1. Restructured the MIB somewhat to now offer the three reporting capabilities in increasing order of detail: a) statistical reports, b) sampled reports, and c) historical reports.
2. Renamed the `usrHistoryGroup` and elements to `samplingGroup`. This is in line with its actual capabilities.
3. Added a new `historyGroup` which provides a history of change events.
4. Updated the 4 Conformance section to reflect the above changes and additions. But did not yet run `smilint` to check MIB syntax.

Changes from `draft-cole-manet-report-mib-00` to `draft-cole-manet-report-mib-01` draft.

1. Added (copied) the `usrHistory` group from `RMON2` into the `reportSampledMIB` module.
2. Restructured the MIB to account for the inclusion of the `reportSampledMibObjects`.
3. Dropped the `reportCurReportsTable` as this did not make sense within the context of the `reportSampledMIB` module.
4. Added the Compliance and Conformance material. Defined several Compliance Groups to all for base implementations of the `reportSampledMIB` module for only statistical reports, for only historical reports or for both. Allow for enhanced implementations to address higher capacity issues and extension to metric reporting for statistical reporting.
5. Ran the MIB through the `smilint` checker and in the process corrected numerous typos, omissions, `TEXTUAL CONVENTIONS`, `IMPORTS`, etc.
6. Updated main text to reflect changes.

Appendix B. Open Issues

This section contains the set of open issues related to the development and design of the `reportSampledMIB` module. This section will not be present in the final version of the MIB and will be removed once all the open issues have been resolved.

1. Provide references within the `REFERENCE` clauses in the MIB module.

- 2. Identify all objects requiring non-volatile storage in their DESCRIPTION clauses.
- 3. Request an initial review of this MIB module by a MIB Doctor familiar with the work of the DISMAN WG, preferably an author of the dismanEventMIB module.

Appendix C.

```

*****
* Note to the RFC Editor (to be removed prior to publication) *
*
* 1) The reference to RFCXXXX within the DESCRIPTION clauses *
* of the MIB module point to this draft and are to be *
* assigned by the RFC Editor. *
*
* 2) The reference to RFCXXX2 throughout this document point *
* to the current draft-ietf-manet-report-xx.txt. This *
* need to be replaced with the XXX RFC number. *
*
*****

```

Authors' Addresses

Robert G. Cole
 US Army CERDEC
 6010 Frankford Road
 Aberdeen Proving Ground, Maryland 21005
 USA

Phone: +1 443 395 8744
 EMail: robert.g.cole@us.army.mil

Joseph Macker
 Naval Research Laboratory
 Washington, D.C. 20375
 USA

EMail: macker@itd.nrl.navy.mil

Internet-Draft

The REPORT-SAMPLED-MIB

December 2014

Andy Bierman
YumaWorks, Inc.
Redwood City, CA 94065

EMail: andy@yumaworks.com

