draft-stephan-cdni-control-operations-00 IETF85 – Atlanta WG CDNi

E. Stephan, G. Bertrand, A. Marrec, Y. Le Louedec (Orange)

Rational

Clarify the positioning of the control interface

[I-D.ietf-cdni-framework] defines the role of the CDNI control interface as encompassing "the operations to discover, initialize, and parameterize the other CDNI interfaces, as well as operations to pre-position, revalidate, and purge both metadata and content."

[RFC6707] indicates that the "exact inter-CDN control functionality required to be supported by the CDNI Control interface is less well defined than the other three CDNI interfaces"

[I-D.ietf-cdni-framework] says "There is some ambiguity as to the line between the set of trigger-based operations in the CDNI Control interface and the Metadata interface".

There is not any draft specifying the the control operations for CDNI

Overview

- What is does
 - Clarify the role of the CDNI control interface;
 - Proposes a framework for control operations;
 - Specify the parameters that should be exchanged;
- What it does not
 - Make assumption about the protocol implementation;
 - it may be either manual or automated

Role of the CDNI control interface

In scope

- bootstrapping the other CDNI interfaces,
- updating or deleting instances of the other
 CDNI interfaces.

Out of Scope

- Operations related to content management are handle on the metadata interface:
 - So trigger-based operations are the responsibility of the metadata interface
 - pre-position, revalidate, and purge both metadata and content.

Framework

Service Agreement

A Service Agreement includes all information required to set up the CDN interconnection. It can be specified with a hierarchical datamodel

++		
Service Agreement		
+		
Delivery Service	++	
+	Delivery Service	
Delivery Service	+	
+	Class-of-requests	
+	+	++
uCDN identifier	Class-of-requests	Class-of requests
+	+	++
dCDN identifier	Class-of-requests	footprint
+	+	++
+	+	+
Parameters	Parameters	properties
+	+	++
++	++	++

Boostrapping

The two CDNs exchange the control parameters previously agreed by the operators of the CDNs. Then, each CDN uses these control parameters to configure appropriately each CDNI functional interface (CDNI Metadata, CDNI Logging and CDNI Request Routing)

/		uCDN		\		/		dCDN	_ \
 	+ 	Control		 	CDNI		+-	Control	+
	 	Control parameters	\ <	 	Control	 	 ->	Control parameters	
 	 +						 +-		 +
`\				/		\			

CDNI Control Operations

Service Agreement Parameters

- Connectivity and security control parameters
- Redirection parameters

Delivery Service Parameters

- CDNI Logging parameters
- CDNI Delivery Requirements parameters

class-of-requests

- class-of-requests identifier
- footprint
- Content request commun properties

That's it.