

PCE Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: April 27, 2015

A. Koushik  
Brocade Communications Inc.  
E. Stephan  
Orange  
Q. Zhao  
Huawei Technology  
D. King  
Old Dog Consulting  
J. Hardwick  
Metaswitch  
October 24, 2014

Path Computation Element Communications Protocol (PCEP) Management  
Information Base (MIB) Module  
draft-ietf-pce-pcep-mib-11

#### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling of Path Computation Element communications Protocol (PCEP) for communications between a Path Computation Client (PCC) and a Path Computation Element (PCE), or between two PCEs.

#### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 27, 2015.

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1.	Introduction . . . . .	2
1.1.	Requirements Language . . . . .	3
1.2.	Terminology . . . . .	3
2.	The Internet-Standard Management Framework . . . . .	3
3.	PCEP MIB Module Architecture . . . . .	4
3.1.	pcePcepEntityTable . . . . .	4
3.2.	pcePcepPeerTable . . . . .	5
3.3.	pcePcepSessTable . . . . .	5
3.4.	PCEP Notifications . . . . .	6
3.5.	Relationship to other MIB modules . . . . .	6
3.6.	Illustrative example . . . . .	6
4.	Object Definitions . . . . .	7
4.1.	PCE-PCEP-MIB . . . . .	7
5.	Security Considerations . . . . .	48
6.	IANA Considerations . . . . .	49
7.	Acknowledgement . . . . .	49
8.	References . . . . .	49
8.1.	Normative References . . . . .	49
8.2.	Informative References . . . . .	50
Appendix A.	Contributors . . . . .	51
Appendix B.	PCEP MIB Module Example . . . . .	51
B.1.	Contents of PCEP MIB module at PCE2 . . . . .	51
B.2.	Contents of PCEP MIB module at PCCb . . . . .	59

## 1. Introduction

The Path Computation Element (PCE) defined in [RFC4655] is an entity that is capable of computing a network path or route based on a network graph, and applying computational constraints. A Path Computation Client (PCC) may make requests to a PCE for paths to be computed.

PCEP is the communication protocol between a PCC and PCE and is defined in [RFC5440]. PCEP interactions include path computation requests and path computation replies as well as notifications of specific states related to the use of a PCE in the context of Multiprotocol Label Switching (MPLS) and Generalized MPLS (GMPLS) Traffic Engineering (TE).

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines a MIB module that can be used to monitor PCEP interactions between a PCC and a PCE, or between two PCEs.

The scope of this document is to provide a MIB module for the PCEP base protocol defined in [RFC5440]. Extensions to the PCEP base protocol are beyond the scope for this document.

### 1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

### 1.2. Terminology

This document uses the terminology defined in [RFC4655] and [RFC5440]. In particular, it uses the following acronyms.

- o Path Computation Request message (PCReq).
- o Path Computation Reply message (PCRep).
- o Notification message (PCNtf).
- o Error message (PCErr).
- o Request Parameters object (RP).
- o Synchronization Vector object (SVEC).
- o Explicit Route object (ERO).

This document uses the term "PCEP entity" to refer to a local PCEP speaker, "peer" to refer to a remote PCEP speaker and "PCEP speaker" where it is not necessary to distinguish between local and remote.

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579], and STD 58, RFC 2580 [RFC2580].

### 3. PCEP MIB Module Architecture

The PCEP MIB module contains the following information:

- a. PCE and PCC local entity status (see `pcePcepEntityTable`).
- b. PCEP peer information (see `pcePcepPeerTable`).
- c. PCEP session information (see `pcePcepSessTable`).
- d. Notifications to indicate PCEP session changes.

The PCEP MIB module is limited to "read-only" access except for `pcePcepNotificationsMaxRate`, which is used to throttle the rate at which the implementation generates notifications.

#### 3.1. `pcePcepEntityTable`

The PCEP MIB module may contain status information for multiple logical local PCEP entities. There are several scenarios in which there may be more than one local PCEP entity, including the following.

- o A physical router, which is partitioned into multiple virtual routers, each with its own PCC.
- o A PCE device which front-ends a cluster of compute resources, each with a different set of capabilities that are accessed via different IP addresses.

The `pcePcepEntityTable` contains one row for each local PCEP entity. Each row is read-only and contains current status information plus the PCEP entity's running configuration.

The `pcePcepEntityTable` is indexed by `pcePcepEntityIndex`, which also acts as the primary index for the other tables in this MIB module.

### 3.2. `pcePcepPeerTable`

The `pcePcepPeerTable` contains one row for each peer that the local PCEP entity knows about. Each row is read-only and contains information to identify the peer, the running configuration relating to that peer and statistics that track the messages exchanged with that peer and its response times.

A PCEP speaker is identified by its IP address. If there is a PCEP speaker in the network that uses multiple IP addresses then it looks like multiple distinct peers to the other PCEP speakers in the network.

The `pcePcepPeerTable` is indexed first by `pcePcepEntityIndex`, then by `pcePcepPeerAddrType` and `pcePcepPeerAddr`. This indexing structure allows each local PCEP entity to report its own set of peers.

Since PCEP sessions can be ephemeral, the `pcePcepPeerTable` tracks a peer even when no PCEP session currently exists to that peer. The statistics contained in `pcePcepPeerTable` are an aggregate of the statistics for all successive sessions to that peer.

To limit the quantity of information that is stored, an implementation MAY choose to discard a row from the `pcePcepPeerTable` if and only if no PCEP session exists to the corresponding peer.

### 3.3. `pcePcepSessTable`

The `pcePcepSessTable` contains one row for each PCEP session that the PCEP entity (PCE or PCC) is currently participating in. Each row is read-only and contains the running configuration that is applied to the session, plus identifiers and statistics for the session.

The statistics in `pcePcepSessTable` are semantically different from those in `pcePcepPeerTable` since the former apply to the current session only, whereas the latter are the aggregate for all sessions that have existed to that peer.

Although [RFC5440] forbids there from being more than one active PCEP session between a given pair of PCEP entities at any one time, there is a window during session establishment where the `pcePcepSessTable` may contain two rows for a given peer, one representing a session initiated by the local PCEP entity and one representing a session initiated by the peer. If either of these sessions reaches active state, then the other is discarded.

The pcePcepSessTable is indexed first by pcePcepEntityIndex, then by pcePcepPeerAddrType and pcePcepPeerAddr, and finally by pcePcepSessInitiator. This indexing structure allows each local PCEP entity to report its own set of active sessions. The pcePcepSessInitiator index allows two rows to exist transiently for a given peer, as discussed above.

### 3.4. PCEP Notifications

The PCEP MIB module contains notifications for the following conditions.

- a. pcePcepSessUp: PCEP Session has gone up.
- b. pcePcepSessDown: PCEP Session has gone down.
- c. pcePcepSessLocalOverload: Local PCEP entity has sent an overload PCNTf on this session.
- d. pcePcepSessLocalOverloadClear: Local PCEP entity has sent an overload-cleared PCNTf on this session.
- e. pcePcepSessPeerOverload: Peer has sent an overload PCNTf on this session.
- f. pcePcepSessPeerOverloadClear: Peer has sent an overload-cleared PCNTf on this session.

### 3.5. Relationship to other MIB modules

The PCEP MIB module imports the following textual conventions from the INET-ADDRESS-MIB defined in RFC 4001 [RFC4001]:

- o InetAddressType
- o InetAddress

PCEP relies on existing protocols which have specialized MIB objects to monitor their own activities. Consequently this document considers that the monitoring of underlying protocols is out of scope of the PCEP MIB module.

### 3.6. Illustrative example

The following diagram illustrates the relationships between the pcePcepEntityTable, pcePcepPeerTable and pcePcepSessTable.



```

Counter32
    FROM SNMPv2-SMI                -- RFC 2578
TruthValue,
TimeStamp
    FROM SNMPv2-TC                -- RFC 2579
MODULE-COMPLIANCE,
OBJECT-GROUP,
NOTIFICATION-GROUP
    FROM SNMPv2-CONF              -- RFC 2580
InetAddressType,
InetAddress
    FROM INET-ADDRESS-MIB;        -- RFC 4001

pcePcepMIB MODULE-IDENTITY
LAST-UPDATED
    "201410241200Z" -- 24 October 2014
ORGANIZATION
    "IETF Path Computation Element (PCE) Working Group"
CONTACT-INFO
    "Email: pce@ietf.org
    WG charter:
        http://www.ietf.org/html.charters/pce-charter.html"

DESCRIPTION
    "This MIB module defines a collection of objects for managing
    Path Computation Element communications Protocol (PCEP).

    Copyright (C) The IETF Trust (2014). This version of this
    MIB module is part of RFC YYYY; see the RFC itself for full
    legal notices."
-- RFC Ed.: replace YYYY with actual RFC number & remove this note
REVISION
    "201410241200Z" -- 24 October 2014
DESCRIPTION
    "Initial version, published as RFC YYYY."
-- RFC Ed.: replace YYYY with actual RFC number & remove this note
::= { mib-2 XXX }
-- RFC Ed.: replace XXX with IANA-assigned number & remove this note

pcePcepNotifications OBJECT IDENTIFIER ::= { pcePcepMIB 0 }
pcePcepObjects        OBJECT IDENTIFIER ::= { pcePcepMIB 1 }
pcePcepConformance    OBJECT IDENTIFIER ::= { pcePcepMIB 2 }

--
-- PCEP Entity Objects
--

pcePcepEntityTable OBJECT-TYPE

```

```

SYNTAX      SEQUENCE OF PcePcepEntityEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "This table contains information about local PCEP entities.
    The entries in this table are read-only."
 ::= { pcePcepObjects 1 }

```

```

pcePcepEntityEntry OBJECT-TYPE
    SYNTAX      PcePcepEntityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This entry represents a local PCEP entity."
    INDEX       { pcePcepEntityIndex }
    ::= { pcePcepEntityTable 1 }

```

```

PcePcepEntityEntry ::= SEQUENCE {
    pcePcepEntityIndex          Unsigned32,
    pcePcepEntityAdminStatus    INTEGER,
    pcePcepEntityOperStatus     INTEGER,
    pcePcepEntityAddrType       InetAddressType,
    pcePcepEntityAddr           InetAddress,
    pcePcepEntityConnectTimer    Unsigned32,
    pcePcepEntityConnectMaxRetry Unsigned32,
    pcePcepEntityInitBackoffTimer Unsigned32,
    pcePcepEntityMaxBackoffTimer Unsigned32,
    pcePcepEntityOpenWaitTimer   Unsigned32,
    pcePcepEntityKeepWaitTimer   Unsigned32,
    pcePcepEntityKeepAliveTimer  Unsigned32,
    pcePcepEntityDeadTimer       Unsigned32,
    pcePcepEntityAllowNegotiation TruthValue,
    pcePcepEntityMaxKeepAliveTimer Unsigned32,
    pcePcepEntityMaxDeadTimer    Unsigned32,
    pcePcepEntityMinKeepAliveTimer Unsigned32,
    pcePcepEntityMinDeadTimer    Unsigned32,
    pcePcepEntitySyncTimer       Unsigned32,
    pcePcepEntityRequestTimer    Unsigned32,
    pcePcepEntityMaxSessions     Unsigned32,
    pcePcepEntityMaxUnknownReqs  Unsigned32,
    pcePcepEntityMaxUnknownMsgs  Unsigned32
}

```

```

pcePcepEntityIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION

```

"This index is used to uniquely identify the PCEP entity."  
 ::= { pcePcepEntityEntry 1 }

pcePcepEntityAdminStatus OBJECT-TYPE

SYNTAX INTEGER {  
     adminStatusUp(1),  
     adminStatusDown(2)  
 }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The administrative status of this PCEP Entity.

This is the desired operational status as currently set by an operator or by default in the implementation. The value of pcePcepEntityOperStatus represents the current status of an attempt to reach this desired status."

::= { pcePcepEntityEntry 2 }

pcePcepEntityOperStatus OBJECT-TYPE

SYNTAX INTEGER {  
     operStatusUp(1),  
     operStatusDown(2),  
     operStatusGoingUp(3),  
     operStatusGoingDown(4),  
     operStatusFailed(5),  
     operStatusFailedPerm(6)  
 }

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The operational status of the PCEP entity. Takes one of the following values.

- operStatusUp(1): the PCEP entity is active.
- operStatusDown(2): the PCEP entity is inactive.
- operStatusGoingUp(3): the PCEP entity is activating.
- operStatusGoingDown(4): the PCEP entity is deactivating.
- operStatusFailed(5): the PCEP entity has failed and will recover when possible.
- operStatusFailedPerm(6): the PCEP entity has failed and will not recover without operator intervention."

::= { pcePcepEntityEntry 3 }

pcePcepEntityAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of the PCEP entity's Internet address. This object specifies how the value of the pcePcepEntityAddr object should be interpreted. Only values unknown(0), ipv4(1), or ipv6(2) are supported."  
 ::= { pcePcepEntityEntry 4 }

pcePcepEntityAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The local Internet address of this PCEP entity. The type is given by pcePcepEntityAddrType.

If operating as a PCE server, the PCEP entity listens on this address. If operating as a PCC, the PCEP entity binds outgoing TCP connections to this address.

It is possible for the PCEP entity to operate both as a PCC and a PCE Server, in which case it uses this address both to listen for incoming TCP connections and to bind outgoing TCP connections."

::= { pcePcepEntityEntry 5 }

pcePcepEntityConnectTimer OBJECT-TYPE

SYNTAX Unsigned32 (1..65535)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time that the PCEP entity will wait to establish a TCP connection with a peer. If a TCP connection is not established within this time then PCEP aborts the session setup attempt."

::= { pcePcepEntityEntry 6 }

pcePcepEntityConnectMaxRetry OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The maximum number of times the system tries to establish a TCP connection to a peer before the session with the peer transitions to the idle state.

When the session transitions to the idle state:

- pcePcepPeerSessionExists transitions to false(2)
- the associated PcePcepSessEntry is deleted

```
        - a backoff timer runs before the session is tried again."
 ::= { pcePcepEntityEntry 7 }

pcePcepEntityInitBackoffTimer OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The initial back-off time for retrying a failed session
        setup attempt to a peer.

        The back-off time increases for each failed session setup
        attempt, until a maximum back-off time is reached.  The
        maximum back-off time is pcePcepEntityMaxBackoffTimer."
 ::= { pcePcepEntityEntry 8 }

pcePcepEntityMaxBackoffTimer OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The maximum back-off time for retrying a failed session
        setup attempt to a peer.

        The back-off time increases for each failed session setup
        attempt, until this maximum value is reached.  Session
        setup attempts then repeat periodically without any
        further increase in back-off time."
 ::= { pcePcepEntityEntry 9 }

pcePcepEntityOpenWaitTimer OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time that the PCEP entity will wait to receive an Open
        message from a peer after the TCP connection has come up.
        If no Open message is received within this time then PCEP
        terminates the TCP connection and deletes the associated
        PcePcepSessEntry."
 ::= { pcePcepEntityEntry 10 }

pcePcepEntityKeepWaitTimer OBJECT-TYPE
    SYNTAX      Unsigned32 (1..65535)
    UNITS       "seconds"
```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The time that the PCEP entity will wait to receive a
    Keepalive or PCErr message from a peer during session
    initialization after receiving an Open message.  If no
    Keepalive or PCErr message is received within this time then
    PCEP terminates the TCP connection and deletes the
    associated PcePcepSessEntry."
 ::= { pcePcepEntityEntry 11 }

pcePcepEntityKeepAliveTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The keep alive transmission timer that this PCEP entity will
    propose in the initial OPEN message of each session it is
    involved in.  This is the maximum time between two
    consecutive messages sent to a peer.  Zero means that
    the PCEP entity prefers not to send Keepalives at all.

    Note that the actual Keepalive transmission intervals, in
    either direction of an active PCEP session, are determined
    by negotiation between the peers as specified by RFC
    5440, and so may differ from this configured value.  For
    the actually negotiated values (per-session), see
    pcePcepSessKeepaliveTimer and
    pcePcepSessPeerKeepaliveTimer."
 ::= { pcePcepEntityEntry 12 }

pcePcepEntityDeadTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The dead timer that this PCEP entity will propose in the
    initial OPEN message of each session it is involved in.
    This is the time after which a peer should declare a
    session down if it does not receive any PCEP messages.
    Zero suggests that the peer does not run a dead timer at
    all."
 ::= { pcePcepEntityEntry 13 }

pcePcepEntityAllowNegotiation OBJECT-TYPE
SYNTAX TruthValue
```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Whether the PCEP entity will permit negotiation of session
    parameters."
 ::= { pcePcepEntityEntry 14 }

pcePcepEntityMaxKeepAliveTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "In PCEP session parameter negotiation, the maximum value
    that this PCEP entity will accept from a peer for the
    interval between Keepalive transmissions. Zero means that
    the PCEP entity will allow no Keepalive transmission at
    all."
 ::= { pcePcepEntityEntry 15 }

pcePcepEntityMaxDeadTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "In PCEP session parameter negotiation, the maximum value
    that this PCEP entity will accept from a peer for the Dead
    timer. Zero means that the PCEP entity will allow not
    running a Dead timer."
 ::= { pcePcepEntityEntry 16 }

pcePcepEntityMinKeepAliveTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "In PCEP session parameter negotiation, the minimum value
    that this PCEP entity will accept for the interval between
    Keepalive transmissions. Zero means that the PCEP entity
    insists on no Keepalive transmission at all."
 ::= { pcePcepEntityEntry 17 }

pcePcepEntityMinDeadTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
```

```
STATUS      current
DESCRIPTION
  "In PCEP session parameter negotiation, the minimum value
  that this PCEP entity will accept for the Dead timer. Zero
  means that the PCEP entity insists on not running a Dead
  timer."
 ::= { pcePcepEntityEntry 18 }
```

pcePcepEntitySyncTimer OBJECT-TYPE

```
SYNTAX      Unsigned32 (0..65535)
UNITS       "seconds"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The value of SyncTimer is used in the case of synchronized path computation request using the SVEC object.

Consider the case where a PCReq message is received by a PCE that contains the SVEC object referring to M synchronized path computation requests. If after the expiration of the SyncTimer all the M path computation requests have not been received, a protocol error is triggered and the PCE MUST cancel the whole set of path computation requests.

The aim of the SyncTimer is to avoid the storage of unused synchronized requests should one of them get lost for some reasons (for example, a misbehaving PCC).

A value of zero is returned if and only if the entity does not use the SyncTimer."

```
 ::= { pcePcepEntityEntry 19 }
```

pcePcepEntityRequestTimer OBJECT-TYPE

```
SYNTAX      Unsigned32 (1..65535)
UNITS       "seconds"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The maximum time that the PCEP entity will wait for a response to a PCReq message."

```
 ::= { pcePcepEntityEntry 20 }
```

pcePcepEntityMaxSessions OBJECT-TYPE

```
SYNTAX      Unsigned32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"Maximum number of sessions involving this PCEP entity

```
        that can exist at any time."
 ::= { pcePcepEntityEntry 21 }

pcePcepEntityMaxUnknownReqs OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The maximum number of unrecognized requests and replies that
        any session on this PCEP entity is willing to accept per
        minute before terminating the session.

        A PCRep message contains an unrecognized reply if it
        contains an RP object whose request ID does not correspond
        to any in-progress request sent by this PCEP entity.

        A PCReq message contains an unrecognized request if it
        contains an RP object whose request ID is zero."
 ::= { pcePcepEntityEntry 22 }

pcePcepEntityMaxUnknownMsgs OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The maximum number of unknown messages that any session
        on this PCEP entity is willing to accept per minute before
        terminating the session."
 ::= { pcePcepEntityEntry 23 }

--
-- The PCEP Peer Table
--

pcePcepPeerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PcePcepPeerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains information about peers known by
        the local PCEP entity.  The entries in this table are
        read-only.

        This table gives peer information that spans PCEP
        sessions.  Information about current PCEP sessions can be
        found in the pcePcepSessTable table."
 ::= { pcePcepObjects 2 }
```

```

pcePcepPeerEntry OBJECT-TYPE
    SYNTAX      PcePcepPeerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a single peer which spans all PCEP
        sessions to that peer."
    INDEX { pcePcepEntityIndex,
            pcePcepPeerAddrType,
            pcePcepPeerAddr }
    ::= { pcePcepPeerTable 1 }

PcePcepPeerEntry ::= SEQUENCE {
    pcePcepPeerAddrType      InetAddressType,
    pcePcepPeerAddr          InetAddress,
    pcePcepPeerRole          INTEGER,
    pcePcepPeerDiscontinuityTime  TimeStamp,
    pcePcepPeerInitiateSession  TruthValue,
    pcePcepPeerSessionExists    TruthValue,
    pcePcepPeerNumSessSetupOK    Counter32,
    pcePcepPeerNumSessSetupFail  Counter32,
    pcePcepPeerSessionUpTime     TimeStamp,
    pcePcepPeerSessionFailTime   TimeStamp,
    pcePcepPeerSessionFailUpTime TimeStamp,
    pcePcepPeerAvgRspTime        Unsigned32,
    pcePcepPeerLWMRspTime        Unsigned32,
    pcePcepPeerHWMRspTime        Unsigned32,
    pcePcepPeerNumPCReqSent      Counter32,
    pcePcepPeerNumPCReqRcvd     Counter32,
    pcePcepPeerNumPCRepSent     Counter32,
    pcePcepPeerNumPCRepRcvd     Counter32,
    pcePcepPeerNumPCErrSent     Counter32,
    pcePcepPeerNumPCErrRcvd     Counter32,
    pcePcepPeerNumPCNtfSent     Counter32,
    pcePcepPeerNumPCNtfRcvd     Counter32,
    pcePcepPeerNumKeepaliveSent  Counter32,
    pcePcepPeerNumKeepaliveRcvd  Counter32,
    pcePcepPeerNumUnknownRcvd   Counter32,
    pcePcepPeerNumCorruptRcvd   Counter32,
    pcePcepPeerNumReqSent       Counter32,
    pcePcepPeerNumSvecSent      Counter32,
    pcePcepPeerNumSvecReqSent    Counter32,
    pcePcepPeerNumReqSentPendRep Counter32,
    pcePcepPeerNumReqSentEroRcvd Counter32,
    pcePcepPeerNumReqSentNoPathRcvd Counter32,
    pcePcepPeerNumReqSentCancelRcvd Counter32,
    pcePcepPeerNumReqSentErrorRcvd Counter32,
    pcePcepPeerNumReqSentTimeout Counter32,

```

```

    pcePcepPeerNumReqSentCancelSent      Counter32,
    pcePcepPeerNumReqSentClosed          Counter32,
    pcePcepPeerNumReqRcvd                Counter32,
    pcePcepPeerNumSvecRcvd               Counter32,
    pcePcepPeerNumSvecReqRcvd            Counter32,
    pcePcepPeerNumReqRcvdPendRep         Counter32,
    pcePcepPeerNumReqRcvdEroSent         Counter32,
    pcePcepPeerNumReqRcvdNoPathSent      Counter32,
    pcePcepPeerNumReqRcvdCancelSent      Counter32,
    pcePcepPeerNumReqRcvdErrorSent       Counter32,
    pcePcepPeerNumReqRcvdCancelRcvd      Counter32,
    pcePcepPeerNumReqRcvdClosed          Counter32,
    pcePcepPeerNumRepRcvdUnknown         Counter32,
    pcePcepPeerNumReqRcvdUnknown         Counter32
}

pcePcepPeerAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The type of the peer's Internet address. This object
        specifies how the value of the pcePcepPeerAddr object should
        be interpreted. Only values unknown(0), ipv4(1), or
        ipv6(2) are supported."
    ::= { pcePcepPeerEntry 1 }

pcePcepPeerAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The Internet address of the peer. The type is given by
        pcePcepPeerAddrType."
    ::= { pcePcepPeerEntry 2 }

pcePcepPeerRole OBJECT-TYPE
    SYNTAX      INTEGER {
                unknown(0),
                pcc(1),
                pce(2),
                pccAndPce(3)
            }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The role that this peer took the last time a session was
        established. Takes one of the following values."

```

- unknown(0): this peer's role is not known.
- pcc(1): this peer is a Path Computation Client (PCC).
- pce(2): this peer is a Path Computation Server (PCE).
- pccAndPce(3): this peer is both a PCC and a PCE."

```
::= { pcePcepPeerEntry 3 }
```

pcePcepPeerDiscontinuityTime OBJECT-TYPE

```
SYNTAX          TimeStamp
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The value of sysUpTime at the time that the information and
    statistics in this row were last reset."
::= { pcePcepPeerEntry 4 }
```

pcePcepPeerInitiateSession OBJECT-TYPE

```
SYNTAX          TruthValue
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "Indicates whether the local PCEP entity initiates sessions
    to this peer, or waits for the peer to initiate a session."
::= { pcePcepPeerEntry 5 }
```

pcePcepPeerSessionExists OBJECT-TYPE

```
SYNTAX          TruthValue
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "Indicates whether a session with this peer currently
    exists."
::= { pcePcepPeerEntry 6 }
```

pcePcepPeerNumSessSetupOK OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The number of PCEP sessions successfully established with
    the peer, including any current session. This counter is
    incremented each time a session with this peer is
    successfully established."
::= { pcePcepPeerEntry 7 }
```

pcePcepPeerNumSessSetupFail OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
```

## DESCRIPTION

"The number of PCEP sessions with the peer that have been attempted but failed before being fully established. This counter is incremented each time a session retry to this peer fails."

::= { pcePcepPeerEntry 8 }

## pcePcepPeerSessionUpTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime the last time a session with this peer was successfully established.

If pcePcepPeerNumSessSetupOK is zero, then this object contains zero."

::= { pcePcepPeerEntry 9 }

## pcePcepPeerSessionFailTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime the last time a session with this peer failed to be established.

If pcePcepPeerNumSessSetupFail is zero, then this object contains zero."

::= { pcePcepPeerEntry 10 }

## pcePcepPeerSessionFailUpTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime the last time a session with this peer failed from active.

If pcePcepPeerNumSessSetupOK is zero, then this object contains zero."

::= { pcePcepPeerEntry 11 }

## pcePcepPeerAvgRspTime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The average response time for this peer.

If an average response time has not been calculated for this peer then this object has the value zero.

If pcePcepPeerRole is pcc then this field is meaningless and is set to zero."

::= { pcePcepPeerEntry 12 }

## pcePcepPeerLWMrspTime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The smallest (low-water mark) response time seen from this peer.

If no responses have been received from this peer then this object has the value zero.

If pcePcepPeerRole is pcc then this field is meaningless and is set to zero."

::= { pcePcepPeerEntry 13 }

## pcePcepPeerHWMrspTime OBJECT-TYPE

SYNTAX Unsigned32

UNITS "milliseconds"

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The greatest (high-water mark) response time seen from this peer.

If no responses have been received from this peer then this object has the value zero.

If pcePcepPeerRole is pcc then this field is meaningless and is set to zero."

::= { pcePcepPeerEntry 14 }

## pcePcepPeerNumPCReqSent OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of PCReq messages sent to this peer."

```
 ::= { pcePcepPeerEntry 15 }

pcePcepPeerNumPCReqRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCReq messages received from this peer."
 ::= { pcePcepPeerEntry 16 }

pcePcepPeerNumPCRepSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCRep messages sent to this peer."
 ::= { pcePcepPeerEntry 17 }

pcePcepPeerNumPCRepRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCRep messages received from this peer."
 ::= { pcePcepPeerEntry 18 }

pcePcepPeerNumPCErrSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCErr messages sent to this peer."
 ::= { pcePcepPeerEntry 19 }

pcePcepPeerNumPCErrRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCErr messages received from this peer."
 ::= { pcePcepPeerEntry 20 }

pcePcepPeerNumPCNtfSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCNtf messages sent to this peer."
```

```
 ::= { pcePcepPeerEntry 21 }

pcePcepPeerNumPCNtfRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCNtf messages received from this peer."
    ::= { pcePcepPeerEntry 22 }

pcePcepPeerNumKeepaliveSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Keepalive messages sent to this peer."
    ::= { pcePcepPeerEntry 23 }

pcePcepPeerNumKeepaliveRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Keepalive messages received from this peer."
    ::= { pcePcepPeerEntry 24 }

pcePcepPeerNumUnknownRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of unknown messages received from this peer."
    ::= { pcePcepPeerEntry 25 }

pcePcepPeerNumCorruptRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of corrupted PCEP message received from this
        peer."
    ::= { pcePcepPeerEntry 26 }

pcePcepPeerNumReqSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

"The number of requests sent to this peer. A request corresponds 1:1 with an RP object in a PCReq message.

This might be greater than pcePcepPeerNumPCReqSent because multiple requests can be batched into a single PCReq message."

::= { pcePcepPeerEntry 27 }

pcePcepPeerNumSvecSent OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of SVEC objects sent to this peer in PCReq messages. An SVEC object represents a set of synchronized requests."

::= { pcePcepPeerEntry 28 }

pcePcepPeerNumSvecReqSent OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of requests sent to this peer that appeared in one or more SVEC objects."

::= { pcePcepPeerEntry 29 }

pcePcepPeerNumReqSentPendRep OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of requests that have been sent to this peer for which a response is still pending."

::= { pcePcepPeerEntry 30 }

pcePcepPeerNumReqSentEroRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of requests that have been sent to this peer for which a response with an ERO object was received. Such responses indicate that a path was successfully computed by the peer."

::= { pcePcepPeerEntry 31 }

pcePcepPeerNumReqSentNoPathRcvd OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The number of requests that have been sent to this peer for
    which a response with a NO-PATH object was received.  Such
    responses indicate that the peer could not find a path to
    satisfy the request."
 ::= { pcePcepPeerEntry 32 }
```

pcePcepPeerNumReqSentCancelRcvd OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The number of requests that were cancelled by the peer with
    a PCNtf message.

    This might be different than pcePcepPeerNumPCNtfRcvd because
    not all PCNtf messages are used to cancel requests, and a
    single PCNtf message can cancel multiple requests."
 ::= { pcePcepPeerEntry 33 }
```

pcePcepPeerNumReqSentErrorRcvd OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The number of requests that were rejected by the peer with a
    PCErr message.

    This might be different than pcePcepPeerNumPCErrRcvd because
    not all PCErr messages are used to reject requests, and a
    single PCErr message can reject multiple requests."
 ::= { pcePcepPeerEntry 34 }
```

pcePcepPeerNumReqSentTimeout OBJECT-TYPE

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The number of requests that have been sent to a peer and
    have been abandoned because the peer has taken too long to
    respond to them."
 ::= { pcePcepPeerEntry 35 }
```

pcePcepPeerNumReqSentCancelSent OBJECT-TYPE

```
SYNTAX          Counter32
```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of requests that were sent to the peer and
    explicitly canceled by the local PCEP entity sending a
    PCNtf."
 ::= { pcePcepPeerEntry 36 }
```

```
pcePcepPeerNumReqSentClosed OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of requests that were sent to the peer and
    implicitly canceled when the session they were sent over was
    closed."
 ::= { pcePcepPeerEntry 37 }
```

```
pcePcepPeerNumReqRcvd OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of requests received from this peer. A request
    corresponds 1:1 with an RP object in a PCReq message.

    This might be greater than pcePcepPeerNumPCReqRcvd because
    multiple requests can be batched into a single PCReq
    message."
 ::= { pcePcepPeerEntry 38 }
```

```
pcePcepPeerNumSvecRcvd OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of SVEC objects received from this peer in PCReq
    messages. An SVEC object represents a set of synchronized
    requests."
 ::= { pcePcepPeerEntry 39 }
```

```
pcePcepPeerNumSvecReqRcvd OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of requests received from this peer that appeared
    in one or more SVEC objects."
```

```
 ::= { pcePcepPeerEntry 40 }

pcePcepPeerNumReqRcvdPendRep OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests that have been received from this
        peer for which a response is still pending."
    ::= { pcePcepPeerEntry 41 }

pcePcepPeerNumReqRcvdEroSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests that have been received from this
        peer for which a response with an ERO object was sent.  Such
        responses indicate that a path was successfully computed by
        the local PCEP entity."
    ::= { pcePcepPeerEntry 42 }

pcePcepPeerNumReqRcvdNoPathSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests that have been received from this
        peer for which a response with a NO-PATH object was sent.
        Such responses indicate that the local PCEP entity could
        not find a path to satisfy the request."
    ::= { pcePcepPeerEntry 43 }

pcePcepPeerNumReqRcvdCancelSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests received from this peer that were
        cancelled by the local PCEP entity sending a PCNtf message.

        This might be different than pcePcepPeerNumPCNtfSent because
        not all PCNtf messages are used to cancel requests, and a
        single PCNtf message can cancel multiple requests."
    ::= { pcePcepPeerEntry 44 }

pcePcepPeerNumReqRcvdErrorSent OBJECT-TYPE
    SYNTAX      Counter32
```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of requests received from this peer that were
    rejected by the local PCEP entity sending a PCErr message.

    This might be different than pcePcepPeerNumPCErrSent because
    not all PCErr messages are used to reject requests, and a
    single PCErr message can reject multiple requests."
 ::= { pcePcepPeerEntry 45 }

pcePcepPeerNumReqRcvdCancelRcvd OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of requests that were received from the peer and
        explicitly canceled by the peer sending a PCNtf."
    ::= { pcePcepPeerEntry 46 }

pcePcepPeerNumReqRcvdClosed OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of requests that were received from the peer and
        implicitly canceled when the session they were received over
        was closed."
    ::= { pcePcepPeerEntry 47 }

pcePcepPeerNumRepRcvdUnknown OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of responses to unknown requests received from
        this peer. A response to an unknown request is a response
        whose RP object does not contain the request ID of any
        request that is currently outstanding on the session."
    ::= { pcePcepPeerEntry 48 }

pcePcepPeerNumReqRcvdUnknown OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of unknown requests that have been received from
        a peer. An unknown request is a request whose RP object
```

```

        contains a request ID of zero."
 ::= { pcePcepPeerEntry 49 }

--
-- The PCEP Sessions Table
--

pcePcepSessTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PcePcepSessEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table of PCEP sessions that involve the local PCEP
        entity.  Each entry in this table represents a single
        session.  The entries in this table are read-only.

        An entry appears in this table when the corresponding PCEP
        session transitions out of idle state.  If the PCEP session
        transitions back into idle state then the corresponding
        entry in this table is removed."
 ::= { pcePcepObjects 3 }

pcePcepSessEntry OBJECT-TYPE
    SYNTAX      PcePcepSessEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This entry represents a single PCEP session in which the
        local PCEP entity participates.

        This entry exists only if the corresponding PCEP session has
        been initialized by some event, such as manual user
        configuration, autodiscovery of a peer, or an incoming TCP
        connection."
    INDEX { pcePcepEntityIndex,
            pcePcepPeerAddrType,
            pcePcepPeerAddr,
            pcePcepSessInitiator }
 ::= { pcePcepSessTable 1 }

PcePcepSessEntry ::= SEQUENCE {
    pcePcepSessInitiator          INTEGER,
    pcePcepSessStateLastChange   TimeStamp,
    pcePcepSessState              INTEGER,
    pcePcepSessConnectRetry      Counter32,
    pcePcepSessLocalID           Unsigned32,
    pcePcepSessRemoteID          Unsigned32,
    pcePcepSessKeepaliveTimer    Unsigned32,

```

```

pcePcepSessPeerKeepaliveTimer      Unsigned32,
pcePcepSessDeadTimer                Unsigned32,
pcePcepSessPeerDeadTimer            Unsigned32,
pcePcepSessKAHoldTimeRem            Unsigned32,
pcePcepSessOverloaded               TruthValue,
pcePcepSessOverloadTime             Unsigned32,
pcePcepSessPeerOverloaded           TruthValue,
pcePcepSessPeerOverloadTime         Unsigned32,
pcePcepSessDiscontinuityTime        TimeStamp,
pcePcepSessAvgRspTime               Unsigned32,
pcePcepSessLWMrspTime               Unsigned32,
pcePcepSessHWMrspTime               Unsigned32,
pcePcepSessNumPCReqSent              Counter32,
pcePcepSessNumPCReqRcvd              Counter32,
pcePcepSessNumPCRepSent              Counter32,
pcePcepSessNumPCRepRcvd              Counter32,
pcePcepSessNumPCErrSent              Counter32,
pcePcepSessNumPCErrRcvd              Counter32,
pcePcepSessNumPCNtfSent              Counter32,
pcePcepSessNumPCNtfRcvd              Counter32,
pcePcepSessNumKeepaliveSent          Counter32,
pcePcepSessNumKeepaliveRcvd          Counter32,
pcePcepSessNumUnknownRcvd            Counter32,
pcePcepSessNumCorruptRcvd            Counter32,
pcePcepSessNumReqSent                Counter32,
pcePcepSessNumSvecSent                Counter32,
pcePcepSessNumSvecReqSent            Counter32,
pcePcepSessNumReqSentPendRep          Counter32,
pcePcepSessNumReqSentEroRcvd          Counter32,
pcePcepSessNumReqSentNoPathRcvd       Counter32,
pcePcepSessNumReqSentCancelRcvd       Counter32,
pcePcepSessNumReqSentErrorRcvd        Counter32,
pcePcepSessNumReqSentTimeout          Counter32,
pcePcepSessNumReqSentCancelSent       Counter32,
pcePcepSessNumReqRcvd                 Counter32,
pcePcepSessNumSvecRcvd                 Counter32,
pcePcepSessNumSvecReqRcvd             Counter32,
pcePcepSessNumReqRcvdPendRep           Counter32,
pcePcepSessNumReqRcvdEroSent           Counter32,
pcePcepSessNumReqRcvdNoPathSent        Counter32,
pcePcepSessNumReqRcvdCancelSent        Counter32,
pcePcepSessNumReqRcvdErrorSent         Counter32,
pcePcepSessNumReqRcvdCancelRcvd        Counter32,
pcePcepSessNumRepRcvdUnknown           Counter32,
pcePcepSessNumReqRcvdUnknown           Counter32
}

pcePcepSessInitiator OBJECT-TYPE

```

```

SYNTAX      INTEGER {
                local(1),
                remote(2)
            }
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The initiator of the session, that is, whether the TCP
    connection was initiated by the local PCEP entity or the
    peer.

    There is a window during session initialization where two
    sessions can exist between a pair of PCEP speakers, each
    initiated by one of the speakers.  One of these sessions is
    always discarded before it leaves OpenWait state.  However,
    before it is discarded, two sessions to the given peer
    appear transiently in this MIB module.  The sessions are
    distinguished by who initiated them, and so this field is an
    index for the pcePcepSessTable."
 ::= { pcePcepSessEntry 1 }

```

```
pcePcepSessStateLastChange OBJECT-TYPE
```

```

SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value of sysUpTime at the time this session entered its
    current state as denoted by the pcePcepSessState object."
 ::= { pcePcepSessEntry 2 }

```

```
pcePcepSessState OBJECT-TYPE
```

```

SYNTAX      INTEGER {
                tcpPending(1),
                openWait(2),
                keepWait(3),
                sessionUp(4)
            }
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The current state of the session.

    The set of possible states excludes the idle state since
    entries do not exist in this table in the idle state."
 ::= { pcePcepSessEntry 3 }

```

```
pcePcepSessConnectRetry OBJECT-TYPE
```

```

SYNTAX      Counter32

```

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of times that the local PCEP entity has
    attempted to establish a TCP connection for this session
    without success. The PCEP entity gives up when this
    reaches pcePcepEntityConnectMaxRetry."
 ::= { pcePcepSessEntry 4 }
```

```
pcePcepSessLocalID OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The value of the PCEP session ID used by the local PCEP
    entity in the Open message for this session.

    If pcePcepSessState is tcpPending then this is the session
    ID that will be used in the Open message. Otherwise, this
    is the session ID that was sent in the Open message."
 ::= { pcePcepSessEntry 5 }
```

```
pcePcepSessRemoteID OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The value of the PCEP session ID used by the peer in its
    Open message for this session.

    If pcePcepSessState is tcpPending or openWait then this
    field is not used and MUST be set to zero."
 ::= { pcePcepSessEntry 6 }
```

```
pcePcepSessKeepaliveTimer OBJECT-TYPE
SYNTAX Unsigned32 (0..255)
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The agreed maximum interval at which the local PCEP entity
    transmits PCEP messages on this PCEP session. Zero means
    that the local PCEP entity never sends Keepalives on this
    session.

    This field is used if and only if pcePcepSessState is
    sessionUp. Otherwise, it is not used and MUST be set to
    zero."
```

```
::= { pcePcepSessEntry 7 }
```

pcePcepSessPeerKeepaliveTimer OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The agreed maximum interval at which the peer transmits PCEP messages on this PCEP session. Zero means that the peer never sends Keepalives on this session.

This field is used if and only if pcePcepSessState is sessionUp. Otherwise, it is not used and MUST be set to zero."

```
::= { pcePcepSessEntry 8 }
```

pcePcepSessDeadTimer OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The DeadTimer interval for this PCEP session."

```
::= { pcePcepSessEntry 9 }
```

pcePcepSessPeerDeadTimer OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The peer's DeadTimer interval for this PCEP session.

If pcePcepSessState is tcpPending or openWait then this field is not used and MUST be set to zero."

```
::= { pcePcepSessEntry 10 }
```

pcePcepSessKAHoldTimeRem OBJECT-TYPE

SYNTAX Unsigned32 (0..255)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The keep alive hold time remaining for this session.

If pcePcepSessState is tcpPending or openWait then this field is not used and MUST be set to zero."

```
 ::= { pcePcepSessEntry 11 }

pcePcepSessOverloaded OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "If the local PCEP entity has informed the peer that it is
         currently overloaded, then this is set to true.  Otherwise,
         it is set to false."
    ::= { pcePcepSessEntry 12 }

pcePcepSessOverloadTime OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The interval of time that is remaining until the local PCEP
         entity will cease to be overloaded on this session.

         This field is only used if pcePcepSessOverloaded is set to
         true.  Otherwise, it is not used and MUST be set to zero."
    ::= { pcePcepSessEntry 13 }

pcePcepSessPeerOverloaded OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "If the peer has informed the local PCEP entity that it is
         currently overloaded, then this is set to true.  Otherwise,
         it is set to false."
    ::= { pcePcepSessEntry 14 }

pcePcepSessPeerOverloadTime OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The interval of time that is remaining until the peer will
         cease to be overloaded.  If it is not known how long the
         peer will stay in overloaded state, this field is set to
         zero.

         This field is only used if pcePcepSessPeerOverloaded is set
         to true.  Otherwise, it is not used and MUST be set to
```

```
        zero."
 ::= { pcePcepSessEntry 15 }

pcePcepSessDiscontinuityTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time that the statistics in
        this row were last reset."
 ::= { pcePcepSessEntry 16 }

pcePcepSessAvgRspTime OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The average response time for this peer on this session.

        If an average response time has not been calculated for this
        peer then this object has the value zero."
 ::= { pcePcepSessEntry 17 }

pcePcepSessLWMrspTime OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The smallest (low-water mark) response time seen from this
        peer on this session.

        If no responses have been received from this peer then this
        object has the value zero."
 ::= { pcePcepSessEntry 18 }

pcePcepSessHWMrspTime OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "milliseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The greatest (high-water mark) response time seen from this
        peer on this session.

        If no responses have been received from this peer then this
        object has the value zero."
```

```
 ::= { pcePcepSessEntry 19 }

pcePcepSessNumPCReqSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCReq messages sent on this session."
 ::= { pcePcepSessEntry 20 }

pcePcepSessNumPCReqRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCReq messages received on this session."
 ::= { pcePcepSessEntry 21 }

pcePcepSessNumPCRepSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCRep messages sent on this session."
 ::= { pcePcepSessEntry 22 }

pcePcepSessNumPCRepRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCRep messages received on this session."
 ::= { pcePcepSessEntry 23 }

pcePcepSessNumPCErrSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCErr messages sent on this session."
 ::= { pcePcepSessEntry 24 }

pcePcepSessNumPCErrRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCErr messages received on this session."
```

```
 ::= { pcePcepSessEntry 25 }

pcePcepSessNumPCNtfSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCNtf messages sent on this session."
 ::= { pcePcepSessEntry 26 }

pcePcepSessNumPCNtfRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of PCNtf messages received on this session."
 ::= { pcePcepSessEntry 27 }

pcePcepSessNumKeepaliveSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Keepalive messages sent on this session."
 ::= { pcePcepSessEntry 28 }

pcePcepSessNumKeepaliveRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of Keepalive messages received on this session."
 ::= { pcePcepSessEntry 29 }

pcePcepSessNumUnknownRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of unknown messages received on this session."
 ::= { pcePcepSessEntry 30 }

pcePcepSessNumCorruptRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of corrupted PCEP message received on this
```

```
        session."
 ::= { pcePcepSessEntry 31 }

pcePcepSessNumReqSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests sent on this session. A request
        corresponds 1:1 with an RP object in a PCReq message.

        This might be greater than pcePcepSessNumPCReqSent because
        multiple requests can be batched into a single PCReq
        message."
 ::= { pcePcepSessEntry 32 }

pcePcepSessNumSvecSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of SVEC objects sent on this session in PCReq
        messages. An SVEC object represents a set of synchronized
        requests."
 ::= { pcePcepSessEntry 33 }

pcePcepSessNumSvecReqSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests sent on this session that appeared in
        one or more SVEC objects."
 ::= { pcePcepSessEntry 34 }

pcePcepSessNumReqSentPendRep OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests that have been sent on this session
        for which a response is still pending."
 ::= { pcePcepSessEntry 35 }

pcePcepSessNumReqSentEroRcvd OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
```

## DESCRIPTION

"The number of successful responses received on this session. A response corresponds 1:1 with an RP object in a PCRep message. A successful response is a response for which an ERO was successfully computed."

::= { pcePcepSessEntry 36 }

## pcePcepSessNumReqSentNoPathRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of unsuccessful responses received on this session. A response corresponds 1:1 with an RP object in a PCRep message. An unsuccessful response is a response with a NO-PATH object."

::= { pcePcepSessEntry 37 }

## pcePcepSessNumReqSentCancelRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests sent on this session that were cancelled by the peer with a PCNtf message.

This might be different than pcePcepSessNumPCNtfRcvd because not all PCNtf messages are used to cancel requests, and a single PCNtf message can cancel multiple requests."

::= { pcePcepSessEntry 38 }

## pcePcepSessNumReqSentErrorRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests sent on this session that were rejected by the peer with a PCErr message.

This might be different than pcePcepSessNumPCErrRcvd because not all PCErr messages are used to reject requests, and a single PCErr message can reject multiple requests."

::= { pcePcepSessEntry 39 }

## pcePcepSessNumReqSentTimeout OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests sent on this session that have been sent to a peer and have been abandoned because the peer has taken too long to respond to them."

::= { pcePcepSessEntry 40 }

## pcePcepSessNumReqSentCancelSent OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests sent on this session that were sent to the peer and explicitly canceled by the local PCEP entity sending a PCNtf."

::= { pcePcepSessEntry 41 }

## pcePcepSessNumReqRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests received on this session. A request corresponds 1:1 with an RP object in a PCReq message.

This might be greater than pcePcepSessNumPCReqRcvd because multiple requests can be batched into a single PCReq message."

::= { pcePcepSessEntry 42 }

## pcePcepSessNumSvecRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of SVEC objects received on this session in PCReq messages. An SVEC object represents a set of synchronized requests."

::= { pcePcepSessEntry 43 }

## pcePcepSessNumSvecReqRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests received on this session that appeared in one or more SVEC objects."

::= { pcePcepSessEntry 44 }

```
pcePcepSessNumReqRcvdPendRep OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests that have been received on this
        session for which a response is still pending."
    ::= { pcePcepSessEntry 45 }

pcePcepSessNumReqRcvdEroSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of successful responses sent on this session. A
        response corresponds 1:1 with an RP object in a PCRep
        message. A successful response is a response for which an
        ERO was successfully computed."
    ::= { pcePcepSessEntry 46 }

pcePcepSessNumReqRcvdNoPathSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of unsuccessful responses sent on this session.
        A response corresponds 1:1 with an RP object in a PCRep
        message. An unsuccessful response is a response with a
        NO-PATH object."
    ::= { pcePcepSessEntry 47 }

pcePcepSessNumReqRcvdCancelSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of requests received on this session that were
        cancelled by the local PCEP entity sending a PCNtf message.

        This might be different than pcePcepSessNumPCNtfSent because
        not all PCNtf messages are used to cancel requests, and a
        single PCNtf message can cancel multiple requests."
    ::= { pcePcepSessEntry 48 }

pcePcepSessNumReqRcvdErrorSent OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
```

## DESCRIPTION

"The number of requests received on this session that were rejected by the local PCEP entity sending a PCErr message.

This might be different than pcePcepSessNumPCErrSent because not all PCErr messages are used to reject requests, and a single PCErr message can reject multiple requests."

::= { pcePcepSessEntry 49 }

## pcePcepSessNumReqRcvdCancelRcvd OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of requests that were received on this session and explicitly canceled by the peer sending a PCNtf."

::= { pcePcepSessEntry 50 }

## pcePcepSessNumRepRcvdUnknown OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of responses to unknown requests received on this session. A response to an unknown request is a response whose RP object does not contain the request ID of any request that is currently outstanding on the session."

::= { pcePcepSessEntry 51 }

## pcePcepSessNumReqRcvdUnknown OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of unknown requests that have been received on this session. An unknown request is a request whose RP object contains a request ID of zero."

::= { pcePcepSessEntry 52 }

---

--- Notifications Configuration

---

## pcePcepNotificationsMaxRate OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-write

STATUS current

## DESCRIPTION

```

    "This variable indicates the maximum number of
    notifications issued per second. If events occur
    more rapidly, the implementation may simply fail to
    emit these notifications during that period, or may
    queue them until an appropriate time. A value of 0
    means no notifications are emitted and all should be
    discarded (that is, not queued)."
```

```
 ::= { pcePcepObjects 4 }
```

```

---
--- Notifications
---

pcePcepSessUp NOTIFICATION-TYPE
  OBJECTS      {
                pcePcepSessState,
                pcePcepSessStateLastChange
              }
  STATUS       current
  DESCRIPTION   "This notification is sent when the value of
                'pcePcepSessState' enters the 'sessionUp' state."
  ::= { pcePcepNotifications 1 }

pcePcepSessDown NOTIFICATION-TYPE
  OBJECTS      {
                pcePcepSessState,
                pcePcepSessStateLastChange
              }
  STATUS       current
  DESCRIPTION   "This notification is sent when the value of
                'pcePcepSessState' leaves the 'sessionUp' state."
  ::= { pcePcepNotifications 2 }

pcePcepSessLocalOverload NOTIFICATION-TYPE
  OBJECTS      {
                pcePcepSessOverloaded,
                pcePcepSessOverloadTime
              }
  STATUS       current
  DESCRIPTION   "This notification is sent when the local PCEP entity enters
                overload state for a peer."
  ::= { pcePcepNotifications 3 }

pcePcepSessLocalOverloadClear NOTIFICATION-TYPE
  OBJECTS      {
```

```

                pcePcepSessOverloaded
            }
    STATUS      current
    DESCRIPTION
        "This notification is sent when the local PCEP entity leaves
        overload state for a peer."
    ::= { pcePcepNotifications 4 }

pcePcepSessPeerOverload NOTIFICATION-TYPE
    OBJECTS      {
                pcePcepSessPeerOverloaded,
                pcePcepSessPeerOverloadTime
            }
    STATUS      current
    DESCRIPTION
        "This notification is sent when a peer enters overload
        state."
    ::= { pcePcepNotifications 5 }

pcePcepSessPeerOverloadClear NOTIFICATION-TYPE
    OBJECTS      {
                pcePcepSessPeerOverloaded
            }
    STATUS      current
    DESCRIPTION
        "This notification is sent when a peer leaves overload
        state."
    ::= { pcePcepNotifications 6 }

--
-- Module Conformance Statement
--

pcePcepCompliances
    OBJECT IDENTIFIER ::= { pcePcepConformance 1 }

pcePcepGroups
    OBJECT IDENTIFIER ::= { pcePcepConformance 2 }

--
-- Read-Only Compliance
--

pcePcepModuleReadOnlyCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The Module is implemented with support for read-only. In
        other words, only monitoring is available by implementing

```

```
    this MODULE-COMPLIANCE."

MODULE -- this module
    MANDATORY-GROUPS {
        pcePcepGeneralGroup,
        pcePcepNotificationsGroup
    }

OBJECT      pcePcepEntityAddrType
SYNTAX      InetAddressType { unknown(0), ipv4(1), ipv6(2) }
DESCRIPTION "Only unknown(0), ipv4(1) and ipv6(2) support
            is required."

OBJECT      pcePcepPeerAddrType
SYNTAX      InetAddressType { unknown(0), ipv4(1), ipv6(2) }
DESCRIPTION "Only unknown(0), ipv4(1) and ipv6(2) support
            is required."

 ::= { pcePcepCompliances 1 }

-- units of conformance

pcePcepGeneralGroup OBJECT-GROUP
    OBJECTS { pcePcepEntityAdminStatus,
              pcePcepEntityOperStatus,
              pcePcepEntityAddrType,
              pcePcepEntityAddr,
              pcePcepEntityConnectTimer,
              pcePcepEntityConnectMaxRetry,
              pcePcepEntityInitBackoffTimer,
              pcePcepEntityMaxBackoffTimer,
              pcePcepEntityOpenWaitTimer,
              pcePcepEntityKeepWaitTimer,
              pcePcepEntityKeepAliveTimer,
              pcePcepEntityDeadTimer,
              pcePcepEntityAllowNegotiation,
              pcePcepEntityMaxKeepAliveTimer,
              pcePcepEntityMaxDeadTimer,
              pcePcepEntityMinKeepAliveTimer,
              pcePcepEntityMinDeadTimer,
              pcePcepEntitySyncTimer,
              pcePcepEntityRequestTimer,
              pcePcepEntityMaxSessions,
              pcePcepEntityMaxUnknownReqs,
              pcePcepEntityMaxUnknownMsgs,
              pcePcepPeerRole,
              pcePcepPeerDiscontinuityTime,
              pcePcepPeerInitiateSession,
```

pcePcepPeerSessionExists,  
pcePcepPeerNumSessSetupOK,  
pcePcepPeerNumSessSetupFail,  
pcePcepPeerSessionUpTime,  
pcePcepPeerSessionFailTime,  
pcePcepPeerSessionFailUpTime,  
pcePcepPeerAvgRspTime,  
pcePcepPeerLWMRspTime,  
pcePcepPeerHWMRspTime,  
pcePcepPeerNumPCReqSent,  
pcePcepPeerNumPCReqRcvd,  
pcePcepPeerNumPCRepSent,  
pcePcepPeerNumPCRepRcvd,  
pcePcepPeerNumPCErrSent,  
pcePcepPeerNumPCErrRcvd,  
pcePcepPeerNumPCNtfSent,  
pcePcepPeerNumPCNtfRcvd,  
pcePcepPeerNumKeepaliveSent,  
pcePcepPeerNumKeepaliveRcvd,  
pcePcepPeerNumUnknownRcvd,  
pcePcepPeerNumCorruptRcvd,  
pcePcepPeerNumReqSent,  
pcePcepPeerNumSvecSent,  
pcePcepPeerNumSvecReqSent,  
pcePcepPeerNumReqSentPendRep,  
pcePcepPeerNumReqSentEroRcvd,  
pcePcepPeerNumReqSentNoPathRcvd,  
pcePcepPeerNumReqSentCancelRcvd,  
pcePcepPeerNumReqSentErrorRcvd,  
pcePcepPeerNumReqSentTimeout,  
pcePcepPeerNumReqSentCancelSent,  
pcePcepPeerNumReqSentClosed,  
pcePcepPeerNumReqRcvd,  
pcePcepPeerNumSvecRcvd,  
pcePcepPeerNumSvecReqRcvd,  
pcePcepPeerNumReqRcvdPendRep,  
pcePcepPeerNumReqRcvdEroSent,  
pcePcepPeerNumReqRcvdNoPathSent,  
pcePcepPeerNumReqRcvdCancelSent,  
pcePcepPeerNumReqRcvdErrorSent,  
pcePcepPeerNumReqRcvdCancelRcvd,  
pcePcepPeerNumReqRcvdClosed,  
pcePcepPeerNumRepRcvdUnknown,  
pcePcepPeerNumReqRcvdUnknown,  
pcePcepSessStateLastChange,  
pcePcepSessState,  
pcePcepSessConnectRetry,  
pcePcepSessLocalID,

pcePcepSessRemoteID,  
pcePcepSessKeepaliveTimer,  
pcePcepSessPeerKeepaliveTimer,  
pcePcepSessDeadTimer,  
pcePcepSessPeerDeadTimer,  
pcePcepSessKAHoldTimeRem,  
pcePcepSessOverloaded,  
pcePcepSessOverloadTime,  
pcePcepSessPeerOverloaded,  
pcePcepSessPeerOverloadTime,  
pcePcepSessDiscontinuityTime,  
pcePcepSessAvgRspTime,  
pcePcepSessLWMrspTime,  
pcePcepSessHWMrspTime,  
pcePcepSessNumPCReqSent,  
pcePcepSessNumPCReqRcvd,  
pcePcepSessNumPCRepSent,  
pcePcepSessNumPCRepRcvd,  
pcePcepSessNumPCErrSent,  
pcePcepSessNumPCErrRcvd,  
pcePcepSessNumPCNtfSent,  
pcePcepSessNumPCNtfRcvd,  
pcePcepSessNumKeepaliveSent,  
pcePcepSessNumKeepaliveRcvd,  
pcePcepSessNumUnknownRcvd,  
pcePcepSessNumCorruptRcvd,  
pcePcepSessNumReqSent,  
pcePcepSessNumSvecSent,  
pcePcepSessNumSvecReqSent,  
pcePcepSessNumReqSentPendRep,  
pcePcepSessNumReqSentEroRcvd,  
pcePcepSessNumReqSentNoPathRcvd,  
pcePcepSessNumReqSentCancelRcvd,  
pcePcepSessNumReqSentErrorRcvd,  
pcePcepSessNumReqSentTimeout,  
pcePcepSessNumReqSentCancelSent,  
pcePcepSessNumReqRcvd,  
pcePcepSessNumSvecRcvd,  
pcePcepSessNumSvecReqRcvd,  
pcePcepSessNumReqRcvdPendRep,  
pcePcepSessNumReqRcvdEroSent,  
pcePcepSessNumReqRcvdNoPathSent,  
pcePcepSessNumReqRcvdCancelSent,  
pcePcepSessNumReqRcvdErrorSent,  
pcePcepSessNumReqRcvdCancelRcvd,  
pcePcepSessNumRepRcvdUnknown,  
pcePcepSessNumReqRcvdUnknown,  
pcePcepNotificationsMaxRate

```

    }
    STATUS current
    DESCRIPTION
        "Objects that apply to all PCEP MIB module implementations."
    ::= { pcePcepGroups 1 }

pcePcepNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { pcePcepSessUp,
                    pcePcepSessDown,
                    pcePcepSessLocalOverload,
                    pcePcepSessLocalOverloadClear,
                    pcePcepSessPeerOverload,
                    pcePcepSessPeerOverloadClear
    }
    STATUS current
    DESCRIPTION
        "The notifications for a PCEP MIB module implementation."
    ::= { pcePcepGroups 2 }

END

```

## 5. Security Considerations

The `pcePcepNotificationsMaxRate` object defined in this MIB module has a MAX-ACCESS clause of read-write. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. In particular, `pcePcepNotificationsMaxRate` may be used improperly to stop notifications being issued, or to permit a flood of notifications to be sent to the management agent at a high rate.

The readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments since, collectively, they provide information about the amount and frequency of path computation requests and responses within the network and can reveal some aspects of its configuration. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 6. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
pcepPcepMIB	{ mib-2 XXX }

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "XXX" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.

## 7. Acknowledgement

The authors would like to thank Santanu Mazumder, Meral Shirazipour and Adrian Farrel for their valuable input.

Funding for the RFC Editor function is currently provided by the Internet Society.

## 8. References

### 8.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.
- [RFC5440] Vasseur, JP. and JL. Le Roux, "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, March 2009.

## 8.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, December 2002.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, June 2004.
- [RFC4655] Farrel, A., Vasseur, J., and J. Ash, "A Path Computation Element (PCE)-Based Architecture", RFC 4655, August 2006.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 5591, June 2009.
- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, June 2009.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, RFC 6353, July 2011.


## Appendix A. Contributors

Dhruv Dhody  
 Huawei Technologies  
 Leela Palace  
 Bangalore, Karnataka 560008  
 India

E-Mail: dhruv.ietf@gmail.com

## Appendix B. PCEP MIB Module Example

This example considers the set of PCC / PCE relationships shown in the following figure. The example shows the contents of the PCEP MIB module as read at PCE2 and PCCb.



The IP addresses of the PCE speakers in this diagram are given in the following table.

PCE1	1.1.1.1
PCE2	2.2.2.2
PCE3	3.3.3.3
PCCa	11.11.11.11
PCCb	22.22.22.22
PCCc	33.33.33.33

In this example, the PCEP session between PCCb and PCE3 is currently down.

## B.1. Contents of PCEP MIB module at PCE2

At PCE2, there is a single local PCEP entity which has three peers (PCCa, PCCb and PCE1). There is a session active to all of these peers.

The contents of the PCEP MIB module as read at PCE2 are as follows.

```

In pcePcepEntityTable {
    pcePcepEntityIndex                1,
    pcePcepEntityAdminStatus          adminStatusUp(1),
    pcePcepEntityOperStatus           operStatusUp(1),
    pcePcepEntityAddrType             ipv4(1),
    pcePcepEntityAddr                 2.2.2.2, -- PCE2
    pcePcepEntityConnectTimer         60,
    pcePcepEntityConnectMaxRetry      5,
    pcePcepEntityInitBackoffTimer     30,
    pcePcepEntityMaxBackoffTimer      3600,
    pcePcepEntityOpenWaitTimer        60,
    pcePcepEntityKeepWaitTimer        60,
    pcePcepEntityKeepAliveTimer       1,
    pcePcepEntityDeadTimer            4,
    pcePcepEntityAllowNegotiation     true(1),
    pcePcepEntityMaxKeepAliveTimer    60,
    pcePcepEntityMaxDeadTimer         240,
    pcePcepEntityMinKeepAliveTimer    1,
    pcePcepEntityMinDeadTimer         4,
    pcePcepEntitySyncTimer            60,
    pcePcepEntityRequestTimer         120,
    pcePcepEntityMaxSessions          999,
    pcePcepEntityMaxUnknownReqs       5,
    pcePcepEntityMaxUnknownMsgs       5
}

In pcePcepPeerTable {
    pcePcepPeerAddrType               ipv4(1), --PCE1
    pcePcepPeerAddr                   1.1.1.1,
    pcePcepPeerRole                    pccAndPce(3),
    pcePcepPeerDiscontinuityTime      TimeStamp,
    pcePcepPeerInitiateSession        true(1),
    pcePcepPeerSessionExists          true(1),
    pcePcepPeerNumSessSetupOK         1,
    pcePcepPeerNumSessSetupFail       0,
    pcePcepPeerSessionUpTime          TimeStamp,
    pcePcepPeerSessionFailTime        0,
    pcePcepPeerSessionFailUpTime     TimeStamp,
    pcePcepPeerAvgRspTime              0,
    pcePcepPeerLWMRspTime             0,
    pcePcepPeerHWMRspTime             0,
    pcePcepPeerNumPCReqSent           0,
    pcePcepPeerNumPCReqRcvd           0,
    pcePcepPeerNumPCRepSent           0,
    pcePcepPeerNumPCRepRcvd           0,
    pcePcepPeerNumPCErrSent           0,

```

```

pcePcepPeerNumPCErrRcvd           0,
pcePcepPeerNumPCNtfSent           0,
pcePcepPeerNumPCNtfRcvd           0,
pcePcepPeerNumKeepaliveSent       123,
pcePcepPeerNumKeepaliveRcvd       123,
pcePcepPeerNumUnknownRcvd         0,
pcePcepPeerNumCorruptRcvd         0,
pcePcepPeerNumReqSent              0,
pcePcepPeerNumSvecSent             0,
pcePcepPeerNumSvecReqSent          0,
pcePcepPeerNumReqSentPendRep       0,
pcePcepPeerNumReqSentEroRcvd       0,
pcePcepPeerNumReqSentNoPathRcvd    0,
pcePcepPeerNumReqSentCancelRcvd    0,
pcePcepPeerNumReqSentErrorRcvd     0,
pcePcepPeerNumReqSentTimeout       0,
pcePcepPeerNumReqSentCancelSent    0,
pcePcepPeerNumReqSentClosed        0,
pcePcepPeerNumReqRcvd              0,
pcePcepPeerNumSvecRcvd             0,
pcePcepPeerNumSvecReqRcvd          0,
pcePcepPeerNumReqRcvdPendRep       0,
pcePcepPeerNumReqRcvdEroSent       0,
pcePcepPeerNumReqRcvdNoPathSent    0,
pcePcepPeerNumReqRcvdCancelSent    0,
pcePcepPeerNumReqRcvdErrorSent     0,
pcePcepPeerNumReqRcvdCancelRcvd    0,
pcePcepPeerNumReqRcvdClosed        0,
pcePcepPeerNumRepRcvdUnknown       0,
pcePcepPeerNumReqRcvdUnknown       0
},
{
pcePcepPeerAddrType                ipv4(1), --PCCa
pcePcepPeerAddr                    11.11.11.11,
pcePcepPeerRole                    pcc(1),
pcePcepPeerDiscontinuityTime       timeStamp,
pcePcepPeerInitiateSession         false(0),
pcePcepPeerSessionExists           true(1),
pcePcepPeerNumSessSetupOK          1,
pcePcepPeerNumSessSetupFail        0,
pcePcepPeerSessionUpTime           timeStamp,
pcePcepPeerSessionFailTime         0,
pcePcepPeerSessionFailUpTime       timeStamp,
pcePcepPeerAvgRspTime              200,
pcePcepPeerLWMRspTime              100,
pcePcepPeerHWMRspTime              300,
pcePcepPeerNumPCReqSent            0,
pcePcepPeerNumPCReqRcvd            3,

```

```

pcePcepPeerNumPCRepSent      3,
pcePcepPeerNumPCRepRcvd     0,
pcePcepPeerNumPCErrSent     0,
pcePcepPeerNumPCErrRcvd    0,
pcePcepPeerNumPCNtfSent     0,
pcePcepPeerNumPCNtfRcvd    0,
pcePcepPeerNumKeepaliveSent 123,
pcePcepPeerNumKeepaliveRcvd 123,
pcePcepPeerNumUnknownRcvd   0,
pcePcepPeerNumCorruptRcvd   0,
pcePcepPeerNumReqSent       0,
pcePcepPeerNumSvecSent      0,
pcePcepPeerNumSvecReqSent   0,
pcePcepPeerNumReqSentPendRep 0,
pcePcepPeerNumReqSentEroRcvd 0,
pcePcepPeerNumReqSentNoPathRcvd 0,
pcePcepPeerNumReqSentCancelRcvd 0,
pcePcepPeerNumReqSentErrorRcvd 0,
pcePcepPeerNumReqSentTimeout 0,
pcePcepPeerNumReqSentCancelSent 0,
pcePcepPeerNumReqSentClosed 0,
pcePcepPeerNumReqRcvd       3,
pcePcepPeerNumSvecRcvd      0,
pcePcepPeerNumSvecReqRcvd   0,
pcePcepPeerNumReqRcvdPendRep 0,
pcePcepPeerNumReqRcvdEroSent 3,
pcePcepPeerNumReqRcvdNoPathSent 0,
pcePcepPeerNumReqRcvdCancelSent 0,
pcePcepPeerNumReqRcvdErrorSent 0,
pcePcepPeerNumReqRcvdCancelRcvd 0,
pcePcepPeerNumReqRcvdClosed 0,
pcePcepPeerNumRepRcvdUnknown 0,
pcePcepPeerNumReqRcvdUnknown 0
},
{
pcePcepPeerAddrType          ipv4(1), -- PCCb
pcePcepPeerAddr              22.22.22.22,
pcePcepPeerRole              pcc(1),
pcePcepPeerDiscontinuityTime TimeStamp,
pcePcepPeerInitiateSession  true(1),
pcePcepPeerSessionExists    true(1),
pcePcepPeerNumSessSetupOK    1,
pcePcepPeerNumSessSetupFail  0,
pcePcepPeerSessionUpTime    TimeStamp,
pcePcepPeerSessionFailTime   0,
pcePcepPeerSessionFailUpTime TimeStamp,
pcePcepPeerAvgRspTime        200,
pcePcepPeerLWMRspTime        100,

```

```

pcePcepPeerHWMRspTime          300,
pcePcepPeerNumPCReqSent        0,
pcePcepPeerNumPCReqRcvd        4,
pcePcepPeerNumPCRepSent        4,
pcePcepPeerNumPCRepRcvd        0,
pcePcepPeerNumPCErrSent        0,
pcePcepPeerNumPCErrRcvd        0,
pcePcepPeerNumPCNtfSent        0,
pcePcepPeerNumPCNtfRcvd        0,
pcePcepPeerNumKeepaliveSent    123,
pcePcepPeerNumKeepaliveRcvd    123,
pcePcepPeerNumUnknownRcvd      0,
pcePcepPeerNumCorruptRcvd      0,
pcePcepPeerNumReqSent          0,
pcePcepPeerNumSvecSent         0,
pcePcepPeerNumSvecReqSent      0,
pcePcepPeerNumReqSentPendRep   0,
pcePcepPeerNumReqSentEroRcvd   0,
pcePcepPeerNumReqSentNoPathRcvd 0,
pcePcepPeerNumReqSentCancelRcvd 0,
pcePcepPeerNumReqSentErrorRcvd 0,
pcePcepPeerNumReqSentTimeout   0,
pcePcepPeerNumReqSentCancelSent 0,
pcePcepPeerNumReqSentClosed    0,
pcePcepPeerNumReqRcvd          4,
pcePcepPeerNumSvecRcvd         0,
pcePcepPeerNumSvecReqRcvd      0,
pcePcepPeerNumReqRcvdPendRep   0,
pcePcepPeerNumReqRcvdEroSent   3,
pcePcepPeerNumReqRcvdNoPathSent 1,
pcePcepPeerNumReqRcvdCancelSent 0,
pcePcepPeerNumReqRcvdErrorSent 0,
pcePcepPeerNumReqRcvdCancelRcvd 0,
pcePcepPeerNumReqRcvdClosed    0,
pcePcepPeerNumRepRcvdUnknown   0,
pcePcepPeerNumReqRcvdUnknown   0
}

In pcePcepSessTable {
    pcePcepSessInitiator          local(1), --PCE1
    pcePcepSessStateLastChange    TimeStamp,
    pcePcepSessState              sessionUp(4),
    pcePcepSessConnectRetry       0,
    pcePcepSessLocalID            1,
    pcePcepSessRemoteID           2,
    pcePcepSessKeepaliveTimer     1,
    pcePcepSessPeerKeepaliveTimer 1,
    pcePcepSessDeadTimer          4,

```

```

pcePcepSessPeerDeadTimer          4,
pcePcepSessKAHoldTimeRem          1,
pcePcepSessOverloaded             false(0),
pcePcepSessOverloadTime           0,
pcePcepSessPeerOverloaded         false(0),
pcePcepSessPeerOverloadTime       0,
pcePcepSessDiscontinuityTime      TimeStamp,
pcePcepSessAvgRspTime              0,
pcePcepSessLWMRspTime             0,
pcePcepSessHWMRspTime             0,
pcePcepSessNumPCReqSent           0,
pcePcepSessNumPCReqRcvd           0,
pcePcepSessNumPCRepSent           0,
pcePcepSessNumPCRepRcvd           0,
pcePcepSessNumPCErrSent           0,
pcePcepSessNumPCErrRcvd           0,
pcePcepSessNumPCNTfSent           0,
pcePcepSessNumPCNTfRcvd           0,
pcePcepSessNumKeepaliveSent       123,
pcePcepSessNumKeepaliveRcvd       123,
pcePcepSessNumUnknownRcvd         0,
pcePcepSessNumCorruptRcvd         0,
pcePcepSessNumReqSent              0,
pcePcepSessNumSvecSent             0,
pcePcepSessNumSvecReqSent         0,
pcePcepSessNumReqSentPendRep      0,
pcePcepSessNumReqSentEroRcvd      0,
pcePcepSessNumReqSentNoPathRcvd   0,
pcePcepSessNumReqSentCancelRcvd   0,
pcePcepSessNumReqSentErrorRcvd    0,
pcePcepSessNumReqSentTimeout      0,
pcePcepSessNumReqSentCancelSent   0,
pcePcepSessNumReqRcvd              0,
pcePcepSessNumSvecRcvd             0,
pcePcepSessNumSvecReqRcvd         0,
pcePcepSessNumReqRcvdPendRep      0,
pcePcepSessNumReqRcvdEroSent      0,
pcePcepSessNumReqRcvdNoPathSent   0,
pcePcepSessNumReqRcvdCancelSent   0,
pcePcepSessNumReqRcvdErrorSent    0,
pcePcepSessNumReqRcvdCancelRcvd   0,
pcePcepSessNumRepRcvdUnknown      0,
pcePcepSessNumReqRcvdUnknown      0
},
{
pcePcepSessInitiator               remote(2), --PCCa
pcePcepSessStateLastChange         TimeStamp,
pcePcepSessState                    sessionUp(4),

```

```

pcePcepSessConnectRetry          0,
pcePcepSessLocalID              2,
pcePcepSessRemoteID             1,
pcePcepSessKeepaliveTimer       1,
pcePcepSessPeerKeepaliveTimer   1,
pcePcepSessDeadTimer            4,
pcePcepSessPeerDeadTimer        4,
pcePcepSessKAHoldTimeRem        1,
pcePcepSessOverloaded           false(0),
pcePcepSessOverloadTime         0,
pcePcepSessPeerOverloaded       false(0),
pcePcepSessPeerOverloadTime     0,
pcePcepSessDiscontinuityTime    TimeStamp,
pcePcepSessAvgRspTime           200,
pcePcepSessLWMRspTime           100,
pcePcepSessHWMRspTime           300,
pcePcepSessNumPCReqSent         0,
pcePcepSessNumPCReqRcvd        1,
pcePcepSessNumPCRepSent         1,
pcePcepSessNumPCRepRcvd        0,
pcePcepSessNumPCErrSent         0,
pcePcepSessNumPCErrRcvd        0,
pcePcepSessNumPCNtfSent         0,
pcePcepSessNumPCNtfRcvd        0,
pcePcepSessNumKeepaliveSent     123,
pcePcepSessNumKeepaliveRcvd    123,
pcePcepSessNumUnknownRcvd       0,
pcePcepSessNumCorruptRcvd       0,
pcePcepSessNumReqSent           0,
pcePcepSessNumSvecSent          0,
pcePcepSessNumSvecReqSent       0,
pcePcepSessNumReqSentPendRep    0,
pcePcepSessNumReqSentEroRcvd    0,
pcePcepSessNumReqSentNoPathRcvd 0,
pcePcepSessNumReqSentCancelRcvd 0,
pcePcepSessNumReqSentErrorRcvd 0,
pcePcepSessNumReqSentTimeout    0,
pcePcepSessNumReqSentCancelSent 0,
pcePcepSessNumReqRcvd           3,
pcePcepSessNumSvecRcvd          0,
pcePcepSessNumSvecReqRcvd       0,
pcePcepSessNumReqRcvdPendRep    0,
pcePcepSessNumReqRcvdEroSent    3,
pcePcepSessNumReqRcvdNoPathSent 0,
pcePcepSessNumReqRcvdCancelSent 0,
pcePcepSessNumReqRcvdErrorSent  0,
pcePcepSessNumReqRcvdCancelRcvd 0,
pcePcepSessNumRepRcvdUnknown    0,

```

```

    pcePcepSessNumReqRcvdUnknown          0
  },
  {
    pcePcepSessInitiator                  remote(2), --PCCb
    pcePcepSessStateLastChange            TimeStamp,
    pcePcepSessState                       sessionUp(4),
    pcePcepSessConnectRetry                0,
    pcePcepSessLocalID                    2,
    pcePcepSessRemoteID                   1,
    pcePcepSessKeepaliveTimer              1,
    pcePcepSessPeerKeepaliveTimer          1,
    pcePcepSessDeadTimer                   4,
    pcePcepSessPeerDeadTimer               4,
    pcePcepSessKAHoldTimeRem               1,
    pcePcepSessOverloaded                  false(0),
    pcePcepSessOverloadTime                0,
    pcePcepSessPeerOverloaded              false(0),
    pcePcepSessPeerOverloadTime            0,
    pcePcepSessDiscontinuityTime           TimeStamp,
    pcePcepSessAvgRspTime                  200,
    pcePcepSessLWMRspTime                  100,
    pcePcepSessHWMRspTime                  300,
    pcePcepSessNumPCReqSent                0,
    pcePcepSessNumPCReqRcvd                4,
    pcePcepSessNumPCRepSent                4,
    pcePcepSessNumPCRepRcvd                0,
    pcePcepSessNumPCErrSent                0,
    pcePcepSessNumPCErrRcvd                0,
    pcePcepSessNumPCNTfSent                0,
    pcePcepSessNumPCNTfRcvd                0,
    pcePcepSessNumKeepaliveSent            123,
    pcePcepSessNumKeepaliveRcvd            123,
    pcePcepSessNumUnknownRcvd              0,
    pcePcepSessNumCorruptRcvd              0,
    pcePcepSessNumReqSent                   0,
    pcePcepSessNumSvecSent                  0,
    pcePcepSessNumSvecReqSent              0,
    pcePcepSessNumReqSentPendRep           0,
    pcePcepSessNumReqSentEroRcvd           0,
    pcePcepSessNumReqSentNoPathRcvd        0,
    pcePcepSessNumReqSentCancelRcvd        0,
    pcePcepSessNumReqSentErrorRcvd         0,
    pcePcepSessNumReqSentTimeout           0,
    pcePcepSessNumReqSentCancelSent        0,
    pcePcepSessNumReqRcvd                  4,
    pcePcepSessNumSvecRcvd                 0,
    pcePcepSessNumSvecReqRcvd              0,
    pcePcepSessNumReqRcvdPendRep           0,

```

```

    pcePcepSessNumReqRcvdEroSent      3,
    pcePcepSessNumReqRcvdNoPathSent   1,
    pcePcepSessNumReqRcvdCancelSent   0,
    pcePcepSessNumReqRcvdErrorSent    0,
    pcePcepSessNumReqRcvdCancelRcvd   0,
    pcePcepSessNumRepRcvdUnknown      0,
    pcePcepSessNumReqRcvdUnknown      0
}

```

## B.2. Contents of PCEP MIB module at PCCb

At PCCb, there is a single local PCEP entity which has two peers (PCE2 and PCE3). There is a session active to PCE2, but the session to PCE3 is currently down.

The contents of the PCEP MIB module as read at PCCb are as follows.

```

In pcePcepEntityTable {
    pcePcepEntityIndex          1,
    pcePcepEntityAdminStatus    adminStatusUp(1),
    pcePcepEntityOperStatus     operStatusUp(1),
    pcePcepEntityAddrType       ipv4(1),
    pcePcepEntityAddr           22.22.22.22, -- PCCb
    pcePcepEntityConnectTimer   60,
    pcePcepEntityConnectMaxRetry 5,
    pcePcepEntityInitBackoffTimer 30,
    pcePcepEntityMaxBackoffTimer 3600,
    pcePcepEntityOpenWaitTimer   60,
    pcePcepEntityKeepWaitTimer   60,
    pcePcepEntityKeepAliveTimer  1,
    pcePcepEntityDeadTimer       4,
    pcePcepEntityAllowNegotiation true(1),
    pcePcepEntityMaxKeepAliveTimer 60,
    pcePcepEntityMaxDeadTimer     240,
    pcePcepEntityMinKeepAliveTimer 1,
    pcePcepEntityMinDeadTimer     4,
    pcePcepEntitySyncTimer        60,
    pcePcepEntityRequestTimer     120,
    pcePcepEntityMaxSessions      999,
    pcePcepEntityMaxUnknownReqs   5,
    pcePcepEntityMaxUnknownMsgs   5
}

```

```

In pcePcepPeerTable {
    pcePcepPeerAddrType         ipv4(1), --PCE2
    pcePcepPeerAddr             2.2.2.2,
    pcePcepPeerRole              pce(2),
    pcePcepPeerDiscontinuityTime TimeStamp,
}

```

```

pcePcepPeerInitiateSession      true(1),
pcePcepPeerSessionExists        true(1)),
pcePcepPeerNumSessSetupOK       0,
pcePcepPeerNumSessSetupFail     1,
pcePcepPeerSessionUpTime        TimeStamp,
pcePcepPeerSessionFailTime      TimeStamp,
pcePcepPeerSessionFailUpTime    TimeStamp,
pcePcepPeerAvgRspTime           0,
pcePcepPeerLWMRspTime           0,
pcePcepPeerHWMRspTime           0,
pcePcepPeerNumPCReqSent         4,
pcePcepPeerNumPCReqRcvd         0,
pcePcepPeerNumPCRepSent         0,
pcePcepPeerNumPCRepRcvd         4,
pcePcepPeerNumPCErrSent         0,
pcePcepPeerNumPCErrRcvd         0,
pcePcepPeerNumPCNtfSent         0,
pcePcepPeerNumPCNtfRcvd         0,
pcePcepPeerNumKeepaliveSent     0,
pcePcepPeerNumKeepaliveRcvd     0,
pcePcepPeerNumUnknownRcvd       0,
pcePcepPeerNumCorruptRcvd       0,
pcePcepPeerNumReqSent           4,
pcePcepPeerNumSvecSent          0,
pcePcepPeerNumSvecReqSent       0,
pcePcepPeerNumReqSentPendRep    0,
pcePcepPeerNumReqSentEroRcvd    3,
pcePcepPeerNumReqSentNoPathRcvd 1,
pcePcepPeerNumReqSentCancelRcvd 0,
pcePcepPeerNumReqSentErrorRcvd  0,
pcePcepPeerNumReqSentTimeout    0,
pcePcepPeerNumReqSentCancelSent 0,
pcePcepPeerNumReqSentClosed     0,
pcePcepPeerNumReqRcvd           0,
pcePcepPeerNumSvecRcvd          0,
pcePcepPeerNumSvecReqRcvd       0,
pcePcepPeerNumReqRcvdPendRep    0,
pcePcepPeerNumReqRcvdEroSent    0,
pcePcepPeerNumReqRcvdNoPathSent 0,
pcePcepPeerNumReqRcvdCancelSent 0,
pcePcepPeerNumReqRcvdErrorSent  0,
pcePcepPeerNumReqRcvdCancelRcvd 0,
pcePcepPeerNumReqRcvdClosed     0,
pcePcepPeerNumRepRcvdUnknown    0,
pcePcepPeerNumReqRcvdUnknown    0
},
{
pcePcepPeerAddrType              ipv4(1),  --PCE3

```

```

pcePcepPeerAddr          3.3.3.3,
pcePcepPeerRole          pce(2),
pcePcepPeerDiscontinuityTime  TimeStamp,
pcePcepPeerInitiateSession true(1),
pcePcepPeerSessionExists  false(0),
pcePcepPeerNumSessSetupOK  1,
pcePcepPeerNumSessSetupFail 0,
pcePcepPeerSessionUpTime  TimeStamp,
pcePcepPeerSessionFailTime TimeStamp,
pcePcepPeerSessionFailUpTime TimeStamp,
pcePcepPeerAvgRspTime     200,
pcePcepPeerLWMRspTime    100,
pcePcepPeerHWMRspTime    300,
pcePcepPeerNumPCReqSent   4,
pcePcepPeerNumPCReqRcvd   0,
pcePcepPeerNumPCRepSent   0,
pcePcepPeerNumPCRepRcvd   3,
pcePcepPeerNumPCErrSent   0,
pcePcepPeerNumPCErrRcvd   0,
pcePcepPeerNumPCNtfSent   0,
pcePcepPeerNumPCNtfRcvd   0,
pcePcepPeerNumKeepaliveSent 123,
pcePcepPeerNumKeepaliveRcvd 123,
pcePcepPeerNumUnknownRcvd  0,
pcePcepPeerNumCorruptRcvd  0,
pcePcepPeerNumReqSent      4,
pcePcepPeerNumSvecSent     0,
pcePcepPeerNumSvecReqSent  0,
pcePcepPeerNumReqSentPendRep 0,
pcePcepPeerNumReqSentEroRcvd 3,
pcePcepPeerNumReqSentNoPathRcvd 0,
pcePcepPeerNumReqSentCancelRcvd 0,
pcePcepPeerNumReqSentErrorRcvd 0,
pcePcepPeerNumReqSentTimeout 0,
pcePcepPeerNumReqSentCancelSent 0,
pcePcepPeerNumReqSentClosed 1,
pcePcepPeerNumReqRcvd     0,
pcePcepPeerNumSvecRcvd    0,
pcePcepPeerNumSvecReqRcvd 0,
pcePcepPeerNumReqRcvdPendRep 0,
pcePcepPeerNumReqRcvdEroSent 0,
pcePcepPeerNumReqRcvdNoPathSent 0,
pcePcepPeerNumReqRcvdCancelSent 0,
pcePcepPeerNumReqRcvdErrorSent 0,
pcePcepPeerNumReqRcvdCancelRcvd 0,
pcePcepPeerNumReqRcvdClosed 0,
pcePcepPeerNumRepRcvdUnknown 0,
pcePcepPeerNumReqRcvdUnknown 0

```

```

}

In pcePcepSessTable {
    pcePcepSessInitiator                local(1), --PCE2
    pcePcepSessStateLastChange          TimeStamp,
    pcePcepSessState                    sessionUp(4),
    pcePcepSessConnectRetry             0,
    pcePcepSessLocalID                  1,
    pcePcepSessRemoteID                 1,
    pcePcepSessKeepaliveTimer           1,
    pcePcepSessPeerKeepaliveTimer       1,
    pcePcepSessDeadTimer                 4,
    pcePcepSessPeerDeadTimer            4,
    pcePcepSessKAHoldTimeRem            1,
    pcePcepSessOverloaded                false(0),
    pcePcepSessOverloadTime             0,
    pcePcepSessPeerOverloaded           false(0),
    pcePcepSessPeerOverloadTime         0,
    pcePcepSessDiscontinuityTime        TimeStamp,
    pcePcepSessAvgRspTime                200,
    pcePcepSessLWMRspTime               100,
    pcePcepSessHWMRspTime               300,
    pcePcepSessNumPCReqSent              4,
    pcePcepSessNumPCReqRcvd             0,
    pcePcepSessNumPCRepSent              0,
    pcePcepSessNumPCRepRcvd             4,
    pcePcepSessNumPCErrSent              0,
    pcePcepSessNumPCErrRcvd             0,
    pcePcepSessNumPCNTfSent             0,
    pcePcepSessNumPCNTfRcvd             0,
    pcePcepSessNumKeepaliveSent          123,
    pcePcepSessNumKeepaliveRcvd         123,
    pcePcepSessNumUnknownRcvd           0,
    pcePcepSessNumCorruptRcvd           0,
    pcePcepSessNumReqSent                4,
    pcePcepSessNumSvecSent               0,
    pcePcepSessNumSvecReqSent            0,
    pcePcepSessNumReqSentPendRep        0,
    pcePcepSessNumReqSentEroRcvd        3,
    pcePcepSessNumReqSentNoPathRcvd    1,
    pcePcepSessNumReqSentCancelRcvd     0,
    pcePcepSessNumReqSentErrorRcvd     0,
    pcePcepSessNumReqSentTimeout        0,
    pcePcepSessNumReqSentCancelSent     0,
    pcePcepSessNumReqRcvd               0,
    pcePcepSessNumSvecRcvd              0,
    pcePcepSessNumSvecReqRcvd          0,
    pcePcepSessNumReqRcvdPendRep        0,

```

```
pcePcepSessNumReqRcvdEroSent      0,  
pcePcepSessNumReqRcvdNoPathSent   0,  
pcePcepSessNumReqRcvdCancelSent   0,  
pcePcepSessNumReqRcvdErrorSent    0,  
pcePcepSessNumReqRcvdCancelRcvd   0,  
pcePcepSessNumRepRcvdUnknown      0,  
pcePcepSessNumReqRcvdUnknown      0  
}
```

-- no session to PCE3

#### Authors' Addresses

Agrahara Kiran Koushik  
Brocade Communications Inc.

EMail: [kkoushik@brocade.com](mailto:kkoushik@brocade.com)

Emile Stephan  
Orange  
2 avenue Pierre Marzin  
Lannion F-22307  
France

EMail: [emile.stephan@orange.com](mailto:emile.stephan@orange.com)

Quintin Zhao  
Huawei Technology  
125 Nagog Technology Park  
Acton, MA 01719  
US

EMail: [qzhao@huawei.com](mailto:qzhao@huawei.com)

Daniel King  
Old Dog Consulting

EMail: [daniel@olddog.co.uk](mailto:daniel@olddog.co.uk)

Jonathan Hardwick  
Metaswitch  
100 Church Street  
Enfield EN2 6BQ  
UK

EMail: [jonathan.hardwick@metaswitch.com](mailto:jonathan.hardwick@metaswitch.com)