LWIG terminology document draft-ietf-lwig-terminology-01

Carsten Bormann < cabo@tzi.org > IETF86, 2013-03-13

History

- Split out the stable terminology from the guidance document.
- Decided in Atlanta, implemented shortly before Orlando.
- Pretty much done, ship it?
- But then, Peter van der Stok suggested to add power terminology

3: "Classes of Constrained Devices"

Distinguish 3 rough classes of constrained nodes:

- **(0)** ≪10 KiB data/≪100 KiB code ("class 0")
- (1) 10 KiB data/100 KiB code ("quite constrained")
- (2) 50 KiB data/250 KiB code ("not so constrained")
- Stable Terminology since Prague Workshop (2011)

2: Base terminology

- Constrained nodes
- Constrained networks
 - ⊋ challenged networks
- Constrained node networks
 - LLNs (?)
 - LoWPANs, 6LoWPANs

Proposal: Add power terminology

- RFC 6606: "power-affluent" vs. primary battery
 - emergency lights are "battery-operated", right?
- LLN "Low-power ..."????
- RFC 5673: Scavenging
 - from 4..20 mA: milliwatts
 - from vibration: microwatts
- Scavenging? Harvesting?
 Solar operated parking cash points?
- 333

Systematic approach?

- Quantitative scale
 - sustained average power (in W)
 - lifetime energy (in J, if defined)
- Boolean attributes
 - lifetime energy-limited
 (primary battery, irreplaceable)
 - "Every packet they send today is a packet they cannot send tomorrow."
 - event energy-limited (harvesting light switch)
 - period energy-limited (daily recharge, solar cycle)

Trying a scale for sustained power

- Kilowatt (data center)
- Hectowatt, Decawatt (desktop, laptop)
- Watt (iPad, smartphone in active state)
- Deciwatt (recharged daily, in-wall, ...)
- Centiwatt (recharged weekly)
- Milliwatt, sub-milliwatt, ...
- Tens of Microwatt (Decade off AA)

• ...

Hmm.

- Are there useful clusters?
- Can't we just use the SI units?

Can we agree on some useful clusters?

 We could still define good names for some Booleans.

Way forward?

Let's timebox this.

- If we come up with consensus in March: put it in.
- Otherwise, ship terminology to IESG as is.