

PCP Anycast

Stuart Cheshire <cheshire@apple.com>
IETF 86, 12th March 2013, Orlando, Florida

Basic Concept

- If outbound TCP SYN addressed to a host “on the Internet” can create implicit mapping state, then why not use an outbound PCP packet addressed to a pretend host “on the Internet” to create state?
- Six-page Internet Draft (2 pages of content)
 - <http://www.ietf.org/id/draft-cheshire-pcp-anycast-01.txt>

Observation

- Anycast often used for service discovery; often requires careful configuration
- In this case anycast specifically requires no configuration — we want outbound packets to take their natural path

Comparison with draft-kiesel-pcp-ip-based-srv-disc-00

- draft-kiesel-pcp-ip-based-srv-disc is a separate discovery step, prior to issuing PCP mapping requests
- draft-cheshire-pcp-anycast is not a separate step, it's just an address to use for PCP mapping requests

Why not DHCP?

- TCP SYNs today make mappings without additional help from DHCP.
 - Why should PCP need special DHCP support?
- DHCP Server may be run by different dept.
 - Anything configured can be configured wrong
- 3GPP doesn't use DHCP
 - (Prior to Release 10?)

Discussion

- What about cases where the PCP client needs to create rules in multiple different egress/ingress firewalls?
- But... will any PCP client try to handle that?