ALTO Server Discovery

IETF#87, Berlin, 2013-07-29

Sebastian Kiesel

sebastian.kiesel@izus.uni-stuttgart.de

Recap

One architecture, two drafts

Step 1

 DHCP
 Manual Input
 Reverse-DNS
 Step 2
 U-NAPTR Lookup

 Step 1

 draft-kist-alto-3pdisc-04
 draft-kiesel-alto-3pdisc-impl-00

IETF#87, Berlin, 2013-07-29

Sebastian Kiesel

sebastian.kiesel@izus.uni-stuttgart.de

- IETF Last Call on -08 2013-06-06 .. 2013-06-20
- Thanks for feedback to
 - Meral Shirazipour (Gen-ART): Typos
 - Tina Tsou (Secdir):
 - Inconsistency in order DHCP vs. manual input
 - Security considerations in general
 - Typos
- New version -09 submitted today!
 - Delayed due to submission cutoff
 - Tina has reviewed a preview version and says her issues are resolved

Diffs -08 to -09

- It has always been intended that manual input serves as a fallback if DHCP is not available
 AND to override DHCP if the user wants to
- Clarify that presence of a manual configuration has to be checked before trying DHCP – otherwise overriding won't work

- Security Considerations section nearly re-written from scratch
 - Now matches the high quality of other ALTO documents ©
- Discussion of four protection goals
 - Integrity of the ALTO Server's URI
 - probably the most serious security concern related to ALTO server discovery
 - Possible attack vectors: manual c., DHCP, DNS follow BCPs for securing DHCP, DNS
 - Note: if DHCP or DNS are compromised, much worse things can happen
 - Note: TLS cert will auth. The IRD URI, not the U-NAPTR input domain name
 - Availability of the ALTO Server Discovery Procedure
 - Undesirable, but not extremely critical (apps should be able to handle unavailability)
 - Follow BCPs for securing DHCP and DNS
 - Confidentiality of the ALTO Server's URI
 - Not a threat in the deployment scenarios discussed so far re-evaluate if necessary
 - Privacy for ALTO Clients
 - Not a threat in the deployment scenarios discussed so far re-evaluate if necessary

Next steps

- Ready for publication!
- Thanks to all contributors & reviewers!

IETF#87, Berlin, 2013-07-29

Sebastian Kiesel

sebastian.kiesel@izus.uni-stuttgart.de

- The "missing piece" document
 - Support for 3pdisc is a requirement (AR-33 in RFC 6708)
 - May also be useful* if DHCP is not available and manual configuration is undesirable (i.e., if the other draft does not work)

^{*} various footnotes on UNSAF and other deployment issues apply

Since last meeting

- -03 (2013-05-16) adds lots of clarifications and deployment considerations, but does not change the algorithm
- -04 (2013-06-15) change to the algorithm, still ongoing discussion with DNS directorate
 - Store NAPTR records directly in "reverse tree"
 - Proof-of-concept implementation changed and verified to work,
 but new version not published yet

Discussions with the DNS directorate

- Thanks to Olafur Gudmundsson for extensive discussions
- Discussions are still ongoing, focusing on details
- So far, we did not receive a written certificate that the DNS directorate thinks that this is a really good idea
- But, we did not receive a "oh no! the Internet will melt down if you do that!" either ☺

Next Steps

- Continue discussions with DNS folks
- Publish updated implementation and testbed
- Adopt as a WG item?