Separation of Control and User Plane for Proxy Mobile IPv6

IETF 87

Ryuji Wakikawa

Rajesh S. Pazhyannur

Sri Gundavelli

Motivation

1) Proxy Mobile IP (RFC5213)

| MN | MAG | LMA | Internet |

2) Alternate CoA mobility option

MAG: CP, UP — LMA — Internet; MN connects to MAG.

3) LMA User Plane Address Mobility Option

MAG: CP, UP — LMA: CP, UP — Internet; MN connects to MAG.

Use Cases: Service Provider WiFi

LMA User Plane Address Mobility Option

```
 0                   1                   2                   3
 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|     Type      |    Length     |           Reserved            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                                                               |
+                                                               +
|                                                               |
.                  LMA User Plane Address                       .
+                                                               +
|                                                               |
+                                                               +
|                                                               |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
```

Next Step

- This work is repeatedly proposed since 2008.
- There are many supports on ML.

- Adapting this work in netext working group!?
  - Definition of a mobility option for LMA User Plane Address.