

CCAMP Working Group  
Internet Draft  
Intended status: Standards Track

Vishnu Pavan Beeram (Ed)  
Juniper Networks  
Igor Bryskin (Ed)  
ADVA Optical Networking

Expires: April 21, 2014

October 21, 2013

Shared Resource Link Group (SRCLG)  
draft-beeram-ccamp-srclg-00.txt

#### Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on April 21, 2014.

#### Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in

Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Abstract

This document introduces the concept of SRcLG ("Shared Resource Link Group") and discusses its usage in the context of mutually exclusive Virtual TE Links.

## Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC-2119 [RFC2119].

## Table of Contents

|  |   |
|--|---|
| 1. Introduction.....                       | 2 |
| 2. Dynamic Mutual Exclusivity.....         | 3 |
| 3. Shared Resource Link Group (SRcLG)..... | 5 |
| 3.1. Construct.....                        | 6 |
| 3.2. Advertising Rules.....                | 7 |
| 3.3. Processing Rules.....                 | 7 |
| 4. Security Considerations.....            | 7 |
| 5. IANA Considerations.....                | 7 |
| 6. Normative References.....               | 7 |
| 7. Acknowledgments.....                    | 8 |

## 1. Introduction

A Virtual TE Link (as defined in [RFC6001]) advertised into a Client Network Domain represents a potentiality to setup an LSP in the Server Network Domain to support the advertised TE link. The Virtual TE Link gets advertised like any other TE link and follows the same rules that are defined for the advertising, processing and use of regular TE links [RFC4202]. However, "mutual exclusivity" is one attribute that is specific to Virtual TE Links.

[DRAFT-MELG] discusses the different types of mutual exclusivity (Static vs Dynamic) that come into play, explains the need to advertise this information into the Client TE Domain and introduces a new TE construct (MELG) to carry static mutual exclusivity information.

This document is a companion document to [DRAFT-MELG]. It discusses "Dynamic Mutual Exclusivity" in detail and introduces a new TE construct (SRcLG) to carry dynamic mutual exclusivity information.

2. Dynamic Mutual Exclusivity

As discussed in [DRAFT-MELG], this type of mutual exclusivity exists temporarily within a given network configuration. It comes into play when two or more Virtual TE Links depend on the usage of the same shareable underlying server network domain resource. Mutual Exclusivity exists when the amount of the said server resource that is available for sharing is limited temporarily; it ceases to exist when sufficient amount of the resource is available for accommodating all corresponding Virtual TE Links.




Figure 1a: Sample topology

Consider the network topology depicted in Figure 1a. This is a typical packet optical transport deployment scenario where the WDM layer network domain serves as a Server Network Domain providing transport connectivity to the packet layer network Domain (Client Network Domain).

Nodes R1, R2, R3 and R4 are IP routers that are connected to an Optical WDM transport network. A, B, C, D, E and F are WDM nodes



shown in Fig 2a and the corresponding augmented Client TE topology is as illustrated in Fig 2b.




Figure 2b: Client TE Database - Mutually Exclusive Virtual TE Links

In this particular example, all three potential paths traverse through the WDM-Link {D-F}. Now assume that this link has only 2 lambda channels available. Also assume that any available lambda can get picked for each of these 3 corresponding underlying server LSPs. This means that only two out of the three Virtual TE Links can get committed at the moment. This dynamic mutual exclusivity ceases to exist when a third lambda channel becomes available on the WDM-link {D-F}.

This document proposes the use of "Shared Resource Link Group (SRcLG)" for catering to this scenario.


### 3. Shared Resource Link Group (SRcLG)

SRLG (Shared Risk Link Group - [RFC4202]) represents a set of links that share a resource whose failure may affect all links in the set. Since dynamic mutual exclusivity comes into play when the underlying server resource is shareable, all corresponding Virtual TE-Links would belong to the same SRLG. This document introduces the notion of a "Shared Resource Link Group (SRcLG)", which is meaningful only in the context of Virtual TE Links. SRcLG represents a set of Virtual TE-links that depend on the usage of a shared server-layer

resource that has a variable bandwidth capacity and as a result may sometimes not be able to simultaneously accommodate all corresponding Virtual TE-Links in the set. As is the case with SRLGs, a given Virtual TE Link may belong to multiple SRcLGs.

3.1. Construct

In terms of the TE construct that gets advertised, an SRcLG is nothing but an SRLG with some additional information to help determine which and how many of the corresponding virtual TE Links can get committed simultaneously. This additional information is the per-priority available shared resource bandwidth associated with a given SRLG. Since an SRcLG cannot exist without the presence of a corresponding SRLG, the SRcLG is identified by the corresponding 32-bit SRLG-ID. In other words, the SRcLG-ID is the same as the identifier of the SRLG it represents.



The SRcLG information advertised into the Client TE Domain is an unordered list of SRcLGs present in a given Virtual Topology. Unlike the SRLG construct or the MELG construct, the SRcLG construct does not get advertised per TE-Link. This is because the information carried in this construct is quite dynamic in nature and advertising it per TE-Link poses serious scaling concerns.

### 3.2. Advertising Rules

As far as the advertisement of a Virtual TE-Link is concerned, there is no perceived difference between SRLG and SRcLG. The 32-bit IDs of all SRcLGs that a Virtual TE-Link belongs to are advertised via the SRLG construct. Additionally, all SRcLG information associated with a given Virtual Topology is advertised into the Client TE Domain by the provider of the Virtual Topology. It is the responsibility of this provider to keep the bandwidth availability information for each SRcLG current with timely updates. The draft envisions that one or more server domain OSPF/ISIS TE speakers will be tasked to provide these timely updates. This TE speaker may advertise all SRcLG information (that it is responsible for) in the same OSPF-LSA/ISIS-LSP or advertise each SRcLG TLV separately - one in each OSPF-LSA/ISIS-LSP.

### 3.3. Processing Rules

The intended consumer of this SRcLG information is the PCE in the Client TE Domain. The Client PCE should take this advertised information into account when performing path selection for services over the Virtual Topology provided by the network domain. In particular, this information should be used when deciding how many Virtual TE links could be accommodated simultaneously on a given SRcLG at a given priority level.

## 4. Security Considerations

TBD

## 5. IANA Considerations

TBD

## 6. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC4202] K.Kompella, Y.Rekhter, "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", RFC4202, October 2005.
- [RFC6001] D.Papadimitriou, M.Vigoureaux, K.Shiomoto, D.Brungard

and JL. Le Roux, "GMPLS Protocol Extensions for Multi-Layer and Multi-Region Networks", RFC 6001, October 2010.

[DRAFT-MELG] Beeram, V., "Mutual Exclusive Shared Link Group", draft-beeram-ccamp-melg, October 2013

## 7. Acknowledgments

TBD

## Authors' Addresses

Vishnu Pavan Beeram  
Juniper Networks  
Email: vbeeram@juniper.net

Igor Bryskin  
ADVA Optical Networking  
Email: ibryskin@advaoptical.com

Cyril Margaria  
Email: cyril.margaria@gmail.com

Fatai Zhang  
Huawei Technologies  
Email: zhangfatai@huawei.com