

Network Working Group
INTERNET-DRAFT
Intended Status: Proposed Standard
Expires: January 12, 2014

Takuo Suganuma
Tohoku University
Naoki Nakamura
Tohoku University
Satoru Izumi
Tohoku University
Hiroshi Tsunoda
Tohoku Institute of Technology
Masahiro Matsuda
Tohoku Institute of Technology
Kohei Ohta
Cyber Solutions
July 11, 2013

<Green Usage Monitoring Information Base>
draft-suganuma-greenmib-02.txt

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This document is a product of the EMAN Working Group. Comments should be addressed to the authors or the mailing list at eman@ietf.org

This Internet-Draft will expire on January 12, 2014.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Abstract

This memo defines a portion of the Management Information Base (MIB), the GreenUsage MIB, for use with network management protocols in the Internet community. In particular, the GreenUsage MIB can be used to monitor the power-on/power-off status of electrical devices.

Table of Contents

1. The Internet-Standard Management Framework	3
2. Overview	3
2.1. The GreenUsage monitoring concept	3
2.2. Terminology	3
3. GreenUsage Monitoring Requirements	4
4. MIB Design	4
5. MIB Definitions	5
5.1. The GreenUsage MIB	5
6. Security Considerations	13
7. IANA Considerations	13
8. References	14
8.1. Normative References	14
8.2. Informative References	14
9. Acknowledgements	15
10. Authors' Addresses	15

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP).

Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

2. Overview

2.1. The GreenUsage monitoring concept

Monitor the power-on/power-off status of electrical devices. If a device is in power-on state beyond business hours, it is wasteful usage of electricity. The GreenUsage concept aims to monitor and reduce this wastage.

The GreenUsage-MIB is simple and easy to use and develop. The GreenUsage-MIB aims to reduce the wastage of the existing network systems in easy way. The GreenUsage-MIB is a simple structure, but ALL connected devices can be monitored based on their network activity.

This document defines a set of managed objects (MOs) that can be used to monitor the power-on/power-off status of electrical devices.

2.2. Terminology

Electrical device: a device that consumes electricity. Power-on/power-off status indicates whether the device is powered on or not. Often it is not possible to get a direct indication of whether a device is powered on or not. But indirect means may be used to infer the power-on/power-off status of a device. For example, if a device shows some network activity, it can be inferred that the device is powered on. Note that it is difficult to infer that a device is powered off. Also, there may be several states between power-on and power-off e.g. sleep state, power-saving state etc.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

3. GreenUsage Monitoring Requirements

Multiple mechanisms may be used to determine whether a device is powered on or not. The mechanisms will depend on the nature of the device. Since the number of devices may be very large, the identification, usage type, and location of devices needs to be addressed with care.

4. MIB Design

The basic principle has been to keep the MIB as simple as possible and at the same time to make it effective enough so that the essential needs of monitoring are met.

The GreenUsage-MIB is composed of the following

- device Table: a list of the devices that will be monitored
- deviceStatus Table: the power-on/power-off status of the devices

5. MIB Definitions

5.1. The GreenUsage MIB

```
GREENUSAGE-MIB DEFINITIONS ::= BEGIN
    IMPORTS
        MODULE-IDENTITY, mib-2, Unsigned32, OBJECT-TYPE
            FROM SNMPv2-SMI -- RFC 2578
        TimeStamp, MacAddress, TEXTUAL-CONVENTION
            FROM SNMPv2-TC -- RFC 2579
        MODULE-COMPLIANCE, OBJECT-GROUP
            FROM SNMPv2-CONF -- RFC 2580
        SnmpAdminString
            FROM SNMP-FRAMEWORK-MIB
    ;

greenUsageMIB MODULE-IDENTITY
    LAST-UPDATED "201301080000Z" -- 8th January, 2013
    ORGANIZATION "PREDICT Working Group"
    CONTACT-INFO
        "
            Takuo Suganuma
            Postal: Tohoku University.
                    2-1-1 Katahira
                    Aoba-ku, Sendai, Japan 980-8577.
            Tel: +81-22-217-5081
            Fax: +81-22-217-5080
            E-mail: suganuma@isc.tohoku.ac.jp

            Naoki Nakamura
            Postal: Tohoku University.
                    2-1 Seiryomachi,
                    Aoba-ku, Sendai, Japan 980-8575.
            Tel: +81-22-717-8024
            Fax: +81-22-717-8024
            E-mail: nakamura@med.tohoku.ac.jp

            Satoru Izumi
            Postal: Tohoku University.
                    2-1-1 Katahira
                    Aoba-ku, Sendai, Japan 980-8577.
            Tel: +81-22-217-5080
            Fax: +81-22-217-5080
            E-mail: izumi@shiratori.riec.tohoku.ac.jp
```

Hiroshi Tsunoda
Postal: Tohoku Institute of Technology.
35-1, Yagiyama Kasumi-cho
Taihaku-ku, Sendai, Japan 982-8577.
Tel: +81-22-305-3411
E-mail: tsuno@m.ieice.org

Masahiro Matsuda
Postal: Tohoku Institute of Technology.
35-1, Yagiyama Kasumi-cho
Taihaku-ku, Sendai, Japan 982-8577.

Tel: +81-22-305-3424
E-mail: mmatsuda@tohotech.ac.jp

Kohei Ohta
Postal: Cyber Solutions Inc.
6-6-3, Minami Yoshinari
Aoba-ku, Sendai, Japan 989-3204.
Tel: +81-22-303-4012
Fax: +81-22-303-4015
E-mail: kohei@cysols.com

Support Group E-mail: xxxxxxxxxxxxxxxx

"

DESCRIPTION

"This MIB module is for monitoring the power-on/power-off
status of electrical devices.

Copyright (C) The IETF Trust (2012). This version of
this MIB module is part of RFC XXXX; see the RFC itself for
full legal notices.

"

-- RFC Ed.: replace XXXX with the actual RFC number & remove this
-- note

REVISION "201301080000Z" -- 8th January, 2013

DESCRIPTION

"added gumDevUsageCreatedTimeStamp to usage table"

REVISION "201207070000Z" -- 7th July, 2012

DESCRIPTION

"The initial version, published as draft-suganuma-greenmib-00.txt"

-- RFC Ed.: replace XXXX with the actual RFC number & remove this
-- note

::= { mib-2 YYY1 } -- Will be assigned by IANA

-- IANA Reg.: Please assign a value for "YYY1" under the
-- 'mib-2' subtree and record the assignment in the SMI
-- Numbers registry.

-- RFC Ed.: When the above assignment has been made, please
-- remove the above note
-- replace "YYY1" here with the assigned value and
-- remove this note.

-- Textual Conventions

GumStatusDetectionMethod ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"The object specifies the technology which is used
to detect the power-on/power-off status of a device.
The enumerated values and the corresponding
technology are as follows:

reserved	(0): reserved (Not used)
arpSensing	(1): arp packets from the device
neighborDiscoverySensing	(2): neighbor discovery packets from the device
icmpEchoProbing	(3): ICMP echo packets
switchMonitoring	(4): switch monitoring

"

SYNTAX INTEGER

{
 reserved (0),
 arpSensing (1),
 neighborDiscoverySensing (2),

```

        icmpEchoProbing          (3),
        switchMonitoring         (4)
    }

GumDeviceStatus ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The object represents the power-on/power-off
        status of a monitored device.
        unknown          (0)
        powerOn          (1): device is powered on
        powerOff         (2): device is powered off
        sleepMode        (3): device is in sleep mode
        powerSavingMode  (4): device is in
                        powersaving mode
    "
    SYNTAX INTEGER
    {
        unknown          (0),
        powerOn          (1),
        powerOff         (2),
        sleepMode        (3),
        powerSavingMode  (4)
    }

```

-- The GREENUSAGE MIB has the following 3 primary groups

```

gumNotifications    OBJECT IDENTIFIER ::= { greenUsageMIB 0 }
gumObjects           OBJECT IDENTIFIER ::= { greenUsageMIB 1 }
gumConformance      OBJECT IDENTIFIER ::= { greenUsageMIB 2 }

```

```

gumDeviceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF GumDeviceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table models the device list

        Entries in this table are required to survive
        a reboot of the managed entity.
    "
    ::= { gumObjects 1 }

```

```

gumDeviceEntry OBJECT-TYPE
    SYNTAX      GumDeviceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION

```



```
        "This entry represents a conceptual row in the
        gumDevice table. It represents a device that
        will be monitored for power-on/power-off status.
        "
INDEX { gumDeviceID }
 ::= { gumDeviceTable 1 }

GumDeviceEntry ::=
SEQUENCE {
    gumDeviceID          Unsigned32,
    gumDeviceName        SnmpAdminString,
    gumDeviceMacAddress  MacAddress,
    gumDeviceType        SnmpAdminString,
    gumDeviceLocation    SnmpAdminString
}

gumDeviceID OBJECT-TYPE
SYNTAX      Unsigned32
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A unique arbitrary identifier for this device."
 ::= { gumDeviceEntry 1 }

gumDeviceName OBJECT-TYPE
SYNTAX      SnmpAdminString (SIZE(1..64))
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Administratively assigned textual name of this
    device."
 ::= { gumDeviceEntry 2 }

gumDeviceMacAddress OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "MAC Address of this device.
    If there is no MAC address, this object will be
    inaccessible."
 ::= { gumDeviceEntry 3 }

gumDeviceType OBJECT-TYPE
SYNTAX      SnmpAdminString (SIZE(1..64))
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

```
        "Administratively assigned textual description about
        usage type of this device."
 ::= { gumDeviceEntry 4 }

gumDeviceLocation OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..64))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Administratively assigned textual location
        name of this device."
 ::= { gumDeviceEntry 5 }

gumDevUsageTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF GumDevUsageEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table models the device usage status

        Entries in this table are required to survive
        a reboot of the managed entity.
        "
 ::= { gumObjects 2 }

gumDevUsageEntry OBJECT-TYPE
    SYNTAX      GumDevUsageEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This entry represents a conceptual row in the
        gumDevUsage table. It represents a power-on/power-off
        status of a monitored device.
        "
    INDEX { gumDeviceID, gumDevUsageDetID }
 ::= { gumDevUsageTable 1 }

GumDevUsageEntry ::=
    SEQUENCE {
        gumDevUsageDetID      GumStatusDetectionMethod,
        gumDevUsageDetStatus  GumDeviceStatus,
        gumDevUsageDetTimeStamp  TimeStamp,
        gumDevUsageCreatedTimeStamp  TimeStamp
    }

gumDevUsageDetID OBJECT-TYPE
    SYNTAX      GumStatusDetectionMethod
    MAX-ACCESS  not-accessible
```

```
STATUS      current
DESCRIPTION
    "The detection method by which the usage status is
    computed."
 ::= { gumDevUsageEntry 1 }

gumDevUsageDetStatus OBJECT-TYPE
SYNTAX      GumDeviceStatus
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "the usage status of the device."
 ::= { gumDevUsageEntry 2 }

gumDevUsageDetTimeStamp OBJECT-TYPE
SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "the time at which the usage status of the
    device was computed."
 ::= { gumDevUsageEntry 3 }

gumDevUsageCreatedTimeStamp OBJECT-TYPE
SYNTAX      TimeStamp
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "the time at which the entry of usage table created."
 ::= { gumDevUsageEntry 4 }

-- Units of conformance
gumGroups      OBJECT IDENTIFIER ::= { gumConformance 1}
gumCompliances OBJECT IDENTIFIER ::= { gumConformance 2}

gumObjectsGroup OBJECT-GROUP
OBJECTS {
    gumDeviceName,
    gumDeviceMacAddress,
    gumDeviceType,
    gumDeviceLocation,
    gumDevUsageDetStatus,
    gumDevUsageDetTimeStamp,
    gumDevUsageCreatedTimeStamp
}
STATUS      current
DESCRIPTION
    " A collection of objects for basic GreenUsage
```

```
        monitoring."
    ::= { gumGroups 1 }

-- Compliance statements
gumCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for SNMP entities
        which implement the GREENUSAGE-MIB
        "
    MODULE -- this module
        MANDATORY-GROUPS { gumObjectsGroup
        }
    ::= { gumCompliances 1 }

END
```

6. Security Considerations

There are no management objects defined in this MIB module with a MAX-ACCESS clause of read-write.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- gumDeviceName,
- gumDeviceMacAddress,
- gumDeviceType,
- gumDeviceLocation,
- gumDevUsageDetStatus,
- gumDevUsageDetTimeStamp

The above objects may be used to identify users and their activities. Thus these objects may be considered to be particularly sensitive and/or private.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

7. IANA Considerations

IANA should assign

1. a base arc in the 'mib-2' (standards track) OID tree for the 'greenUsageMIB' MODULE-IDENTITY defined in the

GREENUSAGE-MIB.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., Key words for use in RFCs to Indicate Requirements Levels, BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, Structure of Management Information Version 2 (SMIv2), STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, Textual Conventions for SMIv2, STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, Conformance Statements for SMIv2, STD 58, RFC 2580, April 1999.
- [RFC4293] Routhier, S., Management Information Base for the Internet Protocol (IP), RFC 4293, April 2006.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S. and Schoenwaelder, J., Textual Conventions for Internet Network Addresses, RFC 4001, February 2005.
- [RFC2863] McCloghrie, K., and Kastenholtz., F., The Interfaces Group MIB, RFC 2863, June 2000.

8.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D. and B. Stewart, Introduction and Applicability Statements for Internet-Standard Management Framework, RFC 3410, December 2002.

9. Acknowledgements

The following individuals and groups have contributed to this draft with discussions and comments:

Norio Shiratori
WIDE Project netman-WG
EMAN WG of the IETF

The authors would like to thank Glenn Mansfield Keeni for proposing this MIB module and comments for improving this document.

10. Authors' Addresses

Takuo Suganuma
Tohoku University.
2-1-1, Katahira
Aoba-ku, Sendai, Japan 980-5877.

Phone: +81-22-217-5081
E-mail: suganuma@isc.tohoku.ac.jp

Naoki Nakamura
Tohoku University.
2-1 Seiryō-machi,
Aoba-ku, Sendai, Japan 980-8575.

Phone: +81-22-717-8024
E-mail: nakamura@med.tohoku.ac.jp

Satoru Izumi
Tohoku University.
2-1-1 Katahira
Aoba-ku, Sendai, Japan 980-8577.

Phone: +81-22-217-5080
E-mail: izumi@shiratori.riec.tohoku.ac.jp

Hiroshi Tsunoda
Tohoku Institute of Technology.
35-1, Yagiyama Kasumi-cho
Taihaku-ku, Sendai, Japan 982-8577.

Phone: +81-22-305-3411
E-mail: tsuno@m.ieice.org

Masahiro Matsuda
Tohoku Institute of Technology.

35-1, Yagiyama Kasumi-cho
Taihaku-ku, Sendai, Japan 982-8577.

Phone: +81-22-305-3424
E-mail: mmatsuda@tohotech.ac.jp

Kohei Ohta
Cyber Solutions Inc.
6-6-3, Minami Yoshinari
Aoba-ku, Sendai, Japan 989-3204.

Phone: +81-22-303-4012
E-mail: kohei@cysols.com