

Network Working Group
Internet-Draft
Intended status: Informational
Expires: April 4, 2014

D. Lewis
Cisco Systems, Inc.
P. Agarwal
Broadcom
L. Kreeger
F. Maino
P. Quinn
Cisco Systems, Inc.
M. Smith
N. Yadav
Insieme Networks
October 1, 2013

LISP Generic Protocol Extension
draft-lewis-lisp-gpe-01.txt

Abstract

This draft describes a mechanism for adding generalized multi-protocol support to the Locator/ID Separation Protocol (LISP) [RFC6830]. Protocol identification is carried in the LISP header and is used to describe the encapsulated payload.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 4, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. LISP Header	4
3. Generic Protocol Extension for LISP (LISP-gpe)	5
3.1. LISP-gpe Header	5
4. Backward Compatibility	6
4.1. LISP-gpe Routers to (legacy) LISP Routers	6
4.2. (legacy) LISP Routers to LISP-gpe Routers	6
4.3. Type of Service	6
4.4. VLAN Identifier (VID)	6
5. LISP-gpe Examples	7
6. Security Considerations	9
7. Acknowledgments	10
8. IANA Considerations	11
9. References	12
9.1. Normative References	12
9.2. Informative References	12
Authors' Addresses	13

1. Introduction

LISP [RFC6830] defines an encapsulation format that carries IPv4 or IPv6 (henceforth referred to as IP) packets in a LISP header and outer UDP/IP transport. The LISP header does not specify the protocol being encapsulated and therefore is currently limited to encapsulating only IP packet payloads. Other protocols, most notably VXLAN [VXLAN] (which defines a similar header format to LISP), are used to encapsulate L2 protocols such as Ethernet. LISP [RFC6830] can be extended to indicate the inner protocol, enabling the encapsulation of Ethernet, IP or any other desired protocol all the while ensuring compatibility with existing LISP [RFC6830] deployments.

This document describes extending LISP ([RFC6830]) to support additional payload types beyond IP packets. To support this capability, two elements of the existing LISP header are modified.

1. A flag bit is allocated, and set in the LISP header.
2. A 16 bit Protocol Type field is present in the LISP header.

These changes allow for the LISP header to support many different types of payloads. Backward compatibility with existing LISP tunnel routers is discussed in section 4.

2. LISP Header

As described in the introduction, the LISP header has no protocol identifier that indicates the type of payload being carried by LISP. Because of this, LISP is limited to an IP payload.

The LISP header contains flags (some defined, some reserved), a Nonce/Map-version field and an instance ID/Locator-status-bit field. The flags provide flexibility to define how the reserved bits can be used to change the definition of the LISP header.




Figure 1: LISP Header

3. Generic Protocol Extension for LISP (LISP-gpe)

3.1. LISP-gpe Header

This draft defines two changes to the LISP header in order to support multi-protocol encapsulation.

P Bit: Flag bit 5 is defined as the P bit. The P bit **MUST** be set to 1 to indicate the presence of the 16 bit protocol type field in the lower 16 bits of the first word.

P = 0 indicates that the payload **MUST** conform to LISP as defined in [RFC6830].

Flag bit 5 was chosen as the P bit because this flag bit is currently unallocated in LISP [RFC6830].

Protocol Type Field: The lower 16 bits of the first word are used to carry a protocol type. This protocol type field contains the protocol, as defined in in [RFC1700] and in [ETYPES], of the encapsulated payload packet.

LISP [RFC6830] uses the lower 16 bits of the first word for either a nonce, an echo-nonce ([RFC6830]) or to support map-versioning ([RFC6834]). These are all optional capabilities that are indicated by setting the N, E, and the V bit respectively.

To maintain the desired data plane compatibility, when the P bit is set, the N, E, and V bits **MUST** be set to zero.




Figure 2: UDP + LISP-gpe

4. Backward Compatibility

An undefined (in RFC6830) flag bit, 5, was selected to ensure compatibility with existing LISP [RFC6830] deployments.

Similarly, using P = 0 to indicate that the format of the header and payload conforms to [RFC6830] ensures compatibility with existing LISP hardware forwarding platforms.

4.1. LISP-gpe Routers to (legacy) LISP Routers

A LISP-gpe router MUST not encapsulate non-IP packets to a LISP router. A method for determining the capabilities of a LISP router (gpe or "legacy") is out of the scope of this draft.

When encapsulating IP packets to a LISP router the P bit SHOULD be set to 1 and the UDP port MUST be set to 4341. The Protocol Type field SHOULD be 0x800 or 0x86DD. The (legacy) LISP router will ignore the P bit and the protocol type field. The (legacy) LISP router will treat the packet as a LISP packet and inspect the first nibble of the payload to determine the IP version.

When the P bit is set, the N, E, and V bits MUST be set to zero. The receiving (legacy) LISP router will ignore N, E and V bits, when the P bit is set.

4.2. (legacy) LISP Routers to LISP-gpe Routers

When a LISP-gpe router receives a packet from a (legacy) LISP router, the P bit MUST not be set and the UDP port MUST be 4341. The payload MUST be IP, and the LISP-gpe router will inspect the first nibble of the payload to determine IP version.

4.3. Type of Service

When a LISP-gpe router performs Ethernet encapsulation, the inner 802.1Q [IEEE8021Q] priority code point (PCP) field MAY be mapped from the encapsulated frame to the Type of Service field in the outer IPv4 header, or in the case of IPv6 the 'Traffic Class' field.

4.4. VLAN Identifier (VID)

When a LISP-gpe router performs Ethernet encapsulation, the inner header 802.1Q [IEEE8021Q] VLAN Identifier (VID) MAY be mapped to, or used to determine the LISP Instance ID field.

5. LISP-gpe Examples

This section provides two examples of IP protocols, and one example of Ethernet encapsulated LISP-gpe using the generic extension described in this document.




Figure 3: IPv4 and LISP-gpe




Figure 4: IPv6 and LISP-gpe




Figure 5: Ethernet and LISP-gpe

6. Security Considerations

LISP-gpe security considerations are similar to the LISP security considerations documented at length in LISP [RFC6830]. With LISP-gpe, issues such as dataplane spoofing, flooding, and traffic redirection are dependent on the particular protocol payload encapsulated.

7. Acknowledgments

A special thank you goes to Dino Farinacci for his guidance and detailed review.

8. IANA Considerations

This document creates no new requirements on IANA namespaces [RFC5226].

9. References

9.1. Normative References

- [RFC0768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, August 1980.
- [RFC0791] Postel, J., "Internet Protocol", STD 5, RFC 791, September 1981.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, May 2008.

9.2. Informative References

- [ETYPES] The IEEE Registration Authority, "IEEE 802 Numbers", 2012, <<http://www.iana.org/assignments/ieee-802-numbers/ieee-802-numbers.xml>>.
- [IEEE8021Q] The IEEE Computer Society, "Media Access Control (MAC) Bridges and Virtual Bridge Local Area Networks", August 2012, <<http://standards.ieee.org/getieee802/download/802.1Q-2011.pdf>>.
- [RFC1700] Reynolds, J. and J. Postel, "Assigned Numbers", RFC 1700, October 1994.
- [RFC6830] Farinacci, D., Fuller, V., Meyer, D., and D. Lewis, "The Locator/ID Separation Protocol (LISP)", RFC 6830, January 2013.
- [RFC6834] Iannone, L., Saucez, D., and O. Bonaventure, "Locator/ID Separation Protocol (LISP) Map-Versioning", RFC 6834, January 2013.
- [VXLAN] Dutt, D., Mahalingam, M., Duda, K., Agarwal, P., Kreeger, L., Sridhar, T., Bursell, M., and C. Wright, "VXLAN: A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks", 2013.

Authors' Addresses

Darrel Lewis
Cisco Systems, Inc.

Email: darlewis@cisco.com

Puneet Agarwal
Broadcom

Email: pagarwal@broadcom.com

Larry Kreeger
Cisco Systems, Inc.

Email: kreeger@cisco.com

Fabio Maino
Cisco Systems, Inc.

Email: kreeger@cisco.com

Paul Quinn
Cisco Systems, Inc.

Email: paulq@cisco.com

Michael Smith
Insieme Networks

Email: michsmit@insiemenetworks.com

Navindra Yadav
Insieme Networks

Email: nyadav@insiemenetworks.com

