

Internet Working Group

Y. Jiang

Internet Draft

Y. Luo

Huawei

Intended status: Standards Track

Expires: April 2014

October 21, 2013

Multi-chassis PON Protection in MPLS
draft-jiang-pwe3-mc-pon-00.txt

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on April 21, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Abstract

While MPLS is deployed further and further to the access network, a converging network edge point which provides both MPLS and PON access capability appears. To provide resiliency for its services, multi-homing is needed to support PON access in MPLS. This document describes the multi-chassis PON protection architecture in MPLS and also proposes the ICCP extension to support it.

Table of Contents

1.	Conventions used in this document	2
2.	Terminology	3
3.	Introduction	3
3.1.	Multi-chassis PON Application TLVs	5
3.1.1.	PON Connect TLV	5
3.1.2.	PON Disconnect TLV	6
3.1.3.	PON Configuration TLV	6
3.1.4.	PON State TLV	7
4.	Dual Homing protection procedures	8
4.1.	Protection procedure upon PON interface failures	9
4.2.	Protection procedure upon PW failures	9
4.3.	Protection procedure upon the working OLT failure	9
5.	Security Considerations	10
6.	IANA Considerations	10
7.	References	10
7.1.	Normative References	10
7.2.	Informative References	10
8.	Acknowledgments	10
	Authors' Addresses	11

1. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

2. Terminology

FTTx Fiber-to-the-x (FTTx, x = H for home, P for premises, C for curb)

ICCP Inter-Chassis Communication Protocol

OLT Optical Line Termination

ONU Optical Network Unit

MPLS Multi-Protocol Label Switching

PON Passive Optical Network

3. Introduction

MPLS is extending further and further to the edge of networks, for example, the seamless MPLS use cases as described in [SEAMLESS], and the MS-PW with PON access use case as described in [RFC6456], all show that MPLS is approaching the access networks.

Passive Optical Network (PON) can provide high bandwidth of 1Gbps or even 10Gbps, and provide support of access for dozens to more than one hundred subscribers at the same time. A huge number of PON access networks have been deployed over the last few years with the wide spread of FTTx technology.

With the fast growth of mobile data traffic, more and more LTE small cells and Wi-Fi hotspots will be deployed in the future. How to backhaul a large number of small cells or hotspots will pose a great challenge to mobile service providers.

PON access technology has the following advantages:

- saving trunk fibers with its point-to-multipoint physical topology;
- High bandwidth capability up to 10Gbps;
- Low Total Cost of Ownership (TCO).

PON also provides synchronization features, e.g., SyncE and IEEE1588 functionality, which can fulfill synchronization needs of mobile backhaul services. Some optical layer of protection mechanisms, such as Type B protection and Type C protection are also specified [G983.1] to avoid single point of failure in the access.

Therefore, PON may play a greater role in the access end for the mobile backhaul networks. Providing OLTs with MPLS functionality further facilitates multi-service convergence.

Type B protection architecture is an economical PON resiliency mechanism, where the working OLT and the working link between the working splitter and the working OLT (i.e., the working fiber) is protected by a redundant protection OLT and a redundant fiber between the working splitter and the protection OLT. This is different from the more complex and costly Type C protection architecture where working splitter and the working fibers from ONUs to the working splitter are further protected. Figure 1 demonstrates a typical scenario of Type B PON protection.




Figure 1 Type B PON protection Architecture

Though the above PON architecture provides redundancy in its physical topology, some standard mechanisms are needed to exchange PON link status and network status between OLTs in a Redundancy Group (RG) so that protection and restoration can be done reliably, especially when the OLTs also support MPLS. Thus there is a need for Multi-chassis PON protection protocol in MPLS.

ICCP [ICCP] provides a framework for inter-chassis synchronization of state and configuration data between a set of two or more PEs. Currently ICCP only defines application specific messages for PW redundancy and mLACP, but it can be easily extended to support Type B PON as an Attachment Circuit (AC) redundancy.


This document proposes the extension of ICCP to support Multi-chassis PON protection in MPLS.

3.1. Multi-chassis PON Application TLVs

A set of multi-chassis PON application TLVs are defined in the following sub-sections.

3.1.1. PON Connect TLV

This TLV is included in the RG Connect message to signal the establishment of PON application connection.




- U and F Bits, both are set to 0.
- Type, set to 0x00XX for "PON Connect TLV".
- Length, Length of the TLV in octets excluding the U-bit, F-bit, Type, and Length fields.
- Protocol Version, the version of this PON specific protocol for the purposes of inter-chassis communication. This is set to 0x0001.
- A Bit, Acknowledgement Bit. Set to 1 if the sender has received a PON Connect TLV from the recipient. Otherwise, set to 0.

- Reserved, Reserved for future use.
- Optional Sub-TLVs, there are no optional Sub-TLVs defined for this version of the protocol.


3.1.2. PON Disconnect TLV

This TLV is included in the RG Disconnect message to indicate that the connection for the PON application is to be terminated.



- U and F Bits, both are set to 0.
- Type, set to 0x00XX for "PON Disconnect TLV".
- Length, Length of the TLV in octets excluding the U-bit, F-bit, Type, and Length fields.
- Optional Sub-TLVs, there are no optional Sub-TLVs defined for this version of the protocol.

3.1.3. PON Configuration TLV



- U and F Bits, both are set to 0.
- Type, set to 0x00XX for "PON Configuration TLV".

4. Dual Homing protection procedures

Two typical MPLS protection network architectures for PON access are depicted in Fig.2 and Fig.3 (PON access segment is the same as in Fig.1 and thus omitted for simplification). OLTs with MPLS functionality are connected to a single PE (Fig.2) or dual home PEs (Fig.3) respectively, thus these devices constitute an MPLS network which provides PW transport services between ONUs and a CE.




Figure 2 An MPLS network with a single PE




Figure 3 An MPLS network with dual home PEs

Faults may be encountered in PON access, or in the MPLS network (including the working OLT). Procedures for these cases are described in this section (it is assumed that both OLTs and PEs are working in independent mode of PW redundancy [RFC6870]).

4.1. Protection procedure upon PON interface failures

When a fault is detected on a working PON link, a working OLT MUST turn off its associated PON interface and MUST send an LDP notification message with a forward defect indication and with the Request Switchover bit being set to its peer PE on the remote end of the PW. At the same time, the working OLT MUST send an ICCP message with PON State TLV to notify the backup OLT of the PON fault. Upon receiving a PON state TLV where Local PON Port state is False, an OLT in the protection mode MUST activate the protection PON link in the protection group.

4.2. Protection procedure upon PW failures

Usually MPLS networks have its own protection mechanism such as LSP protection or Fast Reroute (FRR). But in a link sparse access or aggregation network where protection is impossible in LSP layer, the following PW layer protection procedures can be enabled.

When a fault is detected on its working PW (e.g., by VCCV BFD), a working OLT MUST turn off its associated PON interface and MUST send an ICCP message with PON State TLV to notify the backup OLT of the PON fault.

Upon receiving a PON state TLV where Local PON Port state is False, the backup OLT MUST activate its optical interface to the backup fiber. At the same time, the backup OLT MUST send a PW redundancy message to the remote PE, so that traffic can be switched to the backup PW.

4.3. Protection procedure upon the working OLT failure

If the backup OLT lost connection to the working OLT, it MUST activate its optical interface to the back fiber and activate the specific backup PW upon receiving a PW redundancy message from its remote PE with the Request Switchover bit being set, so that traffic can be reliably switched to the protection link and the backup PW.

5. Security Considerations

Security considerations as described in [ICCP] apply.

6. IANA Considerations

These values are requested from the registry of "ICC RG parameter type":

0x00X0	PON Connect TLV
0x00X1	PON Disconnect TLV
0x00X2	PON Configuration TLV
0x00X3	PON State TLV

7. References

7.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997

[RFC6870] Muley, P., Aissaoui, M., "Pseudowire Preferential Forwarding Status Bit", RFC 6870, February 2013

7.2. Informative References

[RFC6456] Li, H., Zheng, R., and Farrel, A., "Multi-Segment Pseudowires in Passive Optical Networks", RFC 6456, November 2011

[SEAMLESS] Leymann, N., and et al, "Seamless MPLS Architecture", draft-ietf-mpls-seamless-mpls-04, Work in progress

[ICCP] Martini, L. and et al, "Inter-Chassis Communication Protocol for L2VPN PE Redundancy", draft-ietf-pwe3-iccp-11, Work in progress

[G983.1] ITU-T, "Broadband optical access systems based on Passive Optical Networks (PON)", ITU-T G.983.1, January, 2005

8. Acknowledgments

TBD.

Authors' Addresses

Yuanlong Jiang
Huawei Technologies Co., Ltd.
Bantian, Longgang district
Shenzhen 518129, China
Email: jiangyuanlong@huawei.com

Yong Luo
Huawei Technologies Co., Ltd.
Bantian, Longgang district
Shenzhen 518129, China
Email: dennis.luoyong@huawei.com

