

# Residence Time Measurement

draft-mirsky-mpls-residence-time-00

Greg Mirsky [gregory.mirsky@ericsson.com](mailto:gregory.mirsky@ericsson.com)

John Drake [jdrake@juniper.net](mailto:jdrake@juniper.net)

Stewart Bryant [stbryant@cisco.com](mailto:stbryant@cisco.com)

Alexander Vainshtein [Alexander.Vainshtein@ecitele.com](mailto:Alexander.Vainshtein@ecitele.com)


IETF88 November, 2013, Vancouver

# Problem Statement

- Residence Time – time it takes a packet to traverse a node
- Clock synchronization protocols, i.e. IEEE-1588v2, may use residence time
- MPLS Packet Delay Measurement RFC 6374 includes propagation delay – not useful

# Proposed Solution

- New G-ACh – Residence Time Measurement
- Scratch pad – 8 bytes (same size as Correction Field in IEEE 1588v2)
- Optional payload, e.g. PTP packet



# Alleged Benefits

- No special purpose LSP or PW context to transport clock synchronization packets
- Can be used by IEEE 1588 v2 end-to-end Transparent Clock, as well as NTPv4, if the latter is extended to use residence time correction
- Fully backward compatible with existing LSRs

# Next steps

- Add examples of RTM used by IEEE 1588v2
- Solicit comments & feedback from the WG