

# Data Center Interconnect Solution for EVPN Overlay networks

---

draft-rabadan-l2vpn-dci-evpn-overlay-01

Jorge Rabadan

Senthil Sathappan

Wim Henderickx


Florin Balus

Senad Palislamovic


IETF 89, March 2014

London, UK

# The issue we want to address...



# Interconnect requirements (Dec-M)




- Clear and simple demarcation (QoS/ACL enforcement, OAM)
- Minimum or no control plane interaction between DGWs and WAN PEs
- Multi-homing required

- Optimizations on the DC GW:
  - Unknown-flooding reduction
  - Control of the MAC advertisements to the DC
  - ARP-flooding control

# Interconnect requirements (Int-M)


DECOUPLED  
MODEL

INTEGRATED  
MODEL




- Data Plane AND Control plane gateway function on DGWs
- Multi-homing required:
  - Per-service load balancing
  - Per-flow load balancing - only (PBB-)EVPN
- Independent inclusive multicast trees in WAN and DC
- If EVPN in the WAN the following end-to-end features:
  - MAC mobility, protection
  - Proxy-ARP

# DGW Control Plane EVPN extensions proposed to address the e2e EVPN model



# DGW Data Plane EVPN extensions for B/U/M traffic in e2e all-active EVPN: no need for ESI label



(1) (4)

No change in the EVPN procedures  
for split-horizon at the NVEs

(3)

Non-DF will ONLY forward to local ACs  
DF will never forward to WAN SHG or non-DF

(2)

Non-DF will ONLY forward to local ACs  
DF will never forward to DC SHG or non-DF

# NEXT STEPS

- More feedback from WG