

# Generic Overlay OAM and Datapath Failure Detection

Kanwar Singh (Nuage Networks)

Pradeep Jain, Florin Balus

Wim Henderickx

Anil Lohiya, Ravi Shekhar

Vinay Bannai

*Nuage Networks*

*Alcatel-Lucent, Inc*

*Juniper Networks, Inc*

*Paypal, Inc*

# Motivation of Generic Overlay OAM Application

- Existing IP/Ping Trace does not work well for Overlays.
- Consistency of Control and Data Plane Programming.
- Continuity Check .
- Fault Verification.
- Fault Isolation.
- Performance.
  - Packet Delay Statistics.
  - Packet Loss Measurements.

# Requirements for Overlay OAM Framework

- Originating Overlay End Point should send the OAM Frame (Echo Request) following the same Data-Path as that of End-System's traffic.
- Terminating Overlay End Point should be able to differentiate the OAM Frames from the End System Data, and send it to OAM Application for Reply.
- Should be able to achieve OAM for applications using L2 and L3 Overlays.
- Should give capability to Trace the Path taken in the Underlay for a given Overlay Segment.
- Should work for Overlay Technologies as VxLAN, NVGRE, MPLSoGRE, MPLSoUDP.



# Overlay Ping - Originating Overlay End Point Procedures

- Outer Header Should follow Encapsulation similar to Overlay Segment
  - VxLAN / NVGRE : Set Router Alert Bit ([draft-singh-nvo3-vxlan-router-alert](#) / [draft-singh-nvo3-nvgre-router-alert](#)) – indicating Control Packet
  - MPLSoGRE/MPLSoUDP : Add Router Alert Label following Overlay Segment Label.
- Inner Header Encapsulation
  - L2 Overlay
    - Echo Request should have inner Ethernet Header, followed by IP and UDP Header
    - Inner DMAC: 00-00-5E-90-XX-XX (to be assigned by IANA)
    - Inner DST-IP: In Range of 127/8 (for IPv4) or In Range 0:0:0:0:0:FFFF:127/104 (for IPv6)
    - Inner DST-UDP Port: XXXX (assigned by IANA for Overlay OAM).
    - Generic OAM Frame
  - L3 Overlay
    - Echo Request's Encapsulation is same as above, except Inner Ethernet Header.

# Overlay Ping - Terminating Overlay End Point Procedures

- Identify Packet as Control Packet from Outer Header
  - VxLAN / NVGRE : Router Alert Bit ([draft-singh-nvo3-vxlan-router-alert](#) / [draft-singh-nvo3-nvgre-router-alert](#))
  - MPLSoGRE/MPLSoUDP : Router Alert Label.
- Identify Packet as Overlay OAM Packet and sent it to OAM Application using Inner Header Encapsulation
  - L2 Overlay
    - Inner DMAC: 00-00-5E-90-XX-XX (to be assigned by IANA)
    - Inner DST-IP: In Range of 127/8 (for IPv4) or In Range 0:0:0:0:0:FFFF:127/104 (for IPv6)
    - Inner DST-UDP Port: XXXX (assigned by IANA for Overlay OAM).
  - L3 Overlay
    - Inner DST-IP: In Range of 127/8 (for IPv4) or In Range 0:0:0:0:0:FFFF:127/104 (for IPv6)
    - Inner DST-UDP Port: XXXX (assigned by IANA for Overlay OAM).
- Validate Control/Data Plane and Send Echo Reply with Return Code

# Overlay Ping Construct

- Two Type of Packets
  - Echo Request
  - Echo Reply
- Reply Modes
  - Do not reply
  - Reply via IPv4 UDP Packet
  - Reply via Overlay Segment
- Return Codes
  - No return code
  - Malformed Echo Request Received
  - Overlay Segment Not Present
  - Overlay Segment Not Operational
  - Return-Code-OK

# Path Trace Procedures

- Echo Request is prepared via same Encapsulation as that of Overlay Tunnel.
- Echo Request packets are sent with Incremental TTL values 1, 2 ..n of Outer Header to probe the Path taken by the Overlay.
- TTL Expiry creates an Exception, packet is sent to OAM Application based on inner UDP Port.
- Each Transit Node as well as Overlay End Point receiving such an exception should send Echo Reply.



# Procedures End-System Ping

- Originating Overlay End Point
  - Echo Request similar to Overlay Ping along with :-
    - TLV Identifying Overlay Segment.
    - Sub-TLV identifying Type of End-System Ping (e.g MAC, IP or MAC/IP of End-System).
  - Echo Request follows same Data Path as that of End-System Data.
- Terminating Overlay End Point
  - Terminating Overlay End Point validates End-System(s) information and send Echo Reply with proper Return Code for each End-System.
- Return Code
  - End-System Present
  - End-System Not Present

# Next Step

- Looking forward to Comment/Feedback.
- Request the document to be accepted as WG document