

# ISIS Auto-Configuration

## (draft-liu-isis-auto-conf-02)

Bing Liu ([leo.liubing@huawei.com](mailto:leo.liubing@huawei.com)) (speaker)

Bruno Decraene ([bruno.decraene@orange.com](mailto:bruno.decraene@orange.com))

Ian Farrer ([ian.farrer@telekom.de](mailto:ian.farrer@telekom.de))

Mikael Abrahamsson ([mikael.abrahamsson@t-system.se](mailto:mikael.abrahamsson@t-system.se))

*@ISIS-WG, ietf91, Nov 2014*

# Background

- Draft had been presented twice (IETF88/89)
  - Main techniques are in a good shape
  - Specific comments are still welcome (on the list please)
- An implementation
  - Netdef demonstrated an OpenWRT-based implementation of ISIS-Autoconf and source-based routing functions in IETF90 Bits'N'Bites (<http://www.opensourcerouting.org/2014/08/homenet-with-isis-autoconf-and-srcdest-routing-proof-of-concept/>)
  - The implementation aligns with the Homenet architecture

# Regarding to Usage in Homenet

- In last presentation, the main concern was whether Homenet would use ISIS
- The Homenet status on this issue
  - Homenet WG still hasn't made any decision on routing protocols
  - Homenet WG adopted HNCP which is able to negotiate a routing protocol among routers

# Usage in Small or Medium Enterprises

- SMEs also have the requirement for plug-n-play
- They might need different routers than Homenet CPEs; these routers don't need to comply with Homenet architecture or limitations.
- ISIS advantage
  - Doesn't need IPv4/IPv6 up and running before it can get itself started and discover the network topology
  - Compatible to the devices that don't intent to configure IP addresses (e.g. SCADA)

# Conclusions

- ISIS-autoconf fits in home networks
  - The open source implementation run well in demonstration
- Other than home networks, ISIS-autoconf could also benefit scenarios such as small and medium enterprises

# Next Steps

- Adopted as a WG item?

Thank you!

*IETF91, Honolulu*