

Advertising Per-node Administrative Tags in OSPF

draft-ietf-ospf-node-admin-tag-00

Shraddha Hegde shraddha@juniper.net

Harish Raghuveer harish.r.prabhu@gmail.com

Hannes Gredler hannes@juniper.net

Rob Shakir rob.shakir@bt.com

Anton Smirnov as@cisco.com

Lizhenbin lizhenbin@huawei.com

Bruno Decraene bruno.decreaene@orange.com

Overview

- **Administrative tags to be associated with the nodes**
 - Local to administrative domain
 - Identifies a unique function node is associated with
- **Tags to be used in selection of**
 - IP Path
 - ECMP primary paths
 - Backup paths
 - MPLS Path

Applications

- FRR path optimization
- Service auto-discovery
- MPLS path constraints
- Remote LFA tunnel termination

Per-Node Admin Tag TLV

- New TLV in Router Information LSA
 - List of 32-bit admin tags (node colors)
 - Maximum of 64 admin tags
 - Meaning of tag values defined by local policy via configuration.

Updates from previous version

- Application scenario for explicit routing
 - Include/ Exclude/ include all policies
 - Traffic from nodes with certain tags to be forwarded along nodes with certain other tags
- Clarifications for tag ordering
- Clarification related to well known values
- Tag values carried in different scope RI LSAs

Questions & comments