

Use of Multicast Across Inter-Domain Peering Points

Percy S. Tarapore, AT&T

Robert Sayko, AT&T

Greg Shepherd, Cisco

Toerless Eckert, Cisco

Ram Krishnan, Brocade

Scope of Document

- Develop ***Best Current Practice*** (BCP) for Multicast Delivery of Applications Across Peering Point Between Two Administrative Domains (AD):
 - Describe Process & Establish Guidelines for Enabling Process
 - Catalog Required Information Exchange Between AD's to Support Multicast Delivery
- Identify possible follow-up work that may improve process
- Current Status:
 - “Kitchen Sink” Approach towards BCP Development
 - Focus is on SP ⇔ SP interaction to setup service
- ***Discussion Requested (Goldilocks Rules):***
 - ***Is the BCP Draft “Too Much”, “Too Little”, or “Just Right”?***
 - ***What do we have to do get this ready for Last Call?***

Revision History

- Vancouver 2012 - Revision 0 Proposed as a BCP for Content Delivery via Multicast Across CDN Interconnections.
- Atlanta 2012 – Revision 1 Preempted due to Hurricane Sandy
- Orlando 2013 – Revision 2 Proposed as General Case for Multicast Delivery of Any Application Across two AD's:
 - CDNi Case is One Example of this General Scenario
- Berlin 2013 – Revision 3 provides detailed text for Use Cases in section 3 → *Accepted as Working Group Draft.*
- Vancouver 2013 – Revision 4 added new use case (section 3.5) & proposed guidelines for each use case in section 3.
- London 2014 – Revision 5 added sections 4.1 (Transport & Security) & 4.2 (Routing) Guidelines.
- Toronto 2014 – Revision 6 added text in section 4.3 Back-Office Functions
- Honolulu 2014 – Revision 7 added text to sections 4.4 (Operations), 4.5 (Client Reliability Models), 5 (Security) , & 7 (Conclusions
- **Dallas 2015 – General discussion and comments received for potentially shortening BCP.**

Summary of Changes (per Comments from Dallas)

- Renamed BCP as Working Group Draft:
 - Adopted as WG document in Berlin (IETF 87) but draft indicator not changed
 - draft-ietf-mboned-interdomain-peering-bcp-00.txt
- Clarifications added in Scope:
 - Technical Use Cases AND High Level Guidance to Operators for Interconnection
- Section 4.3.4 (Settlement Guidelines) Deleted
- New Section 5 added on Troubleshooting and Diagnostics
- Minor edits throughout the draft

Section 2 - Overview

- Two Independent AD's Connected via Peering Point
- Peering Point is:
 - Multicast Enabled, or
 - Provisioned via a Tunnel which is Either:
 - GRE Tunnel, or
 - AMT
- Domain A is Multicast Enabled; Domain B May or May Not Be
- Application (e.g., Live Stream) Source in Domain A & End User (EU) Associated with Domain B.
- End User (One of Many EUs) Requests Application
- Application Delivered via Multicast from Source Through Peering Point to EU in Domain B

Section 3 – Use Cases

- 3.1: End-to-End Native Multicast
- 3.2:
 - Native Multicast in Both Domains
 - Peering Point Enabled with GRE
- 3.3:
 - Native Multicast in Both Domains
 - Peering Point Enabled with AMT Tunnel
- 3.4:
 - Native Multicast in Domain A
 - No Multicast in Domain B
 - “Long Tunnel” Across Peering Point to End User
- 3.5:
 - Same Scenario as 3.4
 - “Long Tunnel” broken up into chained series of shorter tunnels

Section 4 – Supporting Functions

- 4.1: Network Interconnection Transport & Security Guidelines
- 4.2: Routing Aspects:
 - 4.2.1: Native Multicast Routing
 - 4.2.2: GRE Tunnel Across Peering Point
 - 4.2.3: AMT Tunnels (Use Cases 3.3, 3.4, 3.5)

Section 4 (continued)

- 4.3: Back Office Functions:
 - 4.3.1: Provisioning
 - 4.3.2: Application Accounting and Billing
 - 4.3.3: Log Management
- 4.4: Operations – Service Performance & Monitoring
- 4.5: Client Reliability Models & Service Assurance

Section 5 – Troubleshooting & Diagnostics

- New Section added per comment in Dallas
- Multicast Diagnostics Process Reference:
 - D. Thaler, et al, “Multicast Debugging Handbook”, IETF I-D draft-ietf-mboned-mdh-04.txt, May 2000
 - AD ⇔ AD Notifications & Alerts related to diagnosed trouble assumed to be similar to Service Performance & Operations (Section 4.4)
- AD ⇔ AD Diagnostics Communication Guidelines:
 - Communications channels assumed to exist between Operations & Customer Service for each AD
 - Resolution period could be either default or on case-by-case basis.

Ending Sections

- 6: Security Considerations
- 7: IANA Considerations
- 8: Conclusions:
 - Identified Need to Determine Method for Finding “Optimal” AMT Gateway ⇔ Relay Pairs to Support AMT Tunnel Setup

Question for Consideration

What else do we need to do to start LAST CALL!!