

Active and Passive Metrics and Methods (and everything in-between, or Hybrid)

draft-ietf-ippm-active-passive-03

Al Morton

Nov 2015

Definitions

- First, define Performance Metric and Method of Measurement.
- Next, define Active and Passive Methods
- Then, recognize that IPPM's Active Metrics deliberately incorporate some methods in the Metric Definition – therefore, Active Metrics.
- Hybrid Methods are a combination of Active and Passive attributes
- Multiple categories of Hybrid, Type I, Type II, and the already-named Spatial Metrics, RFC 5644

Reviews, Comments, Support

- Brian - add more complete defs. for Hybrid
- Joachim and Tal - Many refinements to definitions from examining examples.
- Greg, Joachim, and Mike – examined circumstances under which a Hybrid Method could be expected to produce results comparable to Passive (end of 3.8)
- Joachim – clarifications for 2D Figure in section 4.1
- Tal – suggested examination of Y.1731 methods (4.4)
- Nalini and Tiziano – support and additional comments.

Status

- Three updates since last IPPM session
- Version 01 addressed comments at IETF-93
- WGLC generated solid reviews and support
 - Version 02 addressed comments up to the draft deadline, Oct 19th
- One line of examination continued through the end of WGLC, Oct 21st (and beyond)
 - Agreed wording incorporated in Version 03

BACKUP

Revised -00 classification:

2 Dimensions

1. The degree to which the stream of interest affects overall network conditions experienced by that stream and other streams. This is a key dimension for Active measurement error analysis.
2. The degree to which stream characteristics are known a priori. There are methodological advantages of knowing the source stream characteristics, and having complete control of the stream characteristics. ...number of packets ... when sent ... what kind ... This is a key dimension for Passive measurement error analysis.

Section 4.1 ends with a paragraph of examples for error associated with each type of method.

draft-zheng-ippm-framework-passive-03

- * cites metrics of throughput, latency, and errors as active, (sec 4.1)
- >>> These metrics can be measured using many methods
- * uses the phrase "existing traffic" when describing passive measurements, and "existing on the network" when referring to passive metrics (sec 4.2)
- >>> Consistent with IPPM Wg draft-ietf-ippm-active-passive definitions.
- * indicates that definition of Hybrid is a combination of active and passive
- >>> also consistent with draft-ietf-ippm-active-passive definitions (sec 6, Methodology for "IP Passive Performance Measurements" from title)
- BUT cites inserting Y.1731 OAM along with "altering the packet"
- >>> Neither of these are "existing traffic"
- >>> Do detailed methods belong in the framework?

We* didn't start the fire...

- IPPM chartered since 1997, working as part of BMWG before that... RTFM and IPFIX long-timers
- First PAM conference in 2000
- Many terms are in common use in IETF, but *some* lack formal definitions
- The notions of active and passive are well-established, so let's document them.
- Further, let's help classify new methods according to useful criteria


* "we" is likely everyone sitting in the session, except Matt Mathis, Bill Cerveney, and Nevil Brownlee. AI here since '98.

Words and Meaning

- Words can only have strong meaning within a Context (part of the definition)
- We need definitions in Standards Work:
 - Communicate Effectively
 - Avoid Ambiguity
- Start with Fundamental terms and build from there

More Dimensions of Categorization

- Decompose “effect on network conditions” to
 - Effect on the measured stream (itself)
 - Effect on unmeasured flows that share the path
 - Effect on network state or adaptation (features in net under test have influence)



Two Classifications discussed

- PDM
 - Method may have small affect on measured stream
 - Measured stream has unknown characteristics until observed/processed to add PDM header
- Coloring
 - Method may have small affect on measured stream (possibly less than PDM)
 - Measured stream has unknown characteristics until observed/processed to color the header