

Internet Engineering Task Force
Internet-Draft
Intended status: Standards Track
Expires: September 21, 2016

G.Galimberti, Ed.
Cisco
R.Kunze, Ed.
Deutsche Telekom
D. Hiremagalur, Ed.
G. G.Grammel, Ed.
Juniper
March 20, 2016

A YANG model to manage the optical parameters for in a WDM
network
draft-galimbe-ccamp-iv-yang-00

Abstract

This memo defines a Yang model that translate the information model to support Impairment-Aware (IA) Routing and Wavelength Assignment (RWA) functionality. The information model is defined in draft-ietf-ccamp-wson-iv-info and draft-martinelli-ccamp-wson-iv-encode. This document defines proper encoding and extend to the models defined in draft-lee-ccamp-wson-yang to support Impairment-Aware (IA) Routing and Wavelength Assignment (RWA) functions

The Yang model defined in this memo can be used for Optical Parameters monitoring and/or configuration of the multivendor Endpoints and ROADMs

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 21, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. The Internet-Standard Management Framework	3
3. Conventions	4
4. Definition	4
5. Applicability	4
6. Properties	4
7. Overview	4
7.1. Optical Parameters Description	5
7.1.1. Rs-Ss Configuration	6
7.1.2. Table of Application Codes	6
7.2. Use Cases	6
7.3. Optical Parameters for impairment validation in a WDM network	6
8. Structure of the Yang Module	7
9. Yang Module	7
10. Security Considerations	18
11. IANA Considerations	18
12. Acknowledgements	18
13. Contributors	18
14. References	19
14.1. Normative References	19
14.2. Informative References	21
Appendix A. Change Log	22
Appendix B. Open Issues	22
Authors' Addresses	22

1. Introduction

This memo defines a Yang model that translates the existing mib module defined in draft-ietf-ccamp-wson-iv-info and draft-martinelli-ccamp-wson-iv-encode to provide the network impairment information to an SDN controller. One of the key SDN controller features is to support multi vendor network and support the service calculation and deployment in multilayer topologies, for the DWDM layer it is fundamental the SDN controller is aware of the optical impairments to verify the feasibility of new circuits before their provisioning. Although SDN controller will not apply exhaustive and accurate algorithms and the optical channel feasibility verification may have a degree of unreliability this function can work on a multivendor common set of parameter and algorithms to ensure the operator the best change to set a circuit. This document follows the same impairment definition and applicability of draft-ietf-ccamp-wson-iv-info.

For the optical impairments related to the DWDM Transceiver the draft draft-dharini-ccamp-dwdm-if-yang. Applications are defined in G.698.2 [ITU.G698.2] using optical interface parameters at the single-channel connection points between optical transmitters and the optical multiplexer, as well as between optical receivers and the optical demultiplexer in the DWDM system. This Recommendation uses a methodology which explicitly specify the details of the optical network between reference point Ss and Rs, e.g., the passive and active elements or details of the design.

This draft refers and supports the draft-kdkgall-ccamp-dwdm-if-mng-ctrl-fwk

The building of a yang model describing the optical parameters allows the different vendors and operator to retrieve, provision and exchange information across multi-vendor domains in a standardized way. In addition to the parameters specified in ITU recommendations the Yang models support also the "vendor specific parameters".

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

This memo specifies a Yang model for optical interfaces.

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119]. In the description of OIDs the convention: Set (S) Get (G) and Trap (T) conventions will describe the action allowed by the parameter.

4. Definition

For a detailed definition this draft refers to draft-ietf-ccamp-wson-iv-info.

5. Applicability


This document targets at Scenario C defined in [RFC6566] section 4.1.1. as approximate impairment estimation. The Approximate concept refers to the fact that this Information Model covers information mainly provided by [ITU.G680] Computational Model. Although the [RFC6566] provides no or little approximation the parameters described in this draft can be applied to the algorithms verifying the circuit feasibility in the new coherent non compensated DWDM networks. In this case the impairments verification can reach a good reliability and accuracy. This draft does not address computational matters but provides all the information suitable to cover most of the full coherent network algorithms, not being exhaustive the information can give a acceptable or even good approximation in terms of connection feasibility. This may not be true for legacy compensated network.

6. Properties

For the signal properties this draft refers to draft-ietf-ccamp-wson-iv-info Ch.2.3 with some extension of the parameters.

7. Overview

Figure 1 shows a set of reference points, for single-channel connection between transmitters (Tx) and receivers (Rx). Here the DWDM network elements include an OM and an OD (which are used as a pair with the opposing element), one or more optical amplifiers and may also include one or more OADMs.



Ss = reference point at the DWDM network element tributary output
Rs = reference point at the DWDM network element tributary input
Lx = Lambda x
OM = Optical Mux
OD = Optical Demux
OADM = Optical Add Drop Mux

from Fig. 5.1/G.698.2

Figure 1: External transponder in WDM networks

7.1. Optical Parameters Description

The link between the external transponders through a WDM network media channels are managed at the edges, i.e. at the transmitters (Tx) and receivers (Rx) attached to the S and R reference points respectively. The set of parameters that could be managed are defined by the "application code" notation

The definitions of the optical parameters are provided below to increase the readability of the document, where the definition is

ended by (R) the parameter can be retrieve with a read, when (W) it can be provisioned by a write, (R,W) can be either read or written.

7.1.1. Rs-Ss Configuration

For Rs-Ss configuration this draft refers the draft-dharini-ccamp-dwdm-if-yang

7.1.2. Table of Application Codes

For Application Codes configuration this draft refers the draft-dharini-ccamp-dwdm-if-yang

7.2. Use Cases

The use cases are described in draft-kdkgall-ccamp-dwdm-if-mng-ctrl-fwk

7.3. Optical Parameters for impairment validation in a WDM network

The ietf-opt-parameters-wdm is an augment to the ?????. It allows the user to get and set the application Optical Parameters of a DWDM network.

```

module: ietf-opt-parameters-wdm
+--rw gain-degrade-high? dbm-t
augment /if:interfaces/if:interface:
+--rw optical-transport
|   +--rw attenuator-value? attenuator-t
|   +--rw offset? decimal64
|   +--rw channel-power-ref? decimal64
|   +--rw tilt-calibration? tilt-t
+--rw channel-t
|   +--rw grid? uint32
|   +--rw channel-spacing? uint32
|   +--rw identifier? uint32
|   +--rw n? uint32
+--rw channel-n-m
|   +--rw grid? uint32
|   +--rw channel-spacing? uint32
|   +--rw n? uint32
|   +--rw m? uint32

```

8. Structure of the Yang Module

ietf-opt-parameters-wdm is a top level model for the support of this feature.

9. Yang Module

The ietf-opt-parameters-wdm is defined as an extension to ietf interfaces ????.

<CODE BEGINS> file "ietf-opt-parameters-wdm.yang"

```
module ietf-opt-parameters-wdm {  
  namespace "urn:ietf:params:xml:ns:yang:ietf-opt-parameters-wdm";  
  prefix iietf-opt-parameters-wdm;
```

```
  import ietf-interfaces {  
    prefix if;  
  }
```

```
  import iana-if-type {  
    prefix ianaift;  
  }
```

```
  organization  
    "IETF CCAMP  
    Working Group";
```

```
  contact  
    "WG Web:   <http://tools.ietf.org/wg/ccamp/>  
    WG List:   <mailto:ccamp@ietf.org>
```

```
    Editor:     Gabriele Galimberti  
               <mailto:ggalimbe@cisco.com>";
```

```
  description  
    "This module contains a collection of YANG definitions for  
    collecting and configuring Optical Parameters  
    in Optical Networks and calculate the circuit feasibility.
```

```
    Copyright (c) 2016 IETF Trust and the persons identified  
    as authors of the code. All rights reserved.
```

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).";

```
revision "2016-03-11" {
    description
        "Initial revision.";
    reference
        "RFC XXXX: A YANG Data Model for Optical Parameters
        of DWDM Networks
        ";
}

typedef tilt-t {
    type decimal64 {
        fraction-digits 2;
        range "-5..5";
    }
    description "Tilt Type";
}

typedef signal-output-power-t {
    type decimal64 {
        fraction-digits 2;
        range "-10..30";
    }
    description "
        Amplifier Power provisioning ";
}

typedef active-channel-t {
    type union {
        type uint8 {
            range "0..200";
        }
    }
    description "
        Number of channels active on a span - and on an amplifier ";
}

typedef dbm-t {
```



```
    type decimal64 {
      fraction-digits 2;
      range "-50..-30 | -10..5 | 10000000";
    }
    description "
      Amplifier Power in dBm ";
  }

  typedef attenuator-t {
    type decimal64 {
      fraction-digits 2;
      range "-15..-5";
    }
    description "
      Attenuation value (attenuator) applied after the Amplifier ";
  }

  grouping channel-ITU {
    description "channel-ITU";
    container channel-t {
      description "wavelength notation according to RFC-6205";
      leaf grid {
        type uint32;
        description "grid type e.g.: 0=reserved, 1=DWDM, 2=CWDM";
      }
      leaf channel-spacing {
        type uint32;
        description "DWDM grid e.g.: 1=100GHz, 2=50GHz, 3=25GHz";
      }
      leaf identifier {
        type uint32;
        description "Channel identifier";
      }
      leaf n {
        type uint32;
        description "N Value (Channel n-m notation)";
      }
    }
  }

  grouping channel-flex {
    description "channel-flex";
    container channel-n-m {
      description "Channel N / M Notation to describe the
        MEdiachannel";
      leaf grid {
        type uint32;
        description "grid type e.g.: 0=reserved, 1=DWDM, 2=CWDM";
      }
    }
  }
```

```
    }
    leaf channel-spacing {
      type uint32;
      description "DWDM grid e.g.: 1=100GHz, 2=50GHz, 3=25GHz";
    }
    leaf n {
      type uint32;
      description "N Value (Channel n-m notation)";
    }
    leaf m {
      type uint32;
      description "M Value (Channel n-m notation)";
    }
  }
}
```

```
augment "/if:interfaces/if:interface" {
  when "if:type = 'ianaif:opticalTransport'" {
    description "Specific optical-transport Interface Data";
  }
  description "Specific optical-transport Interface Data";
  container optical-transport {
    description "Specific optical-transport Data";

    leaf attenuator-value {
      type attenuator-t;
      description "External attenuator value ";
    }

    leaf offset {
      type decimal64 {
        fraction-digits 2;
        range "-30..30";
      }
      description "Raman and power amplifiers offset";
    }

    leaf channel-power-ref {
      type decimal64 {
        fraction-digits 2;
        range "-10..15";
      }
      description "Optical power per channel";
    }
  }
}
```

```
    leaf tilt-calibration {
      type tilt-t;
      description "Amplifier Tilt tuning";
    }
  }
  uses channel-ITU;
  uses channel-flex;
}

grouping opwr-threshold-warning-grp {
  description "
    Minimum Optical Power threshold
    - this is used to rise Power alarm ";
  leaf opwr-min {
    type dbm-t;
    units "dBm";
    default -1;
    description "Minimum Power Value";
  }

  leaf opwr-min-clear {
    type dbm-t;
    units "dBm";
    default -1;
    description "threshold to clear Minimum Power value Alarm";
  }

  leaf opwr-max {
    type dbm-t;
    units "dBm";
    default 1;
    description "
      Maximum Optical Power threshold
      - this is used to rise Power alarm ";
  }
}

grouping gain-degrade-alarm-grp {
  description "
    Low Optical Power gain threshold
    - this is used to rise Power alarm ";
  leaf gain-degrade-low {
    type dbm-t;
    units "dBm";
    default -1;
    description "Low Gain Degrade Value";
  }
}
```

```
leaf gain-degrade-high {
    type dbm-t;
    units "dBm";
    default 1;
    description "
        High Optical Power gain threshold
        - this is used to rise Power alarm ";
    }
}

grouping power-degrade-high-alarm-grp {
    description "
        High Optical Power gain alarm ";
    leaf gain-degrade-high {
        type dbm-t;
        units "dBm";
        default 1;
        description "Low Gain Degrade Value";
    }
}

grouping power-degrade-low-alarm-grp {
    description "
        Low Optical Power gain alarm ";
    leaf power-degrade-low {
        type dbm-t;
        units "dBm";
        default -1;
        description "High Gain Degrade Value";
    }
}

grouping feasibility-limit-list {
    list feasibility-limit {
        key "id";
        description "Feasibility limit power / osnr pair";
        leaf id {
            type uint32;
            description "Unique Identifier";
        }
        leaf power {
            type decimal64 {
                fraction-digits 2;
            }
            units "dB";
            description "Feasibility power";
        }
    }
}
```

```
    leaf osnr {
      type decimal64 {
        fraction-digits 2;
      }
      description "Feasibility Signal / Noise";
    }
  }
  description "
    Ordered list of feasibility limits
    (should match order of supported FEC types
    given in fec-type-list).
  ";
}

grouping power-failure-low-alarm-grp {
  description "
    Optical Power failure alarm ";
  leaf power-failure-low {
    type dbm-t;
    units "dBm";
    default -1;
    description "Power Failure Low Value";
  }
}

grouping noise {
  leaf noise {
    type decimal64 {
      fraction-digits 2;
    }
    units "dB";
    description "Noise feasibility - reference ITU-T G.680
      OSNR added to the signal by the OMS. The noise is intended
      per channel and is independent of the number of active
      channels in OMS";
  }
  description "Noise feasibility";
}

grouping noise-sigma {
  leaf noise-sigma {
```

```
        type decimal64 {
            fraction-digits 2;
        }
        units "dB";
        description "Noise Sigma feasibility - accuracy of the
            OSNR added to
            the signal by the OMS";
    }
    description "Noise Sigma feasibility";
}

grouping chromatic-dispersion {
    leaf chromatic-dispersion {
        type decimal64 {
            fraction-digits 2;
        }
        units "ps/nm";
        description "Chromatic Dispersion (CD) related to the OMS";
    }
    description "Chromatic Dispersion (CD) feasibility";
}

grouping chromatic-dispersion-slope {
    leaf chromatic-dispersion-slope {
        type decimal64 {
            fraction-digits 2;
        }
        units "ps/nm^2";
        description "Chromatic Dispersion (CD) Slope related to
            the OMS";
    }
    description "Chromatic Dispersion (CD) Slope feasibility";
}

grouping pmd {
    leaf pmd {
        type decimal64 {
            fraction-digits 2;
        }
        units "ps";
        description "Polarization Mode Dispersion (PMD) related
            to OMS";
    }
    description "Polarization Mode Dispersion (PMD) feasibility";
}

grouping pdl {
    leaf pdl {
```

```
        type decimal64 {
            fraction-digits 2;
        }
        units "dB";
        description "Polarization Dependent Loss (PDL) related to
            the OMS";
    }
    description "Polarization Dependent Loss (PDL) feasibility";
}

grouping drop-power {
    leaf drop-power {
        type decimal64 {
            fraction-digits 2;
        }
        units "dBm";
        description "Drop Power value at the DWDM Transceiver RX
            side";
    }
    description "Drop Power feasibility";
}

grouping drop-power-sigma {
    leaf drop-power-sigma {
        type decimal64 {
            fraction-digits 2;
        }
        units "db";
        description "Drop Power Sigma value at the DWDM Transceiver
            RX side";
    }
    description "Drop Power Sigma feasibility";
}

grouping ripple {
    leaf ripple {
        type decimal64 {
            fraction-digits 2;
        }
        units "db";
        description "Channel Ripple";
    }
    description "Channel Ripple";
}

grouping ch-noise-figure {
    list ch-noise-figure {
        description "Channel signal-spontaneous noise figure";
    }
}
```

```
    leaf input-to-output {
      type decimal64 {
        fraction-digits 2;
      }
      units "dB";
      description "from input port to output port";
    }

    leaf input-to-drop {
      type decimal64 {
        fraction-digits 2;
      }
      units "dB";
      description "from input port to drop port";
    }

    leaf add-to-output {
      type decimal64 {
        fraction-digits 2;
      }
      units "dB";
      description "from add port to output port";
    }
  }
  description "Channel signal-spontaneous noise figure";
}

grouping dgd {
  leaf dgd {
    type decimal64 {
      fraction-digits 2;
    }
    units "db";
    description "differential group delay";
  }
  description "differential group delay";
}

grouping ch-isolation {
  list ch-isolation {
    description "adjacent and not adjacent channel isolation";

    leaf ad-ch-isol {
      type decimal64 {
        fraction-digits 2;
      }
      units "dB";
      description "adjacent channel isolation";
    }
  }
}
```


10. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [RFC6241]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [RFC6242]. The NETCONF access control model [RFC6536] provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operation and content.

11. IANA Considerations

This document registers a URI in the IETF XML registry [RFC3688]. Following the format in [RFC3688], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-interfaces:ietf-ext-xponder-wdm-if

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [RFC6020].

This document registers a YANG module in the YANG Module Names registry [RFC6020].

prefix: ietf-ext-xponder-wdm-if reference: RFC XXXX

12. Acknowledgements

Marco Cardani.

13. Contributors

Dean Bogdanovic
Juniper Networks
Westford
U.S.A.
email deanb@juniper.net

Walid Wakim
Cisco
9501 Technology Blvd
ROSEMONT, ILLINOIS 60018
UNITED STATES
email wwakim@cisco.com

Marco Cardani
Cisco
vis S.Maria Molgora, 46b
20871 - Vimercate
Monza Brianza
Italy
email mcardani@cisco.com

Giovanni Martinelli
Cisco
vis S.Maria Molgora, 46b
20871 - Vimercate
Monza Brianza
Italy
email giomarti@cisco.com

14. References

14.1. Normative References

- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, DOI 10.17487/RFC2863, June 2000, <<http://www.rfc-editor.org/info/rfc2863>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.

- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<http://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIV2", STD 58, RFC 2580, DOI 10.17487/RFC2580, April 1999, <<http://www.rfc-editor.org/info/rfc2580>>.
- [RFC3591] Lam, H-K., Stewart, M., and A. Huynh, "Definitions of Managed Objects for the Optical Interface Type", RFC 3591, DOI 10.17487/RFC3591, September 2003, <<http://www.rfc-editor.org/info/rfc3591>>.
- [RFC6205] Otani, T., Ed. and D. Li, Ed., "Generalized Labels for Lambda-Switch-Capable (LSC) Label Switching Routers", RFC 6205, DOI 10.17487/RFC6205, March 2011, <<http://www.rfc-editor.org/info/rfc6205>>.
- [ITU.G698.2] International Telecommunications Union, "Amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces", ITU-T Recommendation G.698.2, November 2009.
- [ITU.G709] International Telecommunications Union, "Interface for the Optical Transport Network (OTN)", ITU-T Recommendation G.709, March 2003.
- [ITU.G872] International Telecommunications Union, "Architecture of optical transport networks", ITU-T Recommendation G.872, November 2001.
- [ITU.G798] International Telecommunications Union, "Characteristics of optical transport network hierarchy equipment functional blocks", ITU-T Recommendation G.798, October 2010.
- [ITU.G874] International Telecommunications Union, "Management aspects of optical transport network elements", ITU-T Recommendation G.874, July 2010.

- [ITU.G874.1]
International Telecommunications Union, "Optical transport network (OTN): Protocol-neutral management information model for the network element view", ITU-T Recommendation G.874.1, January 2002.
- [ITU.G959.1]
International Telecommunications Union, "Optical transport network physical layer interfaces", ITU-T Recommendation G.959.1, November 2009.
- [ITU.G826]
International Telecommunications Union, "End-to-end error performance parameters and objectives for international, constant bit-rate digital paths and connections", ITU-T Recommendation G.826, November 2009.
- [ITU.G8201]
International Telecommunications Union, "Error performance parameters and objectives for multi-operator international paths within the Optical Transport Network (OTN)", ITU-T Recommendation G.8201, April 2011.
- [ITU.G694.1]
International Telecommunications Union, "Spectral grids for WDM applications: DWDM frequency grid", ITU-T Recommendation G.694.1, June 2002.
- [ITU.G7710]
International Telecommunications Union, "Common equipment management function requirements", ITU-T Recommendation G.7710, May 2008.

14.2. Informative References

- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, DOI 10.17487/RFC3410, December 2002, <<http://www.rfc-editor.org/info/rfc3410>>.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", RFC 2629, DOI 10.17487/RFC2629, June 1999, <<http://www.rfc-editor.org/info/rfc2629>>.
- [RFC4181] Heard, C., Ed., "Guidelines for Authors and Reviewers of MIB Documents", BCP 111, RFC 4181, DOI 10.17487/RFC4181, September 2005, <<http://www.rfc-editor.org/info/rfc4181>>.

[I-D.kdkgall-ccamp-dwdm-if-mng-ctrl-fwk]

Kunze, R., Grammel, G., Beller, D., and G. Galimberti, "A framework for Management and Control of G.698.2 optical interface parameters", draft-kdkgall-ccamp-dwdm-if-mng-ctrl-fwk-00 (work in progress), October 2015.

[RFC4054] Strand, J., Ed. and A. Chiu, Ed., "Impairments and Other Constraints on Optical Layer Routing", RFC 4054, DOI 10.17487/RFC4054, May 2005, <<http://www.rfc-editor.org/info/rfc4054>>.

Appendix A. Change Log

This optional section should be removed before the internet draft is submitted to the IESG for publication as an RFC.

Note to RFC Editor: please remove this appendix before publication as an RFC.

Appendix B. Open Issues

Note to RFC Editor: please remove this appendix before publication as an RFC.

Authors' Addresses

Gabriele Galimberti (editor)
Cisco
Via Santa Maria Molgora, 48 c
20871 - Vimercate
Italy

Phone: +390392091462
Email: ggalimbe@cisco.com

Ruediger Kunze (editor)
Deutsche Telekom
Dddd, xx
Berlin
Germany

Phone: +49xxxxxxxxxxx
Email: RKunze@telekom.de

Dharini Hiremagalur (editor)
Juniper
1194 N Mathilda Avenue
Sunnyvale - 94089 California
USA

Email: dharinih@juniper.net

Gert Grammel (editor)
Juniper
Oskar-Schlemmer Str. 15
80807 Muenchen
Germany

Phone: +49 1725186386
Email: ggrammel@juniper.net