

Co-operative DDoS Mitigation

draft-reddy-dots-transport-05

July 2016

IETF 96


Authors: T. Reddy, D. Wing, P. Patil, M. Geller,
M. Boucadair, R. Moskowitz

Presenter : Tirumaleswar Reddy

Changes to draft

- Meets most of the requirements in draft-ietf-dots-requirements-02
 - Happy Eyeballs-like technique for DOTS Signal Channel (v6/v4, UDP/TCP)
 - CoAP for lightweight communication
 - DOTS Signal Channel, UDP/TCP
 - DOTS Data Channel, TCP
 - Mutual Authentication of DOTS Agents & Authorization of DOTS Clients
 - (D)TLS protocol profile and Performance Considerations


Happy Eyeballs-like technique for DOTS Signal Channel




Happy Eyeballs for DOTS Signal Channel

- Order of preference (aligns with RFC6724)
 - IPv6 over DTLS over UDP
 - IPv6 over TLS over TCP
 - IPv4 over DTLS over UDP
 - IPv4 over TLS over TCP
- DNS lookup during peacetime.

DOTS signal and data channel




DOTS signal channel



DOTS data channel


DOTS signal channel




DOTS signal channel

- POST, DELETE, GET, and PUT requests are marked as COAP confirmable messages.
- Asynchronous message exchanges for DDOS mitigation status.


DOTS signal channel




DOTS data channel



Mutual Authentication of DOTS agents



Authorization of DOTS client



(D)TLS profile

- (D)TLS session resumption without server-side state [[RFC5077](#)].
- Raw public keys [[RFC7250](#)].
- (D)TLS Heartbeat.

Performance considerations

- TLS False Start [[I-D.ietf-tls-falsestart](#)].
- Cached Information Extension [[I-D.ietf-tls-cached-info](#)].
- TCP FastOpen [[RFC7413](#)].

draft-reddy-dots-transport-05

- Comments and questions
- Consider adoption of this document as WG item.