

MPLS Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: April 16, 2017

X. Xu  
S. Bryant  
Huawei  
H. Assarpour  
Broadcom  
H. Shah  
Ciena  
L. Contreras  
Telefonica I+D  
D. Bernier  
Bell Canada  
October 13, 2016

Service Chaining using MPLS Source Routing  
draft-xu-mpls-service-chaining-00

Abstract

Source Packet Routing in Networking (SPRING) WG is developing an MPLS source routing mechanism. This MPLS source routing mechanism can be leveraged to realize the service path layer functionality of the service function chaining (i.e., steering the selected traffic through a particular service function path) by encoding the service function path information as an MPLS label stack. This document describes how to use the MPLS source routing mechanism as developed by the SPRING WG to realize the service path layer functionality of service function chaining.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any

time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 16, 2017.

#### Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

1. Introduction . . . . .	2
2. Terminology . . . . .	3
3. Solution Description . . . . .	3
3.1. Encoding SFP Information by an MPLS Label Stack . . . . .	4
4. Acknowledgements . . . . .	5
5. IANA Considerations . . . . .	5
6. Security Considerations . . . . .	6
7. References . . . . .	6
7.1. Normative References . . . . .	6
7.2. Informative References . . . . .	6
Authors' Addresses . . . . .	7

#### 1. Introduction

When applying a particular Service Function Chain (SFC) [RFC7665] to the traffic selected by a service classifier, the traffic need to be steered through an ordered set of Service Functions (SF) in the network. This ordered set of SFs in the network indicates the Service Function Path (SFP) associated with the above SFC. In order to steer the selected traffic through the required ordered list of SFs, the service classifier needs to attach information to the packet specifying which Service Function Forwarders (SFFs) and which SFs are to be visited by the selected traffic. The Source Packet Routing in Networking (SPRING) WG is developing an MPLS source routing mechanism which can be used to steer traffic through an ordered set of routers (i.e., an explicit path) and instruct nodes on that path to execute





an encapsulation aware SF, i.e., it understands how to process a packet with a pre-pended MPLS label stack. In this case the packet would be sent to SF1 by SFF1 with the label stack SID(SFF2)->SID(SF2). SF1 would perform the required service function on the received MPLS packet where the payload is constrained to be an IP packet, and the SF needs to process both IPv4 and IPv6 packets (note that the SF would use the first nibble of the MPLS payload to identify the payload type). After the MPLS packet is returned from SF1, SFF1 would send it to SFF2 according to the top label (i.e., SID(SFF2) ).

If SF1 is a legacy SF, i.e. one that is unable to process the MPLS label stack, the remaining MPLS label stack (i.e., SID(SFF2)->SID(SF2)) MUST be saved and stripped from the packet before sending the packet to SF1. When the packet is returned from SF1, SFF1 would re-impose the MPLS label stack which had been previously stripped and then send the packet to SFF2 according to the current top label (i.e., SID(SFF2) ). As for how to associate the corresponding MPLS label stack with the packets returned from legacy SFs, those mechanisms as described in [I-D.song-sfc-legacy-sf-mapping] could be considered.

When the encapsulated packet arrives at SFF2, SFF2 would perform the similar action to that described above.

If there is no MPLS LSP towards the next node segment (i.e., the next SFF identified by the current top label), the corresponding IP-based tunnel (e.g., MPLS-in-IP/GRE tunnel [RFC4023], MPLS-in-UDP tunnel [RFC7510] or MPLS-in-L2TPv3 tunnel [RFC4817]) would be used instead (for more details about this special usage, please refer to [I-D.xu-mpls-spring-islands-connection-over-ip]). Since the transport (i.e., the underlay) could be IPv4, IPv6 or even MPLS networks, the above approach of encoding the SFP information by an MPLS label stack is fully transport-independent which is one of the major requirements for the SFC encapsulation [RFC7665].

#### 4. Acknowledgements

The authors would like to thank Loa Andersson, Andrew G. Malis, Adrian Farrel, Alexander Vainshtein and Joel M. Halpern for their valuable comments and suggestions on the document

#### 5. IANA Considerations

This document makes no request of IANA.

## 6. Security Considerations

It is fundamental to the SFC design that the classifier is a trusted resource which determines the processing that the packet will be subject to, including for example the firewall. It is also fundamental to the SPRING design that packets are routed through the network using the path specified by the node imposing the SIDs. Where an SF is not encapsulation aware the packet may exist as an IP packet, however this is an intrinsic part of the SFC design which needs to define how a packet is protected in that environment. Where a tunnel is used to link two non-MPLS domains, the tunnel design needs to specify how it is secured. Thus the security vulnerabilities are addressed in the underlying technologies used by this design, which itself does not introduce any new security vulnerabilities.

## 7. References

### 7.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

### 7.2. Informative References

[I-D.ietf-sfc-nsh]  
Quinn, P. and U. Elzur, "Network Service Header", draft-ietf-sfc-nsh-10 (work in progress), September 2016.

[I-D.ietf-spring-segment-routing-mpls]  
Filsfils, C., Previdi, S., Bashandy, A., Decraene, B., Litkowski, S., Horneffer, M., Shakir, R., jefftant@gmail.com, j., and E. Crabbe, "Segment Routing with MPLS data plane", draft-ietf-spring-segment-routing-mpls-05 (work in progress), July 2016.

[I-D.song-sfc-legacy-sf-mapping]  
Song, H., You, J., Yong, L., Jiang, Y., Dunbar, L., Bouthors, N., and D. Dolson, "SFC Header Mapping for Legacy SF", draft-song-sfc-legacy-sf-mapping-08 (work in progress), September 2016.

- [I-D.xu-mpls-spring-islands-connection-over-ip]  
Xu, X., Raszuk, R., Chunduri, U., Contreras, L., and L. Jalil, "Connecting MPLS-SPRING Islands over IP Networks", draft-xu-mpls-spring-islands-connection-over-ip-00 (work in progress), October 2016.
- [RFC4023] Worster, T., Rekhter, Y., and E. Rosen, Ed., "Encapsulating MPLS in IP or Generic Routing Encapsulation (GRE)", RFC 4023, DOI 10.17487/RFC4023, March 2005, <<http://www.rfc-editor.org/info/rfc4023>>.
- [RFC4817] Townsley, M., Pignataro, C., Wainner, S., Seely, T., and J. Young, "Encapsulation of MPLS over Layer 2 Tunneling Protocol Version 3", RFC 4817, DOI 10.17487/RFC4817, March 2007, <<http://www.rfc-editor.org/info/rfc4817>>.
- [RFC7510] Xu, X., Sheth, N., Yong, L., Callon, R., and D. Black, "Encapsulating MPLS in UDP", RFC 7510, DOI 10.17487/RFC7510, April 2015, <<http://www.rfc-editor.org/info/rfc7510>>.
- [RFC7665] Halpern, J., Ed. and C. Pignataro, Ed., "Service Function Chaining (SFC) Architecture", RFC 7665, DOI 10.17487/RFC7665, October 2015, <<http://www.rfc-editor.org/info/rfc7665>>.

#### Authors' Addresses

Xiaohu Xu  
Huawei

Email: [xuxiaohu@huawei.com](mailto:xuxiaohu@huawei.com)

Stewart Bryant  
Huawei

Email: [stewart.bryant@gmail.com](mailto:stewart.bryant@gmail.com)

Hamid Assarpour  
Broadcom

Email: [hamid.assarpour@broadcom.com](mailto:hamid.assarpour@broadcom.com)

Himanshu Shah  
Ciena

Email: [hshah@ciena.com](mailto:hshah@ciena.com)

Luis M. Contreras  
Telefonica I+D  
Ronda de la Comunicacion, s/n  
Sur-3 building, 3rd floor  
Madrid, 28050  
Spain

Email: [luismiguel.contrerasmurillo@telefonica.com](mailto:luismiguel.contrerasmurillo@telefonica.com)  
URI: <http://people.tid.es/LuisM.Contreras/>

Daniel Bernier  
Bell Canada

Email: [daniel.bernier@bell.ca](mailto:daniel.bernier@bell.ca)