

CCAMP Working Group
Internet-Draft
Intended status: Standards Track
Expires: September 9, 2017

X. Zhang
K. Xiang
Huawei Technologies
A. Sharma
Infinera
X. Liu
Ericsson
March 08, 2017

A YANG Data Model for Optical Transport Network Topology
draft-zhang-ccamp-11-topo-yang-06

Abstract

A transport network is a server-layer network designed to provide connectivity services for a client-layer network to carry the client traffic transparently across the server-layer network resources. A transport network can be constructed from equipments utilizing any of a number of different transport technologies such as the evolving Optical Transport Networks (OTN) or packet transport as provided by the MPLS-Transport Profile (MPLS-TP).

This draft describes a YANG data model to describe the topologies of an Optical Transport Network (OTN). It is independent of control plane protocols and captures topological and resource related information pertaining to OTN. This model enables clients, which interact with a transport domain controller via a REST interface, for OTN topology related operations such as obtaining the relevant topology resource information.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 9, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Terminology and Notations	3
3. YANG Data Model for OTN Topology	4
3.1. the YANG Tree	4
3.2. Explanation of the OTN Topology Data Model	5
3.3. The YANG Code	6
4. IANA Considerations	13
5. Manageability Considerations	13
6. Security Considerations	13
7. Acknowledgements	13
8. Contributors	13
9. References	14
9.1. Normative References	14
9.2. Informative References	15
Authors' Addresses	15

1. Introduction

A transport network is a server-layer network designed to provide connectivity services for a client-layer network to carry the client traffic transparently across the server-layer network resources. A transport network can be constructed of equipments utilizing any of a number of different transport technologies such as the Optical

Transport Networks (OTN) or packet transport as provided by the MPLS-Transport Profile (MPLS-TP).

This document defines a data model of an OTN network topology, using YANG [RFC6020]. The model can be used by an application exposing to a transport controller via a REST interface. Furthermore, it can be used by an application for the following purposes (but not limited to):

- o To obtain a whole view of the network topology information of its interest;
- o To receive notifications with regard to the information change of the OTN topology;
- o To enforce the establishment and update of a network topology with the characteristic specified in the data model, e.g., by a client controller;

The YANG model defined in this draft is independent of control plane protocols and captures topology related information pertaining to an Optical Transport Networks (OTN)-electrical layer, as the scope specified by [RFC7062] and [RFC7138]. Furthermore, it is not a stand-alone model, but augmenting from the TE topology YANG model defined in [I-D.ietf-teas-yang-te-topo].

Optical network technologies, including fixed Dense Wavelength Switched Optical Network (WSON) and flexible optical networks (a.k.a., flexi-grid networks), are covered in [I-D.ietf-ccamp-wson-yang] and [I-D.vergara-ccamp-flexigrid-yang], respectively.

2. Terminology and Notations

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in the YANG data tree presented later in this draft is defined in [I-D.ietf-netmod-rfc6087bis]. They are provided below for reference.

- o Brackets "[" and "]" enclose list keys.
- o Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- o Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.

- o Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- o Ellipsis ("...") stands for contents of subtrees that are not shown.

3. YANG Data Model for OTN Topology

3.1. the YANG Tree

```

module: ietf-otn-topology
augment /nd:networks/nd:network/nd:network-types/tet:te-topology:
  +--rw otn-topology!
augment /nd:networks/nd:network:
  +--rw name? string
augment /nd:networks/nd:network/nd:node:
  +--rw name? string
augment /nd:networks/nd:network/lnk:link/tet:te/tet:config:
  +--rw available-odu-info* [priority]
  |   +--rw priority      uint8
  |   +--rw odulist* [odu-type]
  |       +--rw odu-type  identityref
  |       +--rw number?   uint16
  +--rw distance?        uint32
augment /nd:networks/nd:network/lnk:link/tet:te/tet:state:
  +--ro available-odu-info* [priority]
  |   +--ro priority      uint8
  |   +--ro odulist* [odu-type]
  |       +--ro odu-type  identityref
  |       +--ro number?   uint16
  +--ro distance?        uint32
augment /nd:networks/nd:network/nd:node/lnk:termination-point
/tet:te/tet:config:
  +--rw client-facing?          empty
  +--rw tpn?                    uint16
  +--rw tsg?                    identityref
  +--rw protocol-type?          identityref
  +--rw adaptation-type?        adaptation-type
  +--rw sink-adapt-active?      boolean
  +--rw source-adapt-active?    boolean
  +--rw tributary-slots
  |   +--rw values*            uint8
  +--rw supported-payload-types* [index]
  |   +--rw index              uint16
  |   +--rw payload-type?      string
augment /nd:networks/nd:network/nd:node/lnk:termination-point/

```

```

tet:te/tet:state:
  +--ro client-facing?          empty
  +--ro tpn?                    uint16
  +--ro tsng?                   identityref
  +--ro protocol-type?          identityref
  +--ro adaptation-type?        adaptation-type
  +--ro sink-adapt-active?      boolean
  +--ro source-adapt-active?    boolean
  +--ro tributary-slots
  |   +--ro values*             uint8
  +--ro supported-payload-types* [index]
      +--ro index               uint16
      +--ro payload-type?       string

```

3.2. Explanation of the OTN Topology Data Model

As can be seen, from the data tree shown in Section 3.1, the YANG module presented in this draft augments from a more generic Traffic Engineered (TE) network topology data model, i.e., the `ietf-te-topology.yang` as specified in [I-D.ietf-teas-yang-te-topo]. The entities and their attributes, such as node, termination points and links, are still applicable for describing an OTN topology and the model presented in this draft only specifies with technology-specific attributes/information. For example, if the data plane complies with ITU-T G.709 (2012) standards, the switching-capability and encoding attributes MUST be filled as OTN-TDM and G.709 ODUk(Digital Path) respectively.

Note the model in this draft re-uses some attributes defined in `ietf-transport-types.yang`, which is specified in [I-D.sharma-ccamp-otn-tunnel-model].

One of the main augmentations in this model is that it allows to specify the type of ODU container and the number a link can support per priority level. For example, for a ODU3 link, it may advertise 32*ODU0, 16*ODU1, 4*ODU2 available, assuming only a single priority level is supported. If one of ODU2 resource is taken to establish a ODU path, then the availability of this ODU link is updated as 24*ODU0, 12*ODU1, 3*ODU2 available. If there are equipment hardware limitations, then a subset of potential ODU type SHALL be advertised. For instance, an ODU3 link may only support 4*ODU2.

3.3. The YANG Code

```
<CODE BEGINS> file " ietf-otn-topology@2017-03-08.yang"

module ietf-otn-topology {
  yang-version 1.1;

  namespace "urn:ietf:params:xml:ns:yang:ietf-otn-topology";
  prefix "otntopo";

  import ietf-network {
    prefix "nd";
  }

  import ietf-network-topology {
    prefix "lnk";
  }

  import ietf-te-topology {
    prefix "tet";
  }

  import ietf-transport-types {
    prefix "tran-types";
  }

  organization
    "Internet Engineering Task Force (IETF) CCAMP WG";
  contact
    "
    WG List: <mailto:ccamp@ietf.org>

    ID-draft editor:
      Xian ZHANG (zhang.xian@huawei.com);
      Anurag Sharma (AnSharma@infinera.com);
    ";

  description
    "This module defines a protocol independent Layer 1/ODU
    topology data model.";

  revision 2017-03-08 {
    description
      "Revision 0.2";
    reference
      "draft-zhang-ccamp-l1-topo-yang-05.txt";
  }
}
```

```
/*
typedef
*/

typedef adaptation-type {
  type enumeration {
    enum CBR {
      description "Constant Bit Rate.";
    }
    enum ATMvp {
      description "ATM VP.";
    }
    enum GFP {
      description "Generic Framing Procedure.";
    }
    enum NULL {
      description "NULL";
    }
    enum PRBS {
      description "Pseudo Random Binary Sequence";
    }
    enum RSn {
      description "SDH/SONET section";
    }
    enum ODUj-21 {
      description "ODU payload type 21";
    }
    enum ETHERNET_PP-OS {
      description "ETHERNET_PP-OS, for ODU 2 only";
    }
    enum CBRx {
      description "CBRx(0.. 1.25G), for ODU0 only";
    }
    enum ODU {
      description "Optical Data Unit";
    }
  }
  description
    "Defines a type representing the adaptation type
    on the termination point.";
}

/*
Groupings
*/
```

```
grouping otn-topology-type {
  container otn-topology {
    presence "indicates a topology type of Optical
      Transport Network (OTN)-electrical layer.";
    description "otn topology type";
  }
  description "otn-topology-type";
}

grouping otn-topology-attributes {
  leaf name {
    type string;
    description "the topology name";
  }
  description "name attribute for otn topology";
}

grouping otn-node-attributes {
  description "otn-node-attributes";
  leaf name {
    type string;
    description "a name for this node.";
  }
}

grouping otn-link-attributes {
  description "otn link attributes";

  list available-odu-info{
    key "priority";
    max-elements "8";

    description
      "List of ODU type and number on this link";
    leaf priority {
      type uint8 {
        range "0..7";
      }
      description "priority";
    }
  }

  list odulist {
    key "odu-type";

    description
      "the list of available ODUs per priority level";

    leaf odu-type {
```



```
    type identityref {
      base tran-types:tributary-protocol-type;
    }
    description "the type of ODU";
  }

  leaf number {
    type uint16;
    description "the number of odu type supported";
  }
}

leaf distance {
  type uint32;
  description "distance in the unit of kilometers";
}

}

grouping otn-tp-attributes {
  description "otn-tp-attributes";

  leaf client-facing {
    type empty;
    description
      "if present, it means this tp is a client-facing tp.
      adding/dropping client signal flow.";
  }

  leaf tpn {
    type uint16 {
      range "0..4095";
    }
    description
      "Tributary Port Number. Applicable in case of mux services.";
    reference
      "RFC7139: GMPLS Signaling Extensions for Control of Evolving
      G.709 Optical Transport Networks.";
  }

  leaf tsg {
    type identityref {
      base tran-types:tributary-slot-granularity;
    }
    description "Tributary slot granularity.";
    reference
      "G.709/Y.1331, February 2012: Interfaces for the Optical
      Transport Network (OTN)";
  }
}
```

```
}

leaf protocol-type {
  type identityref {
    base tran-types:tributary-protocol-type;
  }
  description "Protocol type for the Termination Point.";
}

leaf adaptation-type {
  type adaptation-type;
  description
    "This attribute indicates the type of the supported
    adaptation function at the termination point.";
  reference
    "G.874.1, January 2002: Optical transport network (OTN):
    Protocol-neutral management information model for the
    network element view.";
}

leaf sink-adapt-active {
  type boolean;
  description
    "This attribute allows for activation or deactivation of
    the sink adaptation function. The value of TRUE means active.";
  reference
    "G.874.1, January 2002: Optical transport network (OTN):
    Protocol-neutral management information model for the
    network element view ";
}

leaf source-adapt-active {
  type boolean;
  description
    "This attribute allows for activation or deactivation of
    the sink adaptation function. The value of TRUE
    means active.";
  reference
    "G.874.1, January 2002: Optical transport network (OTN):
    Protocol-neutral management information model for
    the network element view ";
}

container tributary-slots {
  description
    "A list of tributary slots used by the ODU
    Termination Point.";
```

```
    leaf-list values {
      type uint8;
      description
        "Tributary slot value.";
      reference
        "G.709/Y.1331, February 2012: Interfaces for the
        Optical Transport Network (OTN)";
    }
  }

  list supported-payload-types{
    key "index";

    description "supported payload types of a TP";

    leaf index {
      type uint16;
      description "payload type index";
    }

    leaf payload-type {
      type string;
      description "the payload type supported by this client
      tp";
      reference
        "http://www.iana.org/assignments/gmpls-sig-parameters
        /gmpls-sig-parameters.xhtml
        not: the payload type is defined as the generalized PIDs
        in GMPLS.";
    }
  }
}

/*
 * Data nodes
 */
augment "/nd:networks/nd:network/nd:network-types/tet:te-topology" {
  uses otn-topology-type;
  description "augment network types to include otn newtork";
}

augment "/nd:networks/nd:network" {
  when "nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network";
  }
  uses otn-topology-attributes;
  description "Augment network configuration";
}
```

```
}

augment "/nd:networks/nd:network/nd:node" {
  when "../nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network";
  }
  description "Augment node configuration";
  uses otn-node-attributes;
}

augment "/nd:networks/nd:network/lnk:link/tet:te/tet:config" {
  when "../../../nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network.";
  }
  description "Augment link configuration";

  uses otn-link-attributes;
}

augment "/nd:networks/nd:network/lnk:link/tet:te/tet:state" {
  when "../../../nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network.";
  }
  description "Augment link state";

  uses otn-link-attributes;
}

augment "/nd:networks/nd:network/nd:node/"
+ "lnk:termination-point/tet:te/tet:config" {
  when "../../../nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network";
  }
  description "OTN TP attributes config in a ODU topology.";
  uses otn-tp-attributes;
}

augment "/nd:networks/nd:network/nd:node/"
+ "lnk:termination-point/tet:te/tet:state" {
  when "../../../nd:network-types/tet:te-topology/otn-topology" {
    description "Augment only for otn network";
  }
  description "OTN TP attributes state in a ODU topology.";
  uses otn-tp-attributes;
}
}

<CODE ENDS>
```

4. IANA Considerations

TBD.

5. Manageability Considerations

TBD.

6. Security Considerations

The data following the model defined in this draft is exchanged via, for example, the interface between an orchestrator and a transport network controller. The security concerns mentioned in [I-D.ietf-teas-yang-te-topo] for using ietf-te-topology.yang model also applies to this draft.

The YANG module defined in this document can be accessed via the RESTCONF protocol defined in [I-D.ietf-netconf-restconf], or maybe via the NETCONF protocol [RFC6241].

There are a number of data nodes defined in the YANG module which are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., POST) to these data nodes without proper protection can have a negative effect on network operations.

Editors note: to list specific subtrees and data nodes and their sensitivity/vulnerability.

7. Acknowledgements

We would like to thank Igor Bryskin, Zhe Liu, Dieter Beller and Daniele Ceccarelli for their comments and discussions.

8. Contributors

Baoquan Rao
Huawei Technologies
Email: raobaoquan@huawei.com

Sergio Belotti
Alcatel Lucent
Email: Sergio.belotti@alcatel-lucent.com

Huub van Helvoort
Hai Gaoming BV
the Netherlands

Email: huubatwork@gmail.com

9. References

9.1. Normative References

- [I-D.ietf-netconf-restconf]
Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", draft-ietf-netconf-restconf-18 (work in progress), October 2016.
- [I-D.ietf-netmod-rfc6087bis]
Bierman, A., "Guidelines for Authors and Reviewers of YANG Data Model Documents", draft-ietf-netmod-rfc6087bis-12 (work in progress), March 2017.
- [I-D.ietf-teas-yang-te-topo]
Liu, X., Bryskin, I., Beeram, V., Saad, T., Shah, H., and O. Dios, "YANG Data Model for TE Topologies", draft-ietf-teas-yang-te-topo-06 (work in progress), October 2016.
- [I-D.sharma-ccamp-otn-tunnel-model]
ansharma@infinera.com, a., Rao, R., and X. Zhang, "OTN Tunnel YANG Model", draft-sharma-ccamp-otn-tunnel-model-00 (work in progress), October 2016.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<http://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<http://www.rfc-editor.org/info/rfc6241>>.
- [RFC7062] Zhang, F., Ed., Li, D., Li, H., Belotti, S., and D. Ceccarelli, "Framework for GMPLS and PCE Control of G.709 Optical Transport Networks", RFC 7062, DOI 10.17487/RFC7062, November 2013, <<http://www.rfc-editor.org/info/rfc7062>>.

[RFC7138] Ceccarelli, D., Ed., Zhang, F., Belotti, S., Rao, R., and J. Drake, "Traffic Engineering Extensions to OSPF for GMPLS Control of Evolving G.709 Optical Transport Networks", RFC 7138, DOI 10.17487/RFC7138, March 2014, <<http://www.rfc-editor.org/info/rfc7138>>.

9.2. Informative References

[I-D.ietf-ccamp-wson-yang]
Lee, Y., Dhody, D., Zhang, X., Guo, A., Lopezalvarez, V., King, D., and B. Yoon, "A Yang Data Model for WSON Optical Networks", draft-ietf-ccamp-wson-yang-05 (work in progress), February 2017.

[I-D.vergara-ccamp-flexigrid-yang]
Madrid, U., Perdices, D., Lopezalvarez, V., Dios, O., King, D., Lee, Y., and G. Galimberti, "YANG data model for Flexi-Grid Optical Networks", draft-vergara-ccamp-flexigrid-yang-04 (work in progress), March 2017.

Authors' Addresses

Xian Zhang
Huawei Technologies
F3-5-B R&D Center, Huawei Industrial Base, Bantian, Longgang District
Shenzhen, Guangdong 518129
P.R.China

Email: zhang.xian@huawei.com

Kun Xiang
Huawei Technologies
F3 R&D Center, Huawei Industrial Base, Bantian, Longgang District
Shenzhen, Guangdong 518129
P.R.China

Email: xiangkun@huawei.com

Anurag Sharma
Infinera

Email: ansharma@infinera.com

Xufeng Liu
Ericsson

Email: xufeng.liu@ericsson.com