

# **DetNet Backhaul Networks**

draft-wang-detnet-backhaul-architecture-00  
draft-wang-detnet-joint-scheduling-00

Heng Wang, Ping Wang , Lun Shao

wangheng@cqupt.edu.cn, wangping@cqupt.edu.cn,  
yjssslcqupt@163.com

Chongqing University of Posts and Telecommunications, China

# Motivation and Background


- Describes
  - Industrial backhaul network
  - IPv6 technology
  - WIA-PA standard
  - SDN
- Goal
  - Provide an SDN-based WIA-PA field network/IPv6 backhaul network joint scheduling method.
  - Enable the end-to-end joint scheduling of the cross-network data streams.
  - Enable the recognition of different types of cross-network data streams.
  - Enable the bandwidth guarantee specific to different types of cross-network end-to-end data.
  - Enable the acceleration of cross-network business deployment and reduce the management cost for network operation and maintenance.

# Overview

- Joint Scheduling Architecture.
- Requirements.
- Method.
- Next steps

# Network Structure

- A typical deterministic industrial field networks - backhaul networks structure.
- End-to-end joint scheduling of the cross-network data streams




# Joint Scheduling Architecture

- Control Plane
  - There are many network controllers in the network, which together constitute the control plane for the whole industrial network.
- No uniform standard
  - There is not a unified standard of joint architecture of multiple controllers in the industry at present.
- The main frameworks
  - Distributed architecture.
  - Centralized architecture.


# Joint Scheduling Architecture

- Distributed Architecture
  - East-West architecture.
  - The status of all network controller is equal.
- Disadvantages
  - Need to extend the east-west interface;
  - Maintain a global network topology in each controller.




# Joint Scheduling Architecture

- Centralized Architecture
  - Vertical multi-level architecture;
  - One is the basic control plane composed of a variety of network controllers;
  - Another part is a network controller composed of the main controller.
- Disadvantages
  - The scale of the network is not very large;
  - A single SDN controller is sufficient to meet the control demands of industrial backhaul network.



# Joint Scheduling Architecture

- Control plane
  - WIA-PA System Manager, SDN controller.
  - Joint scheduler is integrated into the SDN controller in the form of plugin.
  - Establishing a connection with the SDN controller.
  - Directly calling the corresponding module of SDN controller.
- Joint Scheduling Architecture
  - Deterministic networks and deterministic Ethernet-based networks are jointly scheduling.
  - Control and scheduling for the entire industrial network by joint scheduler, so as to provide a real-time protection for each data stream.






# Joint Scheduling Requirements

- **Determinacy**
  - The data of Industrial field network-backhaul network directly related to the monitoring and control of industrial production process.
- **Time Synchronization**
  - The industrial field/backhaul network is a converged network and need some scheduling methods to ensure deterministic data stream. So it requires high time synchronization accuracy between devices in the network.
- **Compatibility**
  - Some mechanisms, interfaces, etc. will be necessary when conducting joint scheduling to be compatibility with industrial field/backhaul network.
- **Scalability**
  - Data scalability should be ensured during joint scheduling process.

# Joint Scheduling Method

- Solution

- A joint controller, WIA-PA network managers, gateways and field devices;
- The joint controller consists of an SDN controller and a joint scheduling plugin,
- WIA-PA networks are uniformly managed by the joint controller;
- The joint controller assigns a network identifier (PAN\_ID) to each network manager connected thereto for identifying different WIA-PA networks;



A schematic diagram showing joint scheduling.


# Joint Scheduling Method

- Establish backhaul network

- S1: establishing a connection with the joint controller actively by the network managers ;
- S2: collecting information of the WIA-PA networks periodically;
- S3: receiving and analyzing a business establishing request by the joint controller;
- S4: looking up the PAN\_ID of a source node and a destination node according to analyzed information;
- S5: looking up the information of the corresponding networks and nodes and assigning paths and resources;
- S6: sending a path and resource configuration request;
- S7: sending a mapping table of WIA-PA network addresses and IP addresses to the gateways;
- S8: configuring the controlled IPv6 backhaul network.

# Joint Scheduling Method

- The network access of a network manager
  - Step 1: establishing a connection with the joint controller and reporting network manager information;
  - Step 2: assigning one PAN\_ID to the WIA-PA network and establishing a mapping relation;
  - Step 3: sending a request for getting topology information and node information;
  - Step 4: replying with the topology information and node information;
  - Step 5: sending a configuration completion to end a network access process.




The network access of a network manager.

# Joint Scheduling Method

- WIA-PA Network Joint Scheduling Scheme


- Path deployment and resource allocation for WIA-PA network are performed by calling the WIA-PA network system manager API interface.
- System manager query the corresponding information of the field device in the network
- Then return the received information to the united scheduler.
- Configure communication resources for the corresponding gateway device, routing equipment and field equipment.
- Send a successful reply to the united scheduler after receiving a successful response.



A joint scheduling configuration.

# Joint Scheduling Method


- Gateway protocol conversion
  - Step 1: receiving a data packet and judging whether the data packet is management data by a gateway;
  - Step2: If so, forwarding the data packet to the network manager, otherwise looking up a VCR;
  - Step3: looking up an IPv6 address according to Route\_ID by the gateway;
  - Step 4: encapsulating the WIA-PA data packet in an IPv6 format by the gateway.



Gateway protocol conversion.

# Joint Scheduling Method


- Bandwidth guarantee of the IPv6 backhaul network
  - Step 1: calculating path information and network resource assignment;
  - Step 2: verifying whether a bandwidth in the path is sufficient for meeting a business;
  - Step 3: if so, deploying a flow table through the SDN controller;
  - Step 4: if not, recalculating the path information and resource assignment and selecting other secondary paths.



The bandwidth guarantee for an IPv6 backhaul network

# Joint Scheduling Method

- Consider Industrial Backhaul Network as a Black Box
  - Only consider its delay impacts and ignore its internal details.
  - The approximate delay of packets caused by the industrial backhaul network.
  - Implementing a few of scheduling paths of different priority.
  - Then the data stream goes through the black box, and it will cause uncertain delay which is in a numerical range.
- When the data stream comes out the backhaul network.  
(the deadline is missed / there is time left)





# Next steps

- Ignore the Delay of Industrial Backhaul Network
- Build Delay Model of Industrial Backhaul Network

# Thanks!

Heng Wang, Ping Wang, Lun Shao

wangheng@cqupt.edu.cn, wangping@cqupt.edu.cn,  
yjssslcqupt@163.com

Chongqing University of Posts and Telecommunications , China