
Using Markup in YANG Text Arguments

draft-lhotka-netmod-yang-markup-00

Ladislav Lhotka
<lhotka@nic.cz>

28 March 2017

Objectives

1. Define metadata item for specifying the type of markup used in arguments of selected YANG statements (`yin-element == true`):
 - **contact**
 - **description**
 - **error-message**
 - **organization**
2. Provide guidelines for reasonable and interoperable use of (lightweight) markup languages.

Markup in YANG

Some markup can already be found in existing YANG modules:

- multiple paragraphs separated by empty lines
- bulleted or numbered lists use indented items.

In programmatic use (e.g. for HTML rendering) descriptions etc. often need to be reformatted – tricky with casual markup conventions.

Several “lightweight” markup languages became popular: Markdown (in a number of variants), reStructuredText, MediaWiki, Org mode in Emacs, ...

YANG extension text-media-type

Permitted at the top level of a module or submodule, specifies media type used throughout the (sub)module in arguments of the four YANG statements.

Example:

```
module foo {  
    ...  
    import ietf-yang-media-type {  
        prefix ymt;  
    }  
    // GitHub-flavoured Markdown  
    ymt:text-media-type "text/markdown; charset=UTF-8; variant=GFM";  
    ...  
}
```

Just metadata information, no requirements on implementations.

RECOMMENDED to use only lightweight markup.

Open Issues

1. Restrictions on the set of permitted formats

Proposal: Only IANA-registered text/markdown variants

<https://www.iana.org/assignments/markdown-variants/markdown-variants.xhtml>

2. Permit `yml:text-media-type` anywhere in a module, apply scoping

Use cases:

- interpret markup only in selected YANG statements
- multiple markup formats in the same module