

Network Coding and Satellite Communications


draft-kuhn-nwcrg-network-coding-satellites-00

IETF'99 July 2017

N. Kuhn (CNES) – E. Lochin (ISAE)


Objectives of the draft (1/4)

- **SoA** on the current deployment of network coding schemes within satellite systems
 - DVB-* standards, ...



Objectives of the draft (2/4)

- **SoA** on the current deployment of network coding schemes within satellite systems
 - DVB-* standards, ...



Objectives of the draft (3/4)


- **Identifying opportunities** for further usage of network coding in satellite systems
 - Based on real deployment of NC schemes
 - Feedback from EU or national projects, companies, ...
 - See example below (NetCoP)
 - Other

Network Coding Protocol (NetCoP) - General


- Tomaso de Cola (Tomaso.deCola@dlr.de)
- Stefan Erl (Stefan.Erl@dlr.de)
- Hartmut Brandt (Hartmut.Brandt@dlr.de)

Network Coding Protocol (NetCoP) - General

- Communication protocol for bi-directional communication
- A central Hub (or on-board processor) combines messages from the two communication partners
- Multicast on the FL
- Up to 50% bandwidth or power saving in the forward link



- Encapsulation of IP packets in NC packets
- Testbed implementation on DVB-S2/RCS2 available



Network Coding Protocol (NetCoP) – Header Format

0	8	16	24	32
vsn	flags	address0		
		address1	def_proto0	
def_proto0	def_proto1		pcnt0	
pcnt1	packet_info_block			
				...
...		crc		

- Vsn: Version
- Flags: Indicate presence of address and def_proto fields
- Address: 24bit address of terminals
- Def_proto: Default Ethertype value
- Pcnt: Packet count
- Packet_info_block: Length and CRC of each encoded packet
- CRC is used to identify the packets on encoder and decoder side

Objectives of the draft (4/4)

- We seek a **global vision**
 - To **synthesize numerous activities** in this context
 - With the aim to provide input to build an **architecture-oriented document**
- In other words
 - The best way to use NC and where to put it in a satcom context
 - Contributing to a more generic document
 - We do not seek a taxonomy-like draft
 - We do not promote any solution or architecture

Draft structure

2. A note on satellite topology

→ *Describe the reference architecture*

3. Status of network coding in actually deployed satellite

→ *SoA*

4. Opportunities for more network coding in satellite systems

→ *Feedback from EU or national projects, companies, ...*

5. Deployability and related use cases


→ *usecase*

5.1. Network coding as a VNF

5.2. Network coding and PEP

→ *your proposals ?*

Strategie – Status of network coding in actually deployed satellite



+

End-to-End Coding: A system where coding is performed at the source or (coding) middlebox, and decoding at the destination(s) or (decoding) middlebox. There is no re-coding operation at intermediate nodes. This is the approach followed in the FLUTE/ALC [RFC6726][RFC5775], NORM [RFC5740] and FECFRAME [RFC6363] protocols.

Network Coding: A system where coding can be performed at the source as well as at intermediate forwarding nodes (all or a subset of them). End-to-End Coding can be regarded as a special case of Network Coding. Depending on the use case, additional assumptions can be made: for instance the

damson, et al. Expires January 4, 2018 [Page 7]
 nternet-Draft Network Coding Taxonomy July 2017


knowledge by the destination of the coding node topology and coding operations can help during decoding operations.

Intra-Flow Coding, or Single Source Network Coding: Process where incoming packets to the Coding Node belong to the same flow.

Inter-Flow Coding, or Multi-Source Network Coding: Process where incoming packets to the Coding Node belong to different flows.

Single-Path Coding: Network Coding over a route that has a single path from the source to each destination(s). In case of multicast or broadcast traffic, this route is a tree. Coding may be done end-to-end and/or at intermediate forwarding nodes.

Multi-Path Coding: Network Coding over a route that has multiple (at least partially) disjoint paths from the source to each given destination. Coding may be done end-to-end and/or at intermediate forwarding nodes.



	Upper Appl.	Middle ware	Communication layers	
	Source coding	Network AL-FEC	Packetization UDP/IP	PHY layer
E2E	x			
NC				x
IntraF				
InterF				
SP				
MP				

Figure 1: Network coding and satellite systems


Strategie – Opportunities for more network coding in satellite systems

	Upper Appl.	Middle ware	Communication layers	
	Source coding	Network AL-FEC	Packetization UDP/IP	PHY layer
E2E	x			
NC				x
IntraF				
InterF				
SP				
MP				

Figure 1: Network coding and satellite systems

Feedback from EU or national projects, companies

SoA



	Upper Appl.	Middle ware	Communication layers	
	Source coding	Network AL-FEC	Packetization UDP/IP	PHY layer
E2E	x			
NC		✗		x
IntraF			✗	
InterF			✗	
SP			✗	
MP				

Figure 1: Network coding and satellite systems

What do we need ?

- Step #1
 - Be volunteer to be a contributor and contribute...
 - Input needed in particular for sections 4 and 5 (project, company, etc.)
 - Collect other sub items in section 5
- Step #2
 - Agree with contributors for the plan
 - Nominate a contributor for each given part ?
- Step #3
 - Classification to better map with the taxonomy organization

How to contribute ?

- Send on the mailing-list your contributing text and relevant pointers to be included in the draft
- Do not send us
 - Link to EU project without text description
 - Raw slides
- Organization
 - We will organize remote meetings to integrate/validate each contributions

Questions ?

Nicolas KUHN

CNES – French National Space Agency

nicolas.kuhn@cnes.fr

Emmanuel LOCHIN

ISAE

emmanuel.lochin@isae.fr