PASSporT Extensions

IETF 99 (Prague) STIR WG July 2017

draft-ietf-stir-passport-divert-00

- A feature many people have asked about
 - How do we handle retargeting?
 - To header field of SIP is signed by PASSporT
 - Original value may be lost with retargeting
- We define a special Identity header track it
 - With its own "ppt" "div" for "divert"
- Different from History-Info and Diversion?
 - Yes, as it is signed by the original destination domain
 - Moreover, it only captures "major" changes
 - Thanks to our canonicalization procedures
- Useful for things like SIPBRANDY where integrity protection for retargeting matters

Inverting the signer

- A diverting auth service takes an existing PASSporT, moves the "dest" to "div," and populates "dest" with the new target
- An Identity header with "div" always points to some prior Identity header
 - Though that header may in turn contain a div...
 - Chains back to an original assertion
- Instead of signing for the "orig" value, the auth service for "div" signs the "dest"
 - So relying parties get a direct cryptographic attestation that the original destination domain authorized the new target

Original vs. Divert Passport

Header:

```
{ "typ":"passport",
 "alg":"ES256",
 "x5u":"https://www.example.com/cert.pkx" }
```

Original PASSporT

Claims:

```
{ "orig":{"uri":"alice@example.com"},
"dest":{"uri":"firsttarget@example.com"}, <- original target
"iat": 1443208345 }</pre>
```

Header:

```
{ "typ":"passport",
"alg":"ES256",
"ppt":"div",
"x5u":"https://www.example.com/cert.pkx" }
```

Added when retargeting

Claims:

```
{ "orig":{"uri":"alice@example.com"},
"dest":{"uri":"secondtarget@example.com"}, <- new target
"iat": 1443208345,
"div":{"uri":"firsttarget@example.com"} } <- original target</pre>
```

Issues

- It's pretty straightforward, this seems relatively baked
- Do we need a reason?
 - That is, a cause for the retargeting to be recorded
 - Any actual security value for the threat model?
- Has some interesting interactions with out of band
 - Turns out we probably really need it for that

draft-ietf-stir-passport-rcd-00 (formerly cnam)

- Adds a "rcd" array to PASSporT
 - Baseline include a "nam" key-value pair containing a display-name
- But the "rcd" element is richer than just Caller-ID
 - Scope: anything rendered to the called user to help them decide to pick up the phone or not - extensible
 - Could include information about organizations
 - Government, bank, etc.
 - Maybe some fields in Henning's Caller-Info parameters
 - Location, potentially
 - Likely by reference rather than by value
 - Other rich data associated with the originating persona
 - Social network data, crowdsourced reputation, and so on
 - Creates an IANA registry allowing allocation of more related elements

First and Third

- Operates in two modes
- Without "ppt"
 - This signifies that an originating authentication service provides the caller name
 - Same entity that signs for the originating number
- With "ppt"
 - This signifies that a third party provides the assertion
 - Different entity than signs for the originating number
 - Signature can come from someone that doesn't own the TN
 - Instead the "iss" field identifies who generated it
 - Different Identity header field as well

"rcd" without "ppt"

Header:

Claims:

```
{ "orig":{"tn":"12155551212"},
 "dest":{"tn":"12155551213"},
      "iat": 1443208345,
 "rcd":{"nam:"Alice Atlanta"} }
```

"rcd" with "ppt"

Header:

Claims:

```
{ "orig":{"tn":"12155551212"},
"dest":{"tn":"12155551213"},
      "iat": 1443208345,
      "rcd":{"nam:"Alice Atlanta"} }
```

Issues: LoA

- How do you know who's behind a phone number?
 - Carriers know their direct customers, but not reseller's customers
 - Should a given extension at an enterprise display the name of the organization or the individual or both?
 - Individuals populate names in their address books, claim them in SIP From headers
- Do we need a way to express confidence in names and RCD?
- There is something similar in SHAKEN
 - "Attest" levels of A, B, C could adapt to RCD

Other Issues

- Richer information can be more personal
 - Privacy issues with carrying a "rcd" payload
 - Confidentiality required for these PASSporTs?
 - We have a story for this developing in OOB
- What is the interface for third-person "rcd"?
 - Out of band?
 - There are some interactions with OOB here...
- Need to make sure information propagates down to end user devices...