Security Level:

Requirements of Name Resolution Service in ICN draft-dong-NRS-requirement-00

www.huawei.com



HUAWEI TECHNOLOGIES CO., LTD.

Critical issue in ICN: name resolution

- How to map content name to the actual content within the network
- Different approaches for name resolution
 - Out of band
 - Inband
 - Hybrid
 - Manifest

Critical issue

- For availability
- Security
- Attempted to write down the key requirements of a name resolution system
- Open up conversation, all feedback and contribution welcome!

draft-dong-NRS-requirement-00

Table of Contents

| 1. Introduction | 2 |
|--|----|
| 1.1. Comparisons of Standalone Name Resolution and Name based Routing Approaches | 4 |
| 2. Definition of Name Resolution Service in ICN | 5 |
| 3. Requirements of Name Resolution Service in ICN | 6 |
| 3.1. Resolution Guarantee | 6 |
| 3.2. Delay Sensitivity | 6 |
| 3.3. Minimum Inter-Domain Traffic | 6 |
| 3.4. Failure Resilience | 6 |
| 3.5. Accuracy | 7 |
| 3.6. Security and accessibility | 7 |
| 3.7. Scalability | 7 |
| 3.8. Time Transiency | 8 |
| 3.9. Support for manifest | 8 |
| 3.10. Interoperability | 8 |
| 3.11. Resolution Result Selection | 9 |
| 3.12. Heterogeneity | 9 |
| 3.13. Unspecified Content Name | 10 |
| 4. IANA Considerations | 10 |
| 5. Conclusions | 10 |
| 6. Informative References | 10 |

NRS: Definition

- Definition: The Name Resolution Service (NRS) is defined as the service that is provided by ICN infrastructure to help a client to reach a specific piece of content, service, or host using a persistent name.
- Examples :iDNS [18], Global Name Resolution Service (GNRS)[9], and Locator/ID Separation Protocol (LISP)[26][27] based approaches, etc...

Inband vs Out of band

- In the draft, denoted as 'standalone' and 'name based routing' approaches
- Standalone: a specific infrastructure to return a content location based upon a content name
- Name-based routing: combines the name resolution step with a namebased routing
- Hybrid: a subset of the nodes perform a name based routing, with (some form of) tunneling in between these nodes
- Manifest: resolve the name into a manifest that includes more names and/or locations

Requirements I

• Some "must", some "should"!

Guarantee

Name resolution returns a result if name exists

Delay Sensitivity

In a timely manner

Minimum Inter-Domain Traffic

Without too much impact on traffic

Failure Resilience

NRS nodes may fail, should be graceful

• Accuracy

Good results

Requirements II

• Security and accessibility

Tamper proof, scoped, DoS,

Scalability

A lot of objects out there

• Time Transiency

Content may be ephemeral/short lived

Support for manifest

Allow for some indirection in the resolution

Interoperability

 With some other resolution mechanisms, for instance in the context of IoT

Resolution Result Selection

Heterogeneity

Requirements III

Resolution Result Selection

All results, best result, any result? One or more?

• Heterogeneity

Multiple naming schemes

Unspecified Content Name

Parameter based resolution? Resolution without a name?

Conclusions

- Trying to focus the conversation
- Involvement/feedback/contributions welcome
- Converge onto a set of "musts"

Thank you www.huawei.com

Copyright©2011 Huawei Technologies Co., Ltd. All Rights Reserved.

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.