

# Mapping LWM2M model to CoMI YANG

**draft-vanderstok-core-yang-LWM2M-00**

Peter van der Stok  
Jaime Jiménez

(Work in Progress)

# Purpose

- Standard organisations use hierarchical models that can be specified in XML and describe classes with attributes and operations that can be instantiated to objects.
- OMA LWM2M and IPSO standardise numbered object types.
- CoMI at IETF (draft-vanderstok-core-comi-09) describes a network management interface based on CoAP and YANG.
- Goal: convert a LWM2M xml-based device specification to a YANG MODULE for CoMI consumption.

# Humidity Object

## Object definition


Name	Object ID	Instances	Mandatory	Object URN
Humidity	0	Multiple	Mandatory	urn:oma:lwm2m:ipso:3304

## Resource definitions

ID	Name	Operations	Instances	Mandatory	Type	Units	Description
5700	Sensor Value	R	Single	Mandatory	Float	...	...
5601	Min Measured Value	R	Single	Optional	Float	...	...
5602	Max Measured Value	R	Single	Optional	Float	...	...
5603	Min Range Value	R	Single	Optional	Float	...	...
5604	Max Range Value	R	Single	Optional	Float	...	...
5701	Sensor Units	R	Single	Optional	String	...	...
5605	Reset Min and Max	E	Single	Optional	Opaque	...	...

# Conversion Rules

**LWM2M**




**YANG (RFC6020)**

LWM2M	YANG (RFC6020)
optional /mandatory attribute	false / true statement
R, W attributes	Config statement (False=R, True=W)
E attribute	YANG RPC
range attribute	range statement
units	units statement
Resources	Leafs on a YANG list <code>+--ro ID3301* [instance_number]</code> <code>+--ro 5700 uint16</code>
Object Instance	"instance" key attribute

# URI Conversion

**LWM2M**



**YANG**

URI:

`coap+lwm2m://example.com/object/instance/resource`

RESTCONF URI (example 3):

`http://example.com/type/instance/resource`

CoMI URI (example 3):

`coap://example.com/type/resource?key=0`

if only one instance then

`coap://example.com/type/resource`

- Keys as query parameter for instance number.

# Generated YANG modules

<b>[ ]</b>	list keys	<b>1. module: ietf-yang-humidityID</b>	+--ro ID3301* [instance_number]
<b>rw</b>	configuration data (read and write)		+--ro instance_number uint16
<b>ro</b>	state data (read only)		+--ro ID5700 decimal64
<b>?</b>	optional node		+--ro ID5701? string
<b>*</b>	list and leaf list		+--ro ID5601? decimal64
<b>( )</b>	choice	<b>2. module: ietf-yang-humidityNM</b>	+--ro ID5602? decimal64
<b>:</b>	case nodes		+--ro ID5603? decimal64
<b>...</b>	subtrees not shown		+--ro ID5604? decimal64
			+---x ID5605
			+--ro IPSO-humidity* [instance_number]
			+--ro instance_number uint16
			+--ro Sensor_Value decimal64
			+--ro Units? string
			+--ro Min_Measured_Value? decimal64
			+--ro Max_Measured_Value? decimal64
			+--ro Min_Range_Value? decimal64
			+--ro Max_Range_Value? decimal64
			+---x Reset_Min_and_Max_measured_values

# Generated YANG modules

		<b>3. module: ietf-yang-humidityLF</b>
		+--rw IPSO-humidity
		+--ro identifier      uint16
[ ]	list keys	+--ro resources* [instance_number]
		+--ro instance_number  uint16
		+--ro Sensor_Value
rw	configuration data (read and write)	+--ro identifier?   uint16
		+--ro content      decimal64
ro	state data (read only)	+--ro Units
		+--ro identifier?   uint16
		+--ro content?      string
?	optional node	+--ro Min_Measured_Value
		+--ro identifier?   uint16
*	list and leaf list	+--ro content?      decimal64
		+--ro Max_Measured_Value
		+--ro identifier?   uint16
( )	choice	+--ro content?      decimal64
:	case nodes	+--ro Min_Range_Value
		+--ro identifier?   uint16
		+--ro content?      decimal64
		+--ro Max_Range_Value
...	subtrees not shown	+--ro identifier?   uint16
		+--ro content?      decimal64
		+--ro Reset_Min_and_Max_measured_values
		+--ro identifier?   uint16
		+---x reset

# Takeaways

- Example 1 (module: ietf-yang-humidityID) is a bit forced and lacks the Resource Name.
- Example 2 ( module: ietf-yang-humidityNM) seems to be the best fit.
- Example 3 (ietf-yang-humidityLF) seems too complex.
- YANG is much more expressive than LWM2M, there are many ways to express the same thing.
- Both .XML (3482 characters) and .YANG (4570 characters on example 1) have a lot of “noise” in them.
- Key leafs are just one possible way to represent instances.
- Access Control mapping might be done better.
- YANG has no Float, we use 64 bit precision (float is 32).
- Need to script automatic conversion.
- Where would a converter run? GWs, devices, server?



# Links

- <https://tools.ietf.org/html/rfc6020>
- <http://technical.openmobilealliance.org/Technical/technical-information/release-program/current-releases/oma-lightweightm2m-v1-0>
- <http://ipso-alliance.github.io/pub/>
- (Preliminary work) <http://jaimejim.github.io/drafts/draft-vanderstok-core-yang-lwm2m-00.txt>
- [jaimejim.github.io/drafts/3304.xml](http://jaimejim.github.io/drafts/3304.xml)
- [jaimejim.github.io/drafts/3304.yang](http://jaimejim.github.io/drafts/3304.yang)

# 3304.yang

```
module ietf-humidityID{
```

```
  yang-version 1.1; // needed for action
```

```
  namespace
```

```
    "urn:ietf:params:xml:ns:yang:ietf-humidityID";
```

```
  prefix humid;
```

```
  organization
```

```
    "IPSO";
```

```
  contact
```

```
    "WG Web:  http://tools.ietf.org/wg/core/
```

```
    WG List:  mailto:core@ietf.org
```

```
    WG Chair: Carsten Bormann  
              mailto:cabo@tzi.org
```

```
    WG Chair: Jaime Jimenez  
              mailto:jaime.jimenez@ericsson.com
```

```
    Editor:   Peter van der Stok  
              mailto:consultancy@vanderstok.org
```

```
    Editor:   Jaime Jimenez  
              mailto:jaime.jimenez@ericsson.com";
```

```
  description
```

```
    "This module contains information about the operation of the IPSO LWM2M humidity sensor with ID 3301.
```

```
    Copyright (c) 2016 IETF Trust and the persons identified as  
    authors of the code. All rights reserved.
```

```
    Redistribution and use in source and binary forms, with or
```

```
    without modification, is permitted pursuant to, and subject  
    to the license terms contained in, the Simplified BSD License  
    set forth in Section 4.c of the IETF Trust's Legal Provisions  
    Relating to IETF Documents  
    (http://trustee.ietf.org/license-info).
```

```
    This version of this YANG module is part of RFC XXXX; see  
    the RFC itself for full legal notices.";
```

```
revision "2016-07-25" {
    description "Initial revision.";
    reference
        "I-D:draft-vanderstok-core-yang-LWM2M: YANG language applied to the LWM2M IPSO humidity sensor specification";
}

list ID3301 {
    key instance_number;
    config false;    // should be same for key leaf
    description
        "IPSO humidity: The humidity sensor is composed of a set of instances";
    leaf instance_number {
        type uint16{
            range "0..1";    // only one instance zero (0)
        }
        config false;    // R access
        mandatory "true";
        description
            "the number of the humidity sensor instance";
    }
    leaf ID5700 {
        type decimal64{    // YANG has no float
            fraction-digits 2;
            range "10.0 .. 66.6";}
        config false;    // R access
        mandatory "true";
        description
            "Sensor Value: Last or Current Measured Value from the Sensor";
    }
    leaf ID5701 {
        type string;
        units "Defined by 'Units' resource";
        config false;    // R access
        description
            "Units: Measurement unit definition e.g. 'Cel' for temperature in Celsius";
    }
}
```

```
leaf ID5602 {
    type decimal64{ // YANG has no float
        fraction-digits 2;
        range "10.0 .. 66.6";}
    units "Defined by 'Units' resource";
    config false; // R access
    description
        "Max Measured Value: The maximum value measured by the sensor since power ON or reset";
}
leaf ID5603 {
    type decimal64{ // YANG has no float
        fraction-digits 2;
        range "10.0 .. 66.6";}
    units "Defined by 'Units' resource";
    config false; // R access
    description
        "Min Range Value: The minimum value that can be measured by the sensor";
}
leaf ID5604 {
    type decimal64{ // YANG has no float
        fraction-digits 2;
        range "10.0 .. 66.6";}
    units "Defined by 'Units' resource";
    config false; // R access
    description
        "Max Range Value: The maximum value that can be measured by the sensor";
}
action ID5605 {
    //E access: this is an RPC without input and output parameters
    description
        "Reset Min and Max measured values: Reset the Min and Max measured values to current value";
}
} // list ID3301
} // module ietf-yang-humidity
```