



#### 6 October 2017 Webex

Chairs:

Pascal Thubert Thomas Watteyne

Etherpad for Minutes: <a href="https://etherpad.tools.ietf.org/p/6tisch">https://etherpad.tools.ietf.org/p/6tisch</a>

IPv6 over the TSCH mode of IEEE 802.15.4

#### **Note Well**

Any submission to the IETF intended by the Contributor for publication as all or part of an IETF Internet-Draft or RFC and any statement made within the context of an IETF activity is considered an "IETF Contribution". Such statements include oral statements in IETF sessions, as well as written and electronic communications made at any time or place, which are addressed to:

- The IETF plenary session
- The IESG, or any member thereof on behalf of the IESG
- Any IETF mailing list, including the IETF list itself, any working group or design team list, or any other list functioning under IETF auspices
- Any IETF working group or portion thereof
- Any Birds of a Feather (BOF) session
- The IAB or any member thereof on behalf of the IAB
- The RFC Editor or the Internet-Drafts function

All IETF Contributions are subject to the rules of <u>RFC 5378</u> and <u>RFC 8179</u>.

Statements made outside of an IETF session, mailing list or other function, that are clearly not intended to be input to an IETF activity, group or function, are not IETF Contributions in the context of this notice. Please consult RFC 5378 and RFC 8179 for details.

A participant in any IETF activity is deemed to accept all IETF rules of process, as documented in Best Current Practices RFCs and IESG Statements.

A participant in any IETF activity acknowledges that written, audio and video records of meetings may be made

and may be available to the public.





#### Reminder:

# Minutes are taken \* This meeting is recorded \*\* Presence is logged \*\*\*

- \* Scribe; please contribute online to the minutes at: <a href="https://etherpad.tools.ietf.org/p/6tisch">https://etherpad.tools.ietf.org/p/6tisch</a>
- \*\* Recordings and Minutes are public and may be subject to discovery in the event of litigation.
- \*\*\* From the Webex login

# Agenda bashing



7:05	<ul> <li>Opening, agenda bashing (Chairs)</li> <li>Note-Well, Scribes, Agenda Bashing, Approval minutes from last meeting</li> <li>Status of drafts (WGLC / forthcoming WGLC)</li> <li>Last meeting todos</li> </ul>	10mn
7:15	Starting 6P shepherding (Pascal)	5mn
7:20	6P WGLC issues resolution (Xavi)	15mn
7:35	SFx Readiness (Diego)	5mn
7:40	SF0 what's the plan? (Thomas)	5mn
7:45	Reroute for RPL (Pascal)	15mn
7:58	AOB	QS



# 6P Shepherding and WGLC issues resolution

# 6P shepherding



IPR

#### **Status**

- Last Call process
- Received some comments from Pascal and Diego
- Will produce v09 addressing the comments
  - 8 comments still to be addressed.

### List of issues

#88: update normative references	*	RESOLVED
#87: reference CCM* in Sec. Cons.	*	NEW
#86: move to appendix	*	NEW
#85: add appendix with guidelines	*	NEW
#84: check the relation between SF and 6P in terms of redefinition of formats	*	NEW
#83: verify inconsistency handling	*	NEW
#82: suggest best solution to handle inconsistency?	*	NEW
#81: verify timeout dependencies with transaction actions	*	NEW
#80: introduce and verify all codes are defined	*	RESOLVED
#79: verify version checking	*	NEW
#78: Define EOL	*	RESOLVED
#77: check the incorrect use of at least?	*	RESOLVED
#76: Define NumCandidate before use	*	RESOLVED
#75: check 'recommended' word use	*	RESOLVED
#74: define what celllist is	*	RESOLVED
#73: verify filtering table	*	RESOLVED
#72: correct text on Other Fields description	*	RESOLVED
#71: do not cite specific sections if not necessary	*	RESOLVED
#70: In Fig4 and others when needed add ACKs	*	RESOLVED
#69: state clearly why there are 2 transaction models	*	RESOLVED
#68: Define dedicated cell	*	RESOLVED
#67: ref the 6TiSCH architecture.	*	RESOLVED
#66: introduce that the schedule indicates transmission cells in the [slotOffset,channelOffset] CDU matrix	*	RESOLVED
#65: too much text about SF in the abstract	*	RESOLVED

#### Discussion

- Version Checking comment:
  - Do nodes need to advertise the supported version?

•

- Proposal (as per Pascal suggestion):
  - When a VER\_ERR code is returned the payload of the message contains the version number(s) supported by the responding node.

lacktriangle

#### Discussion

- Timeout dependency:
  - Is there a dependency on the value of a timer on one side vs. the other? Eg in a 3-step, do we want the requester to time out first and retry, or the responder to retry his response before the requester times out?

•

 Response: We want that the timeout on one side enables all possible attempts from the other side to respond. This is, has to take into account the number of L2 retransmissions that are possible.

#### Discussion

#### Inconsistency handling

• 3.4.6.2. Detecting and Handling Schedule Inconsistency Inconsistency may happen when L2 acknowledgment of the last packet in a transaction is lost, i.e. RESPONSE (in 2-step 6P transaction) or CONFIRMATION (in 3-step 6P transaction) have been received on one side while timeout happens on the other side. Take 2step 6P transaction as example, i.e. timeout happens when node B is waiting for L2 acknowledgment to its Response message. Upon the timeout, the SF running on the node that timeout (e.g node B) MUST take action to validate the schedule state on both sides.

•

- Question: Should we suggest an action? e.g counting or listing cells to see if schedules still match?
- Same for the case that one side has reset and INCO\_ERR is returned. What should 6P do next?



# Scheduling functions

#### SFx Readiness



- Proposal: editorial discussion with Diego
- Moved SF0 to SFX as an experimental version of SF0.
- SFO will follow when the parameter values and/or ranges are calculated from the required experiments
- Added an "Experimental Requirements" section to define which experiments are needed: Values for OVERPROVISION, PDR\_THRESHOLD, SFOTHRESH, Timeout and churn/stability analysis.

#### SF0




• internal discussions ongoing, not finalized yet



# Fast reroute for RPL


Using central computation for non-congruent routes to root


### Arc concept



We build Arcs between Junctions


# Arc concept (cont'd)






A collapsed Arc does not have an Intermediate Junction An Edge Junction may belong to multiple collapsed Arcs


# Arc concept (cont'd)





# Software-defined Projected ARROW Arcs for RPL Routing Over Wireless


- Metrics are accumulated as usual in RPL (separated from Rank)
- Siblings are allowed (all ARC members have the same Rank)
- Rank of ARC members defines ARC height




# Conditoins on RPL operation

- Sparrow requires non storing mode (NS-mode).
- Nodes must advertise at least 2 parents and report metrics
- Root computes ARC Set based on NS-mode DAO

# ARROW Example: Initial topology



# Say standard RPL gives:




In blue the preferred parent path

In red the alt path as RPL computes them based on Rank relationship.

These « arrows » are advertised to the root using NS-Mode

We see that most nodes do not have 2 non-congruent solutions (in fact, only J does!)


# Result of the ARC algorithm:



Original RPL DAG

ARC Re-organized DAG


# Result of the algorithm:



# Use C as Do Not alt parent Use D as alt parent Rev Rev Rev Rev 6TiSCH interim 6 October 2017

# Adapting to RPL

- 1) Root considers changes made on DODAG and notifies nodes, e.g. it tells C that D is not more a feasible successor and it tells D that C is a feasible successor. Same goes between E and F. This can be done with a novel variation of the DAO projection
- 2) For collapsed ARCs, e.g. D, we are all set
- 3) For other nodes that are not on collased ARCs, the root computes a path along the ARC towards the other exit of the ARC. For Node C that is Node B.



#### Cont...

- The path to B is installed as either storing or non storing projected DAO
- 2) In NS Mode the source route path from the node to the other ARC edge is indicated to each node
- 3) In Storing Mode, a route is created from both ends of the ARC allowing each edge (a,d all nodes in between) to route to the other edge
- 4) If C loses connectivity to A, it uses a tunnel to B till RPL completes local repair. Tunnel has a routing header in NS mode.
- 5) When the Edge decaps, it must forward outside the ARC; it cannot reinject in the ARC.



# **Any Other Business?**

## PANID compression bit

Table 7-2—PAN ID Compression field value for frame version 0b10

Destination Address	Source Address	Destination PAN ID	Source PAN ID	PAN ID Compression
Not Present	Not Present	Not Present	Not Present	0
Not Present	Not Present	Present	Not Present	1
Present	Not Present	Present	Not Present	0
Present	Not Present	Not Present	Not Present	1
Not Present	Present	Not Present	Present	0
Not Present	Present	Not Present	Not Present	1
Extended	Extended	Present	Not Present	0
Extended	Extended	Not Present	Not Present	1
Short <sup>a</sup>	Short <sup>a</sup>	Present	Present	0
Short <sup>a</sup>	Extended	Present	Present	0
Extended	Short <sup>a</sup>	Present	Present	0
Short <sup>a</sup>	Extended	Present	Not Present	1
Extended	Short <sup>a</sup>	Present	Not Present	1
Short <sup>a</sup>	Short <sup>a</sup>	Present	Not Present	1

<sup>&</sup>lt;sup>a</sup>If both the destination and source addressing information is present and either is a short address, the MAC sublayer shall compare the destination and source PAN IDs and the PAN ID Compression field shall be set to zero if and only if the PAN identifiers are identical.



•src addr: short

•dest addr: short

No PAN address

•src addr: short

•dest addr: short

single PAN address