

# LPWAN WG

WG Chairs:  
Alexander Pelov <[a@ackl.io](mailto:a@ackl.io)>  
Pascal Thubert <[pthubert@cisco.com](mailto:pthubert@cisco.com)>

AD: Suresh Krishnan  
<[suresh@kaloom.com](mailto:suresh@kaloom.com)>

# Note Well

Any submission to the IETF intended by the Contributor for publication as all or part of an IETF Internet-Draft or RFC and any statement made within the context of an IETF activity is considered an "IETF Contribution". Such statements include oral statements in IETF sessions, as well as written and electronic communications made at any time or place, which are addressed to:

- The IETF plenary session
- The IESG, or any member thereof on behalf of the IESG
- Any IETF mailing list, including the IETF list itself, any working group or design team list, or any other list functioning under IETF auspices
- Any IETF working group or portion thereof
- Any Birds of a Feather (BOF) session
- The IAB or any member thereof on behalf of the IAB
- The RFC Editor or the Internet-Drafts function

All IETF Contributions are subject to the rules of [RFC 5378](#) and [RFC 8179](#).

Statements made outside of an IETF session, mailing list or other function, that are clearly not intended to be input to an IETF activity, group or function, are not IETF Contributions in the context of this notice. Please consult [RFC 5378](#) and [RFC 8179](#) for details.

A participant in any IETF activity is deemed to accept all IETF rules of process, as documented in Best Current Practices RFCs and IESG Statements.



A participant in any IETF activity acknowledges that written, audio and video records of meetings may be made and may be available to the public.

# Reminder:

Minutes are taken \*

This meeting is recorded \*\*

Presence is logged \*\*\*

\* Scribe; please contribute online to the minutes at: <https://etherpad.tools.ietf.org/p/lpwan>

\*\* Recordings and Minutes are public and may be subject to discovery in the event of litigation.

\*\*\* From the Webex login

# Agenda bashing

17:00	Opening, agenda bashing (Chairs)	10mn
	<ul style="list-style-type: none"><li>• Note-Well, Scribes, Agenda Bashing, Approval minutes from last meeting</li><li>• Review todo</li><li>• Status of drafts</li></ul>	
17:10	LPWAN Overview - WGLC status and updates	5mn
17:15	Fragmentation comments (Carles)	10mn
17:25	Update on SCHC fragmentation (Ana)	30mn
17:55	AOB	QS

# Last meeting Action items

- ~~Chairs to send IPR statement request on Mailing List (all participants answered)~~
- ~~Laurent to split the FSM into two FSM (both for sender and receiver) and add to draft~~
- ~~Ana to change names of ACK/No ACK to shorter names~~
- ~~Arun to publish the change of the additional column for field length~~
- ~~Publish the version by next Tuesday (October 17th)~~
- ~~Chairs to wait for final IPR statements and continue with publishing LPWAN Overview document~~
  - Shepherd write-up
- The ML should discuss the Time Scale draft

# LPWAN Overview

Editor: Stephen Farrell  
(many contributors)

# WG LC status and updates

- Stephen pushed out the new rev now
- Then chairs to shoot in the pub-req

# LPWAN SCHC Fragmentation

Authors:

Ana Minaburo <[ana@ackl.io](mailto:ana@ackl.io)>

Laurent Toutain <[laurent.toutain@imt-atlantique.fr](mailto:laurent.toutain@imt-atlantique.fr)>

Carles Gomez <[carlesgo@entel.upc.edu](mailto:carlesgo@entel.upc.edu)>

# Problem

- Downlink fragmentation and ACK Always
  - In some technologies, an uplink message is required prior to the transmission of  $X$  downlink messages

- E.g.  $X=4$

-----> downlink  
-----< uplink

If ACK lost, neither the next fragments (if any) nor the “ACK request” can be sent

	Sender	Receiver
	<-- trigger UL -----	
	-----W=0, FCN=3----->	
	-----W=0, FCN=2----->	
	-----W=0, FCN=1----->	
	-----W=0, FCN=0----->	
lost	<--X--ACK, W=1-----	no bitmap
(*)	-----W=0, FCN=0----->	

# Proposed solution

- Allowing the receiver to retransmit an ACK
- A timer is needed at the receiver

# Thanks!

# Comments?

Authors:

Ana Minaburo <[ana@ackl.io](mailto:ana@ackl.io)>

Laurent Toutain <[laurent.toutain@imt-atlantique.fr](mailto:laurent.toutain@imt-atlantique.fr)>

Carles Gomez <[carlesgo@entel.upc.edu](mailto:carlesgo@entel.upc.edu)>

# Fragmentation FSM

## **draft-ietf-lpwlan-ipv6-static-context-hc-07**

Authors:

Laurent Toutain <[Laurent.Toutain@imt-atlantique.fr](mailto:Laurent.Toutain@imt-atlantique.fr)>

Ana Minaburo <[ana@ackl.io](mailto:ana@ackl.io)>

# Updates:

- Add the State Machines and their description
- Clean the rest of the text for fragmentation
- New Fragmentation Formats Packets :All-0 and All-1
- Add: New Bitmap format and Abort



# Fragmentation Formats Packets

- No last-one packets
- ACK format
- All-0 used to know last fragment in window
- All-1 used to know last fragment
- All-0 empty to request ACK
- All-1 empty to request ACK
- All-1 abort
- ACK abort

# Fragmentation Formats

# LPWAN

## Recommended: Little highest value



```
+-----+-----+-----+-----+
| Rule ID | DTag | W | FCN | payload |
+-----+-----+-----+-----+
```

```
+-----+-----+-----+-----+-----+
| Rule ID | DTag | W | 0..0 | payload | All-0
+-----+-----+-----+-----+-----+
```

## ACK bitmap


Rule ID	DTag	W	FCN	payload
---------	------	---	-----	---------

```
+-- ... --+ ...+-+ ... -+---+-----+
| Rule ID | DTag |W| 11..1 | MIC | payload | All-|
+ + + + + + +
```

### ACK bitmap


# Fragmentation Formats

# LPWAN



# Fragmentation Formats


# LPWAN




# Fragmentation Formats

(( LPWAN ))

S                    R




If no optimization, there is no way to define abort



# Fragmentation Formats

S                    R



Timer expires

All-0 empty

6 5 4 3 2 1 all-0

```
+-----+... -++-++-++-++-+
| Rule ID | DTag |W|1|1|1|1|1| 0 |
+-----+... -++-++-++-++-+
```



Timer expires

All-1 empty

ACK

```
+---+---+---+---+---+---+---+
| Rule ID | DTag |W| FCN | payload |
+---+---+---+---+---+---+---+
```

```
+-- ... --+ ... +--+ ... -
| Rule ID | Dtag |W| 0..0 | no payload
+-- ... --+ ... +--+ ... -+
```

ACK


```
+---+---+---+---+---+---+---+
| Rule ID | DTag |W| FCN | payload |
+---+---+---+---+---+---+---+
```

```
+-- ... --+ ... +--+ ... -+----+
| Rule ID | Dtag |W| 1..1 | MIC | no payload
+-- ... --+ ... +--+ ... -+----+
```

ACK

## ACK\_on\_error

# Receiver





# Support Multiple Window Sizes

## For Discussion

- “For Window mode operation, implementers may opt to support a single window size or multiple window sizes. The latter, when feasible, may provide performance optimizations. For example, a large window size may be used for packets that need to be carried by a large number of fragments. However, when the number of fragments required to carry a packet is low, a smaller window size, and thus a shorter bitmap, may be sufficient to provide feedback on all fragments. If multiple window sizes are supported, the Rule ID may be used to signal the window size in use for a specific packet transmission.”
- To use for ACK\_always

# Multiple Window Sizes ACK\_on\_error

(( LPWAN ))



# Missing

- Finish the description of Abort and the optimization of bitmap
- Review the examples to put this new features
- Missing the padding in the format packets as well as in the text

# Thanks

# AOB ?