

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: March 10, 2020

C. Huitema
Private Octopus Inc.
M. Shore
Fastly
A. Mankin
Salesforce
S. Dickinson
Sinodun IT
J. Iyengar
Fastly
September 7, 2019

Specification of DNS over Dedicated QUIC Connections
draft-huitema-quic-dnsquic-07

Abstract

This document describes the use of QUIC to provide transport privacy for DNS. The encryption provided by QUIC has similar properties to that provided by TLS, while QUIC transport eliminates the head-of-line blocking issues inherent with TCP and provides more efficient error corrections than UDP. DNS over QUIC (DNS/QUIC) has privacy properties similar to DNS over TLS specified in RFC7858, and performance similar to classic DNS over UDP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 10, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Key Words	4
3.	Design Considerations	4
3.1.	Scope is Limited to the Stub to Resolver Scenario	4
3.2.	Provide DNS Privacy	5
3.3.	Design for Minimum Latency	5
3.4.	Development of QUIC Protocols and API	6
3.5.	No Specific Middlebox Bypass Mechanism	6
4.	Specifications	7
4.1.	Connection Establishment	7
4.1.1.	Draft Version Identification	7
4.1.2.	Port Selection	7
4.2.	Stream Mapping and Usage	8
4.2.1.	Server Initiated Transactions	8
4.2.2.	Stream Reset	9
4.3.	Closing the DNS/QUIC Connection	9
4.4.	Connection Resume and 0-RTT	9
5.	Implementation Requirements	10
5.1.	Authentication	10
5.2.	Fall Back to Other Protocols on Connection Failure	10
5.3.	Response Sizes	10
5.4.	DNS Message IDs	10
5.5.	Padding	11
5.6.	Connection Handling	11
5.6.1.	Connection Reuse	11
5.6.2.	Connection Close	11
5.6.3.	Idle Timeouts	12
5.7.	Flow Control Mechanisms	12
6.	Security Considerations	12
7.	Privacy Considerations	13
7.1.	Privacy Issues With Zero RTT data	13
7.2.	Privacy Issues With Session Resume	13
7.3.	Traffic Analysis	14
8.	IANA Considerations	14
8.1.	Registration of DNS/QUIC Identification String	14
8.2.	Reservation of Dedicated Port	15

8.2.1. Port number 784 for experimentations	15
9. Acknowledgements	15
10. References	15
10.1. Normative References	15
10.2. Informative References	16
Authors' Addresses	18

1. Introduction

Domain Name System (DNS) concepts are specified in [RFC1034]. This document presents a mapping of the DNS protocol [RFC1035] over QUIC transport [I-D.ietf-quic-transport] [I-D.ietf-quic-tls]. The goals of this mapping are:

1. Provide the same DNS privacy protection as DNS over TLS (DNS/TLS) [RFC7858]. This includes an option for the client to authenticate the server by means of an authentication domain name [RFC8310].
2. Provide an improved level of source address validation for DNS servers compared to DNS/UDP [RFC1035].
3. Provide a transport that is not constrained by path MTU limitations on the size of DNS responses it can send.
4. Explore the potential performance gains of using QUIC as a DNS transport, versus other solutions like DNS over UDP (DNS/UDP) [RFC1035] or DNS/TLS [RFC7858].
5. Participate in the definition of QUIC protocols and API, by outlining a use case for QUIC different from HTTP over QUIC [I-D.ietf-quic-http].

In order to achieve these goals, the focus of this document is limited to the "stub to recursive resolver" scenario also addressed by [RFC7858]. That is, the protocol described here works for queries and responses between stub clients and recursive servers. The specific non-goals of this document are:

1. No attempt is made to support zone transfers [RFC5936], as these are not relevant to the stub to recursive resolver scenario.
2. No attempt is made to evade potential blocking of DNS/QUIC traffic by middleboxes.

Users interested in zone transfers should continue using TCP based solutions. Users interested in evading middleboxes should consider using solutions like DNS/HTTPS [RFC8484].

Specifying the transmission of an application over QUIC requires specifying how the application's messages are mapped to QUIC streams, and generally how the application will use QUIC. This is done for HTTP in [I-D.ietf-quic-http]. The purpose of this document is to define the way DNS messages can be transmitted over QUIC.

In this document, Section 3 presents the reasoning that guided the proposed design. Section 4 specifies the actual mapping of DNS/QUIC. Section 5 presents guidelines on the implementation, usage and deployment of DNS/QUIC.

2. Key Words

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC8174].

3. Design Considerations

This section and its subsection present the design guidelines that were used for the proposed mapping of DNS/QUIC. This section is informative in nature.

3.1. Scope is Limited to the Stub to Resolver Scenario

Usage scenarios for the DNS protocol can be broadly classified in three groups: stub to recursive resolver, recursive resolver to authoritative server, and server to server. This design focuses only on the "stub to recursive resolver" scenario following the approach taken in [RFC7858] and [RFC8310].

QUESTION: Should this document specify any aspects of configuration of discoverability differently to DNS/TLS?

No attempt is made to address the recursive to authoritative scenarios. Authoritative resolvers are discovered dynamically through NS records. It is noted that at the time of writing work is ongoing in the DPRIVE working group to attempt to address the analogous problem for DNS/TLS [I-D.bortzmeyer-dprive-resolver-to-auth]. In the absence of an agreed way for authoritative to signal support for QUIC transport, recursive resolvers would have to resort to some trial and error process. At this stage of QUIC deployment, this would be mostly errors, and does not seem attractive. This could change in the future.

The DNS protocol is also used for zone transfers. In the zone transfer scenario ([RFC5936]), the client emits a single AXFR query,

and the server responds with a series of AXFR responses. This creates a unique profile, in which a query results in several responses. Supporting that profile would complicate the mapping of DNS queries over QUIC streams. Zone transfers are not used in the stub to recursive scenario that is the focus here, and seem to be currently well served by the DNS over TCP (DNS/TCP). There is no attempt to support them in this proposed mapping of DNS to QUIC.

3.2. Provide DNS Privacy

DNS privacy considerations are described in [RFC7626]. [RFC7858] defines how to mitigate some of these issues by transmitting DNS messages over TLS and TCP and [RFC8310] specifies Strict and Opportunistic Usage Profiles for DNS/TLS including how stub resolvers can authenticate recursive resolvers.

QUIC connection setup includes the negotiation of security parameters using TLS, as specified in [I-D.ietf-quic-tls], enabling encryption of the QUIC transport. Transmitting DNS messages over QUIC will provide essentially the same privacy protections as [RFC7858] and [RFC8310]. Further discussion on this is provided in Section 7.

3.3. Design for Minimum Latency

QUIC is specifically designed to reduce the delay between HTTP queries and HTTP responses. This is achieved through three main components:

1. Support for 0-RTT data during session resumption.
2. Support for advanced error recovery procedures as specified in [I-D.ietf-quic-recovery].
3. Mitigation of head-of-line blocking by allowing parallel delivery of data on multiple streams.

This mapping of DNS to QUIC will take advantage of these features in three ways:

1. Optional support for sending 0-RTT data during session resumption (the security and privacy implications of this are discussed in later sections).
2. Long-lived QUIC connections over which multiple DNS transactions are performed, generating the sustained traffic required to benefit from advanced recovery features.

3. Mapping of each DNS Query/Response transaction to a separate stream, to mitigate head-of-line blocking.

These considerations will be reflected in the mapping of DNS traffic to QUIC streams in Section 4.2.

3.4. Development of QUIC Protocols and API

QUIC is defined as a layered protocol, with application-specific mapping layered on top of the generic QUIC transport. The only mapping defined at this stage is HTTP over QUIC [I-D.ietf-quic-http]. Adding a different mapping for a different application contributes to the development of QUIC.

HTTP/QUIC parallels the definition of HTTP/2.0, in which HTTP queries and responses are carried as series of frames. The HTTP/QUIC mapping provide with some simplification compared to HTTP/TLS/TCP, as QUIC already provides concepts like stream identification or end of stream marks. Dedicated control channel are used to carry connection data, such as settings or the relative priority of queries. It would be completely possible to use the HTTP/QUIC mapping to carry DNS requests as HTTP queries, as specified in [RFC8484]. We are somewhat concerned that this mapping carries the overhead of HTTP into the DNS protocol, resulting in additional complexity and overhead.

In this document a different design is deliberately explored, in which clients and servers can initiate queries as determined by the DNS application logic, opening new streams as necessary. This provides for maximum parallelism between queries, as noted in Section 3.3. It also places constraints on the API. Client and servers will have to be notified of the opening of a new stream by their peer. Instead of orderly closing the control stream, client and server will have to use orderly connection closure mechanisms and manage the potential loss of data if closing on one end conflicts with opening of a stream on the other end.

3.5. No Specific Middlebox Bypass Mechanism

Being different from HTTP/QUIC is a design choice. The advantage is that the mapping can be defined for minimal overhead and maximum performance. The downside is that the difference can be noted by firewalls and middleboxes. There may be environments in which HTTP/QUIC will be allowed, but DNS/QUIC will be disallowed and blocked by these middle boxes.

It is recognized that this might be a problem, but there is currently no indication on how widespread that problem might be. The problem might be acute enough that the only realistic solution would be to

communicate with independent recursive resolvers using DNS/HTTPS, or maybe DNS/HTTP/QUIC. Or the problem might be rare enough and the performance gains significant enough that the appropriate solution would be to use DNS/QUIC most of the time, and fall back to DNS/HTTPS some of the time. Measurements and experimentation will inform that decision.

It may indeed turn out that the complexity and overhead concerns are negligible compared to the potential advantages of DNS/HTTPS, such as integration with web services or firewall traversal, and that DNS/QUIC does not provide sufficient performance gains to justify a new protocol. We will evaluate that once implementations are available and can be compared. In the meanwhile, we believe that a clean design is most likely to inform the QUIC development, as explained in Section 3.4.

4. Specifications

4.1. Connection Establishment

DNS/QUIC connections are established as described in [I-D.ietf-quic-transport]. During connection establishment, DNS/QUIC support is indicated by selecting the ALPN token "dq" in the crypto handshake.

4.1.1. Draft Version Identification

***RFC Editor's Note:** Please remove this section prior to publication of a final version of this document.

Only implementations of the final, published RFC can identify themselves as "dq". Until such an RFC exists, implementations **MUST NOT** identify themselves using this string.

Implementations of draft versions of the protocol **MUST** add the string "-" and the corresponding draft number to the identifier. For example, draft-huitema-quic-dnsquic-01 is identified using the string "dq-h01".

4.1.2. Port Selection

By default, a DNS server that supports DNS/QUIC **MUST** listen for and accept QUIC connections on the dedicated UDP port TBD (number to be defined in Section 8), unless it has mutual agreement with its clients to use a port other than TBD for DNS/QUIC. In order to use a port other than TBD, both clients and servers would need a configuration option in their software.

By default, a DNS client desiring to use DNS/QUIC with a particular server MUST establish a QUIC connection to UDP port TBD on the server, unless it has mutual agreement with its server to use a port other than port TBD for DNS/QUIC. Such another port MUST NOT be port 53 or port 853. This recommendation against use of port 53 for DNS/QUIC is to avoid confusion between DNS/QUIC and DNS/UDP as specified in [RFC1035]. Similarly, using port 853 would cause confusion between DNS/QUIC and DNS/DTLS as specified in [RFC8094].

4.2. Stream Mapping and Usage

The mapping of DNS traffic over QUIC streams takes advantage of the QUIC stream features detailed in Section 10 of [I-D.ietf-quic-transport].

The stub to resolver DNS traffic follows a simple pattern in which the client sends a query, and the server provides a response. This design specifies that for each subsequent query on a QUIC connection the client MUST select the next available client-initiated bidirectional stream, in conformance with [I-D.ietf-quic-transport].

The client MUST send the DNS query over the selected stream, and MUST indicate through the STREAM FIN mechanism that no further data will be sent on that stream.

The server MUST send the response on the same stream, and MUST indicate through the STREAM FIN mechanism that no further data will be sent on that stream.

Therefore, a single client initiated DNS transaction consumes a single stream. This means that the client's first query occurs on QUIC stream 4, the second on 8, and so on.

4.2.1. Server Initiated Transactions

There are planned traffic patterns in which a server sends unsolicited queries to a client, such as for example PUSH messages defined in [I-D.ietf-dnssd-push]. These occur when a client subscribes to changes for a particular DNS RRset or resource record type. When a PUSH server wishes to send such updates it MUST select the next available server initiated bidirectional stream, in conformance with [I-D.ietf-quic-transport].

The server MUST send the DNS query over the selected stream, and MUST indicate through the STREAM FIN mechanism that no further data will be sent on that stream.

The client MUST send the response on the same stream, and MUST indicate through the STREAM FIN mechanism that no further data will be sent on that stream.

Therefore a single server initiated DNS transaction consumes a single stream. This means that the servers's first query occurs on QUIC stream 1, the second on 5, and so on.

4.2.2. Stream Reset

Stream transmission may be abandoned by either party, using the stream "reset" facility. A stream reset indicates that one party is unwilling to continue processing the transaction associated with the stream. The corresponding transaction MUST be abandoned. A Server Failure (SERVFAIL, [RFC1035]) SHOULD be notified to the initiator of the transaction.

4.3. Closing the DNS/QUIC Connection

QUIC connections are closed using the CONNECTION_CLOSE mechanisms specified in [I-D.ietf-quic-transport]. Connections can be closed at the initiative of either the client or the server (also see Section 5.6.2). The party initiating the connection closure SHOULD use the QUIC GOAWAY mechanism to initiate a graceful shutdown of a connection.

The transactions corresponding to stream number higher than indicated in the GO AWAY frames MUST be considered failed. Similarly, if streams are still open when the CONNECTION_CLOSE is received, the corresponding transactions MUST be considered failed. In both cases, a Server Failure (SERVFAIL, [RFC1035]) SHOULD be notified to the initiator of the transaction.

4.4. Connection Resume and 0-RTT

A stub resolver MAY take advantage of the connection resume mechanisms supported by QUIC transport [I-D.ietf-quic-transport] and QUIC TLS [I-D.ietf-quic-tls]. Stub resolvers SHOULD consider potential privacy issues associated with session resume before deciding to use this mechanism. These privacy issues are detailed in Section 7.2.

When resuming a session, a stub resolver MAY take advantage of the 0-RTT mechanism supported by QUIC. The 0-RTT mechanism MUST NOT be used to send data that is not "replayable" transactions. For example, a stub resolver MAY transmit a Query as 0-RTT, but MUST NOT transmit an Update.

5. Implementation Requirements

5.1. Authentication

For the stub to recursive resolver scenario, the authentication requirements are the same as described in [RFC7858] and [RFC8310]. There is no need to authenticate the client's identity in either scenario.

5.2. Fall Back to Other Protocols on Connection Failure

If the establishment of the DNS/QUIC connection fails, clients SHOULD attempt to fall back to DNS/TLS and then potentially clear text, as specified in [RFC7858] and [RFC8310], depending on their privacy profile.

DNS clients SHOULD remember server IP addresses that don't support DNS/QUIC, including timeouts, connection refusals, and QUIC handshake failures, and not request DNS/QUIC from them for a reasonable period (such as one hour per server). DNS clients following an out-of-band key-pinned privacy profile ([RFC7858]) MAY be more aggressive about retrying DNS/QUIC connection failures.

5.3. Response Sizes

DNS/QUIC does not suffer from the limitation on the size of responses that can be delivered as DNS/UDP [RFC1035] does, since large responses will be sent in separate STREAM frames in separate packets.

QUESTION: However, this raises a new issue because the responses sent over QUIC can be significantly larger than those sent over TCP (65,535 bytes). According to [I-D.ietf-quic-transport] "The largest offset delivered on a stream - the sum of the re-constructed offset and data length - MUST be less than 2^{62} ". Should a specific limit be applied for DNS/QUIC responses or not?

5.4. DNS Message IDs

When sending multiple queries over a QUIC connection, clients MUST NOT reuse the DNS Message ID of an in-flight query on that connection in order to avoid Message ID collisions.

Clients MUST match responses to outstanding queries using the STREAM ID and Message ID and if the response contains a question section, the client MUST match the QNAME, QCLASS, and QTYPE fields. Failure to match is a DNS/QUIC protocol error. Clients observing such errors SHOULD close the connection immediately, indicating the application

specific error code 0x00000001. The client should also mark the server as inappropriate for future use of DNS/QUIC.

5.5. Padding

There are mechanisms specified for both padding individual DNS messages [RFC7830], [RFC8467] and padding within QUIC packets (see Section 8.6 of [I-D.ietf-quic-transport]), which may contain multiple frames.

Implementations SHOULD NOT use DNS options for padding individual DNS messages, because QUIC transport MAY transmit multiple STREAM frames containing separate DNS messages in a single QUIC packet. Instead, implementations SHOULD use QUIC PADDING frames to align the packet length to a small set of fixed sizes, aligned with the recommendations of [RFC8467].

5.6. Connection Handling

[RFC7766] provides updated guidance on DNS/TCP much of which is applicable to DNS/QUIC. This section attempts to specify how those considerations apply to DNS/QUIC.

5.6.1. Connection Reuse

Historic implementations of DNS stub resolvers are known to open and close TCP connections for each DNS query. To avoid excess QUIC connections, each with a single query, clients SHOULD reuse a single QUIC connection to the recursive resolver.

In order to achieve performance on par with UDP, DNS clients SHOULD send their queries concurrently over the QUIC streams on a QUIC connection. That is, when a DNS client sends multiple queries to a server over a QUIC connection, it SHOULD NOT wait for an outstanding reply before sending the next query.

5.6.2. Connection Close

In order to amortize QUIC and TLS connection setup costs, clients and servers SHOULD NOT immediately close a QUIC connection after each response. Instead, clients and servers SHOULD reuse existing QUIC connections for subsequent queries as long as they have sufficient resources. In some cases, this means that clients and servers may need to keep idle connections open for some amount of time.

Under normal operation DNS clients typically initiate connection closing on idle connections; however, DNS servers can close the connection if the idle timeout set by local policy is exceeded.

Also, connections can be closed by either end under unusual conditions such as defending against an attack or system failure/reboot.

Clients and servers that keep idle connections open MUST be robust to termination of idle connection by either party. As with current DNS over TCP, DNS servers MAY close the connection at any time (perhaps due to resource constraints). As with current DNS/TCP, clients MUST handle abrupt closes and be prepared to reestablish connections and/or retry queries.

5.6.3. Idle Timeouts

Proper management of established and idle connections is important to the healthy operation of a DNS server. An implementation of DNS/QUIC SHOULD follow best practices for DNS/TCP, as described in [RFC7766]. Failure to do so may lead to resource exhaustion and denial of service.

This document does not make specific recommendations for timeout values on idle connections. Clients and servers should reuse and/or close connections depending on the level of available resources. Timeouts may be longer during periods of low activity and shorter during periods of high activity. Current work in this area may also assist DNS/TLS clients and servers in selecting useful timeout values [RFC7828] [RFC8490] [TDNS].

TODO: Clarify what timers (idle timeouts, response timeouts) apply at the stream level and at the connection level.

TODO: QUIC provides an efficient mechanism for resuming connections, including the possibility of sending 0-RTT data. Does that change the tradeoff? Is it plausible to use shorter timers than specified for TCP?

5.7. Flow Control Mechanisms

Servers MAY use the "maximum stream ID" option of the QUIC transport to limit the number of streams opened by the client. This mechanism will effectively limit the number of DNS queries that a client can send.

6. Security Considerations

The security considerations of DNS/QUIC should be comparable to those of DNS/TLS [RFC7858].

7. Privacy Considerations

DNS/QUIC is specifically designed to protect the DNS traffic between stub and resolver from observations by third parties, and thus protect the privacy of queries from the stub. However, the recursive resolver has full visibility of the stub's traffic, and could be used as an observation point, as discussed in [RFC7626]. These considerations do not differ between DNS/TLS and DNS/QUIC and are not discussed further here.

QUIC incorporates the mechanisms of TLS 1.3 [RFC8446] and this enables QUIC transmission of "Zero-RTT" data. This can provide interesting latency gains, but it raises two concerns:

1. Adversaries could replay the zero-RTT data and infer its content from the behavior of the receiving server.
2. The zero-RTT mechanism relies on TLS resume, which can provide linkability between successive client sessions.

These issues are developed in Section 7.1 and Section 7.2.

7.1. Privacy Issues With Zero RTT data

The zero-RTT data can be replayed by adversaries. That data may triggers a query by a recursive resolver to an authoritative resolvers. Adversaries may be able to pick a time at which the recursive resolver outgoing traffic is observable, and thus find out what name was queried for in the 0-RTT data.

This risk is in fact a subset of the general problem of observing the behavior of the recursive resolver discussed in [RFC7626]. The attack is partially mitigated by reducing the observability of this traffic. However, the risk is amplified for 0-RTT data, because the attacker might replay it at chosen times, several times.

The recommendation in [RFC8446] is that the capability to use 0-RTT data should be turned off by default, on only enabled if the user clearly understands the associated risks.

QUESTION: Should 0-RTT only be used with Opportunistic profiles (i.e. disabled by default for Strict only)?

7.2. Privacy Issues With Session Resume

The QUIC session resume mechanism reduces the cost of reestablishing sessions and enables zero-RTT data. There is a linkability issue associated with session resume, if the same resume token is used

several times, but this risk is mitigated by the mechanisms incorporated in QUIC and in TLS 1.3. With these mechanisms, clients and servers can cooperate to avoid linkability by third parties. However, the server will always be able to link the resumed session to the initial session. This creates a virtual long duration session. The series of queries in that session can be used by the server to identify the client.

Enabling the server to link client sessions through session resume is probably not a large additional risk if the client's connectivity did not change between the sessions, since the two sessions can probably be correlated by comparing the IP addresses. On the other hand, if the addresses did change, the client SHOULD consider whether the linkability risk exceeds the privacy benefits. This evaluation will obviously depend on the level of trust between stub and recursive.

7.3. Traffic Analysis

Even though QUIC packets are encrypted, adversaries can gain information from observing packet lengths, in both queries and responses, as well as packet timing. Many DNS requests are emitted by web browsers. Loading a specific web page may require resolving dozen of DNS names. If an application adopts a simple mapping of one query or response per packet, or "one QUIC STREAM frame per packet", then the succession of packet lengths may provide enough information to identify the requested site.

Implementations SHOULD use the mechanisms defined in Section 5.5 to mitigate this attack.

8. IANA Considerations

8.1. Registration of DNS/QUIC Identification String

This document creates a new registration for the identification of DNS/QUIC in the "Application Layer Protocol Negotiation (ALPN) Protocol IDs" registry established in [RFC7301].

The "dq" string identifies DNS/QUIC:

Protocol: DNS/QUIC

Identification Sequence: 0x64 0x71 ("dq")

Specification: This document

8.2. Reservation of Dedicated Port

IANA is required to add the following value to the "Service Name and Transport Protocol Port Number Registry" in the System Range. The registry for that range requires IETF Review or IESG Approval [RFC6335], and such a review was requested using the early allocation process [RFC7120] for the well-known UDP port in this document. Since port 853 is reserved for 'DNS query-response protocol run over TLS' consideration is requested for reserving port TBD for 'DNS query-response protocol run over QUIC'.

Service Name	domain-s
Transport Protocol(s)	TCP/UDP
Assignee	IESG
Contact	IETF Chair
Description	DNS query-response protocol run over QUIC
Reference	This document

8.2.1. Port number 784 for experimentations

**RFC Editor's Note:* Please remove this section prior to publication of a final version of this document.

Early experiments MAY use port 784. This port is marked in the IANA registry as unassigned.

9. Acknowledgements

This document liberally borrows text from [I-D.ietf-quic-http] edited by Mike Bishop, and from [RFC7858] authored by Zi Hu, Liang Zhu, John Heidemann, Allison Mankin, Duane Wessels, and Paul Hoffman.

The privacy issue with 0-RTT data and session resume were analyzed by Daniel Kahn Gillmor (DKG) in a message to the IETF "DPRIV" working group [DNSORTT].

Thanks to our wide cast of supporters.

10. References

10.1. Normative References

[I-D.ietf-quic-tls]
Thomson, M. and S. Turner, "Using TLS to Secure QUIC",
draft-ietf-quic-tls-22 (work in progress), July 2019.

- [I-D.ietf-quic-transport]
Iyengar, J. and M. Thomson, "QUIC: A UDP-Based Multiplexed and Secure Transport", draft-ietf-quic-transport-22 (work in progress), July 2019.
- [RFC1034] Mockapetris, P., "Domain names - concepts and facilities", STD 13, RFC 1034, DOI 10.17487/RFC1034, November 1987, <<https://www.rfc-editor.org/info/rfc1034>>.
- [RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, RFC 1035, DOI 10.17487/RFC1035, November 1987, <<https://www.rfc-editor.org/info/rfc1035>>.
- [RFC7301] Friedl, S., Popov, A., Langley, A., and E. Stephan, "Transport Layer Security (TLS) Application-Layer Protocol Negotiation Extension", RFC 7301, DOI 10.17487/RFC7301, July 2014, <<https://www.rfc-editor.org/info/rfc7301>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8310] Dickinson, S., Gillmor, D., and T. Reddy, "Usage Profiles for DNS over TLS and DNS over DTLS", RFC 8310, DOI 10.17487/RFC8310, March 2018, <<https://www.rfc-editor.org/info/rfc8310>>.

10.2. Informative References

- [DNSORTT] Kahn Gillmor, D., "DNS + 0-RTT", Message to DNS-Privacy WG mailing list, April 2016, <<https://www.ietf.org/mail-archive/web/dns-privacy/current/msg01276.html>>.
- [I-D.bortzmeyer-dprive-resolver-to-auth]
Bortzmeyer, S., "Encryption and authentication of the DNS resolver-to-authoritative communication", draft-bortzmeyer-dprive-resolver-to-auth-01 (work in progress), March 2018.
- [I-D.ietf-dnssd-push]
Pusateri, T. and S. Cheshire, "DNS Push Notifications", draft-ietf-dnssd-push-24 (work in progress), August 2019.
- [I-D.ietf-quic-http]
Bishop, M., "Hypertext Transfer Protocol Version 3 (HTTP/3)", draft-ietf-quic-http-22 (work in progress), July 2019.

- [I-D.ietf-quic-recovery]
Iyengar, J. and I. Swett, "QUIC Loss Detection and Congestion Control", draft-ietf-quic-recovery-22 (work in progress), July 2019.
- [RFC5936] Lewis, E. and A. Hoenes, Ed., "DNS Zone Transfer Protocol (AXFR)", RFC 5936, DOI 10.17487/RFC5936, June 2010, <<https://www.rfc-editor.org/info/rfc5936>>.
- [RFC6335] Cotton, M., Eggert, L., Touch, J., Westerlund, M., and S. Cheshire, "Internet Assigned Numbers Authority (IANA) Procedures for the Management of the Service Name and Transport Protocol Port Number Registry", BCP 165, RFC 6335, DOI 10.17487/RFC6335, August 2011, <<https://www.rfc-editor.org/info/rfc6335>>.
- [RFC7120] Cotton, M., "Early IANA Allocation of Standards Track Code Points", BCP 100, RFC 7120, DOI 10.17487/RFC7120, January 2014, <<https://www.rfc-editor.org/info/rfc7120>>.
- [RFC7626] Bortzmeyer, S., "DNS Privacy Considerations", RFC 7626, DOI 10.17487/RFC7626, August 2015, <<https://www.rfc-editor.org/info/rfc7626>>.
- [RFC7766] Dickinson, J., Dickinson, S., Bellis, R., Mankin, A., and D. Wessels, "DNS Transport over TCP - Implementation Requirements", RFC 7766, DOI 10.17487/RFC7766, March 2016, <<https://www.rfc-editor.org/info/rfc7766>>.
- [RFC7828] Wouters, P., Abley, J., Dickinson, S., and R. Bellis, "The edns-tcp-keepalive EDNS0 Option", RFC 7828, DOI 10.17487/RFC7828, April 2016, <<https://www.rfc-editor.org/info/rfc7828>>.
- [RFC7830] Mayrhofer, A., "The EDNS(0) Padding Option", RFC 7830, DOI 10.17487/RFC7830, May 2016, <<https://www.rfc-editor.org/info/rfc7830>>.
- [RFC7858] Hu, Z., Zhu, L., Heidemann, J., Mankin, A., Wessels, D., and P. Hoffman, "Specification for DNS over Transport Layer Security (TLS)", RFC 7858, DOI 10.17487/RFC7858, May 2016, <<https://www.rfc-editor.org/info/rfc7858>>.
- [RFC8094] Reddy, T., Wing, D., and P. Patil, "DNS over Datagram Transport Layer Security (DTLS)", RFC 8094, DOI 10.17487/RFC8094, February 2017, <<https://www.rfc-editor.org/info/rfc8094>>.

- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8467] Mayrhofer, A., "Padding Policies for Extension Mechanisms for DNS (EDNS(0))", RFC 8467, DOI 10.17487/RFC8467, October 2018, <<https://www.rfc-editor.org/info/rfc8467>>.
- [RFC8484] Hoffman, P. and P. McManus, "DNS Queries over HTTPS (DoH)", RFC 8484, DOI 10.17487/RFC8484, October 2018, <<https://www.rfc-editor.org/info/rfc8484>>.
- [RFC8490] Bellis, R., Cheshire, S., Dickinson, J., Dickinson, S., Lemon, T., and T. Pusateri, "DNS Stateful Operations", RFC 8490, DOI 10.17487/RFC8490, March 2019, <<https://www.rfc-editor.org/info/rfc8490>>.
- [TDNS] Zhu, L., Hu, Z., Heidemann, J., Wessels, D., Mankin, A., and N. Somaiya, "Connection-Oriented DNS to Improve Privacy and Security", 2015 IEEE Symposium on Security and Privacy (SP), DOI 10.1109/SP.2015.18, <<http://dx.doi.org/10.1109/SP.2015.18>>.

Authors' Addresses

Christian Huitema
Private Octopus Inc.
Friday Harbor WA 98250
U.S.A

Email: huitema@huitema.net

Melinda Shore
Fastly

Email: mshore@fastly.com

Allison Mankin
Salesforce

Email: amankin@salesforce.com

Sara Dickinson
Sinodun IT
Magdalen Centre
Oxford Science Park
Oxford OX4 4GA
U.K.

Email: sara@sinodun.com

Jana Iyengar
Fastly

Email: jri.ietf@gmail.com